The CiaoPP Program Processor

A Program Analysis, Verification, Debugging, and Optimization Tool
REFERENCE MANUAL
The Ciao Documentation Series
`https://ciao-lang.org/`
Generated/Printed on: 22 July 2023
Technical Report CLIP 1/06 (first version 8/95).
Version 1.5 (2022/3/2, 20:34:30 CET)

The Ciao Development Team
Edited by:
Francisco Bueno
Manuel Hermenegildo
Pedro López
José Francisco Morales
Germán Puebla

The Computational logic, Languages, Implementation, and Parallelism (CLIP) Lab
`https://www.cliplab.org/`
School of CS, T. U. of Madrid (UPM)
IMDEA Software Institute

Copyright © 1996-2011 Francisco Bueno, Manuel Hermenegildo, Pedro López, José Francisco Morales, and Germán Puebla.

This document may be freely read, stored, reproduced, disseminated, translated or quoted by any means and on any medium provided the following conditions are met:

1. Every reader or user of this document acknowledges that is aware that no guarantee is given regarding its contents, on any account, and specifically concerning veracity, accuracy and fitness for any purpose.
2. No modification is made other than cosmetic, change of representation format, translation, correction of obvious syntactic errors, or as permitted by the clauses below.
3. Comments and other additions may be inserted, provided they clearly appear as such; translations or fragments must clearly refer to an original complete version, preferably one that is easily accessed whenever possible.
4. Translations, comments and other additions or modifications must be dated and their author(s) must be identifiable (possibly via an alias).
5. This licence is preserved and applies to the whole document with modifications and additions (except for brief quotes), independently of the representation format.
6. Any reference to the "official version", "original version" or "how to obtain original versions" of the document is preserved verbatim. Any copyright notice in the document is preserved verbatim. Also, the title and author(s) of the original document should be clearly mentioned as such.
7. In the case of translations, verbatim sentences mentioned in (6.) are preserved in the language of the original document accompanied by verbatim translations to the language of the traslated document. All translations state clearly that the author is not responsible for the translated work. This license is included, at least in the language in which it is referenced in the original version.
8. Whatever the mode of storage, reproduction or dissemination, anyone able to access a digitized version of this document must be able to make a digitized copy in a format directly usable, and if possible editable, according to accepted, and publicly documented, public standards.
9. Redistributing this document to a third party requires simultaneous redistribution of this licence, without modification, and in particular without any further condition or restriction, expressed or implied, related or not to this redistribution. In particular, in case of inclusion in a database or collection, the owner or the manager of the database or the collection renounces any right related to this inclusion and concerning the possible uses of the document after extraction from the database or the collection, whether alone or in relation with other documents.

Any incompatibility of the above clauses with legal, contractual or judiciary decisions or constraints implies a corresponding limitation of reading, usage, or redistribution rights for this document, verbatim or modified.

Table of Contents

1 Summary 1

2 Introduction 3

2.1 How to use this manual 3
2.2 Note 4
2.3 Version/Change Log 4

3 PART I - Using CiaoPP 9

4 The CiaoPP high-level interface 11

4.1 Usage and interface 11
4.2 Documentation on exports 12
auto_analyze/1 (pred) 12
auto_optimize/1 (pred) 12
auto_check_assert/1 (pred) 12
auto_analyze/2 (pred) 12
auto_optimize/2 (pred) 12
auto_check_assert/2 (pred) 12
customize/0 (pred) 12
customize/1 (pred) 12
customize_and_preprocess/0 (pred) 13
customize_and_preprocess/1 (pred) 13
customize_but_dont_save/1 (pred) 13
again/0 (pred) 13
get_menu_configs/1 (pred) 13
save_menu_config/1 (pred) 13
remove_menu_config/1 (pred) 13
restore_menu_config/1 (pred) 14
show_menu_configs/0 (pred) 14
show_menu_config/1 (pred) 14
get_menu_flag/3 (udreexp) 14
get_menu_flag/3 (udreexp) 14
set_menu_flag/3 (udreexp) 14
set_menu_flag/3 (udreexp) 14
menu_branch/4 (udreexp) 14
menu_branch/3 (udreexp) 14
true/2 (udreexp) 14
true1/1 (udreexp) 15
functor1/2 (udreexp) 15
4.3 Documentation on multifiles 15
hook_menu_flag_values/3 (pred) 15
hook_menu_check_flag_value/3 (pred) 15
hook_menu_flag_help/3 (pred) 15
hook_menu_default_option/3 (pred) 15
aidomain/1 (pred) 15
4.4 Documentation on imports 15

5 The CiaoPP low-level interface 17

5.1 Usage and interface 17
5.2 Documentation on exports 17
current_pp_flag/2 (pred) 17
current_pp_flag/2 (pred) 17
set_pp_flag/2 (pred) 18
push_pp_flag/2 (pred) 18
pop_pp_flag/1 (pred) 18
pp_flag/1 (pred) 18
flag_value/1 (regtype) 20
valid_flag_value/2 (prop) 20
is_library/1 (udreexp) 20
get_data/2 (udreexp) 20
clean_ciaopp_db/1 (udreexp) 20
clean_all_ciaopp_db/0 (udreexp) 20
dump/2 (udreexp) 20
dump_dir/1 (udreexp) 20
add_to_db/1 (udreexp) 21
show_dump/1 (udreexp) 21
restore/2 (udreexp) 21
restore/1 (udreexp) 21
dump/1 (udreexp) 21
gen_and_load_libcache/0 (udreexp) 21
ensure_libcache_loaded/0 (udreexp) 21
write_one_type/2 (udreexp) 21
output_by_ext/2 (udreexp) 21
output_ext/1 (udreexp) 21
output/2 (udreexp) 21
output/1 (pred) 22
output/0 (pred) 22
get_output_path/2 (udreexp) 22
pop_history/1 (udreexp) 22
push_history/1 (udreexp) 22
cleanup_history/0 (udreexp) 22
is_library/1 (udreexp) 22
assrt_used_as_entry/2 (udreexp) 22
entry_assertion/3 (udreexp) 22
module/1 (pred) 22
language_output_extension/2 (udreexp) 23
transform/1 (pred) 23
cleanup_for_codegen/0 (udreexp) 23
clean_analysis_info0/0 (udreexp) 23
acheck/2 (udreexp) 23
acheck/0 (pred) 23
get_assert_count/1 (udreexp) 23
acheck_summary/2 (udreexp) 24
acheck_summary/1 (udreexp) 24
ctcheck_sum/1 (udreexp) 24
analyze1/2 (udreexp) 24
analyze/1 (pred) 24
last_domain_used/1 (udreexp) 24
assert_domain/1 (udreexp) 24
menu_branch/4 (udreexp) 24
menu_branch/3 (udreexp) 24
true/2 (udreexp) 24
true1/1 (udreexp) 25

functor1/2 (udreexp) 25
customize_and_preprocess/0 (udreexp) 25
customize/0 (udreexp) 25
5.3 Documentation on multifiles 25
typeslib_flag/1 (pred) 25
typeslib_is_user_type/1 (pred) 25
typeslib_is_visible/2 (pred) 25
typeslib_interesting_type/2 (pred) 25
5.4 Documentation on internals 26
transformation/1 (prop) 26
analysis/1 (prop) 26
5.5 Documentation on imports 26

6 The CiaoPP command-line interface 27
6.1 Command-line options 27
6.2 Description of the execution examples 28

7 Available abstract domains 31
7.0.1 Groundness and sharing 32
7.0.2 Term structure 32
7.0.3 Types 32
7.0.4 Partial evaluation 32
7.0.5 Constraint domains 32
7.0.6 Properties of the computation 32
7.0.7 Size of terms 32
7.0.8 Number of resolution steps of the computation 32
7.0.9 Execution time of the computation 32

8 aeq (library) 33
8.1 Usage and interface 33
8.2 Documentation on multifiles 33
aidomain/1 (pred) 33
aidom.init_abstract_domain/2 (pred) 33
aidom.amgu/5 (pred) 33
aidom.augment_asub/4 (pred) 33
aidom.augment_two_asub/4 (pred) 33
aidom.call_to_entry/10 (pred) 33
aidom.exit_to_prime/8 (pred) 33
aidom.project/6 (pred) 33
aidom.widencall/4 (pred) 33
aidom.needs/2 (pred) 34
aidom.widen/4 (pred) 34
aidom.compute_lub/3 (pred) 34
aidom.compute_clauses_lub/4 (pred) 34
aidom.compute_clauses_glb/4 (pred) 34
aidom.fixpoint_covered/3 (pred) 34
aidom.fixpoint_covered_gfp/3 (pred) 34
aidom.identical_abstract/3 (pred) 34
aidom.abs_sort/3 (pred) 34
aidom.extend/6 (pred) 34
aidom.less_or_equal/3 (pred) 34
aidom.glb/4 (pred) 34
aidom.eliminate_equivalent/3 (pred) 35
aidom.abs_subset/3 (pred) 35
aidom.call_to_success_fact/10 (pred) 35

aidom.special_builtin/6 (pred) 35
aidom.combined_special_builtin0/3 (pred) 35
aidom.body_succ_builtin/9 (pred) 35
aidom.split_combined_domain/4 (pred) 35
aidom.success_builtin/7 (pred) 35
aidom.call_to_success_builtin/7 (pred) 35
aidom.obtain_info/5 (pred) 35
aidom.input_interface/5 (pred) 35
aidom.input_user_interface/6 (pred) 35
aidom.asub_to_native/6 (pred) 36
aidom.concrete/4 (pred) 36
aidom.unknown_call/5 (pred) 36
aidom.unknown_entry/4 (pred) 36
aidom.empty_entry/4 (pred) 36
aidom.part_conc/5 (pred) 36
aidom.multi_part_conc/4 (pred) 36
aidom.collect_auxinfo_asub/4 (pred) 36
aidom.rename_auxinfo_asub/4 (pred) 36
aidom.dom_statistics/2 (pred) 36
aidom.contains_parameters/2 (pred) 36
8.3 Documentation on imports 37

9 def (library) 39
9.1 Usage and interface 39
9.2 Documentation on exports 39
call_to_entry/9 (pred) 39
exit_to_prime/7 (pred) 39
project/5 (pred) 39
compute_lub/2 (pred) 39
compute_lub_el/3 (pred) 40
glb/3 (pred) 40
abs_sort/2 (pred) 40
extend/5 (pred) 40
call_to_success_fact/9 (pred) 40
special_builtin/5 (pred) 40
success_builtin/6 (pred) 40
input_user_interface/5 (pred) 40
input_interface/4 (pred) 40
asub_to_native/5 (pred) 40
unknown_call/4 (pred) 40
unknown_entry/3 (pred) 40
empty_entry/3 (pred) 41
less_or_equal/2 (pred) 41
9.3 Documentation on multifiles 41
aidomain/1 (pred) 41
aidom.init_abstract_domain/2 (pred) 41
aidom.amgu/5 (pred) 41
aidom.augment_asub/4 (pred) 41
aidom.augment_two_asub/4 (pred) 41
aidom.call_to_entry/10 (pred) 41
aidom.exit_to_prime/8 (pred) 41
aidom.project/6 (pred) 41
aidom.widencall/4 (pred) 41
aidom.needs/2 (pred) 41
aidom.widen/4 (pred) 42
aidom.compute_lub/3 (pred) 42

aidom.compute_clauses_lub/4 (pred) 42
aidom.compute_clauses_glb/4 (pred) 42
aidom.fixpoint_covered/3 (pred) 42
aidom.fixpoint_covered_gfp/3 (pred) 42
aidom.identical_abstract/3 (pred) 42
aidom.abs_sort/3 (pred) 42
aidom.extend/6 (pred) 42
aidom.less_or_equal/3 (pred) 42
aidom.glb/4 (pred) 42
aidom.eliminate_equivalent/3 (pred) 43
aidom.abs_subset/3 (pred) 43
aidom.call_to_success_fact/10 (pred) 43
aidom.special_builtin/6 (pred) 43
aidom.combined_special_builtin0/3 (pred) 43
aidom.body_succ_builtin/9 (pred) 43
aidom.split_combined_domain/4 (pred) 43
aidom.success_builtin/7 (pred) 43
aidom.call_to_success_builtin/7 (pred) 43
aidom.obtain_info/5 (pred) 43
aidom.input_interface/5 (pred) 43
aidom.input_user_interface/6 (pred) 43
aidom.asub_to_native/6 (pred) 44
aidom.concrete/4 (pred) 44
aidom.unknown_call/5 (pred) 44
aidom.unknown_entry/4 (pred) 44
aidom.empty_entry/4 (pred) 44
aidom.part_conc/5 (pred) 44
aidom.multi_part_conc/4 (pred) 44
aidom.collect_auxinfo_asub/4 (pred) 44
aidom.rename_auxinfo_asub/4 (pred) 44
aidom.dom_statistics/2 (pred) 44
aidom.contains_parameters/2 (pred) 44
9.4 Documentation on imports 45

10 deftypes: defined types (based on termsd) (abstract domain) 47

10.1 Usage and interface 47
10.2 Documentation on multifiles 47
aidomain/1 (pred) 47
aidom.init_abstract_domain/2 (pred) 47
aidom.amgu/5 (pred) 47
aidom.augment_asub/4 (pred) 47
aidom.augment_two_asub/4 (pred) 47
aidom.call_to_entry/10 (pred) 47
aidom.exit_to_prime/8 (pred) 47
aidom.project/6 (pred) 47
aidom.widencall/4 (pred) 48
aidom.needs/2 (pred) 48
aidom.widen/4 (pred) 48
aidom.compute_lub/3 (pred) 48
aidom.compute_clauses_lub/4 (pred) 48
aidom.compute_clauses_glb/4 (pred) 48
aidom.fixpoint_covered/3 (pred) 48
aidom.fixpoint_covered_gfp/3 (pred) 48
aidom.identical_abstract/3 (pred) 48

aidom.abs_sort/3 (pred) 48
aidom.extend/6 (pred) 48
aidom.less_or_equal/3 (pred) 48
aidom.glb/4 (pred) 49
aidom.eliminate_equivalent/3 (pred) 49
aidom.abs_subset/3 (pred) 49
aidom.call_to_success_fact/10 (pred) 49
aidom.special_builtin/6 (pred) 49
aidom.combined_special_builtin0/3 (pred) 49
aidom.body_succ_builtin/9 (pred) 49
aidom.split_combined_domain/4 (pred) 49
aidom.success_builtin/7 (pred) 49
aidom.call_to_success_builtin/7 (pred) 49
aidom.obtain_info/5 (pred) 49
aidom.input_interface/5 (pred) 49
aidom.input_user_interface/6 (pred) 50
aidom.asub_to_native/6 (pred) 50
aidom.concrete/4 (pred) 50
aidom.unknown_call/5 (pred) 50
aidom.unknown_entry/4 (pred) 50
aidom.empty_entry/4 (pred) 50
aidom.part_conc/5 (pred) 50
aidom.multi_part_conc/4 (pred) 50
aidom.collect_auxinfo_asub/4 (pred) 50
aidom.rename_auxinfo_asub/4 (pred) 50
aidom.dom_statistics/2 (pred) 50
aidom.contains_parameters/2 (pred) 50
10.3 Documentation on imports 51

11 depthk (library) 53
11.1 Usage and interface 53
11.2 Documentation on multifiles 53
aidomain/1 (pred) 53
aidom.init_abstract_domain/2 (pred) 53
aidom.amgu/5 (pred) 53
aidom.augment_asub/4 (pred) 53
aidom.augment_two_asub/4 (pred) 53
aidom.call_to_entry/10 (pred) 53
aidom.exit_to_prime/8 (pred) 53
aidom.project/6 (pred) 53
aidom.widencall/4 (pred) 53
aidom.needs/2 (pred) 54
aidom.widen/4 (pred) 54
aidom.compute_lub/3 (pred) 54
aidom.compute_clauses_lub/4 (pred) 54
aidom.compute_clauses_glb/4 (pred) 54
aidom.fixpoint_covered/3 (pred) 54
aidom.fixpoint_covered_gfp/3 (pred) 54
aidom.identical_abstract/3 (pred) 54
aidom.abs_sort/3 (pred) 54
aidom.extend/6 (pred) 54
aidom.less_or_equal/3 (pred) 54
aidom.glb/4 (pred) 54
aidom.eliminate_equivalent/3 (pred) 55
aidom.abs_subset/3 (pred) 55
aidom.call_to_success_fact/10 (pred) 55

aidom.special_builtin/6 (pred) 55
aidom.combined_special_builtin0/3 (pred) 55
aidom.body_succ_builtin/9 (pred) 55
aidom.split_combined_domain/4 (pred) 55
aidom.success_builtin/7 (pred) 55
aidom.call_to_success_builtin/7 (pred) 55
aidom.obtain_info/5 (pred) 55
aidom.input_interface/5 (pred) 55
aidom.input_user_interface/6 (pred) 55
aidom.asub_to_native/6 (pred) 56
aidom.concrete/4 (pred) 56
aidom.unknown_call/5 (pred) 56
aidom.unknown_entry/4 (pred) 56
aidom.empty_entry/4 (pred) 56
aidom.part_conc/5 (pred) 56
aidom.multi_part_conc/4 (pred) 56
aidom.collect_auxinfo_asub/4 (pred) 56
aidom.rename_auxinfo_asub/4 (pred) 56
aidom.dom_statistics/2 (pred) 56
aidom.contains_parameters/2 (pred) 56
11.3 Documentation on imports 57

12 eterms: types with lnewiden_el/4 (abstract domain) 59

12.1 Usage and interface 59
12.2 Documentation on exports 60
get_type/3 (pred) 60
eterms_init_abstract_domain/1 (pred) 60
eterms_compute_lub/2 (pred) 60
eterms_compute_lub_el/3 (pred) 60
eterms_widencall/3 (pred) 60
eterms_needs/1 (pred) 60
eterms_widen/3 (pred) 60
eterms_call_to_entry/9 (pred) 61
eterms_exit_to_prime/7 (pred) 62
replace_names/3 (pred) 62
normal_asub/2 (pred) 62
update_names/2 (pred) 62
generate_subs_exit/4 (pred) 62
generate_subs/3 (pred) 63
eterms_project/5 (pred) 63
eterms_abs_sort/2 (pred) 63
eterms_extend/5 (pred) 63
eterms_less_or_equal/2 (pred) 64
eterms_glb/3 (pred) 64
eterms_glbnames/3 (pred) 64
eterms_concrete/3 (pred) 64
eterms_unknown_entry/3 (pred) 64
eterms_empty_entry/3 (pred) 65
eterms_unknown_call/4 (pred) 65
variables_are_top_type/2 (pred) 65
eterms_call_to_success_fact/9 (pred) 66
eterms_special_builtin/5 (pred) 66
eterms_success_builtin/6 (pred) 67
keys_same_value/3 (pred) 67

eterms_arg_call_to_success/9 (pred) 67
eterms_call_to_success_builtin/6 (pred) 67
eterms_obtain_info/4 (pred) 68
eterms_input_user_interface/5 (pred) 68
eterms_input_interface/4 (pred) 68
eterms_asub_to_native/5 (pred) 68
eterms_output_interface/2 (pred) 68
eterms_collect_auxinfo_asub/3 (pred) 69
eterms_rename_auxinfo_asub/3 (pred) 69
eterms_identical_abstract/2 (pred) 69
getargtypes/6 (pred) 69
replacetype/4 (pred) 69
getfunctors/2 (pred) 69
split_f/4 (pred) 69
getvalue/2 (pred) 69
unifytoterm/1 (pred) 69
abs_eval_arithcomp/4 (pred) 69
generateSucc0_cond/5 (pred) 69
abs_eval_arith/3 (pred) 69
getvalues_comp_cond/3 (pred) 70
get_list_names_is/2 (pred) 70
determinate_sel/3 (pred) 70
replaceintype/5 (pred) 70
eterms_multi_part_conc/3 (pred) 70
eterms_part_conc/4 (pred) 70
obtains_names/4 (pred) 70
12.3 Documentation on multifiles 70
aidomain/1 (pred) 70
aidom.init_abstract_domain/2 (pred) 70
aidom.amgu/5 (pred) 70
aidom.augment_asub/4 (pred) 70
aidom.augment_two_asub/4 (pred) 70
aidom.call_to_entry/10 (pred) 71
aidom.exit_to_prime/8 (pred) 71
aidom.project/6 (pred) 71
aidom.widencall/4 (pred) 71
aidom.needs/2 (pred) 71
aidom.widen/4 (pred) 71
aidom.compute_lub/3 (pred) 71
aidom.compute_clauses_lub/4 (pred) 71
aidom.compute_clauses_glb/4 (pred) 71
aidom.fixpoint_covered/3 (pred) 71
aidom.fixpoint_covered_gfp/3 (pred) 71
aidom.identical_abstract/3 (pred) 72
aidom.abs_sort/3 (pred) 72
aidom.extend/6 (pred) 72
aidom.less_or_equal/3 (pred) 72
aidom.glb/4 (pred) 72
aidom.eliminate_equivalent/3 (pred) 72
aidom.abs_subset/3 (pred) 72
aidom.call_to_success_fact/10 (pred) 72
aidom.special_builtin/6 (pred) 72
aidom.combined_special_builtin0/3 (pred) 72
aidom.body_succ_builtin/9 (pred) 72
aidom.split_combined_domain/4 (pred) 72
aidom.success_builtin/7 (pred) 73

aidom.call_to_success_builtin/7 (pred) 73
aidom.obtain_info/5 (pred) 73
aidom.input_interface/5 (pred) 73
aidom.input_user_interface/6 (pred) 73
aidom.asub_to_native/6 (pred) 73
aidom.concrete/4 (pred) 73
aidom.unknown_call/5 (pred) 73
aidom.unknown_entry/4 (pred) 73
aidom.empty_entry/4 (pred) 73
aidom.part_conc/5 (pred) 73
aidom.multi_part_conc/4 (pred) 73
aidom.collect_auxinfo_asub/4 (pred) 74
aidom.rename_auxinfo_asub/4 (pred) 74
aidom.dom_statistics/2 (pred) 74
aidom.contains_parameters/2 (pred) 74
12.4 Documentation on imports 74

13 etermsvar: eterms with variables (abstract domain) 75

13.1 Usage and interface 75
13.2 Documentation on exports 75
etermsvar_init_abstract_domain/1 (pred) 75
etermsvar_compute_lub/2 (pred) 76
etermsvar_compute_lub_el/3 (pred) 76
etermsvar_widencall/3 (pred) 76
etermsvar_needs/1 (pred) 76
etermsvar_widen/3 (pred) 76
etermsvar_call_to_entry/9 (pred) 76
etermsvar_exit_to_prime/7 (pred) 77
etermsvar_project/5 (pred) 77
etermsvar_abs_sort/2 (pred) 77
etermsvar_extend/5 (pred) 78
etermsvar_less_or_equal/2 (pred) 78
etermsvar_glb/3 (pred) 78
etermsvar_concrete/3 (pred) 78
etermsvar_unknown_entry/3 (pred) 79
etermsvar_empty_entry/3 (pred) 79
etermsvar_unknown_call/4 (pred) 79
etermsvar_call_to_success_fact/9 (pred) 79
etermsvar_special_builtin/5 (pred) 80
etermsvar_success_builtin/6 (pred) 80
etermsvar_arg_call_to_success/9 (pred) 80
etermsvar_call_to_success_builtin/6 (pred) 81
etermsvar_obtain_info/4 (pred) 81
etermsvar_input_user_interface/5 (pred) 81
etermsvar_input_interface/4 (pred) 81
etermsvar_asub_to_native/5 (pred) 81
etermsvar_output_interface/2 (pred) 81
etermsvar_collect_auxinfo_asub/3 (pred) 81
etermsvar_rename_auxinfo_asub/3 (pred) 81
etermsvar_identical_abstract/2 (pred) 82
etermsvar_multi_part_conc/3 (pred) 82
etermsvar_part_conc/4 (pred) 82
13.3 Documentation on multifiles 82
aidomain/1 (pred) 82

aidom.init_abstract_domain/2 (pred) 82
aidom.amgu/5 (pred) 82
aidom.augment_asub/4 (pred) 82
aidom.augment_two_asub/4 (pred) 82
aidom.call_to_entry/10 (pred) 82
aidom.exit_to_prime/8 (pred) 82
aidom.project/6 (pred) 82
aidom.widencall/4 (pred) 82
aidom.needs/2 (pred) 83
aidom.widen/4 (pred) 83
aidom.compute_lub/3 (pred) 83
aidom.compute_clauses_lub/4 (pred) 83
aidom.compute_clauses_glb/4 (pred) 83
aidom.fixpoint_covered/3 (pred) 83
aidom.fixpoint_covered_gfp/3 (pred) 83
aidom.identical_abstract/3 (pred) 83
aidom.abs_sort/3 (pred) 83
aidom.extend/6 (pred) 83
aidom.less_or_equal/3 (pred) 83
aidom.glb/4 (pred) 84
aidom.eliminate_equivalent/3 (pred) 84
aidom.abs_subset/3 (pred) 84
aidom.call_to_success_fact/10 (pred) 84
aidom.special_builtin/6 (pred) 84
aidom.combined_special_builtin0/3 (pred) 84
aidom.body_succ_builtin/9 (pred) 84
aidom.split_combined_domain/4 (pred) 84
aidom.success_builtin/7 (pred) 84
aidom.call_to_success_builtin/7 (pred) 84
aidom.obtain_info/5 (pred) 84
aidom.input_interface/5 (pred) 84
aidom.input_user_interface/6 (pred) 85
aidom.asub_to_native/6 (pred) 85
aidom.concrete/4 (pred) 85
aidom.unknown_call/5 (pred) 85
aidom.unknown_entry/4 (pred) 85
aidom.empty_entry/4 (pred) 85
aidom.part_conc/5 (pred) 85
aidom.multi_part_conc/4 (pred) 85
aidom.collect_auxinfo_asub/4 (pred) 85
aidom.rename_auxinfo_asub/4 (pred) 85
aidom.dom_statistics/2 (pred) 85
aidom.contains_parameters/2 (pred) 85
13.4 Documentation on imports 86

14 frdef (library) 87

14.1 Usage and interface 87
14.2 Documentation on exports 87
frdef_call_to_entry/9 (pred) 87
frdef_call_to_success_fact/9 (pred) 87
frdef_compute_lub/2 (pred) 87
frdef_exit_to_prime/7 (pred) 87
frdef_extend/5 (pred) 88
frdef_identical_abstract/2 (pred) 88
frdef_input_user_interface/5 (pred) 88
frdef_input_interface/4 (pred) 88
frdef_less_or_equal/2 (pred) 88
frdef_glb/3 (pred) 88
frdef_asub_to_native/5 (pred) 88
frdef_project/5 (pred) 88
frdef_abs_sort/2 (pred) 88
frdef_special_builtin/5 (pred) 88
frdef_success_builtin/6 (pred) 88
frdef_unknown_call/4 (pred) 89
frdef_unknown_entry/3 (pred) 89
frdef_empty_entry/3 (pred) 89
14.3 Documentation on multifiles 89
aidomain/1 (pred) 89
aidom.init_abstract_domain/2 (pred) 89
aidom.amgu/5 (pred) 89
aidom.augment_asub/4 (pred) 89
aidom.augment_two_asub/4 (pred) 89
aidom.call_to_entry/10 (pred) 89
aidom.exit_to_prime/8 (pred) 89
aidom.project/6 (pred) 89
aidom.widencall/4 (pred) 89
aidom.needs/2 (pred) 90
aidom.widen/4 (pred) 90
aidom.compute_lub/3 (pred) 90
aidom.compute_clauses_lub/4 (pred) 90
aidom.compute_clauses_glb/4 (pred) 90
aidom.fixpoint_covered/3 (pred) 90
aidom.fixpoint_covered_gfp/3 (pred) 90
aidom.identical_abstract/3 (pred) 90
aidom.abs_sort/3 (pred) 90
aidom.extend/6 (pred) 90
aidom.less_or_equal/3 (pred) 90
aidom.glb/4 (pred) 91
aidom.eliminate_equivalent/3 (pred) 91
aidom.abs_subset/3 (pred) 91
aidom.call_to_success_fact/10 (pred) 91
aidom.special_builtin/6 (pred) 91
aidom.combined_special_builtin0/3 (pred) 91
aidom.body_succ_builtin/9 (pred) 91
aidom.split_combined_domain/4 (pred) 91
aidom.success_builtin/7 (pred) 91
aidom.call_to_success_builtin/7 (pred) 91
aidom.obtain_info/5 (pred) 91
aidom.input_interface/5 (pred) 91
aidom.input_user_interface/6 (pred) 92
aidom.asub_to_native/6 (pred) 92

aidom.concrete/4 (pred) 92
aidom.unknown_call/5 (pred) 92
aidom.unknown_entry/4 (pred) 92
aidom.empty_entry/4 (pred) 92
aidom.part_conc/5 (pred) 92
aidom.multi_part_conc/4 (pred) 92
aidom.collect_auxinfo_asub/4 (pred) 92
aidom.rename_auxinfo_asub/4 (pred) 92
aidom.dom_statistics/2 (pred) 92
aidom.contains_parameters/2 (pred) 92
14.4 Documentation on imports 93

15 fr_top (library) 95
15.1 Usage and interface 95
15.2 Documentation on exports 95
fr_call_to_entry/9 (pred) 95
fr_call_to_success_fact/9 (pred) 95
fr_compute_lub/2 (pred) 95
fr_exit_to_prime/7 (pred) 95
fr_extend/5 (pred) 96
fr_identical_abstract/2 (pred) 96
fr_input_user_interface/5 (pred) 96
fr_input_interface/4 (pred) 96
fr_less_or_equal/2 (pred) 96
fr_glb/3 (pred) 96
fr_output_interface/3 (pred) 96
fr_project/5 (pred) 96
fr_abs_sort/2 (pred) 96
fr_special_builtin/5 (pred) 96
fr_success_builtin/6 (pred) 96
fr_asub_to_native/5 (pred) 97
fr_unknown_call/4 (pred) 97
fr_unknown_entry/3 (pred) 97
fr_empty_entry/3 (pred) 97
get_free_vars/3 (pred) 97
15.3 Documentation on multifiles 97
aidomain/1 (pred) 97
aidom.init_abstract_domain/2 (pred) 97
aidom.amgu/5 (pred) 97
aidom.augment_asub/4 (pred) 97
aidom.augment_two_asub/4 (pred) 97
aidom.call_to_entry/10 (pred) 97
aidom.exit_to_prime/8 (pred) 97
aidom.project/6 (pred) 98
aidom.widencall/4 (pred) 98
aidom.needs/2 (pred) 98
aidom.widen/4 (pred) 98
aidom.compute_lub/3 (pred) 98
aidom.compute_clauses_lub/4 (pred) 98
aidom.compute_clauses_glb/4 (pred) 98
aidom.fixpoint_covered/3 (pred) 98
aidom.fixpoint_covered_gfp/3 (pred) 98
aidom.identical_abstract/3 (pred) 98
aidom.abs_sort/3 (pred) 98
aidom.extend/6 (pred) 99
aidom.less_or_equal/3 (pred) 99

aidom.glb/4 (pred) 99
aidom.eliminate_equivalent/3 (pred) 99
aidom.abs_subset/3 (pred) 99
aidom.call_to_success_fact/10 (pred) 99
aidom.special_builtin/6 (pred) 99
aidom.combined_special_builtin0/3 (pred) 99
aidom.body_succ_builtin/9 (pred) 99
aidom.split_combined_domain/4 (pred) 99
aidom.success_builtin/7 (pred) 99
aidom.call_to_success_builtin/7 (pred) 99
aidom.obtain_info/5 (pred) 100
aidom.input_interface/5 (pred) 100
aidom.input_user_interface/6 (pred) 100
aidom.asub_to_native/6 (pred) 100
aidom.concrete/4 (pred) 100
aidom.unknown_call/5 (pred) 100
aidom.unknown_entry/4 (pred) 100
aidom.empty_entry/4 (pred) 100
aidom.part_conc/5 (pred) 100
aidom.multi_part_conc/4 (pred) 100
aidom.collect_auxinfo_asub/4 (pred) 100
aidom.rename_auxinfo_asub/4 (pred) 100
aidom.dom_statistics/2 (pred) 101
aidom.contains_parameters/2 (pred) 101
15.4 Documentation on imports 101

16 Simple groundness abstract domain 103

16.1 Usage and interface 103
16.2 Documentation on multifiles 103
aidomain/1 (pred) 103
aidom.init_abstract_domain/2 (pred) 103
aidom.amgu/5 (pred) 103
aidom.augment_asub/4 (pred) 103
aidom.augment_two_asub/4 (pred) 103
aidom.call_to_entry/10 (pred) 103
aidom.exit_to_prime/8 (pred) 104
aidom.project/6 (pred) 104
aidom.widencall/4 (pred) 104
aidom.needs/2 (pred) 104
aidom.widen/4 (pred) 104
aidom.compute_lub/3 (pred) 104
aidom.compute_clauses_lub/4 (pred) 104
aidom.compute_clauses_glb/4 (pred) 104
aidom.fixpoint_covered/3 (pred) 104
aidom.fixpoint_covered_gfp/3 (pred) 104
aidom.identical_abstract/3 (pred) 104
aidom.abs_sort/3 (pred) 104
aidom.extend/6 (pred) 105
aidom.less_or_equal/3 (pred) 105
aidom.glb/4 (pred) 105
aidom.eliminate_equivalent/3 (pred) 105
aidom.abs_subset/3 (pred) 105
aidom.call_to_success_fact/10 (pred) 105
aidom.special_builtin/6 (pred) 105
aidom.combined_special_builtin0/3 (pred) 105
aidom.body_succ_builtin/9 (pred) 105

aidom.split_combined_domain/4 (pred) 105
aidom.success_builtin/7 (pred) 105
aidom.call_to_success_builtin/7 (pred) 105
aidom.obtain_info/5 (pred) 106
aidom.input_interface/5 (pred) 106
aidom.input_user_interface/6 (pred) 106
aidom.asub_to_native/6 (pred) 106
aidom.concrete/4 (pred) 106
aidom.unknown_call/5 (pred) 106
aidom.unknown_entry/4 (pred) 106
aidom.empty_entry/4 (pred) 106
aidom.part_conc/5 (pred) 106
aidom.multi_part_conc/4 (pred) 106
aidom.collect_auxinfo_asub/4 (pred) 106
aidom.rename_auxinfo_asub/4 (pred) 106
aidom.dom_statistics/2 (pred) 107
aidom.contains_parameters/2 (pred) 107
16.3 Documentation on internals 107
asub/1 (prop) 107
asub_elem/1 (prop) 107
gr_mode/1 (regtype) 107
extrainfo/1 (prop) 107
binds/1 (prop) 107
binding/1 (prop) 107
16.4 Documentation on imports 108

17 lsign domain 109

17.1 Usage and interface 109
17.2 Documentation on exports 109
lsign_init_abstract_domain/1 (pred) 109
lsign_call_to_entry/9 (pred) 109
lsign_call_to_success_fact/9 (pred) 109
lsign_compute_lub/2 (pred) 110
lsign_extend/5 (pred) 110
lsign_eliminate_equivalent/2 (pred) 110
lsign_exit_to_prime/7 (pred) 110
lsign_global_info/5 (pred) 110
lsign_input_user_interface/5 (pred) 110
lsign_input_interface/4 (pred) 110
lsign_asub_to_native/5 (pred) 110
lsign_abs_subset/2 (pred) 110
lsign_less_or_equal/2 (pred) 110
lsign_glb/3 (pred) 110
lsign_project/5 (pred) 110
lsign_abs_sort/2 (pred) 111
lsign_special_builtin/5 (pred) 111
lsign_success_builtin/6 (pred) 111
lsign_unknown_call/4 (pred) 111
lsign_unknown_entry/3 (pred) 111
lsign_empty_entry/3 (pred) 111
lsign_sum/3 (pred) 111
lsign_output_interface/2 (pred) 111
lsign_propagate_fixpoint/8 (pred) 111
17.3 Documentation on multifiles 111
aidomain/1 (pred) 111
aidom.init_abstract_domain/2 (pred) 111

aidom.amgu/5 (pred) 111
aidom.augment_asub/4 (pred) 112
aidom.augment_two_asub/4 (pred) 112
aidom.call_to_entry/10 (pred) 112
aidom.exit_to_prime/8 (pred) 112
aidom.project/6 (pred) 112
aidom.widencall/4 (pred) 112
aidom.needs/2 (pred) 112
aidom.widen/4 (pred) 112
aidom.compute_lub/3 (pred) 112
aidom.compute_clauses_lub/4 (pred) 112
aidom.compute_clauses_glb/4 (pred) 112
aidom.fixpoint_covered/3 (pred) 113
aidom.fixpoint_covered_gfp/3 (pred) 113
aidom.identical_abstract/3 (pred) 113
aidom.abs_sort/3 (pred) 113
aidom.extend/6 (pred) 113
aidom.less_or_equal/3 (pred) 113
aidom.glb/4 (pred) 113
aidom.eliminate_equivalent/3 (pred) 113
aidom.abs_subset/3 (pred) 113
aidom.call_to_success_fact/10 (pred) 113
aidom.special_builtin/6 (pred) 113
aidom.combined_special_builtin0/3 (pred) 113
aidom.body_succ_builtin/9 (pred) 114
aidom.split_combined_domain/4 (pred) 114
aidom.success_builtin/7 (pred) 114
aidom.call_to_success_builtin/7 (pred) 114
aidom.obtain_info/5 (pred) 114
aidom.input_interface/5 (pred) 114
aidom.input_user_interface/6 (pred) 114
aidom.asub_to_native/6 (pred) 114
aidom.concrete/4 (pred) 114
aidom.unknown_call/5 (pred) 114
aidom.unknown_entry/4 (pred) 114
aidom.empty_entry/4 (pred) 114
aidom.part_conc/5 (pred) 115
aidom.multi_part_conc/4 (pred) 115
aidom.collect_auxinfo_asub/4 (pred) 115
aidom.rename_auxinfo_asub/4 (pred) 115
aidom.dom_statistics/2 (pred) 115
aidom.contains_parameters/2 (pred) 115
17.4 Documentation on imports 115

18 lsigndiff domain 117
18.1 Usage and interface 117
18.2 Documentation on exports 117
difflsign_call_to_entry/9 (pred) 117
difflsign_call_to_success_fact/9 (pred) 117
difflsign_compute_lub/2 (pred) 117
difflsign_exit_to_prime/7 (pred) 118
difflsign_extend/5 (pred) 118
difflsign_input_user_interface/5 (pred) 118
difflsign_input_interface/4 (pred) 118
difflsign_asub_to_native/5 (pred) 118
difflsign_less_or_equal/2 (pred) 118
difflsign_glb/3 (pred) 118
difflsign_project/5 (pred) 118
difflsign_abs_sort/2 (pred) 118
difflsign_special_builtin/5 (pred) 118
difflsign_success_builtin/6 (pred) 118
difflsign_unknown_call/4 (pred) 118
difflsign_unknown_entry/3 (pred) 119
difflsign_empty_entry/3 (pred) 119
18.3 Documentation on multifiles 119
aidomain/1 (pred) 119
aidom.init_abstract_domain/2 (pred) 119
aidom.amgu/5 (pred) 119
aidom.augment_asub/4 (pred) 119
aidom.augment_two_asub/4 (pred) 119
aidom.call_to_entry/10 (pred) 119
aidom.exit_to_prime/8 (pred) 119
aidom.project/6 (pred) 119
aidom.widencall/4 (pred) 119
aidom.needs/2 (pred) 119
aidom.widen/4 (pred) 120
aidom.compute_lub/3 (pred) 120
aidom.compute_clauses_lub/4 (pred) 120
aidom.compute_clauses_glb/4 (pred) 120
aidom.fixpoint_covered/3 (pred) 120
aidom.fixpoint_covered_gfp/3 (pred) 120
aidom.identical_abstract/3 (pred) 120
aidom.abs_sort/3 (pred) 120
aidom.extend/6 (pred) 120
aidom.less_or_equal/3 (pred) 120
aidom.glb/4 (pred) 120
aidom.eliminate_equivalent/3 (pred) 121
aidom.abs_subset/3 (pred) 121
aidom.call_to_success_fact/10 (pred) 121
aidom.special_builtin/6 (pred) 121
aidom.combined_special_builtin0/3 (pred) 121
aidom.body_succ_builtin/9 (pred) 121
aidom.split_combined_domain/4 (pred) 121
aidom.success_builtin/7 (pred) 121
aidom.call_to_success_builtin/7 (pred) 121
aidom.obtain_info/5 (pred) 121
aidom.input_interface/5 (pred) 121
aidom.input_user_interface/6 (pred) 121
aidom.asub_to_native/6 (pred) 122
aidom.concrete/4 (pred) 122

aidom.unknown_call/5 (pred) 122
aidom.unknown_entry/4 (pred) 122
aidom.empty_entry/4 (pred) 122
aidom.part_conc/5 (pred) 122
aidom.multi_part_conc/4 (pred) 122
aidom.collect_auxinfo_asub/4 (pred) 122
aidom.rename_auxinfo_asub/4 (pred) 122
aidom.dom_statistics/2 (pred) 122
aidom.contains_parameters/2 (pred) 122
18.4 Documentation on imports 123

19 detplai (library) 125

19.1 Usage and interface 125
19.2 Documentation on exports 125
det_init_abstract_domain/1 (pred) 125
det_call_to_entry/9 (pred) 125
det_exit_to_prime/7 (pred) 125
det_project/5 (pred) 126
det_extend/5 (pred) 126
det_widen/3 (pred) 126
det_widencall/3 (pred) 126
det_compute_lub/2 (pred) 126
det_compute_clauses_lub/3 (pred) 126
det_glb/3 (pred) 126
det_eliminate_equivalent/2 (pred) 126
det_less_or_equal/2 (pred) 126
det_identical_abstract/2 (pred) 126
det_abs_sort/2 (pred) 126
det_call_to_success_fact/9 (pred) 126
det_split_combined_domain/3 (pred) 127
det_special_builtin/5 (pred) 127
det_combined_special_builtin0/2 (pred) 127
det_success_builtin/6 (pred) 127
det_input_interface/4 (pred) 127
det_input_user_interface/5 (pred) 127
det_asub_to_native/5 (pred) 127
det_unknown_call/4 (pred) 127
det_unknown_entry/3 (pred) 127
det_empty_entry/3 (pred) 127
det_dom_statistics/1 (pred) 127
det_obtain_info/4 (pred) 127
det_asub/1 (regtype) 128
asub/4 (pred) 128
det_collect_auxinfo_asub/3 (pred) 128
det_rename_auxinfo_asub/3 (pred) 128
19.3 Documentation on multifiles 128
aidomain/1 (pred) 128
aidom.init_abstract_domain/2 (pred) 128
aidom.amgu/5 (pred) 128
aidom.augment_asub/4 (pred) 128
aidom.augment_two_asub/4 (pred) 128
aidom.call_to_entry/10 (pred) 128
aidom.exit_to_prime/8 (pred) 128
aidom.project/6 (pred) 129
aidom.widencall/4 (pred) 129
aidom.needs/2 (pred) 129

aidom.widen/4 (pred) 129
aidom.compute_lub/3 (pred) 129
aidom.compute_clauses_lub/4 (pred) 129
aidom.compute_clauses_glb/4 (pred) 129
aidom.fixpoint_covered/3 (pred) 129
aidom.fixpoint_covered_gfp/3 (pred) 129
aidom.identical_abstract/3 (pred) 129
aidom.abs_sort/3 (pred) 129
aidom.extend/6 (pred) 130
aidom.less_or_equal/3 (pred) 130
aidom.glb/4 (pred) 130
aidom.eliminate_equivalent/3 (pred) 130
aidom.abs_subset/3 (pred) 130
aidom.call_to_success_fact/10 (pred) 130
aidom.special_builtin/6 (pred) 130
aidom.combined_special_builtin0/3 (pred) 130
aidom.body_succ_builtin/9 (pred) 130
aidom.split_combined_domain/4 (pred) 130
aidom.success_builtin/7 (pred) 130
aidom.call_to_success_builtin/7 (pred) 130
aidom.obtain_info/5 (pred) 131
aidom.input_interface/5 (pred) 131
aidom.input_user_interface/6 (pred) 131
aidom.asub_to_native/6 (pred) 131
aidom.concrete/4 (pred) 131
aidom.unknown_call/5 (pred) 131
aidom.unknown_entry/4 (pred) 131
aidom.empty_entry/4 (pred) 131
aidom.part_conc/5 (pred) 131
aidom.multi_part_conc/4 (pred) 131
aidom.collect_auxinfo_asub/4 (pred) 131
aidom.rename_auxinfo_asub/4 (pred) 131
aidom.dom_statistics/2 (pred) 132
aidom.contains_parameters/2 (pred) 132
19.4 Documentation on imports 132

20 nfplai (library) 133
20.1 Usage and interface 133
20.2 Documentation on exports 133
nf_init_abstract_domain/1 (pred) 133
nf_call_to_entry/9 (pred) 133
nf_exit_to_prime/7 (pred) 133
nf_project/5 (pred) 134
nf_extend/5 (pred) 134
nf_widen/3 (pred) 134
nf_widencall/3 (pred) 134
nf_compute_lub/2 (pred) 134
nf_compute_clauses_lub/3 (pred) 134
nf_glb/3 (pred) 134
nf_eliminate_equivalent/2 (pred) 134
nf_less_or_equal/2 (pred) 135
nf_identical_abstract/2 (pred) 135
nf_abs_sort/2 (pred) 135
nf_call_to_success_fact/9 (pred) 135
nf_split_combined_domain/3 (pred) 135
nf_special_builtin/5 (pred) 135

nf_combined_special_builtin0/2 (pred) 135
nf_success_builtin/6 (pred) 135
nf_input_interface/4 (pred) 135
nf_input_user_interface/5 (pred) 135
nf_asub_to_native/5 (pred) 135
nf_unknown_call/4 (pred) 135
nf_unknown_entry/3 (pred) 136
nf_empty_entry/3 (pred) 136
nf_dom_statistics/1 (pred) 136
nf_obtain_info/4 (pred) 136
nf_par_asub/2 (regtype) 136
nf_asub/1 (regtype) 136
nf_pred_asub/1 (regtype) 136
nf_pred_asub_sl/1 (regtype) 136
asub/4 (pred) 137
nf_collect_auxinfo_asub/3 (pred) 137
nf_rename_auxinfo_asub/3 (pred) 137
20.3 Documentation on multifiles 137
aidomain/1 (pred) 137
aidom.init_abstract_domain/2 (pred) 137
aidom.amgu/5 (pred) 137
aidom.augment_asub/4 (pred) 137
aidom.augment_two_asub/4 (pred) 137
aidom.call_to_entry/10 (pred) 137
aidom.exit_to_prime/8 (pred) 137
aidom.project/6 (pred) 137
aidom.widencall/4 (pred) 137
aidom.needs/2 (pred) 138
aidom.widen/4 (pred) 138
aidom.compute_lub/3 (pred) 138
aidom.compute_clauses_lub/4 (pred) 138
aidom.compute_clauses_glb/4 (pred) 138
aidom.fixpoint_covered/3 (pred) 138
aidom.fixpoint_covered_gfp/3 (pred) 138
aidom.identical_abstract/3 (pred) 138
aidom.abs_sort/3 (pred) 138
aidom.extend/6 (pred) 138
aidom.less_or_equal/3 (pred) 138
aidom.glb/4 (pred) 139
aidom.eliminate_equivalent/3 (pred) 139
aidom.abs_subset/3 (pred) 139
aidom.call_to_success_fact/10 (pred) 139
aidom.special_builtin/6 (pred) 139
aidom.combined_special_builtin0/3 (pred) 139
aidom.body_succ_builtin/9 (pred) 139
aidom.split_combined_domain/4 (pred) 139
aidom.success_builtin/7 (pred) 139
aidom.call_to_success_builtin/7 (pred) 139
aidom.obtain_info/5 (pred) 139
aidom.input_interface/5 (pred) 139
aidom.input_user_interface/6 (pred) 140
aidom.asub_to_native/6 (pred) 140
aidom.concrete/4 (pred) 140
aidom.unknown_call/5 (pred) 140
aidom.unknown_entry/4 (pred) 140
aidom.empty_entry/4 (pred) 140

aidom.part_conc/5 (pred) 140
aidom.multi_part_conc/4 (pred) 140
aidom.collect_auxinfo_asub/4 (pred) 140
aidom.rename_auxinfo_asub/4 (pred) 140
aidom.dom_statistics/2 (pred) 140
aidom.contains_parameters/2 (pred) 140
20.4 Documentation on imports 141

21 Interval Domain 143
21.1 Usage and interface 143
21.2 Documentation on multifiles 143
aidomain/1 (pred) 143
aidom.init_abstract_domain/2 (pred) 143
aidom.amgu/5 (pred) 143
aidom.augment_asub/4 (pred) 143
aidom.augment_two_asub/4 (pred) 143
aidom.call_to_entry/10 (pred) 143
aidom.exit_to_prime/8 (pred) 143
aidom.project/6 (pred) 144
aidom.widencall/4 (pred) 144
aidom.needs/2 (pred) 144
aidom.widen/4 (pred) 144
aidom.compute_lub/3 (pred) 144
aidom.compute_clauses_lub/4 (pred) 144
aidom.compute_clauses_glb/4 (pred) 144
aidom.fixpoint_covered/3 (pred) 144
aidom.fixpoint_covered_gfp/3 (pred) 144
aidom.identical_abstract/3 (pred) 144
aidom.abs_sort/3 (pred) 144
aidom.extend/6 (pred) 145
aidom.less_or_equal/3 (pred) 145
aidom.glb/4 (pred) 145
aidom.eliminate_equivalent/3 (pred) 145
aidom.abs_subset/3 (pred) 145
aidom.call_to_success_fact/10 (pred) 145
aidom.special_builtin/6 (pred) 145
aidom.combined_special_builtin0/3 (pred) 145
aidom.body_succ_builtin/9 (pred) 145
aidom.split_combined_domain/4 (pred) 145
aidom.success_builtin/7 (pred) 145
aidom.call_to_success_builtin/7 (pred) 145
aidom.obtain_info/5 (pred) 146
aidom.input_interface/5 (pred) 146
aidom.input_user_interface/6 (pred) 146
aidom.asub_to_native/6 (pred) 146
aidom.concrete/4 (pred) 146
aidom.unknown_call/5 (pred) 146
aidom.unknown_entry/4 (pred) 146
aidom.empty_entry/4 (pred) 146
aidom.part_conc/5 (pred) 146
aidom.multi_part_conc/4 (pred) 146
aidom.collect_auxinfo_asub/4 (pred) 146
aidom.rename_auxinfo_asub/4 (pred) 146
aidom.dom_statistics/2 (pred) 147
aidom.contains_parameters/2 (pred) 147
21.3 Documentation on internals 147

nonrel_top/2 (pred) 147
nonrel_bot/2 (pred) 147
nonrel_var_elem/2 (pred) 147
nonrel_less_or_equal_elem/3 (pred) 147
nonrel_compute_glb_elem/4 (pred) 147
nonrel_compute_lub_elem/4 (pred) 148
nonrel_widen_elem/4 (pred) 148
nonrel_amgu/5 (pred) 148
nonrel_unknown_entry/4 (pred) 149
nonrel_abs_sort/2 (pred) 149
nonrel_project/5 (pred) 149
nonrel_call_to_entry/10 (pred) 149
nonrel_exit_to_prime/8 (pred) 150
nonrel_compute_lub/3 (pred) 151
nonrel_extend/6 (pred) 151
nonrel_call_to_success_fact/10 (pred) 151
nonrel_special_builtin/6 (pred) 152
nonrel_success_builtin/7 (pred) 152
nonrel_call_to_success_builtin/7 (pred) 153
nonrel_input_user_interface/6 (pred) 153
nonrel_input_interface/5 (pred) 153
nonrel_asub_to_native/6 (pred) 154
nonrel_unknown_call/5 (pred) 154
nonrel_less_or_equal/3 (pred) 154
nonrel_glb/4 (pred) 155
nonrel_identical_abstract/2 (pred) 155
nonrel_widen/4 (pred) 155
nonrel_widencall/4 (pred) 155
21.4 Documentation on imports 156

22 PD domain 157
22.1 Usage and interface 157
22.2 Documentation on multifiles 157
aidomain/1 (pred) 157
aidom.init_abstract_domain/2 (pred) 157
aidom.amgu/5 (pred) 157
aidom.augment_asub/4 (pred) 157
aidom.augment_two_asub/4 (pred) 157
aidom.call_to_entry/10 (pred) 157
aidom.exit_to_prime/8 (pred) 157
aidom.project/6 (pred) 157
aidom.widencall/4 (pred) 157
aidom.needs/2 (pred) 158
aidom.widen/4 (pred) 158
aidom.compute_lub/3 (pred) 158
aidom.compute_clauses_lub/4 (pred) 158
aidom.compute_clauses_glb/4 (pred) 158
aidom.fixpoint_covered/3 (pred) 158
aidom.fixpoint_covered_gfp/3 (pred) 158
aidom.identical_abstract/3 (pred) 158
aidom.abs_sort/3 (pred) 158
aidom.extend/6 (pred) 158
aidom.less_or_equal/3 (pred) 158
aidom.glb/4 (pred) 159
aidom.eliminate_equivalent/3 (pred) 159
aidom.abs_subset/3 (pred) 159

aidom.call_to_success_fact/10 (pred) 159
aidom.special_builtin/6 (pred) 159
aidom.combined_special_builtin0/3 (pred) 159
aidom.body_succ_builtin/9 (pred) 159
aidom.split_combined_domain/4 (pred) 159
aidom.success_builtin/7 (pred) 159
aidom.call_to_success_builtin/7 (pred) 159
aidom.obtain_info/5 (pred) 159
aidom.input_interface/5 (pred) 159
aidom.input_user_interface/6 (pred) 160
aidom.asub_to_native/6 (pred) 160
aidom.concrete/4 (pred) 160
aidom.unknown_call/5 (pred) 160
aidom.unknown_entry/4 (pred) 160
aidom.empty_entry/4 (pred) 160
aidom.part_conc/5 (pred) 160
aidom.multi_part_conc/4 (pred) 160
aidom.collect_auxinfo_asub/4 (pred) 160
aidom.rename_auxinfo_asub/4 (pred) 160
aidom.dom_statistics/2 (pred) 160
aidom.contains_parameters/2 (pred) 160
22.3 Documentation on imports 161

23 PD domain with bottom 163

23.1 Usage and interface 163
23.2 Documentation on multifiles 163
aidomain/1 (pred) 163
aidom.init_abstract_domain/2 (pred) 163
aidom.amgu/5 (pred) 163
aidom.augment_asub/4 (pred) 163
aidom.augment_two_asub/4 (pred) 163
aidom.call_to_entry/10 (pred) 163
aidom.exit_to_prime/8 (pred) 163
aidom.project/6 (pred) 163
aidom.widencall/4 (pred) 164
aidom.needs/2 (pred) 164
aidom.widen/4 (pred) 164
aidom.compute_lub/3 (pred) 164
aidom.compute_clauses_lub/4 (pred) 164
aidom.compute_clauses_glb/4 (pred) 164
aidom.fixpoint_covered/3 (pred) 164
aidom.fixpoint_covered_gfp/3 (pred) 164
aidom.identical_abstract/3 (pred) 164
aidom.abs_sort/3 (pred) 164
aidom.extend/6 (pred) 164
aidom.less_or_equal/3 (pred) 164
aidom.glb/4 (pred) 165
aidom.eliminate_equivalent/3 (pred) 165
aidom.abs_subset/3 (pred) 165
aidom.call_to_success_fact/10 (pred) 165
aidom.special_builtin/6 (pred) 165
aidom.combined_special_builtin0/3 (pred) 165
aidom.body_succ_builtin/9 (pred) 165
aidom.split_combined_domain/4 (pred) 165
aidom.success_builtin/7 (pred) 165
aidom.call_to_success_builtin/7 (pred) 165

aidom.obtain_info/5 (pred) 165
aidom.input_interface/5 (pred) 165
aidom.input_user_interface/6 (pred) 166
aidom.asub_to_native/6 (pred) 166
aidom.concrete/4 (pred) 166
aidom.unknown_call/5 (pred) 166
aidom.unknown_entry/4 (pred) 166
aidom.empty_entry/4 (pred) 166
aidom.part_conc/5 (pred) 166
aidom.multi_part_conc/4 (pred) 166
aidom.collect_auxinfo_asub/4 (pred) 166
aidom.rename_auxinfo_asub/4 (pred) 166
aidom.dom_statistics/2 (pred) 166
aidom.contains_parameters/2 (pred) 166
23.3 Documentation on imports 167

24 polyhedra (library) 169
24.1 Usage and interface 169
24.2 Documentation on exports 169
polyhedra_initialize/0 (pred) 169
polyhedra_finalize/0 (pred) 169
less_or_equal/2 (pred) 169
input_user_interface/5 (pred) 169
24.3 Documentation on multifiles 170
aidomain/1 (pred) 170
aidom.init_abstract_domain/2 (pred) 170
aidom.amgu/5 (pred) 170
aidom.augment_asub/4 (pred) 170
aidom.augment_two_asub/4 (pred) 170
aidom.call_to_entry/10 (pred) 170
aidom.exit_to_prime/8 (pred) 170
aidom.project/6 (pred) 170
aidom.widencall/4 (pred) 170
aidom.needs/2 (pred) 170
aidom.widen/4 (pred) 170
aidom.compute_lub/3 (pred) 170
aidom.compute_clauses_lub/4 (pred) 171
aidom.compute_clauses_glb/4 (pred) 171
aidom.fixpoint_covered/3 (pred) 171
aidom.fixpoint_covered_gfp/3 (pred) 171
aidom.identical_abstract/3 (pred) 171
aidom.abs_sort/3 (pred) 171
aidom.extend/6 (pred) 171
aidom.less_or_equal/3 (pred) 171
aidom.glb/4 (pred) 171
aidom.eliminate_equivalent/3 (pred) 171
aidom.abs_subset/3 (pred) 171
aidom.call_to_success_fact/10 (pred) 172
aidom.special_builtin/6 (pred) 172
aidom.combined_special_builtin0/3 (pred) 172
aidom.body_succ_builtin/9 (pred) 172
aidom.split_combined_domain/4 (pred) 172
aidom.success_builtin/7 (pred) 172
aidom.call_to_success_builtin/7 (pred) 172
aidom.obtain_info/5 (pred) 172
aidom.input_interface/5 (pred) 172

aidom.input_user_interface/6 (pred) 172
aidom.asub_to_native/6 (pred) 172
aidom.concrete/4 (pred) 172
aidom.unknown_call/5 (pred) 173
aidom.unknown_entry/4 (pred) 173
aidom.empty_entry/4 (pred) 173
aidom.part_conc/5 (pred) 173
aidom.multi_part_conc/4 (pred) 173
aidom.collect_auxinfo_asub/4 (pred) 173
aidom.rename_auxinfo_asub/4 (pred) 173
aidom.dom_statistics/2 (pred) 173
aidom.contains_parameters/2 (pred) 173
24.4 Documentation on imports 173

25 ptypes: types with topological class widening (abstract domain) 175

25.1 Usage and interface 175
25.2 Documentation on multifiles 175
aidomain/1 (pred) 175
aidom.init_abstract_domain/2 (pred) 175
aidom.amgu/5 (pred) 175
aidom.augment_asub/4 (pred) 175
aidom.augment_two_asub/4 (pred) 175
aidom.call_to_entry/10 (pred) 175
aidom.exit_to_prime/8 (pred) 175
aidom.project/6 (pred) 175
aidom.widencall/4 (pred) 176
aidom.needs/2 (pred) 176
aidom.widen/4 (pred) 176
aidom.compute_lub/3 (pred) 176
aidom.compute_clauses_lub/4 (pred) 176
aidom.compute_clauses_glb/4 (pred) 176
aidom.fixpoint_covered/3 (pred) 176
aidom.fixpoint_covered_gfp/3 (pred) 176
aidom.identical_abstract/3 (pred) 176
aidom.abs_sort/3 (pred) 176
aidom.extend/6 (pred) 176
aidom.less_or_equal/3 (pred) 176
aidom.glb/4 (pred) 177
aidom.eliminate_equivalent/3 (pred) 177
aidom.abs_subset/3 (pred) 177
aidom.call_to_success_fact/10 (pred) 177
aidom.special_builtin/6 (pred) 177
aidom.combined_special_builtin0/3 (pred) 177
aidom.body_succ_builtin/9 (pred) 177
aidom.split_combined_domain/4 (pred) 177
aidom.success_builtin/7 (pred) 177
aidom.call_to_success_builtin/7 (pred) 177
aidom.obtain_info/5 (pred) 177
aidom.input_interface/5 (pred) 177
aidom.input_user_interface/6 (pred) 178
aidom.asub_to_native/6 (pred) 178
aidom.concrete/4 (pred) 178
aidom.unknown_call/5 (pred) 178
aidom.unknown_entry/4 (pred) 178

aidom.empty_entry/4 (pred) 178
aidom.part_conc/5 (pred) 178
aidom.multi_part_conc/4 (pred) 178
aidom.collect_auxinfo_asub/4 (pred) 178
aidom.rename_auxinfo_asub/4 (pred) 178
aidom.dom_statistics/2 (pred) 178
aidom.contains_parameters/2 (pred) 178
25.3 Documentation on imports 179

26 sharing+freeness (abstract domain) 181
26.1 Usage and interface 181
26.2 Documentation on exports 181
needs/1 (pred) 181
project/5 (pred) 181
project_freeness/3 (pred) 182
call_to_entry/9 (pred) 182
exit_to_prime/7 (pred) 182
abs_sort/2 (pred) 182
compute_lub/2 (pred) 182
compute_lub_el/3 (pred) 182
compute_lub_sh/3 (pred) 182
glb/3 (pred) 182
extend/5 (pred) 182
call_to_success_fact/9 (pred) 182
call_to_prime_fact/6 (pred) 182
unknown_entry/3 (pred) 182
empty_entry/3 (pred) 183
input_user_interface/5 (pred) 183
input_interface/4 (pred) 183
asub_to_native/5 (pred) 183
obtain_info/4 (pred) 183
obtain_info/3 (pred) 183
less_or_equal/2 (pred) 183
special_builtin/5 (pred) 183
success_builtin/6 (pred) 183
call_to_success_builtin/6 (pred) 183
take_coupled/3 (pred) 184
split_coupled/4 (pred) 184
all_terms_identical/2 (pred) 184
update_lambda_sf/5 (pred) 184
update_lambda_non_free/5 (pred) 184
partition_sf/4 (pred) 184
prune/5 (pred) 184
prune/4 (pred) 184
covering/3 (pred) 184
eliminate_non_element/4 (pred) 184
product/8 (pred) 184
insert_each/3 (pred) 185
obtain_freeness/2 (pred) 185
obtain_prime_var_var/3 (pred) 185
sh_free_vars_compatible/2 (pred) 185
make_dependence/5 (pred) 185
unknown_call/4 (pred) 185
values_equal/3 (pred) 185
values_differ/3 (pred) 185
change_values/4 (pred) 185

change_values_if_not_g/4 (pred) 185
change_values_if_f/4 (pred) 185
member_value_freeness_differ/3 (pred) 185
project_freeness_n/3 (pred) 186
propagate_non_freeness/5 (pred) 186
add_environment_vars/3 (pred) 186
26.3 Documentation on multifiles 186
aidomain/1 (pred) 186
aidom.init_abstract_domain/2 (pred) 186
aidom.amgu/5 (pred) 186
aidom.augment_asub/4 (pred) 186
aidom.augment_two_asub/4 (pred) 186
aidom.call_to_entry/10 (pred) 186
aidom.exit_to_prime/8 (pred) 186
aidom.project/6 (pred) 186
aidom.widencall/4 (pred) 186
aidom.needs/2 (pred) 187
aidom.widen/4 (pred) 187
aidom.compute_lub/3 (pred) 187
aidom.compute_clauses_lub/4 (pred) 187
aidom.compute_clauses_glb/4 (pred) 187
aidom.fixpoint_covered/3 (pred) 187
aidom.fixpoint_covered_gfp/3 (pred) 187
aidom.identical_abstract/3 (pred) 187
aidom.abs_sort/3 (pred) 187
aidom.extend/6 (pred) 187
aidom.less_or_equal/3 (pred) 187
aidom.glb/4 (pred) 188
aidom.eliminate_equivalent/3 (pred) 188
aidom.abs_subset/3 (pred) 188
aidom.call_to_success_fact/10 (pred) 188
aidom.special_builtin/6 (pred) 188
aidom.combined_special_builtin0/3 (pred) 188
aidom.body_succ_builtin/9 (pred) 188
aidom.split_combined_domain/4 (pred) 188
aidom.success_builtin/7 (pred) 188
aidom.call_to_success_builtin/7 (pred) 188
aidom.obtain_info/5 (pred) 188
aidom.input_interface/5 (pred) 188
aidom.input_user_interface/6 (pred) 189
aidom.asub_to_native/6 (pred) 189
aidom.concrete/4 (pred) 189
aidom.unknown_call/5 (pred) 189
aidom.unknown_entry/4 (pred) 189
aidom.empty_entry/4 (pred) 189
aidom.part_conc/5 (pred) 189
aidom.multi_part_conc/4 (pred) 189
aidom.collect_auxinfo_asub/4 (pred) 189
aidom.rename_auxinfo_asub/4 (pred) 189
aidom.dom_statistics/2 (pred) 189
aidom.contains_parameters/2 (pred) 189
26.4 Documentation on imports 190

27 amgu-based sharing+freeness domain 191
27.1 Usage and interface 191
27.2 Documentation on exports 191
call_to_entry/9 (pred) 191
exit_to_prime/7 (pred) 191
amgu/4 (pred) 191
augment_asub/3 (pred) 191
augment_asub0/3 (pred) 192
call_to_success_fact/9 (pred) 192
sharefree_delete_variables/3 (pred) 192
call_to_prime_fact/6 (pred) 192
special_builtin/5 (pred) 192
success_builtin/6 (pred) 192
call_to_success_builtin/6 (pred) 192
27.3 Documentation on multifiles 192
aidomain/1 (pred) 192
aidom.init_abstract_domain/2 (pred) 192
aidom.amgu/5 (pred) 192
aidom.augment_asub/4 (pred) 192
aidom.augment_two_asub/4 (pred) 192
aidom.call_to_entry/10 (pred) 193
aidom.exit_to_prime/8 (pred) 193
aidom.project/6 (pred) 193
aidom.widencall/4 (pred) 193
aidom.needs/2 (pred) 193
aidom.widen/4 (pred) 193
aidom.compute_lub/3 (pred) 193
aidom.compute_clauses_lub/4 (pred) 193
aidom.compute_clauses_glb/4 (pred) 193
aidom.fixpoint_covered/3 (pred) 193
aidom.fixpoint_covered_gfp/3 (pred) 193
aidom.identical_abstract/3 (pred) 194
aidom.abs_sort/3 (pred) 194
aidom.extend/6 (pred) 194
aidom.less_or_equal/3 (pred) 194
aidom.glb/4 (pred) 194
aidom.eliminate_equivalent/3 (pred) 194
aidom.abs_subset/3 (pred) 194
aidom.call_to_success_fact/10 (pred) 194
aidom.special_builtin/6 (pred) 194
aidom.combined_special_builtin0/3 (pred) 194
aidom.body_succ_builtin/9 (pred) 194
aidom.split_combined_domain/4 (pred) 194
aidom.success_builtin/7 (pred) 195
aidom.call_to_success_builtin/7 (pred) 195
aidom.obtain_info/5 (pred) 195
aidom.input_interface/5 (pred) 195
aidom.input_user_interface/6 (pred) 195
aidom.asub_to_native/6 (pred) 195
aidom.concrete/4 (pred) 195
aidom.unknown_call/5 (pred) 195
aidom.unknown_entry/4 (pred) 195
aidom.empty_entry/4 (pred) 195
aidom.part_conc/5 (pred) 195
aidom.multi_part_conc/4 (pred) 195
aidom.collect_auxinfo_asub/4 (pred) 196

aidom.rename_auxinfo_asub/4 (pred) 196
aidom.dom_statistics/2 (pred) 196
aidom.contains_parameters/2 (pred) 196
27.4 Documentation on imports 196

28 CLIQUE-Sharing+Freeness domain 197

28.1 Usage and interface 197
28.2 Documentation on exports 197
call_to_entry/9 (pred) 197
exit_to_prime/7 (pred) 197
extend/5 (pred) 197
project/5 (pred) 197
abs_sort/2 (pred) 198
identical_abstract/2 (pred) 198
less_or_equal/2 (pred) 198
call_to_success_fact/9 (pred) 198
compute_lub_el/3 (pred) 198
glb/3 (pred) 198
input_user_interface/5 (pred) 198
input_interface/4 (pred) 198
unknown_call/4 (pred) 198
empty_entry/3 (pred) 198
special_builtin/5 (pred) 198
28.3 Documentation on multifiles 199
aidomain/1 (pred) 199
aidom.init_abstract_domain/2 (pred) 199
aidom.amgu/5 (pred) 199
aidom.augment_asub/4 (pred) 199
aidom.augment_two_asub/4 (pred) 199
aidom.call_to_entry/10 (pred) 199
aidom.exit_to_prime/8 (pred) 199
aidom.project/6 (pred) 199
aidom.widencall/4 (pred) 199
aidom.needs/2 (pred) 199
aidom.widen/4 (pred) 199
aidom.compute_lub/3 (pred) 199
aidom.compute_clauses_lub/4 (pred) 200
aidom.compute_clauses_glb/4 (pred) 200
aidom.fixpoint_covered/3 (pred) 200
aidom.fixpoint_covered_gfp/3 (pred) 200
aidom.identical_abstract/3 (pred) 200
aidom.abs_sort/3 (pred) 200
aidom.extend/6 (pred) 200
aidom.less_or_equal/3 (pred) 200
aidom.glb/4 (pred) 200
aidom.eliminate_equivalent/3 (pred) 200
aidom.abs_subset/3 (pred) 200
aidom.call_to_success_fact/10 (pred) 201
aidom.special_builtin/6 (pred) 201
aidom.combined_special_builtin0/3 (pred) 201
aidom.body_succ_builtin/9 (pred) 201
aidom.split_combined_domain/4 (pred) 201
aidom.success_builtin/7 (pred) 201
aidom.call_to_success_builtin/7 (pred) 201
aidom.obtain_info/5 (pred) 201
aidom.input_interface/5 (pred) 201

aidom.input_user_interface/6 (pred) 201
aidom.asub_to_native/6 (pred) 201
aidom.concrete/4 (pred) 201
aidom.unknown_call/5 (pred) 202
aidom.unknown_entry/4 (pred) 202
aidom.empty_entry/4 (pred) 202
aidom.part_conc/5 (pred) 202
aidom.multi_part_conc/4 (pred) 202
aidom.collect_auxinfo_asub/4 (pred) 202
aidom.rename_auxinfo_asub/4 (pred) 202
aidom.dom_statistics/2 (pred) 202
aidom.contains_parameters/2 (pred) 202
28.4 Documentation on imports 202

29 CLIQUE-Sharing+Freeness+Def domain 203

29.1 Usage and interface 203
29.2 Documentation on multifiles 203
aidomain/1 (pred) 203
aidom.init_abstract_domain/2 (pred) 203
aidom.amgu/5 (pred) 203
aidom.augment_asub/4 (pred) 203
aidom.augment_two_asub/4 (pred) 203
aidom.call_to_entry/10 (pred) 203
aidom.exit_to_prime/8 (pred) 203
aidom.project/6 (pred) 203
aidom.widencall/4 (pred) 203
aidom.needs/2 (pred) 204
aidom.widen/4 (pred) 204
aidom.compute_lub/3 (pred) 204
aidom.compute_clauses_lub/4 (pred) 204
aidom.compute_clauses_glb/4 (pred) 204
aidom.fixpoint_covered/3 (pred) 204
aidom.fixpoint_covered_gfp/3 (pred) 204
aidom.identical_abstract/3 (pred) 204
aidom.abs_sort/3 (pred) 204
aidom.extend/6 (pred) 204
aidom.less_or_equal/3 (pred) 204
aidom.glb/4 (pred) 205
aidom.eliminate_equivalent/3 (pred) 205
aidom.abs_subset/3 (pred) 205
aidom.call_to_success_fact/10 (pred) 205
aidom.special_builtin/6 (pred) 205
aidom.combined_special_builtin0/3 (pred) 205
aidom.body_succ_builtin/9 (pred) 205
aidom.split_combined_domain/4 (pred) 205
aidom.success_builtin/7 (pred) 205
aidom.call_to_success_builtin/7 (pred) 205
aidom.obtain_info/5 (pred) 205
aidom.input_interface/5 (pred) 205
aidom.input_user_interface/6 (pred) 206
aidom.asub_to_native/6 (pred) 206
aidom.concrete/4 (pred) 206
aidom.unknown_call/5 (pred) 206
aidom.unknown_entry/4 (pred) 206
aidom.empty_entry/4 (pred) 206
aidom.part_conc/5 (pred) 206

aidom.multi_part_conc/4 (pred) 206
aidom.collect_auxinfo_asub/4 (pred) 206
aidom.rename_auxinfo_asub/4 (pred) 206
aidom.dom_statistics/2 (pred) 206
aidom.contains_parameters/2 (pred) 206
29.3 Documentation on imports 207

30 sharing+freeness+nonvar (abstract domain) . . 209

30.1 Usage and interface 209
30.2 Documentation on multifiles 209
aidomain/1 (pred) 209
aidom.init_abstract_domain/2 (pred) 209
aidom.amgu/5 (pred) 209
aidom.augment_asub/4 (pred) 209
aidom.augment_two_asub/4 (pred) 209
aidom.call_to_entry/10 (pred) 209
aidom.exit_to_prime/8 (pred) 209
aidom.project/6 (pred) 209
aidom.widencall/4 (pred) 209
aidom.needs/2 (pred) 210
aidom.widen/4 (pred) 210
aidom.compute_lub/3 (pred) 210
aidom.compute_clauses_lub/4 (pred) 210
aidom.compute_clauses_glb/4 (pred) 210
aidom.fixpoint_covered/3 (pred) 210
aidom.fixpoint_covered_gfp/3 (pred) 210
aidom.identical_abstract/3 (pred) 210
aidom.abs_sort/3 (pred) 210
aidom.extend/6 (pred) 210
aidom.less_or_equal/3 (pred) 210
aidom.glb/4 (pred) 211
aidom.eliminate_equivalent/3 (pred) 211
aidom.abs_subset/3 (pred) 211
aidom.call_to_success_fact/10 (pred) 211
aidom.special_builtin/6 (pred) 211
aidom.combined_special_builtin0/3 (pred) 211
aidom.body_succ_builtin/9 (pred) 211
aidom.split_combined_domain/4 (pred) 211
aidom.success_builtin/7 (pred) 211
aidom.call_to_success_builtin/7 (pred) 211
aidom.obtain_info/5 (pred) 211
aidom.input_interface/5 (pred) 211
aidom.input_user_interface/6 (pred) 212
aidom.asub_to_native/6 (pred) 212
aidom.concrete/4 (pred) 212
aidom.unknown_call/5 (pred) 212
aidom.unknown_entry/4 (pred) 212
aidom.empty_entry/4 (pred) 212
aidom.part_conc/5 (pred) 212
aidom.multi_part_conc/4 (pred) 212
aidom.collect_auxinfo_asub/4 (pred) 212
aidom.rename_auxinfo_asub/4 (pred) 212
aidom.dom_statistics/2 (pred) 212
aidom.contains_parameters/2 (pred) 212
30.3 Documentation on imports 213

31 shareson (library) 215
31.1 Usage and interface 215
31.2 Documentation on multifiles 215
aidomain/1 (pred) 215
aidom.init_abstract_domain/2 (pred) 215
aidom.amgu/5 (pred) 215
aidom.augment_asub/4 (pred) 215
aidom.augment_two_asub/4 (pred) 215
aidom.call_to_entry/10 (pred) 215
aidom.exit_to_prime/8 (pred) 215
aidom.project/6 (pred) 215
aidom.widencall/4 (pred) 215
aidom.needs/2 (pred) 216
aidom.widen/4 (pred) 216
aidom.compute_lub/3 (pred) 216
aidom.compute_clauses_lub/4 (pred) 216
aidom.compute_clauses_glb/4 (pred) 216
aidom.fixpoint_covered/3 (pred) 216
aidom.fixpoint_covered_gfp/3 (pred) 216
aidom.identical_abstract/3 (pred) 216
aidom.abs_sort/3 (pred) 216
aidom.extend/6 (pred) 216
aidom.less_or_equal/3 (pred) 216
aidom.glb/4 (pred) 216
aidom.eliminate_equivalent/3 (pred) 217
aidom.abs_subset/3 (pred) 217
aidom.call_to_success_fact/10 (pred) 217
aidom.special_builtin/6 (pred) 217
aidom.combined_special_builtin0/3 (pred) 217
aidom.body_succ_builtin/9 (pred) 217
aidom.split_combined_domain/4 (pred) 217
aidom.success_builtin/7 (pred) 217
aidom.call_to_success_builtin/7 (pred) 217
aidom.obtain_info/5 (pred) 217
aidom.input_interface/5 (pred) 217
aidom.input_user_interface/6 (pred) 217
aidom.asub_to_native/6 (pred) 218
aidom.concrete/4 (pred) 218
aidom.unknown_call/5 (pred) 218
aidom.unknown_entry/4 (pred) 218
aidom.empty_entry/4 (pred) 218
aidom.part_conc/5 (pred) 218
aidom.multi_part_conc/4 (pred) 218
aidom.collect_auxinfo_asub/4 (pred) 218
aidom.rename_auxinfo_asub/4 (pred) 218
aidom.dom_statistics/2 (pred) 218
aidom.contains_parameters/2 (pred) 218
31.3 Documentation on imports 219

32 sharing (abstract domain) 221
32.1 Usage and interface 221
32.2 Documentation on exports 221
project/5 (pred) 221
project_share/3 (pred) 221
call_to_entry/9 (pred) 221
exit_to_prime/7 (pred) 222
abs_sort/2 (pred) 222
compute_lub/2 (pred) 222
lub/3 (pred) 222
glb/3 (pred) 222
extend/5 (pred) 222
call_to_success_fact/9 (pred) 222
call_to_prime_fact/6 (pred) 222
pos/4 (pred) 222
script_p_star/3 (pred) 222
script_p/3 (pred) 222
unknown_entry/3 (pred) 222
empty_entry/3 (pred) 223
asub_to_native/5 (pred) 223
input_user_interface/5 (pred) 223
input_interface/4 (pred) 223
unknown_call/4 (pred) 223
less_or_equal/2 (pred) 223
special_builtin/5 (pred) 223
success_builtin/6 (pred) 223
call_to_success_builtin/6 (pred) 223
32.3 Documentation on multifiles 224
aidomain/1 (pred) 224
aidom.init_abstract_domain/2 (pred) 224
aidom.amgu/5 (pred) 224
aidom.augment_asub/4 (pred) 224
aidom.augment_two_asub/4 (pred) 224
aidom.call_to_entry/10 (pred) 224
aidom.exit_to_prime/8 (pred) 224
aidom.project/6 (pred) 224
aidom.widencall/4 (pred) 224
aidom.needs/2 (pred) 224
aidom.widen/4 (pred) 224
aidom.compute_lub/3 (pred) 224
aidom.compute_clauses_lub/4 (pred) 225
aidom.compute_clauses_glb/4 (pred) 225
aidom.fixpoint_covered/3 (pred) 225
aidom.fixpoint_covered_gfp/3 (pred) 225
aidom.identical_abstract/3 (pred) 225
aidom.abs_sort/3 (pred) 225
aidom.extend/6 (pred) 225
aidom.less_or_equal/3 (pred) 225
aidom.glb/4 (pred) 225
aidom.eliminate_equivalent/3 (pred) 225
aidom.abs_subset/3 (pred) 225
aidom.call_to_success_fact/10 (pred) 226
aidom.special_builtin/6 (pred) 226
aidom.combined_special_builtin0/3 (pred) 226
aidom.body_succ_builtin/9 (pred) 226
aidom.split_combined_domain/4 (pred) 226

aidom.success_builtin/7 (pred) 226
aidom.call_to_success_builtin/7 (pred) 226
aidom.obtain_info/5 (pred) 226
aidom.input_interface/5 (pred) 226
aidom.input_user_interface/6 (pred) 226
aidom.asub_to_native/6 (pred) 226
aidom.concrete/4 (pred) 226
aidom.unknown_call/5 (pred) 227
aidom.unknown_entry/4 (pred) 227
aidom.empty_entry/4 (pred) 227
aidom.part_conc/5 (pred) 227
aidom.multi_part_conc/4 (pred) 227
aidom.collect_auxinfo_asub/4 (pred) 227
aidom.rename_auxinfo_asub/4 (pred) 227
aidom.dom_statistics/2 (pred) 227
aidom.contains_parameters/2 (pred) 227
32.4 Documentation on imports 227

33 amgu-based sharing domain 229
33.1 Usage and interface 229
33.2 Documentation on exports 229
call_to_entry/9 (pred) 229
amgu/4 (pred) 229
augment_asub/3 (pred) 229
augment_two_asub/3 (pred) 229
33.3 Documentation on multifiles 230
aidomain/1 (pred) 230
aidom.init_abstract_domain/2 (pred) 230
aidom.amgu/5 (pred) 230
aidom.augment_asub/4 (pred) 230
aidom.augment_two_asub/4 (pred) 230
aidom.call_to_entry/10 (pred) 230
aidom.exit_to_prime/8 (pred) 230
aidom.project/6 (pred) 230
aidom.widencall/4 (pred) 230
aidom.needs/2 (pred) 230
aidom.widen/4 (pred) 230
aidom.compute_lub/3 (pred) 230
aidom.compute_clauses_lub/4 (pred) 231
aidom.compute_clauses_glb/4 (pred) 231
aidom.fixpoint_covered/3 (pred) 231
aidom.fixpoint_covered_gfp/3 (pred) 231
aidom.identical_abstract/3 (pred) 231
aidom.abs_sort/3 (pred) 231
aidom.extend/6 (pred) 231
aidom.less_or_equal/3 (pred) 231
aidom.glb/4 (pred) 231
aidom.eliminate_equivalent/3 (pred) 231
aidom.abs_subset/3 (pred) 231
aidom.call_to_success_fact/10 (pred) 232
aidom.special_builtin/6 (pred) 232
aidom.combined_special_builtin0/3 (pred) 232
aidom.body_succ_builtin/9 (pred) 232
aidom.split_combined_domain/4 (pred) 232
aidom.success_builtin/7 (pred) 232
aidom.call_to_success_builtin/7 (pred) 232

aidom.obtain_info/5 (pred) . . . 232
aidom.input_interface/5 (pred) . . . 232
aidom.input_user_interface/6 (pred) . . . 232
aidom.asub_to_native/6 (pred) . . . 232
aidom.concrete/4 (pred) . . . 232
aidom.unknown_call/5 (pred) . . . 233
aidom.unknown_entry/4 (pred) . . . 233
aidom.empty_entry/4 (pred) . . . 233
aidom.part_conc/5 (pred) . . . 233
aidom.multi_part_conc/4 (pred) . . . 233
aidom.collect_auxinfo_asub/4 (pred) . . . 233
aidom.rename_auxinfo_asub/4 (pred) . . . 233
aidom.dom_statistics/2 (pred) . . . 233
aidom.contains_parameters/2 (pred) . . . 233
33.4 Documentation on imports . . . 233

34 CLIQUE-Sharing domain . . . 235
34.1 Usage and interface . . . 235
34.2 Documentation on exports . . . 235
call_to_entry/9 (pred) . . . 235
exit_to_prime/7 (pred) . . . 235
amgu/4 (pred) . . . 235
extend/5 (pred) . . . 236
asub_gt/2 (pred) . . . 236
prune_success/5 (pred) . . . 236
sharing_possible/4 (pred) . . . 236
powerset_with_empty_set/2 (pred) . . . 236
augment_asub/3 (pred) . . . 236
project/5 (pred) . . . 236
abs_sort/2 (pred) . . . 236
identical_abstract/2 (pred) . . . 236
eliminate_equivalent/2 (pred) . . . 236
less_or_equal/2 (pred) . . . 236
clique_part_less_or_equal/2 (pred) . . . 237
sharing_part_less_or_equal/3 (pred) . . . 237
call_to_success_fact/9 (pred) . . . 237
call_to_prime_fact/6 (pred) . . . 237
compute_lub/2 (pred) . . . 237
share_clique_lub_cl/3 (pred) . . . 237
glb/3 (pred) . . . 237
input_user_interface/5 (pred) . . . 237
input_interface/4 (pred) . . . 237
may_be_var/2 (pred) . . . 237
myappend/3 (pred) . . . 237
asub_to_native/5 (pred) . . . 237
unknown_call/4 (pred) . . . 238
empty_entry/3 (pred) . . . 238
unknown_entry/3 (pred) . . . 238
widen/4 (pred) . . . 238
widen/5 (pred) . . . 238
special_builtin/5 (pred) . . . 238
success_builtin/6 (pred) . . . 238
call_to_success_builtin/6 (pred) . . . 238
clique_make_decomposition/5 (pred) . . . 238
eliminate_couples_clique/4 (pred) . . . 238
share_make_reduction/5 (pred) . . . 238

projected_gvars_clique/3 (pred) 238
compute_upper_amgu/2 (pred) 238
34.3 Documentation on multifiles 239
aidomain/1 (pred) 239
aidom.init_abstract_domain/2 (pred) 239
aidom.amgu/5 (pred) 239
aidom.augment_asub/4 (pred) 239
aidom.augment_two_asub/4 (pred) 239
aidom.call_to_entry/10 (pred) 239
aidom.exit_to_prime/8 (pred) 239
aidom.project/6 (pred) 239
aidom.widencall/4 (pred) 239
aidom.needs/2 (pred) 239
aidom.widen/4 (pred) 239
aidom.compute_lub/3 (pred) 239
aidom.compute_clauses_lub/4 (pred) 240
aidom.compute_clauses_glb/4 (pred) 240
aidom.fixpoint_covered/3 (pred) 240
aidom.fixpoint_covered_gfp/3 (pred) 240
aidom.identical_abstract/3 (pred) 240
aidom.abs_sort/3 (pred) 240
aidom.extend/6 (pred) 240
aidom.less_or_equal/3 (pred) 240
aidom.glb/4 (pred) 240
aidom.eliminate_equivalent/3 (pred) 240
aidom.abs_subset/3 (pred) 240
aidom.call_to_success_fact/10 (pred) 241
aidom.special_builtin/6 (pred) 241
aidom.combined_special_builtin0/3 (pred) 241
aidom.body_succ_builtin/9 (pred) 241
aidom.split_combined_domain/4 (pred) 241
aidom.success_builtin/7 (pred) 241
aidom.call_to_success_builtin/7 (pred) 241
aidom.obtain_info/5 (pred) 241
aidom.input_interface/5 (pred) 241
aidom.input_user_interface/6 (pred) 241
aidom.asub_to_native/6 (pred) 241
aidom.concrete/4 (pred) 241
aidom.unknown_call/5 (pred) 242
aidom.unknown_entry/4 (pred) 242
aidom.empty_entry/4 (pred) 242
aidom.part_conc/5 (pred) 242
aidom.multi_part_conc/4 (pred) 242
aidom.collect_auxinfo_asub/4 (pred) 242
aidom.rename_auxinfo_asub/4 (pred) 242
aidom.dom_statistics/2 (pred) 242
aidom.contains_parameters/2 (pred) 242
34.4 Documentation on imports 242

35 1-CLIQUE-Sharing domain 243
35.1 Usage and interface 243
35.2 Documentation on multifiles 243
aidomain/1 (pred) 243
aidom.init_abstract_domain/2 (pred) 243
aidom.amgu/5 (pred) 243
aidom.augment_asub/4 (pred) 243
aidom.augment_two_asub/4 (pred) 243
aidom.call_to_entry/10 (pred) 243
aidom.exit_to_prime/8 (pred) 243
aidom.project/6 (pred) 243
aidom.widencall/4 (pred) 243
aidom.needs/2 (pred) 244
aidom.widen/4 (pred) 244
aidom.compute_lub/3 (pred) 244
aidom.compute_clauses_lub/4 (pred) 244
aidom.compute_clauses_glb/4 (pred) 244
aidom.fixpoint_covered/3 (pred) 244
aidom.fixpoint_covered_gfp/3 (pred) 244
aidom.identical_abstract/3 (pred) 244
aidom.abs_sort/3 (pred) 244
aidom.extend/6 (pred) 244
aidom.less_or_equal/3 (pred) 244
aidom.glb/4 (pred) 245
aidom.eliminate_equivalent/3 (pred) 245
aidom.abs_subset/3 (pred) 245
aidom.call_to_success_fact/10 (pred) 245
aidom.special_builtin/6 (pred) 245
aidom.combined_special_builtin0/3 (pred) 245
aidom.body_succ_builtin/9 (pred) 245
aidom.split_combined_domain/4 (pred) 245
aidom.success_builtin/7 (pred) 245
aidom.call_to_success_builtin/7 (pred) 245
aidom.obtain_info/5 (pred) 245
aidom.input_interface/5 (pred) 245
aidom.input_user_interface/6 (pred) 246
aidom.asub_to_native/6 (pred) 246
aidom.concrete/4 (pred) 246
aidom.unknown_call/5 (pred) 246
aidom.unknown_entry/4 (pred) 246
aidom.empty_entry/4 (pred) 246
aidom.part_conc/5 (pred) 246
aidom.multi_part_conc/4 (pred) 246
aidom.collect_auxinfo_asub/4 (pred) 246
aidom.rename_auxinfo_asub/4 (pred) 246
aidom.dom_statistics/2 (pred) 246
aidom.contains_parameters/2 (pred) 246
35.3 Documentation on imports 247

36 CLIQUE-Sharing+Def domain 249
36.1 Usage and interface 249
36.2 Documentation on multifiles 249
aidomain/1 (pred) 249
aidom.init_abstract_domain/2 (pred) 249
aidom.amgu/5 (pred) 249
aidom.augment_asub/4 (pred) 249
aidom.augment_two_asub/4 (pred) 249
aidom.call_to_entry/10 (pred) 249
aidom.exit_to_prime/8 (pred) 249
aidom.project/6 (pred) 249
aidom.widencall/4 (pred) 249
aidom.needs/2 (pred) 250
aidom.widen/4 (pred) 250
aidom.compute_lub/3 (pred) 250
aidom.compute_clauses_lub/4 (pred) 250
aidom.compute_clauses_glb/4 (pred) 250
aidom.fixpoint_covered/3 (pred) 250
aidom.fixpoint_covered_gfp/3 (pred) 250
aidom.identical_abstract/3 (pred) 250
aidom.abs_sort/3 (pred) 250
aidom.extend/6 (pred) 250
aidom.less_or_equal/3 (pred) 250
aidom.glb/4 (pred) 251
aidom.eliminate_equivalent/3 (pred) 251
aidom.abs_subset/3 (pred) 251
aidom.call_to_success_fact/10 (pred) 251
aidom.special_builtin/6 (pred) 251
aidom.combined_special_builtin0/3 (pred) 251
aidom.body_succ_builtin/9 (pred) 251
aidom.split_combined_domain/4 (pred) 251
aidom.success_builtin/7 (pred) 251
aidom.call_to_success_builtin/7 (pred) 251
aidom.obtain_info/5 (pred) 251
aidom.input_interface/5 (pred) 251
aidom.input_user_interface/6 (pred) 252
aidom.asub_to_native/6 (pred) 252
aidom.concrete/4 (pred) 252
aidom.unknown_call/5 (pred) 252
aidom.unknown_entry/4 (pred) 252
aidom.empty_entry/4 (pred) 252
aidom.part_conc/5 (pred) 252
aidom.multi_part_conc/4 (pred) 252
aidom.collect_auxinfo_asub/4 (pred) 252
aidom.rename_auxinfo_asub/4 (pred) 252
aidom.dom_statistics/2 (pred) 252
aidom.contains_parameters/2 (pred) 252
36.3 Documentation on imports 253

37 shfret (library) 255
37.1 Usage and interface 255
37.2 Documentation on exports 255
shfret_init_abstract_domain/1 (pred) 255
shfret_call_to_entry/9 (pred) 255
shfret_exit_to_prime/7 (pred) 255
shfret_project/5 (pred) 256
shfret_extend/5 (pred) 256
shfret_widen/3 (pred) 256
shfret_widencall/3 (pred) 256
shfret_compute_lub/2 (pred) 256
shfret_glb/3 (pred) 256
shfret_eliminate_equivalent/2 (pred) 256
shfret_less_or_equal/2 (pred) 256
shfret_identical_abstract/2 (pred) 256
shfret_abs_sort/2 (pred) 256
shfret_call_to_success_fact/9 (pred) 256
shfret_combined_special_builtin0/2 (pred) 256
shfret_split_combined_domain/3 (pred) 257
shfret_input_interface/4 (pred) 257
shfret_input_user_interface/5 (pred) 257
shfret_asub_to_native/5 (pred) 257
shfret_unknown_call/4 (pred) 257
shfret_unknown_entry/3 (pred) 257
shfret_empty_entry/3 (pred) 257
37.3 Documentation on multifiles 257
aidomain/1 (pred) 257
aidom.init_abstract_domain/2 (pred) 257
aidom.amgu/5 (pred) 257
aidom.augment_asub/4 (pred) 257
aidom.augment_two_asub/4 (pred) 257
aidom.call_to_entry/10 (pred) 258
aidom.exit_to_prime/8 (pred) 258
aidom.project/6 (pred) 258
aidom.widencall/4 (pred) 258
aidom.needs/2 (pred) 258
aidom.widen/4 (pred) 258
aidom.compute_lub/3 (pred) 258
aidom.compute_clauses_lub/4 (pred) 258
aidom.compute_clauses_glb/4 (pred) 258
aidom.fixpoint_covered/3 (pred) 258
aidom.fixpoint_covered_gfp/3 (pred) 258
aidom.identical_abstract/3 (pred) 259
aidom.abs_sort/3 (pred) 259
aidom.extend/6 (pred) 259
aidom.less_or_equal/3 (pred) 259
aidom.glb/4 (pred) 259
aidom.eliminate_equivalent/3 (pred) 259
aidom.abs_subset/3 (pred) 259
aidom.call_to_success_fact/10 (pred) 259
aidom.special_builtin/6 (pred) 259
aidom.combined_special_builtin0/3 (pred) 259
aidom.body_succ_builtin/9 (pred) 259
aidom.split_combined_domain/4 (pred) 259
aidom.success_builtin/7 (pred) 260
aidom.call_to_success_builtin/7 (pred) 260

aidom.obtain_info/5 (pred) 260
aidom.input_interface/5 (pred) 260
aidom.input_user_interface/6 (pred) 260
aidom.asub_to_native/6 (pred) 260
aidom.concrete/4 (pred) 260
aidom.unknown_call/5 (pred) 260
aidom.unknown_entry/4 (pred) 260
aidom.empty_entry/4 (pred) 260
aidom.part_conc/5 (pred) 260
aidom.multi_part_conc/4 (pred) 260
aidom.collect_auxinfo_asub/4 (pred) 261
aidom.rename_auxinfo_asub/4 (pred) 261
aidom.dom_statistics/2 (pred) 261
aidom.contains_parameters/2 (pred) 261
37.4 Documentation on imports 261

38 amgu-based sharing+freeness+linearity domain 263

38.1 Usage and interface 263
38.2 Documentation on multifiles 263
aidomain/1 (pred) 263
aidom.init_abstract_domain/2 (pred) 263
aidom.amgu/5 (pred) 263
aidom.augment_asub/4 (pred) 263
aidom.augment_two_asub/4 (pred) 263
aidom.call_to_entry/10 (pred) 263
aidom.exit_to_prime/8 (pred) 263
aidom.project/6 (pred) 263
aidom.widencall/4 (pred) 263
aidom.needs/2 (pred) 264
aidom.widen/4 (pred) 264
aidom.compute_lub/3 (pred) 264
aidom.compute_clauses_lub/4 (pred) 264
aidom.compute_clauses_glb/4 (pred) 264
aidom.fixpoint_covered/3 (pred) 264
aidom.fixpoint_covered_gfp/3 (pred) 264
aidom.identical_abstract/3 (pred) 264
aidom.abs_sort/3 (pred) 264
aidom.extend/6 (pred) 264
aidom.less_or_equal/3 (pred) 264
aidom.glb/4 (pred) 265
aidom.eliminate_equivalent/3 (pred) 265
aidom.abs_subset/3 (pred) 265
aidom.call_to_success_fact/10 (pred) 265
aidom.special_builtin/6 (pred) 265
aidom.combined_special_builtin0/3 (pred) 265
aidom.body_succ_builtin/9 (pred) 265
aidom.split_combined_domain/4 (pred) 265
aidom.success_builtin/7 (pred) 265
aidom.call_to_success_builtin/7 (pred) 265
aidom.obtain_info/5 (pred) 265
aidom.input_interface/5 (pred) 265
aidom.input_user_interface/6 (pred) 266
aidom.asub_to_native/6 (pred) 266
aidom.concrete/4 (pred) 266

aidom.unknown_call/5 (pred) 266
aidom.unknown_entry/4 (pred) 266
aidom.empty_entry/4 (pred) 266
aidom.part_conc/5 (pred) 266
aidom.multi_part_conc/4 (pred) 266
aidom.collect_auxinfo_asub/4 (pred) 266
aidom.rename_auxinfo_asub/4 (pred) 266
aidom.dom_statistics/2 (pred) 266
aidom.contains_parameters/2 (pred) 266
38.3 Documentation on imports 267

39 shfrson (library) 269
39.1 Usage and interface 269
39.2 Documentation on multifiles 269
aidomain/1 (pred) 269
aidom.init_abstract_domain/2 (pred) 269
aidom.amgu/5 (pred) 269
aidom.augment_asub/4 (pred) 269
aidom.augment_two_asub/4 (pred) 269
aidom.call_to_entry/10 (pred) 269
aidom.exit_to_prime/8 (pred) 269
aidom.project/6 (pred) 269
aidom.widencall/4 (pred) 269
aidom.needs/2 (pred) 270
aidom.widen/4 (pred) 270
aidom.compute_lub/3 (pred) 270
aidom.compute_clauses_lub/4 (pred) 270
aidom.compute_clauses_glb/4 (pred) 270
aidom.fixpoint_covered/3 (pred) 270
aidom.fixpoint_covered_gfp/3 (pred) 270
aidom.identical_abstract/3 (pred) 270
aidom.abs_sort/3 (pred) 270
aidom.extend/6 (pred) 270
aidom.less_or_equal/3 (pred) 270
aidom.glb/4 (pred) 270
aidom.eliminate_equivalent/3 (pred) 271
aidom.abs_subset/3 (pred) 271
aidom.call_to_success_fact/10 (pred) 271
aidom.special_builtin/6 (pred) 271
aidom.combined_special_builtin0/3 (pred) 271
aidom.body_succ_builtin/9 (pred) 271
aidom.split_combined_domain/4 (pred) 271
aidom.success_builtin/7 (pred) 271
aidom.call_to_success_builtin/7 (pred) 271
aidom.obtain_info/5 (pred) 271
aidom.input_interface/5 (pred) 271
aidom.input_user_interface/6 (pred) 271
aidom.asub_to_native/6 (pred) 272
aidom.concrete/4 (pred) 272
aidom.unknown_call/5 (pred) 272
aidom.unknown_entry/4 (pred) 272
aidom.empty_entry/4 (pred) 272
aidom.part_conc/5 (pred) 272
aidom.multi_part_conc/4 (pred) 272
aidom.collect_auxinfo_asub/4 (pred) 272
aidom.rename_auxinfo_asub/4 (pred) 272

aidom.dom_statistics/2 (pred) 272
aidom.contains_parameters/2 (pred) 272
39.3 Documentation on imports 273

40 sondergaard (library) 275
40.1 Usage and interface 275
40.2 Documentation on exports 275
project/5 (pred) 275
call_to_entry/9 (pred) 275
exit_to_prime/7 (pred) 275
abs_sort/2 (pred) 275
compute_lub/2 (pred) 276
lub/3 (pred) 276
glb/3 (pred) 276
extend/5 (pred) 276
call_to_success_fact/9 (pred) 276
call_to_prime_fact/6 (pred) 276
unknown_call/4 (pred) 276
unknown_entry/3 (pred) 276
empty_entry/3 (pred) 276
asub_to_native/5 (pred) 276
input_user_interface/5 (pred) 276
input_interface/4 (pred) 277
less_or_equal/2 (pred) 277
special_builtin/5 (pred) 277
success_builtin/6 (pred) 277
call_to_success_builtin/6 (pred) 277
share_to_son/3 (pred) 277
son_to_share/4 (pred) 277
propagate_to_sh/4 (pred) 277
propagate_to_son/4 (pred) 277
40.3 Documentation on multifiles 277
aidomain/1 (pred) 277
aidom.init_abstract_domain/2 (pred) 277
aidom.amgu/5 (pred) 277
aidom.augment_asub/4 (pred) 278
aidom.augment_two_asub/4 (pred) 278
aidom.call_to_entry/10 (pred) 278
aidom.exit_to_prime/8 (pred) 278
aidom.project/6 (pred) 278
aidom.widencall/4 (pred) 278
aidom.needs/2 (pred) 278
aidom.widen/4 (pred) 278
aidom.compute_lub/3 (pred) 278
aidom.compute_clauses_lub/4 (pred) 278
aidom.compute_clauses_glb/4 (pred) 278
aidom.fixpoint_covered/3 (pred) 279
aidom.fixpoint_covered_gfp/3 (pred) 279
aidom.identical_abstract/3 (pred) 279
aidom.abs_sort/3 (pred) 279
aidom.extend/6 (pred) 279
aidom.less_or_equal/3 (pred) 279
aidom.glb/4 (pred) 279
aidom.eliminate_equivalent/3 (pred) 279
aidom.abs_subset/3 (pred) 279
aidom.call_to_success_fact/10 (pred) 279

aidom.special_builtin/6 (pred) 279
aidom.combined_special_builtin0/3 (pred) 279
aidom.body_succ_builtin/9 (pred) 280
aidom.split_combined_domain/4 (pred) 280
aidom.success_builtin/7 (pred) 280
aidom.call_to_success_builtin/7 (pred) 280
aidom.obtain_info/5 (pred) 280
aidom.input_interface/5 (pred) 280
aidom.input_user_interface/6 (pred) 280
aidom.asub_to_native/6 (pred) 280
aidom.concrete/4 (pred) 280
aidom.unknown_call/5 (pred) 280
aidom.unknown_entry/4 (pred) 280
aidom.empty_entry/4 (pred) 280
aidom.part_conc/5 (pred) 281
aidom.multi_part_conc/4 (pred) 281
aidom.collect_auxinfo_asub/4 (pred) 281
aidom.rename_auxinfo_asub/4 (pred) 281
aidom.dom_statistics/2 (pred) 281
aidom.contains_parameters/2 (pred) 281
40.4 Documentation on imports 281

41 svterms: eterms + same value (abstract domain) 283

41.1 Usage and interface 283
41.2 Documentation on exports 283
svterms_concrete/3 (pred) 283
svterms_compute_lub/2 (pred) 283
svterms_compute_lub_el/3 (pred) 283
svterms_needs/1 (pred) 284
svterms_widencall/3 (pred) 284
svterms_widen/3 (pred) 284
svterms_init_abstract_domain/1 (pred) 284
svterms_call_to_entry/9 (pred) 284
svterms_exit_to_prime/7 (pred) 284
svterms_project/5 (pred) 284
svterms_abs_sort/2 (pred) 284
svterms_extend/5 (pred) 284
svterms_less_or_equal/2 (pred) 284
svterms_glb/3 (pred) 284
svterms_unknown_entry/3 (pred) 285
svterms_empty_entry/3 (pred) 285
svterms_unknown_call/4 (pred) 285
svterms_call_to_success_fact/9 (pred) 285
svterms_special_builtin/5 (pred) 285
svterms_success_builtin/6 (pred) 285
svterms_call_to_success_builtin/6 (pred) 285
svterms_input_user_interface/5 (pred) 285
svterms_input_interface/4 (pred) 285
svterms_asub_to_native/5 (pred) 285
svterms_output_interface/2 (pred) 285
svterms_collect_auxinfo_asub/3 (pred) 285
svterms_rename_auxinfo_asub/3 (pred) 286
svterms_identical_abstract/2 (pred) 286
41.3 Documentation on multifiles 286

aidomain/1 (pred) 286
aidom.init_abstract_domain/2 (pred) 286
aidom.amgu/5 (pred) 286
aidom.augment_asub/4 (pred) 286
aidom.augment_two_asub/4 (pred) 286
aidom.call_to_entry/10 (pred) 286
aidom.exit_to_prime/8 (pred) 286
aidom.project/6 (pred) 286
aidom.widencall/4 (pred) 286
aidom.needs/2 (pred) 286
aidom.widen/4 (pred) 287
aidom.compute_lub/3 (pred) 287
aidom.compute_clauses_lub/4 (pred) 287
aidom.compute_clauses_glb/4 (pred) 287
aidom.fixpoint_covered/3 (pred) 287
aidom.fixpoint_covered_gfp/3 (pred) 287
aidom.identical_abstract/3 (pred) 287
aidom.abs_sort/3 (pred) 287
aidom.extend/6 (pred) 287
aidom.less_or_equal/3 (pred) 287
aidom.glb/4 (pred) 287
aidom.eliminate_equivalent/3 (pred) 288
aidom.abs_subset/3 (pred) 288
aidom.call_to_success_fact/10 (pred) 288
aidom.special_builtin/6 (pred) 288
aidom.combined_special_builtin0/3 (pred) 288
aidom.body_succ_builtin/9 (pred) 288
aidom.split_combined_domain/4 (pred) 288
aidom.success_builtin/7 (pred) 288
aidom.call_to_success_builtin/7 (pred) 288
aidom.obtain_info/5 (pred) 288
aidom.input_interface/5 (pred) 288
aidom.input_user_interface/6 (pred) 288
aidom.asub_to_native/6 (pred) 289
aidom.concrete/4 (pred) 289
aidom.unknown_call/5 (pred) 289
aidom.unknown_entry/4 (pred) 289
aidom.empty_entry/4 (pred) 289
aidom.part_conc/5 (pred) 289
aidom.multi_part_conc/4 (pred) 289
aidom.collect_auxinfo_asub/4 (pred) 289
aidom.rename_auxinfo_asub/4 (pred) 289
aidom.dom_statistics/2 (pred) 289
aidom.contains_parameters/2 (pred) 289
41.4 Documentation on imports 290

42 termsd: types with shortening (abstract domain) 291

42.1 Usage and interface 291
42.2 Documentation on exports 291
terms_input_interface/4 (pred) 291
terms_concrete/3 (pred) 292
terms_compute_lub/2 (pred) 292
terms_compute_lub_el/3 (pred) 292
terms_widencall/3 (pred) 292
terms_needs/1 (pred) 292
terms_widen/3 (pred) 292
terms_init_abstract_domain/1 (pred) 292
terms_call_to_entry/9 (pred) 293
variables_are_variable_type/2 (pred) 294
terms_exit_to_prime/7 (pred) 294
unify_term_and_type_term/5 (pred) 294
generate_a_type_assignment/3 (pred) 295
get_var_types_by_unification/3 (pred) 295
compute_type/3 (pred) 295
find_list_entry/3 (pred) 295
terms_project/5 (pred) 295
terms_abs_sort/2 (pred) 296
terms_extend/5 (pred) 296
terms_less_or_equal/2 (pred) 296
terms_glb/3 (pred) 297
terms_unknown_entry/3 (pred) 297
terms_empty_entry/3 (pred) 297
terms_unknown_call/4 (pred) 298
substitution/3 (pred) 298
variables_are_top_type/2 (pred) 298
terms_call_to_success_fact/9 (pred) 298
terms_special_builtin/5 (pred) 299
terms_success_builtin/6 (pred) 299
terms_call_to_success_builtin/6 (pred) 299
precondition_builtin/2 (pred) 300
postcondition_builtin/4 (pred) 300
terms_input_user_interface/5 (pred) 300
terms_asub_to_native/5 (pred) 300
terms_internal_to_native/3 (pred) 300
terms_output_interface/2 (pred) 300
terms_collect_auxinfo_asub/3 (pred) 300
terms_rename_auxinfo_asub/3 (pred) 300
terms_identical_abstract/2 (pred) 300
42.3 Documentation on multifiles 301
aidomain/1 (pred) 301
aidom.init_abstract_domain/2 (pred) 301
aidom.amgu/5 (pred) 301
aidom.augment_asub/4 (pred) 301
aidom.augment_two_asub/4 (pred) 301
aidom.call_to_entry/10 (pred) 301
aidom.exit_to_prime/8 (pred) 301
aidom.project/6 (pred) 301
aidom.widencall/4 (pred) 301
aidom.needs/2 (pred) 301
aidom.widen/4 (pred) 301
aidom.compute_lub/3 (pred) 301

aidom.compute_clauses_lub/4 (pred) 302
aidom.compute_clauses_glb/4 (pred) 302
aidom.fixpoint_covered/3 (pred) 302
aidom.fixpoint_covered_gfp/3 (pred) 302
aidom.identical_abstract/3 (pred) 302
aidom.abs_sort/3 (pred) 302
aidom.extend/6 (pred) 302
aidom.less_or_equal/3 (pred) 302
aidom.glb/4 (pred) 302
aidom.eliminate_equivalent/3 (pred) 302
aidom.abs_subset/3 (pred) 302
aidom.call_to_success_fact/10 (pred) 303
aidom.special_builtin/6 (pred) 303
aidom.combined_special_builtin0/3 (pred) 303
aidom.body_succ_builtin/9 (pred) 303
aidom.split_combined_domain/4 (pred) 303
aidom.success_builtin/7 (pred) 303
aidom.call_to_success_builtin/7 (pred) 303
aidom.obtain_info/5 (pred) 303
aidom.input_interface/5 (pred) 303
aidom.input_user_interface/6 (pred) 303
aidom.asub_to_native/6 (pred) 303
aidom.concrete/4 (pred) 303
aidom.unknown_call/5 (pred) 304
aidom.unknown_entry/4 (pred) 304
aidom.empty_entry/4 (pred) 304
aidom.part_conc/5 (pred) 304
aidom.multi_part_conc/4 (pred) 304
aidom.collect_auxinfo_asub/4 (pred) 304
aidom.rename_auxinfo_asub/4 (pred) 304
aidom.dom_statistics/2 (pred) 304
aidom.contains_parameters/2 (pred) 304
42.4 Documentation on imports 304

43 top_path_sharing (library) 305

43.1 Usage and interface 305
43.2 Documentation on exports 305
path_to_shfr/3 (pred) 305
43.3 Documentation on multifiles 305
aidomain/1 (pred) 305
aidom.init_abstract_domain/2 (pred) 305
aidom.amgu/5 (pred) 305
aidom.augment_asub/4 (pred) 306
aidom.augment_two_asub/4 (pred) 306
aidom.call_to_entry/10 (pred) 306
aidom.exit_to_prime/8 (pred) 306
aidom.project/6 (pred) 306
aidom.widencall/4 (pred) 306
aidom.needs/2 (pred) 306
aidom.widen/4 (pred) 306
aidom.compute_lub/3 (pred) 306
aidom.compute_clauses_lub/4 (pred) 306
aidom.compute_clauses_glb/4 (pred) 306
aidom.fixpoint_covered/3 (pred) 306
aidom.fixpoint_covered_gfp/3 (pred) 307
aidom.identical_abstract/3 (pred) 307

aidom.abs_sort/3 (pred) . . . 307
aidom.extend/6 (pred) . . . 307
aidom.less_or_equal/3 (pred) . . . 307
aidom.glb/4 (pred) . . . 307
aidom.eliminate_equivalent/3 (pred) . . . 307
aidom.abs_subset/3 (pred) . . . 307
aidom.call_to_success_fact/10 (pred) . . . 307
aidom.special_builtin/6 (pred) . . . 307
aidom.combined_special_builtin0/3 (pred) . . . 307
aidom.body_succ_builtin/9 (pred) . . . 307
aidom.split_combined_domain/4 (pred) . . . 308
aidom.success_builtin/7 (pred) . . . 308
aidom.call_to_success_builtin/7 (pred) . . . 308
aidom.obtain_info/5 (pred) . . . 308
aidom.input_interface/5 (pred) . . . 308
aidom.input_user_interface/6 (pred) . . . 308
aidom.asub_to_native/6 (pred) . . . 308
aidom.concrete/4 (pred) . . . 308
aidom.unknown_call/5 (pred) . . . 308
aidom.unknown_entry/4 (pred) . . . 308
aidom.empty_entry/4 (pred) . . . 308
aidom.part_conc/5 (pred) . . . 308
aidom.multi_part_conc/4 (pred) . . . 309
aidom.collect_auxinfo_asub/4 (pred) . . . 309
aidom.rename_auxinfo_asub/4 (pred) . . . 309
aidom.dom_statistics/2 (pred) . . . 309
aidom.contains_parameters/2 (pred) . . . 309
43.4 Documentation on imports . . . 309

44 Available program transformations . . . 311
44.0.1 Program specialization . . . 312
44.0.2 Partial evaluation . . . 312
44.0.3 Code size reduction . . . 312
44.0.4 Program parallelization . . . 312
44.0.5 Abstract partial deduction . . . 312

45 Available fixpoints . . . 313
45.0.1 Analysis with PLAI . . . 314
45.0.2 Inter-modular analysis . . . 314

46 Other commands . . . 315

47 Display information about CiaoPP files . . . 317
47.1 Usage . . . 317

48 CiaoPP batch processing . . . 319

49 XML report for ciaopp-batch output . . . 321

50 PART II - The Assertion Language and Its Use . . . 323

51 Using assertions for preprocessing programs 325

51.1 Assertions 325
51.1.1 Properties of success states 325
51.1.2 Restricting assertions to a subset of calls 326
51.1.3 Properties of call states 326
51.1.4 Properties of the computation 326
51.1.5 Compound assertions 326
51.1.6 Examples of compound assertions 327
51.2 Properties 327
51.3 Preprocessing units 328
51.4 Foreign code 329
51.4.1 Examples of trust assertions 330
51.5 Dynamic predicates 330
51.6 Entry points 331
51.6.1 Examples of entry declarations 332
51.7 Modules 332
51.8 Dynamic calls 333
51.8.1 Examples of dynamic calls 333
51.9 An overview 334

52 The Ciao assertion language 335

52.1 Getting more information 335
52.2 Some attention points 335
52.3 Usage and interface 336
52.4 Documentation on new declarations 336
pred/1 (decl) 336
pred/2 (decl) 337
calls/1 (decl) 337
calls/2 (decl) 337
success/1 (decl) 338
success/2 (decl) 338
comp/1 (decl) 338
comp/2 (decl) 338
prop/1 (decl) 339
prop/2 (decl) 339
test/1 (decl) 339
test/2 (decl) 339
texec/1 (decl) 340
texec/2 (decl) 340
entry/1 (decl) 340
exit/1 (decl) 340
exit/2 (decl) 341
modedef/1 (decl) 341
decl/1 (decl) 342
decl/2 (decl) 342
doc/2 (decl) 342
comment/2 (decl) 342
52.5 Documentation on exports 343
check/1 (pred) 343
trust/1 (pred) 343
true/1 (pred) 343
false/1 (pred) 343

53 Types and properties related to assertions .. 345
53.1 Usage and interface ... 345
53.2 Documentation on exports ... 345
assrt_body/1 (regtype) ... 345
head_pattern/1 (prop) ... 346
complex_arg_property/1 (regtype) ... 346
property_conjunction/1 (regtype) ... 347
property_starterm/1 (regtype) ... 347
complex_goal_property/1 (regtype) ... 347
nabody/1 (prop) ... 348
dictionary/1 (regtype) ... 348
c_assrt_body/1 (regtype) ... 348
s_assrt_body/1 (regtype) ... 348
g_assrt_body/1 (regtype) ... 349
assrt_status/1 (regtype) ... 349
assrt_type/1 (regtype) ... 350
predfunctor/1 (regtype) ... 350
propfunctor/1 (regtype) ... 350
docstring/1 (prop) ... 350
53.3 Documentation on imports ... 350

54 Declaring regular types ... 351
54.1 Defining properties ... 351
54.2 Usage and interface ... 354
54.3 Documentation on new declarations ... 354
regtype/1 (decl) ... 354
regtype/2 (decl) ... 355

55 Basic data types and properties ... 357
55.1 Usage and interface ... 357
55.2 Documentation on exports ... 357
term/1 (regtype) ... 357
int/1 (regtype) ... 358
nnegint/1 (regtype) ... 358
flt/1 (regtype) ... 359
num/1 (regtype) ... 359
atm/1 (regtype) ... 360
struct/1 (regtype) ... 361
gnd/1 (regtype) ... 361
gndstr/1 (regtype) ... 362
constant/1 (regtype) ... 362
cgoal/1 (regtype) ... 362
callable/1 (prop) ... 363
internal_module_id/1 (regtype) ... 363
operator_specifier/1 (regtype) ... 363
list/1 (regtype) ... 364
list/2 (regtype) ... 365
nlist/2 (regtype) ... 365
member/2 (prop) ... 366
sequence/2 (regtype) ... 366
sequence_or_list/2 (regtype) ... 367
character_code/1 (regtype) ... 367
string/1 (regtype) ... 368
bytelist/1 (regtype) ... 368
predname/1 (regtype) ... 368

atm_or_atm_list/1 (regtype) 369
compat/2 (prop) 369
inst/2 (prop) 370
iso/1 (prop) 370
deprecated/1 (prop) 370
srcloc/4 (prop) 371
example/1 (prop) 371
not_further_inst/2 (prop) 371
sideff/2 (prop) 372
regtype/1 (prop) 372
native/1 (prop) 372
native/2 (prop) 372
rtcheck/1 (prop) 373
rtcheck/2 (prop) 373
no_rtcheck/1 (prop) 373
eval/1 (prop) 374
equiv/2 (prop) 374
bind_ins/1 (prop) 374
error_free/1 (prop) 374
memo/1 (prop) 374
filter/2 (prop) 374
flag_values/1 (regtype) 375
pe_type/1 (prop) 375
check/1 (pred) 375
trust/1 (pred) 375
true/1 (pred) 375
false/1 (pred) 375
55.3 Documentation on imports 375

56 Properties which are native to analyzers 377

57 Properties related to sharing/aliasing, groundness 379

57.1 Usage and interface 379
57.2 Documentation on exports 379
mshare/1 (prop) 379
mshare/2 (prop) 379
indep/2 (prop) 379
indep/1 (prop) 380
covered/2 (prop) 380
linear/1 (prop) 380
ivar/1 (prop) 380
nonground/1 (prop) 380
clique/1 (prop) 380
clique_1/1 (prop) 381
57.3 Documentation on imports 381

58 Properties related to determinacy, failure, choice-points 383
58.1 Usage and interface 383
58.2 Documentation on exports 383
det/1 (prop) 383
fails/1 (prop) 383
semidet/1 (prop) 383
multi/1 (prop) 384
nondet/1 (prop) 384
mut_exclusive/1 (prop) 384
not_mut_exclusive/1 (prop) 384
possibly_not_mut_exclusive/1 (prop) 385
covered/1 (prop) 385
not_covered/1 (prop) 385
possibly_not_covered/1 (prop) 386
no_choicepoints/1 (prop) 386
leaves_choicepoints/1 (prop) 386
is_det/1 (prop) 386
non_det/1 (prop) 386
possibly_nondet/1 (prop) 386
not_fails/1 (prop) 387
possibly_fails/1 (prop) 387
58.3 Documentation on imports 387

59 Properties related to cardinality and exact solutions 389
59.1 Usage and interface 389
59.2 Documentation on exports 389
cardinality/3 (prop) 389
num_solutions/2 (prop) 389
relations/2 (prop) 389
finite_solutions/1 (prop) 390
solutions/2 (prop) 390
59.3 Documentation on imports 390

60 Properties related to exceptions and signals 391
60.1 Usage and interface 391
60.2 Documentation on exports 391
exception/1 (prop) 391
exception/2 (prop) 391
possible_exceptions/2 (prop) 391
no_exception/1 (prop) 391
no_exception/2 (prop) 392
signal/1 (prop) 392
signal/2 (prop) 392
possible_signals/2 (prop) 392
no_signal/1 (prop) 392
no_signal/2 (prop) 392
60.3 Documentation on imports 393

61 Properties related to side effects 395
61.1 Usage and interface 395
61.2 Documentation on exports 395
sideff_pure/1 (prop) 395
sideff_soft/1 (prop) 395
sideff_hard/1 (prop) 395
61.3 Documentation on imports 396

62 Properties related to polyhedral constraints 397
62.1 Usage and interface 397
62.2 Documentation on exports 397
constraint/1 (prop) 397
62.3 Documentation on imports 397

63 Properties related to data sizes, cost, termination 399
63.1 Usage and interface 399
63.2 Documentation on exports 399
approx/1 (regtype) 399
resource_id/1 (prop) 399
cost_expression/1 (regtype) 399
agg_expression/1 (regtype) 400
numeric_constant/1 (regtype) 400
size_term/1 (regtype) 401
indexvar/1 (regtype) 401
number_lattice/1 (regtype) 401
size/2 (prop) 401
size/3 (prop) 401
size/4 (prop) 401
size_lb/2 (prop) 402
size_ub/2 (prop) 402
size_o/2 (prop) 402
size_metric/3 (prop) 403
size_metric/4 (prop) 403
measure_t/1 (regtype) 403
steps_lb/2 (prop) 404
steps_ub/2 (prop) 404
steps/2 (prop) 404
steps_o/2 (prop) 405
rsize/2 (prop) 405
costb/4 (prop) 405
cost/4 (prop) 405
terminates/1 (prop) 406
63.3 Documentation on imports 406

64 Run-time checking of assertions 407
64.1 Run-time checks configuration with flags 407
64.2 Custom implementation for property checks 408
64.3 Usage and interface 408
64.4 Other information 409

65 Applying assertions during fixpoint 411
65.1 Usage and interface 412
65.2 Documentation on exports 412
call_asr/5 (pred) 412
success_asr/6 (pred) 412
cleanup_applied_assertions/1 (pred) 412
apply_assrt_call_to_success/8 (pred) 412
apply_assrt_exit/7 (pred) 413
apply_assrt_no_source/6 (pred) 413
get_call_assertions_asub/5 (pred) 414
get_succ_assertion_asubs/7 (pred) 414
add_success_asr/6 (pred) 414
abs_normalize/8 (pred) 415
get_applicable_status/3 (pred) 415
65.3 Documentation on imports 415

66 PART III - Extending CiaoPP 417

67 Adding a new analysis domain to CiaoPP ... 419

68 Plug-in points for abstract domains 421
68.1 Variable naming convention for CiaoPP domains 421
68.2 Usage and interface 422
68.3 Documentation on exports 422
init_abstract_domain/2 (pred) 422
amgu/5 (pred) 422
augment_asub/4 (pred) 423
augment_two_asub/4 (pred) 423
call_to_entry/10 (pred) 423
exit_to_prime/8 (pred) 424
project/5 (pred) 424
project/6 (pred) 425
needs/2 (pred) 425
widencall/4 (pred) 426
dual_widencall/4 (pred) 426
widen/4 (pred) 426
dual_widen/4 (pred) 426
normalize_asub/3 (pred) 427
compute_lub/3 (pred) 427
compute_glb/3 (pred) 427
identical_proj/5 (pred) 427
identical_proj_1/7 (pred) 428
identical_abstract/3 (pred) 428
abs_sort/3 (pred) 428
extend/6 (pred) 428
less_or_equal_proj/5 (pred) 429
less_or_equal/3 (pred) 429
glb/4 (pred) 429
eliminate_equivalent/3 (pred) 430
abs_subset/3 (pred) 430
call_to_success_fact/10 (pred) 430
special_builtin/6 (pred) 430
body_succ_builtin/9 (pred) 431
success_builtin/7 (pred) 431

obtain_info/5 (pred) 431
info_to_asub/7 (pred) 432
full_info_to_asub/5 (pred) 432
asub_to_info/5 (pred) 432
asub_to_native/6 (pred) 432
concrete/4 (pred) 432
unknown_call/5 (pred) 433
unknown_entry/4 (pred) 433
empty_entry/4 (pred) 433
part_conc/5 (pred) 434
multi_part_conc/4 (pred) 434
collect_types_in_abs/4 (pred) 434
rename_types_in_abs/4 (pred) 434
dom_statistics/2 (pred) 435
abstract_instance/5 (pred) 435
contains_parameters/2 (pred) 435
absub_eliminate_equivalent/3 (pred) 435
absub_fixpoint_covered/3 (pred) 435
body_builtin/9 (pred) 435
undef_call_to_success_builtin/2 (pred) 435
68.4 Documentation on multifiles 436
aidomain/1 (pred) 436
aidom.init_abstract_domain/2 (pred) 436
aidom.amgu/5 (pred) 436
aidom.augment_asub/4 (pred) 436
aidom.augment_two_asub/4 (pred) 436
aidom.call_to_entry/10 (pred) 436
aidom.exit_to_prime/8 (pred) 436
aidom.project/6 (pred) 436
aidom.widencall/4 (pred) 436
aidom.needs/2 (pred) 436
aidom.widen/4 (pred) 436
aidom.compute_lub/3 (pred) 437
aidom.compute_clauses_lub/4 (pred) 437
aidom.compute_clauses_glb/4 (pred) 437
aidom.fixpoint_covered/3 (pred) 437
aidom.fixpoint_covered_gfp/3 (pred) 437
aidom.identical_abstract/3 (pred) 437
aidom.abs_sort/3 (pred) 437
aidom.extend/6 (pred) 437
aidom.less_or_equal/3 (pred) 437
aidom.glb/4 (pred) 437
aidom.eliminate_equivalent/3 (pred) 437
aidom.abs_subset/3 (pred) 437
aidom.call_to_success_fact/10 (pred) 438
aidom.special_builtin/6 (pred) 438
aidom.combined_special_builtin0/3 (pred) 438
aidom.body_succ_builtin/9 (pred) 438
aidom.split_combined_domain/4 (pred) 438
aidom.success_builtin/7 (pred) 438
aidom.call_to_success_builtin/7 (pred) 438
aidom.obtain_info/5 (pred) 438
aidom.input_interface/5 (pred) 438
aidom.input_user_interface/6 (pred) 438
aidom.asub_to_native/6 (pred) 438
aidom.concrete/4 (pred) 438

aidom.unknown_call/5 (pred) 439
aidom.unknown_entry/4 (pred) 439
aidom.empty_entry/4 (pred) 439
aidom.part_conc/5 (pred) 439
aidom.multi_part_conc/4 (pred) 439
aidom.collect_auxinfo_asub/4 (pred) 439
aidom.rename_auxinfo_asub/4 (pred) 439
aidom.dom_statistics/2 (pred) 439
aidom.contains_parameters/2 (pred) 439
68.5 Documentation on internals 439
call_to_success_builtin/7 (pred) 439
input_interface/5 (pred) 440
input_user_interface/6 (pred) 440
68.6 Documentation on imports 440

69 PART IV - CiaoPP Internals 441
69.1 How to use CiaoPP in your own preprocessor 441
69.2 Other information 441
69.3 Basic structure of the code 442

70 Frontend driver (monolithic) 443
70.1 Adding new frontend 443
70.2 Usage and interface 443
70.3 Documentation on exports 443
supported_language/1 (pred) 443
language_extension/2 (pred) 443
language_output_extension/2 (pred) 443
module/1 (pred) 443
module/2 (pred) 444
entry_assertion/3 (pred) 444
assrt_used_as_entry/2 (pred) 444
is_library/1 (pred) 444
cleanup_history/0 (pred) 444
push_history/1 (pred) 445
pop_history/1 (pred) 445
get_output_path/2 (pred) 445
output/0 (pred) 445
output/1 (pred) 445
output/2 (pred) 445
output_ext/1 (pred) 446
output_by_ext/2 (pred) 446
write_one_type/2 (pred) 446
ensure_libcache_loaded/0 (pred) 446
gen_and_load_libcache/0 (pred) 446
get_data/2 (udreexp) 446
clean_ciaopp_db/1 (udreexp) 446
clean_all_ciaopp_db/0 (udreexp) 446
dump/2 (udreexp) 446
dump_dir/1 (udreexp) 446
add_to_db/1 (udreexp) 447
show_dump/1 (udreexp) 447
restore/2 (udreexp) 447
restore/1 (udreexp) 447
dump/1 (udreexp) 447
70.4 Documentation on multifiles 447

hook_compact_global_prop/2 (pred) 447
hook_compact_calls_prop/2 (pred) 447
hook_native_prop/2 (pred) 447
hook_pp_info_clause/3 (pred) 447
hook_pp_info_lit/4 (pred) 447
hook_legal_regtype/1 (pred) 447
hook_insert_regtype/2 (pred) 448
hook_post_init_regtypes/0 (pred) 448
hook_cleanup_lib_regtypes/0 (pred) 448
hook_restore_lib_regtypes/1 (pred) 448
hook_save_lib_regtypes/1 (pred) 448
file_search_path/2 (pred) 448
library_directory/1 (pred) 448
70.5 Documentation on imports 448

71 Advanced output of preprocessor 451
71.1 How to use it 451
71.2 Usage and interface 451
71.3 Documentation on exports 451
raw_output/1 (pred) 451
show_trans_clauses/0 (pred) 452
show_analysis/0 (pred) 452
show_registry_info/0 (pred) 452
show_global_answer_table/1 (pred) 452
show_change_list/0 (pred) 452
71.4 Documentation on imports 452

72 Analyze driver (monolithic) 453
72.1 Adding new analyses 453
72.2 Usage and interface 453
72.3 Documentation on exports 453
assert_domain/1 (pred) 453
last_domain_used/1 (pred) 453
analyze/1 (pred) 453
analyze/2 (pred) 454
analyze1/2 (pred) 454
ctcheck_sum/1 (regtype) 454
acheck_summary/1 (pred) 454
acheck_summary/2 (pred) 454
get_assert_count/1 (pred) 455
acheck/0 (pred) 455
acheck/1 (pred) 455
acheck/2 (pred) 455
clean_analysis_info/0 (pred) 455
clean_analysis_info0/0 (pred) 455
cleanup_for_codegen/0 (pred) 455
trace_fixp/1 (pred) 455
72.4 Documentation on multifiles 456
lazy_analysis/1 (pred) 456
analysis_module/2 (pred) 456
loaded_analysis/1 (pred) 456
analysis/4 (pred) 456
analysis/1 (prop) 456
aidomain/1 (pred) 456
72.5 Documentation on imports 457

73 Transform driver (monolithic) 459
73.1 Adding new transformation 459
73.2 Usage and interface 459
73.3 Documentation on exports 459
transform/1 (pred) 459
transform/2 (pred) 459
73.4 Documentation on multifiles 460
transformation/4 (pred) 460
transformation/1 (prop) 460
73.5 Documentation on imports 460

74 Modular driver 461
74.1 Usage and interface 461
74.2 Documentation on exports 461
cleanup_intermod/0 (pred) 461
valid_mod_analysis/1 (prop) 461
intermod_analyze/2 (pred) 461
intermod_analyze/3 (pred) 462
intermod_ctcheck/2 (pred) 462
intermod_transform/3 (pred) 462
intermod_simp_libs/2 (pred) 462
intermod_simp_libs/3 (pred) 462
inductive_ctcheck/2 (pred) 462
inductive_ctcheck/4 (pred) 462
inductive_ctcheck_summary/3 (pred) 463
intermod_ctcheck_opt/2 (pred) 463
intermod_ctcheck_opt/3 (pred) 463
74.3 Documentation on multifiles 463
dump_flags_list/2 (pred) 463
aidomain/1 (pred) 463
transformation/1 (prop) 463
library_directory/1 (pred) 463
file_search_path/2 (pred) 463
74.4 Documentation on imports 464

75 Database for intermodular analysis driver . . . 465
75.1 Usage and interface 465
75.2 Documentation on exports 465
add_main_module/1 (pred) 465
main_module/2 (pred) 465
punit_module/2 (pred) 465
local_ana_module/2 (pred) 465
registry/3 (pred) 466
registry_header/2 (pred) 466
module_depth/2 (pred) 466
imported_module/2 (pred) 466
caller_module/2 (pred) 466
src_changed/1 (pred) 466
add_src_changed/1 (pred) 466
unset_src_changed/1 (pred) 466
clean_program_structure/0 (pred) 466
set_main_module/1 (pred) 467
set_punit_modules/1 (pred) 467
set_local_ana_modules/1 (pred) 467
get_registry/4 (pred) 467

add_registry/2 (pred) 467
cleanup_registry/1 (pred) 467
reg_version/1 (pred) 467
registry_header_format/2 (pred) 468
mod_typedb/2 (pred) 468
add_mod_typedb/2 (pred) 468
enum_mod_typedb/1 (pred) 468
75.3 Documentation on imports 468

76 Intermodular analysis scheduler 469
76.1 Usage and interface 469
76.2 Documentation on exports 469
modules_analyzed/1 (pred) 469
reset_queue/0 (pred) 469
push/2 (pred) 469
pop/2 (pred) 470
naive_pending_modules/1 (pred) 470
force_analysis/1 (pred) 470
cleanup_intermod_scheduling/0 (pred) 470
naive_module_order/1 (pred) 470
iterations/1 (pred) 470
module_processed/2 (pred) 470
setup_scheduling/4 (pred) 470
is_naive_scheduling/1 (pred) 471
add_naive_pending_modules/1 (pred) 471
76.3 Documentation on imports 471

77 Program structure for intermodular analysis 473
77.1 Usage and interface 473
77.2 Documentation on exports 473
compute_punit_modules/3 (pred) 473
get_punit_modules/1 (pred) 474
get_punit_included_files/1 (pred) 474
get_all_module_cycles/2 (pred) 474
module_is_processable/1 (pred) 475
ensure_registry_file/3 (pred) 475
read_registry_file/3 (pred) 475
write_registry_file/3 (pred) 475
open_mode/3 (pred) 476
change_open_mode/2 (pred) 476
save_registry_info/3 (pred) 476
save_registry_info/2 (pred) 477
compute_imported_modules/0 (pred) 477
get_imported_module_base/2 (pred) 477
get_modules_analyzed/1 (pred) 477
set_modules_analyzed/1 (pred) 477
77.3 Documentation on imports 478

78 Intermodular entry policy 479
78.1 Usage and interface 479
78.2 Documentation on exports 479
check_curr_entry_id/1 (pred) 479
curr_entry_id/1 (pred) 479
get_entry_info/3 (pred) 479
intermod_entry_point/7 (pred) 479
add_entries_to_registry/1 (pred) 480
78.3 Documentation on imports 480

79 Intermodular success policy 481
79.1 Usage and interface 481
79.2 Documentation on exports 481
get_success_info/7 (pred) 481
apply_success_policy/9 (pred) 481
79.3 Documentation on imports 482

80 Preprocessing Flags 483
80.1 Usage and interface 483
80.2 Documentation on exports 483
push_pp_flag/2 (pred) 483
pop_pp_flag/1 (pred) 483
current_pp_flag/2 (pred) 483
set_pp_flag/2 (pred) 484
pp_flag/2 (pred) 484
pp_flag/1 (regtype) 484
flag_value/1 (regtype) 485
valid_flag_value/2 (prop) 485
valid_flag_values/2 (pred) 486
dump_flags/1 (pred) 486
save_config/1 (pred) 486
restore_config/1 (pred) 486
remove_config/1 (pred) 486
show_config/1 (pred) 487
show_configs/0 (pred) 487
sublist2/2 (pred) 487
typeanalysis/1 (pred) 487
80.3 Documentation on multifiles 487
$is_persistent/2 (pred) 487
persistent_dir/2 (pred) 487
persistent_dir/4 (pred) 487
dump_flags_list/2 (pred) 488
80.4 Documentation on imports 488

81 Debugging PLAI analyses 489
81.1 Debug raw analysis result 489
81.2 Inspect analysis graphs 489
81.3 Trace fixpoint operations 489
81.4 Activate run-time checks 490
81.5 Debug fixpoint step by step 490
81.6 Access PLAI databases directly 490

82 Incremental analysis (high level) 491

82.1 Usage 491
82.2 Example 491
82.3 Side effects 492
82.4 Usage and interface 493
82.5 Documentation on exports 493
incremental_module/1 (pred) 493
incremental_module/2 (pred) 493
incremental_analyze/1 (pred) 493
incremental_analyze/2 (pred) 493
reset_incremental_analysis_info/0 (pred) 494
config_incremental_load/1 (pred) 494
all_assertions_pred/4 (pred) 494
82.6 Documentation on imports 494

83 Incremental analysis (low level) 495

83.1 Usage and interface 495
83.2 Documentation on exports 495
init_empty_inc_analysis/0 (pred) 495
init_file_inc_analysis/3 (pred) 495
td_add_clauses/2 (pred) 495
td_delete_clauses/2 (pred) 496
bu_delete_clauses/2 (pred) 496
td_rec_delete_complete/3 (pred) 496
module_has_entries/1 (pred) 497
remove_useless_completes/1 (pred) 497
run_inc_fixpoint/1 (pred) 497
incrementally_update_analysis/2 (pred) 497
process_external_complete_change/6 (pred) 497
83.3 Documentation on imports 498

84 Update plai_db after clause deletion (incremental analysis) 499

84.1 Usage and interface 499
84.2 Documentation on exports 499
remove_clauses_and_related_info_collect_preds/4 (pred) 499
bottom_up_delete_completes_preds/4 (pred) 499
bottom_up_delete_complete/5 (pred) 500
external_calls/4 (pred) 500
84.3 Documentation on imports 500

85 Database for incremental analysis 501
85.1 Usage and interface 501
85.2 Documentation on exports 501
init_clkeys/0 (pred) 501
clean_incremental_db/0 (pred) 501
change_id_clause/2 (pred) 501
insert_after_clkey/2 (pred) 501
save_clause_db/0 (pred) 501
restore_clause_db/0 (pred) 502
remove_clauses_pred/2 (pred) 502
add_all_clauses/1 (pred) 502
add_new_preds/1 (pred) 502
get_current_clauses/1 (pred) 502
get_current_assertions/1 (pred) 502
add_assertion_source_db/1 (pred) 502
del_assertion_source_db/1 (pred) 503
add_changed_registry/4 (pred) 503
get_changed_registry/4 (pred) 503
clean_incanal_mod_data/0 (pred) 503
update_inc_clkey/1 (pred) 503
all_different_mods/0 (pred) 503
set_loaded_mods/1 (pred) 503
loaded_mods/1 (pred) 503
set_analyzed_mods/1 (pred) 504
analyzed_mods/1 (pred) 504
fixpoint_id_/2 (pred) 504
store_current_fixpoint_id/1 (pred) 504
restore_fixpoint_id/1 (pred) 504
85.3 Documentation on imports 504

86 Persistent database for incremental analysis 505
86.1 Usage and interface 505
86.2 Documentation on exports 505
set_loaded_module/1 (pred) 505
reset_persistent_db/0 (pred) 505
load_persistent_if_needed/2 (pred) 505
top_level_of_files/2 (pred) 505
has_dump/2 (pred) 505
set_inc_persistent/1 (pred) 505
inc_persistent_status/1 (regtype) 506
save_persistent_analysis/0 (pred) 506
clean_persistent_analysis/0 (pred) 506
86.3 Documentation on imports 506

87 Incremental computation of tarjan algorithm 507
87.1 Usage and interface 507
87.2 Documentation on exports 507
inc_add_source_clauses/3 (pred) 507
rearrange_tarjan_after_deletion/1 (pred) 507
tarjan_data/1 (pred) 507
predicates/1 (pred) 507
rec/1 (pred) 508
vertexes/1 (pred) 508
rec_preds/1 (pred) 508
87.3 Documentation on imports 508

88 Diff algorithm 509
88.1 Complexity 509
88.2 Pseudocode 509
88.3 Example 509
88.4 Patch 510
88.5 Usage and interface 510
88.6 Documentation on exports 510
diff/4 (pred) 510
patch/3 (pred) 510
diff_item/1 (regtype) 511
88.7 Documentation on imports 511

89 fixpo_dd (library) 513
89.1 Usage and interface 513
89.2 Documentation on exports 513
query/8 (pred) 513
init_fixpoint/0 (pred) 514
cleanup_fixpoint/1 (pred) 514
entry_to_exit/7 (pred) 514
$change_list/3 (pred) 514
proj_to_prime_nr/9 (pred) 514
proj_to_prime_r/8 (pred) 515
proj_to_prime/9 (pred) 515
compute/9 (pred) 516
td_mark_parents_change_list/2 (pred) 516
add_change/5 (pred) 517
mark_parents_change_list_scc/3 (pred) 517
add_change_scc/6 (pred) 518
fixpoint_compute_change/9 (pred) 518
89.3 Documentation on imports 519

90 The Preprocessing Unit Component 521

91 The Preprocessing Unit 523
91.1 The preprocessing unit 523
91.2 Builtin predicates 524
91.3 Native properties 524
91.4 Organization of the code 524

92 Preprocessing Unit Information Server 527
92.1 Usage and interface 527
92.2 Documentation on exports 527
preprocessing_unit/3 (pred) 527
program/2 (pred) 528
filtered_program_clauses/3 (pred) 528
replace_program/2 (pred) 528
native_to_prop/2 (pred) 528
prop_to_native/2 (pred) 529
native_to_props_visible/2 (pred) 529
dynamic_or_unknown_predicate/1 (pred) 529
get_assertion/2 (pred) 529
add_assertions/1 (pred) 529
add_assertion/1 (pred) 529
add_directive/1 (pred) 529
erase_directive/1 (pred) 529
type_of_directive/2 (pred) 530
pr_key_clean/0 (pred) 530
pr_key_add/1 (pred) 530
pr_key_get/1 (pred) 530
add_defined_pred/2 (pred) 530
new_predicate/3 (pred) 531
predicate_names/1 (pred) 531
multifile_predicate_names/1 (pred) 531
inject_output_package/1 (pred) 531
add_output_package/1 (pred) 531
get_output_package/1 (pred) 531
add_output_operator/3 (pred) 532
get_output_operator/3 (pred) 532
add_comment/1 (pred) 532
get_comment/1 (pred) 532
cleanup_comment_db/0 (pred) 532
cleanup_commented_assrt/0 (pred) 532
get_commented_assertion/2 (pred) 532
add_commented_assertions/1 (pred) 533
add_commented_assertion/1 (pred) 533
cleanup_punit/0 (pred) 533
get_call_from_call_assrt/7 (pred) 533
get_pred_mod_defined/2 (pred) 533
assertion_set_status/3 (pred) 533
assertion_set_head/3 (pred) 533
assertion_set_calls/3 (pred) 534
assertion_set_success/3 (pred) 534
assertion_set_comp/3 (pred) 534
cleanup_libcache/0 (pred) 534
loaded_libcache/0 (pred) 534
load_libcache/1 (pred) 534
gen_libcache/1 (pred) 534
type_of_goal/2 (udreexp) 534
92.3 Documentation on multifiles 535
define_flag/3 (pred) 535
hook_compact_global_prop/2 (pred) 535
hook_compact_calls_prop/2 (pred) 535
hook_native_prop/2 (pred) 535
hook_pp_info_clause/3 (pred) 535
hook_pp_info_lit/4 (pred) 535

hook_legal_regtype/1 (pred) 535
hook_insert_regtype/2 (pred) 535
hook_post_init_regtypes/0 (pred) 535
hook_cleanup_lib_regtypes/0 (pred) 535
hook_restore_lib_regtypes/1 (pred) 535
hook_save_lib_regtypes/1 (pred) 536
92.4 Documentation on imports 536

93 native (library) 537
93.1 Usage and interface 537
93.2 Documentation on exports 537
builtin/2 (pred) 537
native_prop_map/3 (pred) 537
native_prop_term/1 (regtype) 537
wam_builtin/2 (pred) 537
93.3 Documentation on multifiles 538
hook_compact_global_prop/2 (pred) 538
hook_compact_calls_prop/2 (pred) 538
hook_native_prop/2 (pred) 538
hook_pp_info_clause/3 (pred) 538
hook_pp_info_lit/4 (pred) 538
hook_legal_regtype/1 (pred) 538
hook_insert_regtype/2 (pred) 538
hook_post_init_regtypes/0 (pred) 538
hook_cleanup_lib_regtypes/0 (pred) 538
hook_restore_lib_regtypes/1 (pred) 538
hook_save_lib_regtypes/1 (pred) 538
93.4 Documentation on internals 539
native/1 (regtype) 539
vlist/1 (regtype) 540
93.5 Documentation on imports 540

94 program_keys (library) 541
94.1 Usage and interface 541
94.2 Documentation on exports 541
cleanup_program_keys/0 (pred) 541
clause_key/2 (pred) 541
clauses_keys/2 (pred) 541
clause_number/2 (pred) 542
first_key/2 (pred) 542
last_clause/1 (pred) 542
make_atom/2 (pred) 542
inverse_rewrite_source_program_cl/2 (pred) 542
inverse_rewrite_source_body/2 (pred) 542
rewrite_source_all_clauses/2 (pred) 542
rewrite_source_clause/3 (pred) 542
decode_litkey/5 (pred) 543
decode_clkey/4 (pred) 543
decode_entrykey/4 (pred) 543
decode_predkey/3 (pred) 543
is_clkey/1 (pred) 544
is_litkey/1 (pred) 544
is_entrykey/1 (pred) 544
is_directive/3 (pred) 544
is_clause/4 (pred) 544

orig_clause_id/2 (pred) . . . 544
lit_ppkey/3 (pred) . . . 544
clid_of_atomid/2 (pred) . . . 544
clause/1 (regtype) . . . 545
clausebody/1 (pred) . . . 545
literal_ppkey/1 (regtype) . . . 545
litkey/1 (regtype) . . . 545
clkey/1 (regtype) . . . 546
predkey/1 (regtype) . . . 546
counter/3 (pred) . . . 546
get_predkey/3 (pred) . . . 546
get_predkeys/2 (pred) . . . 546
predkey_from_sg/2 (pred) . . . 546
get_clkey/4 (pred) . . . 546
get_litkey/5 (pred) . . . 547
94.3 Documentation on internals . . . 547
body/1 (pred) . . . 547
drid/1 (regtype) . . . 547
head/1 (regtype) . . . 547
94.4 Documentation on imports . . . 548

95 tr_syntax (library) . . . 549
95.1 Usage and interface . . . 549
95.2 Documentation on exports . . . 549
cleanup_tr_syntax/0 (pred) . . . 549
traverse_clauses/4 (pred) . . . 549
95.3 Documentation on imports . . . 549

96 The Global Information Server . . . 551

97 Analysis Information Server . . . 553
97.1 Usage and interface . . . 553
97.2 Documentation on exports . . . 553
get_info/5 (pred) . . . 553
get_absint/4 (pred) . . . 553
type2measure/3 (pred) . . . 553
type_holds/3 (pred) . . . 553
type_fails/3 (pred) . . . 553
get_memo_lub/5 (pred) . . . 553
get_completes_lub/6 (pred) . . . 554
get_completes/4 (pred) . . . 554
kind_of_info/7 (pred) . . . 554
97.3 Documentation on imports . . . 554

98 The Abstract Interpretation Component -PLAI . . . 555

99 PLAI- Abstract Interpretation-based Analysis . . . 557

100 Program Analysis (PLAI) 559
100.1 Usage and interface 559
100.2 Documentation on exports 559
plai/5 (pred) 559
cleanup_plai/1 (pred) 559
mod_plai/5 (pred) 559
is_checker/1 (pred) 559
analyze/7 (pred) 560
init_fixpoint/1 (pred) 560
entry_point/5 (pred) 560
generate_trans_clauses/4 (pred) 560
transform_clauses_/5 (pred) 560
topdown_analysis/3 (pred) 560
mod_topdown_analysis/3 (pred) 560
100.3 Documentation on imports 560

101 fixpo_plai (library) 561
101.1 Usage and interface 561
101.2 Documentation on exports 561
query/8 (pred) 561
init_fixpoint/0 (pred) 561
cleanup_fixpoint/1 (pred) 561
entry_to_exit/9 (pred) 562
approx/6 (pred) 562
fixpoint/6 (pred) 562
$depend_list/3 (pred) 562
101.3 Documentation on imports 562

102 Available type domains and widenings 563
102.1 Available widenings 563
102.2 Other type domains 563
102.3 Some experiments 563

103 plai_db (library) 565
103.1 Usage and interface 565
103.2 Documentation on exports 565
complete/7 (pred) 565
lub_complete/6 (pred) 565
memo_call/5 (pred) 566
memo_table/6 (pred) 566
memo_lub/5 (pred) 566
pragma/5 (pred) 566
complete_parent/2 (pred) 566
cleanup_plai_db/1 (pred) 566
invalid_call/6 (pred) 566
raw_success/6 (pred) 567
get_parent_key/4 (pred) 567
get_complete/8 (pred) 567
get_memo_table/7 (pred) 567
get_raw_success/7 (pred) 567
add_parent_complete/5 (pred) 568
del_parent_complete/6 (pred) 568
patch_parents/6 (pred) 568
merge_parents/3 (pred) 569

del_parent/4 (pred) . . . 569
update_complete_id/4 (pred) . . . 569
delete_complete/3 (pred) . . . 569
remove_extra_info_complete/3 (pred) . . . 569
delete_plai_db_one_clause/4 (pred) . . . 569
complete_key_from_id/3 (pred) . . . 570
erase_previous_memo_tables_and_parents/4 (pred) . . . 570
erase_last_memo_table/3 (pred) . . . 570
erase_previous_memo_lubs/2 (pred) . . . 570
erase_previous_parents_info/5 (pred) . . . 570
init_rev_idx/1 (pred) . . . 571
clean_rev_idx/1 (pred) . . . 571
complete_id_key/3 (pred) . . . 571
memo_table_id_key/3 (pred) . . . 571
add_invalid_call/6 (pred) . . . 571
store_raw_success/6 (pred) . . . 571
get_raw_success/6 (pred) . . . 571
plai_db_id/1 (regtype) . . . 572
103.3 Documentation on imports . . . 572

104 Improving Analysis Using Trust Assertions . . . 573
104.1 Complementation of Trust Assertions . . . 573
104.2 Using Trust Assertions . . . 573

105 Debugging the fixpoint operations . . . 575
105.1 Example of visualization . . . 575
105.2 uDraw(Graph) extended features . . . 575

106 Fixpoint tracer . . . 577
106.1 Usage and interface . . . 577
106.2 Documentation on exports . . . 577
fixpoint_trace/7 (pred) . . . 577
trace_fixp/1 (pred) . . . 577
memotable_trace/3 (pred) . . . 578
show_spypoint_op_count/0 (pred) . . . 578
show_updated_memotable/3 (pred) . . . 578
trace_init/0 (pred) . . . 578
trace_end/0 (pred) . . . 578
trace_reset/0 (pred) . . . 578
trace_option/1 (regtype) . . . 578
106.3 Documentation on imports . . . 579

107 view_fixp (library) . . . 581
107.1 Usage and interface . . . 581
107.2 Documentation on exports . . . 581
start_view/0 (pred) . . . 581
end_view/0 (pred) . . . 581
clean_fixpoint_graph/0 (pred) . . . 581
view_fixpoint/7 (pred) . . . 581
107.3 Documentation on imports . . . 581

108 Batch analysis client 583
108.1 Analysis options 583
108.2 Description of the implementation 583
108.2.1 Prolog files: 583
108.2.2 Other directories: 583
108.3 Data files 584
108.4 Usage and interface 584
108.5 Documentation on exports 584
analysis_start/2 (pred) 584
update_tasks_analysis_status/0 (udreexp) 584
update_tasks_analysis_status/0 (udreexp) 584
108.6 Documentation on internals 584
analysis_opt/1 (prop) 584
108.7 Documentation on imports 585

109 ciaopp_master (application) 587

110 Worker for CiaoPP batch processing 589
110.1 Generated data 589
110.2 Usage and interface 589
110.3 Documentation on exports 589
start_worker/1 (pred) 589
logged_once_port_reify/4 (pred) 589
110.4 Documentation on internals 590
task_status/1 (regtype) 590
110.5 Documentation on imports 590

111 Auxiliary predicates 591
111.1 Usage and interface 591
111.2 Documentation on exports 591
dump_file/4 (pred) 591
string_contained/2 (pred) 591
get_mod_name_from_file/2 (pred) 591
newer/2 (pred) 591
make_dir_nofail/1 (pred) 592
111.3 Documentation on imports 592

112 Database for ciaopp_batch process 593
112.1 Usage and interface 593
112.2 Documentation on exports 593
add_task_status/5 (pred) 593
task_status/5 (pred) 593
update_task_status/0 (pred) 593
last_file_log/2 (pred) 594
init_analysis_db/0 (pred) 594
init_tmp_db/1 (pred) 594
clean_db/0 (pred) 594
clean_tmp_db/0 (pred) 594
set_current_task/2 (pred) 594
current_task_proc/2 (pred) 594
set_last_error/3 (pred) 595
update_tasks_analysis_status/0 (pred) 595
report_mod_info/3 (pred) 595
db_data_dir/1 (pred) 595

112.3 Documentation on multifiles 595
$is_persistent/2 (pred) 595
persistent_dir/2 (pred) 595
persistent_dir/4 (pred) 595
112.4 Documentation on imports 596

113 tasks_db (library) 597
113.1 Usage and interface 597
113.2 Documentation on exports 597
add_task/1 (pred) 597
add_tasks/1 (pred) 597
pop_task/4 (pred) 597
analysis_task/4 (pred) 597
clean_db/0 (pred) 597
init_tasks_db/0 (pred) 598
113.3 Documentation on multifiles 598
$is_persistent/2 (pred) 598
persistent_dir/2 (pred) 598
persistent_dir/4 (pred) 598
113.4 Documentation on imports 598

References 599

Library/Module Index 603

Predicate Index 605

Property Index 607

Regular Type Index 609

Declaration Index 611

Concept Index 613

Author Index 615

Global Index 617

1 Summary

CiaoPP is the abstract interpretation-based preprocessor of the Ciao multi-paradigm program development environment. CiaoPP can perform a number of program debugging, analysis, and source-to-source transformation tasks on (Ciao) Prolog programs. These tasks include:

- Inference of properties of the predicates and literals of the program, including types, modes and other variable instantiation properties, non-failure, determinacy, bounds on computational cost, bounds on sizes of terms in the program, etc.
- Certain kinds of static debugging and verification, finding errors before running the program. This includes checking how programs call system library predicates and also checking the assertions present in the program or in other modules used by the program. Such assertions represent essentially partial specifications of the program.
- Several kinds of source to source program transformations such as program specialization, slicing, partial evaluation of a program, program parallelization (taking granularity control into account), inclusion of run-time tests for assertions which cannot be checked completely at compile-time, etc.
- The abstract model of the program inferred by the analyzers can be used to certify that untrusted mobile code is safe w.r.t. a given policy (this implements the *abstraction-carrying code* approach to mobile code safety).

The information generated by analysis, program properties to be verified, descriptions of the system libraries, directives provided to guide analysis, etc. are all written in the same assertion language, which is in turn also processed by the Ciao system documentation generator, `lpdoc`.

CiaoPP is distributed under the GNU general public license.

Note: This is the CiaoPP **reference** manual. To begin using CiaoPP, we suggest you start by following one or more of the companion CiaoPP **tutorials** available in the Ciao system documentation.

This documentation corresponds to version 1.5 (2022/3/2, 20:34:30 CET).

2 Introduction

CiaoPP is the abstract interpretation-based preprocessor of the Ciao multi-paradigm program development environment. CiaoPP can perform a number of program debugging, analysis, and source-to-source transformation tasks on (Ciao) Prolog programs. These tasks include:

- Inference of properties of the predicates and literals of the program, including types, modes (⟨undefined⟩ [groundness and sharing], page ⟨undefined⟩), ⟨undefined⟩ [term structure], page ⟨undefined⟩, and other variable instantiation properties, non-failure, determinacy, bounds on computational cost (e.g., ⟨undefined⟩ [number of resolution steps of the computation], page ⟨undefined⟩), bounds on size of terms in the program, etc (see Chapter 7 [Available abstract domains], page 31).
- Certain kinds of static debugging and verification, finding errors before running the program. This includes checking how programs call system library predicates and also checking the assertions present in the program or in other modules used by the program. Such assertions represent essentially partial specifications of the program.
- Several kinds of source to source program transformations such as program specialization, slicing, partial evaluation of a program, program parallelization (taking granularity control into account), inclusion of run-time tests for assertions which cannot be checked completely at compile-time, etc.
- The abstract model of the program inferred by the analyzers can be used to certify that untrusted mobile code is safe w.r.t. a given policy (this implements the *abstraction-carrying code* approach to mobile code safety).

The information generated by analysis, program properties to be verified, descriptions of the system libraries, directives provided to guide analysis, etc. are all written in the same assertion language, which is in turn also processed by the Ciao system documentation generator, `lpdoc`.

CiaoPP is distributed under the GNU general public license.

2.1 How to use this manual

This is a *reference manual*. I also includes a part on the CiaoPP internals. You can use this manual to:

- Look up descriptions for the commands, flags, options, domains, transformations, etc. of CiaoPP. In the html versions of the manual you can use the search facility to this end. In other versions the Predicate/Method Definition Index can help you in locating commands; the Regular Type Definition Index can help in locating the definitions of the types associated to the arguments of commands; the Concept Definition Index may help in locating the part of the manual where a particular feature of CiaoPP is described; and the Global Index includes all of the above plus references to pages where the command, type, or concept is used (not necessarily defined).
- Learn about how to extend CiaoPP, for example by defining new analysis domains.
- Learn about CiaoPP internals.

Since this is a **reference** manual, to begin using CiaoPP, we suggest you start by following one or more of the companion CiaoPP **tutorials** that are available in the Ciao system documentation.

This manual assumes in some places some familiarity with the techniques that implement the different functionalities, such as abstract interpretation, partial evaluation, etc. However, references are included to technical papers that explain in detail such techniques.

2.2 Note

Since we are often merging new functionality into the CiaoPP distribution from more experimental versions, you may find sometimes that some documented functionality in this manual is not available or not working properly. We will be grateful if you report any missing functionality or bugs you find.

2.3 Version/Change Log

Version 1.5 (2022/3/2, 20:34:30 CET)

- ADDED: CiaoPP is included now by default with the `devenv` bundle.
- ADDED: Output options in the `output/2` predicate.
- ADDED: More examples (most of them for verifly).
- ADDED: Documentation for debugging analyses.
- ADDED: `ciaoppcl` can start as an active module (flycheck).
- IMPROVED: Better automatic selection of analysis domains (covering better the properties to be checked; using mode domains before type domains, etc.); `dom_sel` flag to decide whether to automatically select domains for verification.
- IMPROVED: Refactoring and improving `ctchecks` (compile-time assertion checking) code: modular ctchecking working again (i.e., after intermodular fixpoint); report assertions per module; better messages; many bug fixes.
- IMPROVED: Reducing boilerplate code in the implementation of analysis domains using the new `aidomain` package.
- IMPROVED: Simplified menu, unified menu for analysis and ctchecks.
- IMPROVED: Improved precision of (nf,det) analysis domains. Adding (experimental) new `nfdet` combined analysis domain.
- CHANGED: Change default setting for entry point selection from assertions (exported calls by default).
- CHANGED: Disabled output for `ciaoppcl -V`.
- CHANGED: Assertion simplification (eliminating statically proven properties from run-time checks) now enabled by default during assertion checking.
- CHANGED: `trust pred` assertions expanded to `check calls`, `trust success` and `trust comp` assertions.
- CHANGED: Abort `auto_interface` action early if there is a compilation error.
- CHANGED: `pp_info` flag (printing analysis infor at literal level) moved to the naive menu.
- FIXED: Many bug fixes and performance improvements: eliminated some dangling choicepoints; avoid printing some calls assertions twice; wrong use of `denorm_goal_prop/3` changed to `prop_unapply/3`; missing clause to `abs_exec_cond:type_of/4` to handle `deftypes` domain.
- FIXED: Bug in treatment of dynamic predicates.

Version 1.4 (2020/11/18, 6:18:7 CET)

- General changes and new features:
  - LLVM-based frontend improved and moved to its own bundle (see `ciaopp_llvm` bundle).
  - Split `typeslib` as a separate bundle.
  - Allow heads of entry assertions to be non-normalized.
  - Adapted to new hiord.

    - [new] Command `ciaopp-dump`, which performs several actions over a ciaopp analysis dump: it subsumes the old `ciaopp-dump-cmp` and `ciaopp-dump-cmp` commands. New options for: showing the contents of a dump file, a code reachability report, static, offline checks of assertions using a dump file, and general statistics for the analysis results.
    - [new] Added `-op Suffix` option to ciaopp command-line (useful for fly-check).
    - [new] Warning if no entries were found
    - [new] Unified messages, now controlled by `ciaopp_log.pl`
    - [new] `ciaopp-batch` command to run ciaopp on many files and with time-outs.
    - [new] Modular (non-incremental) analysis with types (shortening).
    - [new] Bottom-up incremental update of fixpoint (at literal level).
    - [new] Modular (non-incremental) analysis with types (shortening).
- Domains:
    - Implemented domains using (a special) trait package.
    - Added `needs/2` operation.
    - Renamed `abstypes_abs` to `auxinfo_asub`.
    - eterms: `member/2`, `=/2` as native properties (for assertions).
    - pdb:
        - Optimize `pdb_compute_lub`: top if any `ASub` is top.
        - Use `fail` literals.
    - sharing: fixed `free/1` handlers
    - shfr: fixes in handlers of `==/2`, `=/2`, `'\=='/2`, `'\='/2`, `free/1` (native version of `var/1`)
- Fixpoints:
    - Split compilation options (`debug`, `trace`, `rtchecks`) in common file `fixpoint_options.pl`
    - Improved tracing of clauses
    - Refactored fixpoints to make them easier to merge
- Fixpoint `dd`:
    - [fix] Reuse a complete with the same head but different vars order
    - [performance] Using get_memo_table because Id+Key is unique
    - [fix] Case in which a literal is not reachable
    - Improved documentation
- Analysis of higher-order code:
    - [new] Flag for automatic generation of entries of meta calls.
    - [fix] `call/N` was not being detected as meta predicate (and flattened when possible).
    - [new] `\+` not treated as meta, flatten calls known at compile time.
- Flags and options menu:
    - [new] Flag to remove useless (unreachable) completes after fixpo.
    - `punit_boundary`: change default value to bundle.
    - Included `incanal` flag, changed `ext_policy` in menu (same as `pp_flag`).
    - Improved options menu (added and simplified dependencies, simplified text, grouped actions, better documentation).

Version 1.3 (2019/11/3, 11:16:23 CEST)

- New functionality:
  - Backported (and improved) incremental analysis (incanal) from CiaoPP 0.8.
  - Integrated incremental and modular analysis (`pp_flag incremental=on`)
  - Integrated modular analysis in the general analysis driver.
  - Added analysis using run-time semantics of assertions to the `dd` fixpoint (`pp_flag old_trusts=off`).
  - Fixes in meta-calls (work in progress).
  - Modularized domains, now they use the aidomain package (work in progress).
  - Added generic, non relational domain with simpler domain operations.
  - New flag value: restrict modular analysis to the modules of a bundle (`pp_flag punit_boundary=bundle`).
- Performance improvements:
  - Added hook to cache library assertions.
  - Added flag to load modules faster by preloading ciao libraries.
  - Fixed many dangling choicepoints across all modules.
  - Fixed performance issues in modular analysis.
  - Fixed bug of metacalls inside a recursion (`dd` fixpoint).
- User interface and documentation:
  - Rearranged manual.
  - Created web interface for demos (see `ciaopp_online` bundle).
  - Added a high level interface for intermental analisis (incanal).
- Benchmarks, internal testing, and debugging:
  - Tests/benchmarks moved to a separate bundle (ciaopp_tests).
  - Added tests for gitlab CI (continuous integration).
  - Some fixes in the davinci interface.
  - Fixed (documentation) assertions. CiaoPP can be run with the package rtchecks.
  - Added analysis_stats.pl to unify statistics collecting.
  - ciaopp-dump-cmp: new command to compare two ciaopp analaysis dumps.
  - ciaopp-dump-fmt: new command that outputs the analysis in dot format.
  - New flag value: Raw analysis printer (`pp_flag output_lang=raw`).
  - Added `pp_flag` to trace fixpoints.
- Other bug fixes, cleanups, refactoring, etc.:
  - Removed `api` (now using `p_unit`).
  - Fixed maintaining `plai_db` for complete operations
  - Fixed classifying mistakenly recursive predicates as non recursive (meta predicates).
  - Fixed issue with reexported predicates in p_unit.
  - Fixed problem with meta_predicates that did not have any meta argument.
  - Added `free/1` to `sharefree_clique` domain.
  - Replaced `runtime_control:statistics/2` by `analysis_stats:pp_statistics/2`.

- Using `p_unit/program_keys.pl` for the keys of ciaopp.

Version 1.2 (2006/1/3, 11:16:23 CEST)
Check point

Version 1.0 (2001/11/7, 19:5:57 CET)
Major code reorganization from CiaoPP 0.8. Moved to repo system. See 0.8 manual for changelog prior to 1.0 (covers 1999-2000).

3 PART I - Using CiaoPP

Author(s): The Ciao Development Team.

This part documents several levels of interaction with CiaoPP. As quick introduction we recommend going through the ⟨undefined⟩ [CiaoPP Quick Tutorial], page ⟨undefined⟩ and ⟨undefined⟩ [Advanced Tutorial on Program Development and Optimization using the CiaoPP Program Processor], page ⟨undefined⟩ sections.

CiaoPP can be used from an intuitive graphical menu interface, based on the `emacs` editor, which allows the interactive selection of configuration options. An equivalent command-line interface, described in Chapter 6 [The CiaoPP command-line interface], page 27, is provided for non-interactive use.

For more advanced uses, CiaoPP can be used directly as a library from a toplevel interface. We provide both a mostly automatic high-level interface, described in Chapter 4 [The CiaoPP high-level interface], page 11, and a low-level interface intended for advanced users, detailed in Chapter 5 [The CiaoPP low-level interface], page 17. Both the graphical and the command-line interfaces are based on the functionality provided by the high and low-level interfaces.

4 The CiaoPP high-level interface

Author(s): CiaoPP development team.

This module defines the high-level interface for CiaoPP, which makes it easy to perform some analysis and transformation tasks, such as checking program assertions (i.e., types, modes, determinacy, non-failure, cost, etc.), and performing optimizations such as specialization and parallelization. The results can be observed both as CiaoPP messages and as a transformed annotated program.

In the `emacs` environment these actions can be performed by clicking on the corresponding button in the toolbar or in the CiaoPP menus. The high-level interface allows calling these actions as predicates from a **CiaoPP top-level** shell:

- `auto_check_assert(File)`: check assertions in File
- `auto_analyze(File)`: analyze File
- `auto_optimize(File)`: optimize File

The actions above can be controlled by a set of **preprocessor flags**. Note that, depending on some of these flags, processing can be of one module or also all the related modules. The default values of the CiaoPP flags can be changed with the following predicates:

- `customize(all)`: select (interactively) the values for the different options (do not perform any action).
- `set_menu_flag/3`: select flag values non-interactively.

The `emacs` environment offers a graphical version of these menus.

These customization menus can be configured to show more or less detailed options, depending on the level of expertise of the user. This can be configured in the menu changing the `Menu Level` flag to `naive` or `expert`. The following predicates provide handy shortcuts to perform customization and preprocessing actions:

- `customize_and_preprocess(File)`: enter a menu to select the preprocessing action and options to be performed on file `File` (or `File` and its related modules), select the different options, and then perform the action.
- `again`: perform again the last actions selected for `customize_and_preprocess/1` on the same file (useful for re-processing after changing a file).

4.1 Usage and interface

- **Library usage:**

  ```
  :- use_module(ciaopp(auto_interface)).
  ```

- **Exports:**
  - *Predicates:*

    `auto_analyze/1`, `auto_optimize/1`, `auto_check_assert/1`, `auto_analyze/2`, `auto_optimize/2`, `auto_check_assert/2`, `customize/0`, `customize/1`, `customize_and_preprocess/0`, `customize_and_preprocess/1`, `customize_but_dont_save/1`, `again/0`.
  - *Multifiles:*

    `hook_menu_flag_values/3`, `hook_menu_check_flag_value/3`, `hook_menu_flag_help/3`, `hook_menu_default_option/3`, `aidomain/1`.

4.2 Documentation on exports

auto_analyze/1: PREDICATE

Usage: `auto_analyze(F)`

Analyze the module `F` with the current analysis options (use `customize(analyze)` to change these options).

auto_optimize/1: PREDICATE

Usage: `auto_optimize(F)`

Optimize file `F` with the current options (use `customize(optimize)` to change these options).

auto_check_assert/1: PREDICATE

Usage: `auto_check_assert(F)`

Check the assertions in file `F`, with the current options, giving errors if assertions are violated (use `customize(check_assertions)` to change these options).

auto_analyze/2: PREDICATE

Usage: `auto_analyze(F,OFile)`

Same as `auto_analyze/1` but the output file will be `OFile`.

auto_optimize/2: PREDICATE

Usage: `auto_optimize(F,OFile)`

Same as `auto_optimize/1` but the output file will be `OFile`.

auto_check_assert/2: PREDICATE

Usage: `auto_check_assert(F,OFile)`

Same as `auto_check_assrt/1` but the output file will be `OFile`.

customize/0: PREDICATE

Usage:

Enter an interactive menu to select the preprocessing action (analysis / assertion checking / transformation / optimization / ...) to be performed by default and the different options (i.e., setting the preprocessor flags).

customize/1: PREDICATE

Usage: `customize(X)`

Customize is used for changing the values of the flags used during preprocessing. These flags are grouped into three main classes of actions: *analyzing*, *checking assertions*, or *optimizing* programs. `X` should be instantiated to one of: `analyze`, `check_assertions`, `optimize`, or `all` (which allows choosing among the previous three).

customize_and_preprocess/0: PREDICATE

Usage:

Select options using `customize/0`, and then call `auto_analyze/1`, `auto_optimize/1`, or `auto_check_assert/1` (as determined by the selected options) on the default file. If no default file is defined, prompt for the name of to be processed, which becomes from now on the default file.

customize_and_preprocess/1: PREDICATE

Usage: `customize_and_preprocess(File)`

Select options using `customize/0`, and then call `auto_analyze/1`, `auto_optimize/1`, or `auto_check_assert/1` (as determined by the selected options) with `File` as argument. `File` is from now on the default file.

customize_but_dont_save/1: PREDICATE

Usage: `customize_but_dont_save(Option)`

Same as customize(`Option`), but menu flags will not be modified.

again/0: PREDICATE

Usage:

Performs the last actions done by `customize_and_preprocess/1`, on the last file previously analyzed, checked, or optimized

get_menu_configs/1: PREDICATE

Usage: `get_menu_configs(X)`

Returns a list of atoms in `X` with the name of stored configurations.

- *The following properties should hold at call time:*

  `X` is a free variable. (`var/1`)
- *The following properties should hold upon exit:*

  `X` is a list of `atm`s. (`list/2`)

save_menu_config/1: PREDICATE

Usage: `save_menu_config(Name)`

Save the current flags configuration under the `Name` key.

- *The following properties should hold at call time:*

  `Name` is an atom. (`atm/1`)

remove_menu_config/1: PREDICATE

Usage: `remove_menu_config(Name)`

Remove the configuration stored with the `Name` key (the same provided in `save_menu_config/1`).

- *The following properties should hold at call time:*

  `Name` is an atom. (`atm/1`)

restore_menu_config/1: PREDICATE

Usage: `restore_menu_config(Name)`

Restore the configuration saved with the `Name` key (the same provided in `save_menu_config/1`).

– *The following properties should hold at call time:*

`Name` is an atom. (`atm/1`)

show_menu_configs/0: PREDICATE

Usage:

Show all stored configurations.

show_menu_config/1: PREDICATE

Usage: `show_menu_config(C)`

Show specific configuration values pointed by `C` key (the same provided in `save_menu_config/1`).

– *The following properties should hold at call time:*

`C` is an atom. (`atm/1`)

get_menu_flag/3: (UNDOC_REEXPORT)

Imported from `menu_generator` (see the corresponding documentation for details).

get_menu_flag/3: (UNDOC_REEXPORT)

Imported from `menu_generator` (see the corresponding documentation for details).

set_menu_flag/3: (UNDOC_REEXPORT)

Imported from `menu_generator` (see the corresponding documentation for details).

set_menu_flag/3: (UNDOC_REEXPORT)

Imported from `menu_generator` (see the corresponding documentation for details).

menu_branch/4: (UNDOC_REEXPORT)

Imported from `menu_rt` (see the corresponding documentation for details).

menu_branch/3: (UNDOC_REEXPORT)

Imported from `menu_rt` (see the corresponding documentation for details).

true/2: (UNDOC_REEXPORT)
Imported from `menu_rt` (see the corresponding documentation for details).

true1/1: (UNDOC_REEXPORT)
Imported from `menu_rt` (see the corresponding documentation for details).

functor1/2: (UNDOC_REEXPORT)
Imported from `menu_rt` (see the corresponding documentation for details).

4.3 Documentation on multifiles

hook_menu_flag_values/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

hook_menu_check_flag_value/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

hook_menu_flag_help/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

hook_menu_default_option/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidomain/1: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

4.4 Documentation on imports

This module has the following direct dependencies:

- *Application modules:*
  `frontend_driver`, `analyze_driver`, `transform_driver`, `ciaopp_log`, `p_dump`, `fixpo_ops`, `acc_ops`, `intermod`, `infer_db`, `infer_dom`, `analysis_stats`, `preprocess_flags`, `static_abs_exec_table`, `abs_exec`.
- *System library modules:*
  `datafacts_rt`, `menu_generator`, `menu_rt`, `assrt_lib`, `p_unit`, `p_unit_db`, `lists`, `aggregates`, `system`, `messages`, `prompt`, `pathnames`, `port_reify`, `llists`, `sort`.
- *Internal (engine) modules:*
  `term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`, `io_basic`.
- *Packages:*
  `prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `fsyntax`, `dcg`, `datafacts`, `ciaopp(ciaopp_options)`, `isomodes`, `menu`, `argnames`.

5 The CiaoPP low-level interface

Author(s): The Ciao Development Team.

This module includes the low-level predicates for interacting with CiaoPP. In this interaction model the user performs a sequence of commands to obtain a certain result (e.g., load program, analyze, check assertions).

The basic commands are:

- `module(File)`: loads a (main) module into the preprocessor.
- `analyze(A)`: perform analysis `A` (see Chapter 7 [Available abstract domains], page 31) on the loaded module.
- `acheck`: check assertions (using current analysis information).
- `transform(T)`: perform transformation `T` on the loaded module.
- `output`: output a file with the current program state (i.e., the output includes transformations, analysis info, assertion checking, etc. as controlled by the flags set and the actions performed).
- `output(File)`: same as `output/0` but output to `File`.

The analyses and transformations are controlled by preprocessor flags. These flags can be modified or consulted with:

- `current_pp_flag(F, V)`: consult the current value `V` of flag `F`.
- `set_pp_flag(F, V)`: change the value of flag `F` to `V`.
- `pp_flag(F)`: `F` is a preprocessor flag.
- `dump_flags(K)`: dump the set of flags identified by `K` (`all` for all).

Other commands useful when developing or debugging CiaoPP:

- `show_dump(File)`: displays the content of a .dump file.
- `show_types`: display all current types (inferred or read).

5.1 Usage and interface

- **Library usage:**
  `:- use_module(ciaopp(ciaopp)).`

5.2 Documentation on exports

current_pp_flag/2: PREDICATE

Usage: `current_pp_flag(Name,Value)`

Preprocess flag `Name` has the value `Value`.

- *The following properties should hold at call time:*
  `Name` is a valid preprocessor flag. (`pp_flag/1`)
- *The following properties should hold upon exit:*
  `Value` is a valid value for preprocessor flag `Name`. (`valid_flag_value/2`)

current_pp_flag/2: PREDICATE

Usage: `current_pp_flag(Name,Value)`

Preprocess flag `Name` has the value `Value`.

– *The following properties should hold at call time:*

`Name` is a valid preprocessor flag. (`pp_flag/1`)

– *The following properties should hold upon exit:*

`Value` is a valid value for preprocessor flag `Name`. (`valid_flag_value/2`)

set_pp_flag/2: PREDICATE

Usage: `set_pp_flag(Name,Value)`

Sets `Value` for preprocessor flag `Name`.

– *The following properties should hold at call time:*

`Name` is a valid preprocessor flag. (`pp_flag/1`)

`Value` is a valid value for preprocessor flag `Name`. (`valid_flag_value/2`)

push_pp_flag/2: PREDICATE

Usage: `push_pp_flag(Flag,Value)`

Sets `Value` for preprocessor flag `Flag`, storing the current value to restore it with `pop_pp_flag/1`.

– *The following properties should hold at call time:*

`Flag` is a valid preprocessor flag. (`pp_flag/1`)

`Value` is a valid value for preprocessor flag `Flag`. (`valid_flag_value/2`)

pop_pp_flag/1: PREDICATE

Usage: `pop_pp_flag(Flag)`

Restores the value of the preprocessor flag `Flag` previous to the last non-canceled `push_pp_flag/2` on it.

– *The following properties should hold at call time:*

`Flag` is a valid preprocessor flag. (`pp_flag/1`)

pp_flag/1: PREDICATE

Valid flags:

(This list is outdated – see source code for a complete description)

- for the output:
  - `analysis_info` (`off, on`) Whether to output the results of analysis.
  - `point_info` (`off,on`) Whether to output analysis information for program points within clauses.
  - `collapse_ai_vers` (`off, on`) to output all the versions of call/success patterns inferred by analysis or just one version (summing-up all of them).

  - `type_output` (`defined, all`) to output the types inferred for predicates in terms only of types defined by the user or including types inferred anew.
  - `simplify_checks` (`on, off`) to output simplified check assertions after verification or not.
- for analysis:
  - `fixpoint` (`plai, dd, di, check_di, check_di2, check_di3, check_di4`) The kind of fixpoint computation used.
  - `multi_success` (`off, on`) Whether to allow success multivariance.
  - `widen` (`off, on`) Whether to perform widening.
  - `intermod` (`off, on, auto`) The policy for inter-modular analysis.
  - `success_policy` (`best, first, all, top, botfirst, botbest, botall, bottom`) The policy for obtaining success information for imported predicates during inter-modular analysis.
  - `entry_policy` (`all, top_level, force, force_assrt`) The policy for obtaining entry call patterns for exported predicates during inter-modular analysis.
  - `process_libraries` (`on, off, no_engine`) Whether to perform the analysis of Ciao system libraries when a modular user program is analyzed.
  - `initial_guess` (`botfirst, botbest, botall, bottom`) The policy for obtaining initial guess when computing the analysis of a predicate from the current module.
  - `use_check_assrt` (`off, on`) Whether to use check assertions for imported predicates as if they were trust assertions.
  - `depth` (a non-negative integer) The maximum depth of abstractions in analyses based on term depth.
  - `type_eval` (`on, off`) Whether to attempt concrete evaluation of types being inferred.
  - `type_precision` (`defined, all`) to use during type analysis only types defined by the user or also types inferred anew.
  - `entry_points_auto` (`none, calls, all`) What kind of assertions to use as entry points: `entry/1` will always be used, `calls/1` and `calls/2` will be used if the flag is **not** set to `none`; and `success/1`, `success/2`, `comp/1` and `comp/2` will be used if the flag is set to `all`.
  - `entry_calls_scope` (`exported, all`) What non-`entry` assertions to use as entry points. If the flag takes the value `exported`, only assertions from exported predicates will be used; if it takes the value `all`, exported and non-exported assertions will be used.
- for partial evaluation:
  - `global_control` (`off, id, inst, hom_emb`) The abstraction function to use to control the creation of new patterns to analyze as a result of unfolding.
  - `comp_rule` (`leftmost, safe_jb, bind_ins_jb, no_sideff_jb, jump_builtin, eval_builtin, local_emb`) The computation rule for the selection of atoms in a goal.
  - `local_control` (`off, orig, inst, det, det_la, depth, first_sol, first_sol_d, all_sol, hom_emb, hom_emb_anc, hom_emb_as, df_hom_emb_as, df_tree_hom_emb, df_hom_emb`) The unfolding rule to use during partial evaluation.
  - `unf_depth` (a non-negative integer) The depth limit for unfolding.
  - `rem_use_cls` (`off, pre, post, both`) Whether to remove useless clauses.

- `abs_spec_defs` (`off, rem, exec, all`) Whether to exploit abstract substitutions while obtaining specialized definitions on unfolding.
- `filter_nums` (`off, on`) Whether to filter away numbers in partial evaluation.
- `exec_unif` (`off, on`) Whether to execute unifications during specialization time or not.
- `pres_inf_fail` (`off, on`) Whether infinite failure should be preserved in the specialized program.
- `part_concrete` (`off, mono, multi`) The kind of partial concretization to be performed.

- for parallelization and granularity control:
  - `granularity_threshold` (a non-negative integer) The threshold on computational cost at which parallel execution pays off.

flag_value/1: REGTYPE

Usage: `flag_value(V)`

`V` is a value for a flag.

valid_flag_value/2: PROPERTY

Usage: `valid_flag_value(Name,Value)`

`Value` is a valid value for preprocessor flag `Name`.

– *If the following properties should hold at call time:*

`Name` is a valid preprocessor flag. (`pp_flag/1`)

`Value` is a value for a flag. (`flag_value/1`)

is_library/1: (UNDOC_REEXPORT)

Imported from `frontend_driver` (see the corresponding documentation for details).

get_data/2: (UNDOC_REEXPORT)

Imported from `frontend_driver` (see the corresponding documentation for details).

clean_ciaopp_db/1: (UNDOC_REEXPORT)

Imported from `frontend_driver` (see the corresponding documentation for details).

clean_all_ciaopp_db/0: (UNDOC_REEXPORT)

Imported from `frontend_driver` (see the corresponding documentation for details).

dump/2: (UNDOC_REEXPORT)

Imported from `frontend_driver` (see the corresponding documentation for details).

dump_dir/1: (UNDOC_REEXPORT)
Imported from `frontend_driver` (see the corresponding documentation for details).

add_to_db/1: (UNDOC_REEXPORT)
Imported from `frontend_driver` (see the corresponding documentation for details).

show_dump/1: (UNDOC_REEXPORT)
Imported from `frontend_driver` (see the corresponding documentation for details).

restore/2: (UNDOC_REEXPORT)
Imported from `frontend_driver` (see the corresponding documentation for details).

restore/1: (UNDOC_REEXPORT)
Imported from `frontend_driver` (see the corresponding documentation for details).

dump/1: (UNDOC_REEXPORT)
Imported from `frontend_driver` (see the corresponding documentation for details).

gen_and_load_libcache/0: (UNDOC_REEXPORT)
Imported from `frontend_driver` (see the corresponding documentation for details).

ensure_libcache_loaded/0: (UNDOC_REEXPORT)
Imported from `frontend_driver` (see the corresponding documentation for details).

write_one_type/2: (UNDOC_REEXPORT)
Imported from `frontend_driver` (see the corresponding documentation for details).

output_by_ext/2: (UNDOC_REEXPORT)
Imported from `frontend_driver` (see the corresponding documentation for details).

output_ext/1: (UNDOC_REEXPORT)
Imported from `frontend_driver` (see the corresponding documentation for details).

output/2: (UNDOC_REEXPORT)
Imported from `frontend_driver` (see the corresponding documentation for details).

output/1: PREDICATE

Usage: `output(File)`

Outputs to `File` the current module preprocessing state with the default output options. If unbound, `File` is unified with a default name (encoding the preprocessing steps). Equivalent to `output(File,[])`.

output/0: PREDICATE

Usage:

Outputs the current module preprocessing state with the default output options. Equivalent to `output(File,[])`.

get_output_path/2: (UNDOC_REEXPORT)

Imported from `frontend_driver` (see the corresponding documentation for details).

pop_history/1: (UNDOC_REEXPORT)

Imported from `frontend_driver` (see the corresponding documentation for details).

push_history/1: (UNDOC_REEXPORT)

Imported from `frontend_driver` (see the corresponding documentation for details).

cleanup_history/0: (UNDOC_REEXPORT)

Imported from `frontend_driver` (see the corresponding documentation for details).

is_library/1: (UNDOC_REEXPORT)

Imported from `frontend_driver` (see the corresponding documentation for details).

assrt_used_as_entry/2: (UNDOC_REEXPORT)

Imported from `frontend_driver` (see the corresponding documentation for details).

entry_assertion/3: (UNDOC_REEXPORT)

Imported from `frontend_driver` (see the corresponding documentation for details).

module/1: PREDICATE

Usage 1: `module(FileName)`

Reads the code of `FileName` and its preprocessing unit, and sets it as the current module.

- *The following properties should hold at call time:*

  `FileName` is currently a term which is not a free variable. (`nonvar/1`)

  `FileName` is a source name. (`sourcename/1`)

Usage 2: `module(FileNameList)`

Reads the code of the list of file names `FileNameList` (and their preprocessing units), and sets them as the current modules.

– *The following properties should hold at call time:*

`FileNameList` is currently a term which is not a free variable. (`nonvar/1`)

`FileNameList` is a list of `atm`s. (`list/2`)

language_output_extension/2: (UNDOC_REEXPORT)

Imported from `frontend_driver` (see the corresponding documentation for details).

transform/1: PREDICATE

Usage 1: `transform(Trans)`

Returns on backtracking all available program transformation identifiers.

– *The following properties should hold at call time:*

`Trans` is a free variable. (`var/1`)

– *The following properties should hold upon exit:*

`Trans` is a valid transformation identifier. (`transformation/1`)

Usage 2: `transform(Trans)`

Performs transformation `Trans` on the current module.

– *The following properties should hold at call time:*

`Trans` is currently a term which is not a free variable. (`nonvar/1`)

`Trans` is a valid transformation identifier. (`transformation/1`)

cleanup_for_codegen/0: (UNDOC_REEXPORT)

Imported from `analyze_driver` (see the corresponding documentation for details).

clean_analysis_info0/0: (UNDOC_REEXPORT)

Imported from `analyze_driver` (see the corresponding documentation for details).

acheck/2: (UNDOC_REEXPORT)

Imported from `analyze_driver` (see the corresponding documentation for details).

acheck/0: PREDICATE

Usage:

Checks assertions w.r.t. analysis information, obtains from `domain/1` which analyses were run.

get_assert_count/1: (UNDOC_REEXPORT)

Imported from `analyze_driver` (see the corresponding documentation for details).

acheck_summary/2: (UNDOC_REEXPORT)
Imported from `analyze_driver` (see the corresponding documentation for details).

acheck_summary/1: (UNDOC_REEXPORT)
Imported from `analyze_driver` (see the corresponding documentation for details).

ctcheck_sum/1: (UNDOC_REEXPORT)
Imported from `analyze_driver` (see the corresponding documentation for details).

analyze1/2: (UNDOC_REEXPORT)
Imported from `analyze_driver` (see the corresponding documentation for details).

analyze/1: PREDICATE

Usage: `analyze(Analysis)`

Analyzes the current module with `Analysis`. If the intermod flag is not off, this predicate may call `module/1`.

- *The following properties should hold at call time:*

  `Analysis` is currently a term which is not a free variable. (`nonvar/1`)

  `Analysis` is a valid analysis identifier. (`analysis/1`)

- *The following properties should hold globally:*

  All the calls of the form `analyze(Analysis)` do not fail. (`not_fails/1`)

  A call to `analyze(Analysis)` does not leave new choicepoints. (`no_choicepoints/1`)

last_domain_used/1: (UNDOC_REEXPORT)
Imported from `analyze_driver` (see the corresponding documentation for details).

assert_domain/1: (UNDOC_REEXPORT)
Imported from `analyze_driver` (see the corresponding documentation for details).

menu_branch/4: (UNDOC_REEXPORT)
Imported from `auto_interface` (see the corresponding documentation for details).

menu_branch/3: (UNDOC_REEXPORT)
Imported from `auto_interface` (see the corresponding documentation for details).

true/2: (UNDOC_REEXPORT)
Imported from `auto_interface` (see the corresponding documentation for details).

true1/1: (UNDOC_REEXPORT)
Imported from `auto_interface` (see the corresponding documentation for details).

functor1/2: (UNDOC_REEXPORT)
Imported from `auto_interface` (see the corresponding documentation for details).

customize_and_preprocess/0: (UNDOC_REEXPORT)
Imported from `auto_interface` (see the corresponding documentation for details).

customize/0: (UNDOC_REEXPORT)
Imported from `auto_interface` (see the corresponding documentation for details).

5.3 Documentation on multifiles

typeslib_flag/1: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

typeslib_is_user_type/1: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

typeslib_is_visible/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

typeslib_interesting_type/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

5.4 Documentation on internals

transformation/1: PROPERTY
The current supported transformations are in Chapter 44 [Available program transformations], page 311.
Usage: `transformation(Transformation)`
`Transformation` is a valid transformation identifier.

analysis/1: PROPERTY
The current supported analyses are in Chapter 7 [Available abstract domains], page 31.
Usage: `analysis(Analysis)`
`Analysis` is a valid analysis identifier.

5.5 Documentation on imports

This module has the following direct dependencies:

– *Application modules:*

`frontend_driver`, `transform_driver`, `analyze_driver`, `auto_interface`, `preprocess_flags`.

– *System library modules:*

`typeslib`, `p_unit_db`, `messages`, `system`.

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `runtime_control`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `ciaopp(ciaopp_options)`.

6 The CiaoPP command-line interface

Author(s): The Ciao Development Team.

This is the top-level and command-line interface to CiaoPP. Please look at `ciaopp` documentation for top-level usage information. The command-line interface allows the use of the system in batch mode, using arguments for setting preprocessor flags and performing actions.

6.1 Command-line options

This interface can be used by means of the following command-line options:

```
Usage 1: (batch mode)
    ciaopp [OPTIONS] Action Filename [FlagsValues]

  Where:
    -o <OutFile>
            after processing Filename, the resulting source
            code is written to OutFile.  If this option is
            omitted, the output is written to a file
            automatically named depending on the actions
            performed.
    -op <Suffix>
            Use Suffix as the optional input code suffix

    --cwd Dir
            Switch to the selected directory
    --timeout Timeout
            Execute with a timeout limit (ms).
            Default is 0 (no timeout).

    Action must be one of the following:
    -Q      runs the interactive (text-based) menu for
            preprocessing Filename.
    -A      analyzes Filename with the default options
            except the flag values set with -f at the
            command line.
    -O      optimizes Filename with the default options
            except the flag values set with -f at the
            command line.
    -V      verifies the assertions of Filename with
            the default options except the flag values set
            with -f at the command line.

    -U <Config>
            processes Filename with the options set in the
            configuration Config.

    FlagsValues is a list of options -fFlagName=FlagValue
    separated by blank spaces, where FlagName is a valid
    CiaoPP flag name.  This list is optional, and does not need
    to include all flags applicable to the action to be performed:
    the flags not included in this list will be assumed to take
```

```
    their default value.  Examples:

    -flocal_control=on
            where local_control is expected to be
            a CiaoPP flag;
    -f local_control=on
            same as above, with additional blank spaces

    Internal flags can also be changed using -pIntFlagName=Value.

Usage 2: (top-level mode)
    ciaopp -T <toplevel-opts>

    -T     starts a CiaoPP top-level shell (using <toplevel-opts> as
           options for the toplevel).  Any of the predicates described
           in the Section 'CiaoPP User Menu Interface' of the CiaoPP
           Reference Manual can be used in this top-level.

Usage 3: cache libraries
    ciaopp --gen-lib-cache

    Preloads libraries for faster load in CiaoPP toplevel

Execution Examples:

  ciaopp -Q myfile.pl
  ciaopp -o myfile_checked.pl -V myfile.pl
  ciaopp -O myfile.pl
  ciaopp -A myfile.pl -ftypes=terms -f modes=pd
  ciaopp -T
```

6.2 Description of the execution examples

- The following command will prompt the user with the options needed to preprocess `myfile.pl`:

  `ciaopp -Q myfile.pl`
- If we want to verify the assertions of `myfile.pl`, and generate the resulting source code that will the new status of the assertions (either `checked`, if CiaoPP has proved that the assertion holds, or `false` if it has falsified the assertion), the command line is as follows:

  `ciaopp -o myfile_checked.pl -V myfile.pl`
- To optimize `myfile.pl`, and write the optimize code in a file named automatically (e.g., `myfile_pd_codegen_af_co.pl`), the following command line must be used:

  `ciaopp -O myfile.pl`
- If the default flag values need to be changed, the `-f` option can be used. For example, in order to analyze `myfile.pl` to change the types analysis domain to `terms` instead of the default one, and the mode-aliasing domain to `pd`, the command line to use should be:

  `ciaopp -A myfile.pl -ftypes=terms -f modes=pd`
- Finally, the following command line can be used to start a top-level CiaoPP shell (this is the default behavior):

```
ciaopp -T
```

7 Available abstract domains

7.0.1 Groundness and sharing

- `gr` tracks groundness in a very simple way (see Chapter 16 [Simple groundness abstract domain], page 103).
- `def` tracks groundness dependencies, which improves the accuracy in inferring groundness.
- `share` tracks sharing among (sets of) variables [MH92], which gives a very accurate groundness inference, plus information on dependencies caused by unification.
- `son` tracks sharing among pairs of variables, plus variables which are linear (see [Son86]).
- `shareson` is a combination of the above two [CMB93], which may improve on the accuracy of any of them alone.
- `shfr` tracks sharing and variables which are free (see [MH91]).
- `shfrson` is a combination of `shfr` and `son`.
- `shfrnv` augments `shfr` with knowledge on variables which are not free nor ground.

7.0.2 Term structure

- `depth` tracks the structure of the terms bound to the program variables during execution, up to a certain depth; the depth is fixed with the `depth` flag.
- `path` tracks sharing among variables which occur within the terms bound to the program variables during execution; the occurrence of run-time variables within terms is tracked up to a certain depth, fixed with the `depth` flag.
- `aeq` tracks the structure of the terms bound to the program variables during execution plus the sharing among the run-time variables occurring in such terms, plus freeness and linearity. The depth of terms being tracked is set with the `depth` flag. Sharing can be selected between set-sharing or pair-sharing.

7.0.3 Types

Type analysis supports different degrees of precision. For example, with the flag `type_precision` with value `defined`, the analysis restricts the types to the finite domain of predefined types, i.e., the types defined by the user or in libraries, without generating new types. Another alternative is to use the normal analysis, i.e., creating new type definitions, but having only predefined types in the output. This is handled through the `type_output` flag.

- `eterms` performs structural widening (see [VB02]).

  Greater precision can be obtained evaluating builtins like `is/2` abstractly: `eterms` includes a variant which allows evaluation of the types, which is governed by the `type_eval` flag.
- `ptypes` uses the topological clash widening operator (see [VHCL95]).
- `svterms` implements the rigid types domain of [JB92].
- `terms` uses shortening as the widening operator (see [GdW94]), in several fashions, which are selected via the `depth` flag; depth 0 meaning the use of restricted shortening [SG94].

7.0.4 Partial evaluation

Partial evaluation is performed during analysis when the `local_control` flag is set to other than `off`. Flag `fixpoint` must be set to `di`. Unfolding will take place while analyzing the program, therefore creating new patterns to analyze. The unfolding rule is governed by flag `local_control` (see `transformation(codegen)`).

For partial evaluation to take place, an analysis domain capable of tracking term structure should be used (e.g., `eterms`, `pd`, etc.). In particular:

- `pd` allows to perform traditional partial evaluation but using instead abstract interpretation with specialized definitions [PAH04].
- `pdb` improves the precision of `pd` by detecting calls which cannot succeed, i.e., either loop or fail.

Note that these two analyses will not infer useful information on the program. They are intended only to enable (classical) partial evaluation.

7.0.5 Constraint domains

8 aeq (library)

8.1 Usage and interface

- **Library usage:**
  `:- use_module(domain(aeq)).`

8.2 Documentation on multifiles

aidomain/1: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.init_abstract_domain/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.amgu/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_two_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_entry/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.exit_to_prime/8: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.project/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widencall/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.needs/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widen/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_lub/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_lub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered_gfp/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.identical_abstract/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_sort/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.extend/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.less_or_equal/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.eliminate_equivalent/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_subset/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_fact/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.special_builtin/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.combined_special_builtin0/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.body_succ_builtin/9: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.split_combined_domain/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.obtain_info/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_interface/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_user_interface/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.asub_to_native/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.concrete/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_call/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.empty_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.part_conc/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.multi_part_conc/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.collect_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.rename_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.dom_statistics/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.contains_parameters/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

8.3 Documentation on imports

This module has the following direct dependencies:

– *Application modules:*

`preprocess_flags`, `domains`, `s_eqs`, `sharing`, `pool`, `plai_errors`, `share_aux`.

– *System library modules:*

`datafacts_rt`, `sets`, `sort`, `idlists`, `lists`, `llists`, `keys`, `messages`, `terms_check`, `terms_vars`, `arrays`, `bitcodesets`, `write`, `streams`.

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `hiord_rt`, `io_basic`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `datafacts`, `hiord`, `aidomain`.

9 def (library)

9.1 Usage and interface

- **Library usage:**
  `:- use_module(domain(def)).`
- **Exports:**
  - *Predicates:*
    `call_to_entry/9`, `exit_to_prime/7`, `project/5`, `compute_lub/2`, `compute_lub_el/3`, `glb/3`, `abs_sort/2`, `extend/5`, `call_to_success_fact/9`, `special_builtin/5`, `success_builtin/6`, `input_user_interface/5`, `input_interface/4`, `asub_to_native/5`, `unknown_call/4`, `unknown_entry/3`, `empty_entry/3`, `less_or_equal/2`.
  - *Multifiles:*
    `aidomain/1`, `aidom.init_abstract_domain/2`, `aidom.amgu/5`, `aidom.augment_asub/4`, `aidom.augment_two_asub/4`, `aidom.call_to_entry/10`, `aidom.exit_to_prime/8`, `aidom.project/6`, `aidom.widencall/4`, `aidom.needs/2`, `aidom.widen/4`, `aidom.compute_lub/3`, `aidom.compute_clauses_lub/4`, `aidom.compute_clauses_glb/4`, `aidom.fixpoint_covered/3`, `aidom.fixpoint_covered_gfp/3`, `aidom.identical_abstract/3`, `aidom.abs_sort/3`, `aidom.extend/6`, `aidom.less_or_equal/3`, `aidom.glb/4`, `aidom.eliminate_equivalent/3`, `aidom.abs_subset/3`, `aidom.call_to_success_fact/10`, `aidom.special_builtin/6`, `aidom.combined_special_builtin0/3`, `aidom.body_succ_builtin/9`, `aidom.split_combined_domain/4`, `aidom.success_builtin/7`, `aidom.call_to_success_builtin/7`, `aidom.obtain_info/5`, `aidom.input_interface/5`, `aidom.input_user_interface/6`, `aidom.asub_to_native/6`, `aidom.concrete/4`, `aidom.unknown_call/5`, `aidom.unknown_entry/4`, `aidom.empty_entry/4`, `aidom.part_conc/5`, `aidom.multi_part_conc/4`, `aidom.collect_auxinfo_asub/4`, `aidom.rename_auxinfo_asub/4`, `aidom.dom_statistics/2`, `aidom.contains_parameters/2`.

9.2 Documentation on exports

call_to_entry/9: PREDICATE
No further documentation available for this predicate.

exit_to_prime/7: PREDICATE
No further documentation available for this predicate.

project/5: PREDICATE
No further documentation available for this predicate.

compute_lub/2: PREDICATE
No further documentation available for this predicate.

compute_lub_el/3: PREDICATE
No further documentation available for this predicate.

glb/3: PREDICATE
No further documentation available for this predicate.

abs_sort/2: PREDICATE
No further documentation available for this predicate.

extend/5: PREDICATE
No further documentation available for this predicate.

call_to_success_fact/9: PREDICATE
No further documentation available for this predicate.

special_builtin/5: PREDICATE
No further documentation available for this predicate.

success_builtin/6: PREDICATE
No further documentation available for this predicate.

input_user_interface/5: PREDICATE
No further documentation available for this predicate.

input_interface/4: PREDICATE
No further documentation available for this predicate.

asub_to_native/5: PREDICATE
No further documentation available for this predicate.

unknown_call/4: PREDICATE
No further documentation available for this predicate.

unknown_entry/3: PREDICATE
No further documentation available for this predicate.

empty_entry/3: PREDICATE
No further documentation available for this predicate.

less_or_equal/2: PREDICATE
No further documentation available for this predicate.

9.3 Documentation on multifiles

aidomain/1: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.init_abstract_domain/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.amgu/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_two_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_entry/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.exit_to_prime/8: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.project/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widencall/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.needs/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widen/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_lub/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_lub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered_gfp/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.identical_abstract/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_sort/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.extend/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.less_or_equal/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.eliminate_equivalent/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_subset/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_fact/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.special_builtin/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.combined_special_builtin0/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.body_succ_builtin/9: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.split_combined_domain/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.obtain_info/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_interface/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_user_interface/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.asub_to_native/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.concrete/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_call/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.empty_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.part_conc/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.multi_part_conc/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.collect_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.rename_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.dom_statistics/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.contains_parameters/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

9.4 Documentation on imports

This module has the following direct dependencies:

– *Application modules:*

`preprocess_flags`, `domains`, `deftools`.

– *System library modules:*

`datafacts_rt`, `sets`, `sort`, `terms_check`, `terms_vars`, `p_unit`.

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `datafacts`, `aidomain`.

10 deftypes: defined types (based on termsd) (abstract domain)

Author(s): Pawel Pietrzak (original), Ciao Development Team.

This module implements types abstract domain (based on `termsd`) that only includes library types, user-defined types and instances of parametric rules. Like in `termsd`, an abstract sustitution is list of Var:Type elements, where Var is a variable and Type is a pure type term [DZ92].

10.1 Usage and interface

- **Library usage:**
  `:- use_module(domain(deftypes)).`

10.2 Documentation on multifiles

aidomain/1: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.init_abstract_domain/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.amgu/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_two_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_entry/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.exit_to_prime/8: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.project/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widencall/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.needs/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widen/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_lub/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_lub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered_gfp/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.identical_abstract/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_sort/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.extend/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.less_or_equal/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.eliminate_equivalent/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_subset/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_fact/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.special_builtin/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.combined_special_builtin0/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.body_succ_builtin/9: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.split_combined_domain/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.obtain_info/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_interface/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_user_interface/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.asub_to_native/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.concrete/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_call/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.empty_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.part_conc/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.multi_part_conc/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.collect_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.rename_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.dom_statistics/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.contains_parameters/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

10.3 Documentation on imports

This module has the following direct dependencies:

– *Application modules:*

`preprocess_flags`, `domains`, `termsd`.

– *System library modules:*

`sets`, `sort`, `typeslib`, `terms_check`.

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `regtypes`, `basicmodes`, `aidomain`.

11 depthk (library)

11.1 Usage and interface

- **Library usage:**
  `:- use_module(domain(depthk)).`

11.2 Documentation on multifiles

aidomain/1: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.init_abstract_domain/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.amgu/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_two_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_entry/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.exit_to_prime/8: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.project/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widencall/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.needs/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widen/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_lub/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_lub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered_gfp/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.identical_abstract/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_sort/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.extend/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.less_or_equal/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.eliminate_equivalent/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_subset/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_fact/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.special_builtin/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.combined_special_builtin0/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.body_succ_builtin/9: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.split_combined_domain/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.obtain_info/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_interface/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_user_interface/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.asub_to_native/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.concrete/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_call/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.empty_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.part_conc/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.multi_part_conc/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.collect_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.rename_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.dom_statistics/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.contains_parameters/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

11.3 Documentation on imports

This module has the following direct dependencies:

– *Application modules:*
`preprocess_flags`, `domains`, `s_eqs`.

– *System library modules:*
`sets`, `sort`, `lists`, `terms_check`, `terms_vars`, `write`.

– *Internal (engine) modules:*
`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `io_basic`.

– *Packages:*
`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `aidomain`.

12 eterms: types with lnewiden_el/4 (abstract domain)

Author(s): Claudio Vaucheret, Francisco Bueno, Ciao Development Team.

This module implements the abstract operations of the type domains with widening based on (`lnewiden_el/4`). An abstract sustitution is a list of `Var:(Name,Type)` elements, where `Var` is a variable and `Type` is a pure type term [DZ92].

12.1 Usage and interface

- **Library usage:**
  `:- use_module(domain(eterms)).`
- **Exports:**
  - *Predicates:*
    `get_type/3`, `eterms_init_abstract_domain/1`, `eterms_compute_lub/2`, `eterms_compute_lub_el/3`, `eterms_widencall/3`, `eterms_needs/1`, `eterms_widen/3`, `eterms_call_to_entry/9`, `eterms_exit_to_prime/7`, `replace_names/3`, `normal_asub/2`, `update_names/2`, `generate_subs_exit/4`, `generate_subs/3`, `eterms_project/5`, `eterms_abs_sort/2`, `eterms_extend/5`, `eterms_less_or_equal/2`, `eterms_glb/3`, `eterms_glbnames/3`, `eterms_concrete/3`, `eterms_unknown_entry/3`, `eterms_empty_entry/3`, `eterms_unknown_call/4`, `variables_are_top_type/2`, `eterms_call_to_success_fact/9`, `eterms_special_builtin/5`, `eterms_success_builtin/6`, `keys_same_value/3`, `eterms_arg_call_to_success/9`, `eterms_call_to_success_builtin/6`, `eterms_obtain_info/4`, `eterms_input_user_interface/5`, `eterms_input_interface/4`, `eterms_asub_to_native/5`, `eterms_output_interface/2`, `eterms_collect_auxinfo_asub/3`, `eterms_rename_auxinfo_asub/3`, `eterms_identical_abstract/2`, `getargtypes/6`, `replacetype/4`, `getfunctors/2`, `split_f/4`, `getvalue/2`, `unifytoterm/1`, `abs_eval_arithcomp/4`, `generateSucc0_cond/5`, `abs_eval_arith/3`, `getvalues_comp_cond/3`, `get_list_names_is/2`, `determinate_sel/3`, `replaceintype/5`, `eterms_multi_part_conc/3`, `eterms_part_conc/4`, `obtains_names/4`.
  - *Multifiles:*
    `aidomain/1`, `aidom.init_abstract_domain/2`, `aidom.amgu/5`, `aidom.augment_asub/4`, `aidom.augment_two_asub/4`, `aidom.call_to_entry/10`, `aidom.exit_to_prime/8`, `aidom.project/6`, `aidom.widencall/4`, `aidom.needs/2`, `aidom.widen/4`, `aidom.compute_lub/3`, `aidom.compute_clauses_lub/4`, `aidom.compute_clauses_glb/4`, `aidom.fixpoint_covered/3`, `aidom.fixpoint_covered_gfp/3`, `aidom.identical_abstract/3`, `aidom.abs_sort/3`, `aidom.extend/6`, `aidom.less_or_equal/3`, `aidom.glb/4`, `aidom.eliminate_equivalent/3`, `aidom.abs_subset/3`, `aidom.call_to_success_fact/10`, `aidom.special_builtin/6`, `aidom.combined_special_builtin0/3`, `aidom.body_succ_builtin/9`, `aidom.split_combined_domain/4`, `aidom.success_builtin/7`, `aidom.call_to_success_builtin/7`, `aidom.obtain_info/5`, `aidom.input_interface/5`, `aidom.input_user_interface/6`, `aidom.asub_to_native/6`, `aidom.concrete/4`, `aidom.unknown_call/5`, `aidom.unknown_entry/4`, `aidom.empty_entry/4`, `aidom.part_conc/5`, `aidom.multi_part_conc/4`, `aidom.collect_auxinfo_asub/4`, `aidom.rename_auxinfo_asub/4`, `aidom.dom_statistics/2`, `aidom.contains_parameters/2`.

12.2 Documentation on exports

get_type/3: PREDICATE

No further documentation available for this predicate.

eterms_init_abstract_domain/1: PREDICATE

No further documentation available for this predicate.

eterms_compute_lub/2: PREDICATE

Usage: `eterms_compute_lub(ListASub,Lub)`

It computes the least upper bound of a set of abstract substitutions. For each two abstract substitutions `ASub1` and `ASub2` in `ListASub`, obtaining the lub is foreach X:Type1 in `ASub1` and X:Type2 in `ASub2`, X:TypeUnion is in Lub, and TypeUnion is the deterministic union of Type1 an Type2.

- *The following properties should hold at call time:*

  `ListASub` is currently a term which is not a free variable. (`nonvar/1`)

  `Lub` is a free variable. (`var/1`)

  `ListASub` is a list of `eterms_asub`s. (`list/2`)

- *The following properties should hold upon exit:*

  `Lub` is an abstract substitution (`eterms_asub/1`)

eterms_compute_lub_el/3: PREDICATE

No further documentation available for this predicate.

eterms_widencall/3: PREDICATE

No further documentation available for this predicate.

eterms_needs/1: PREDICATE

No further documentation available for this predicate.

eterms_widen/3: PREDICATE

Usage: `eterms_widen(Prime0,Prime1,NewPrime)`

Induction step on the abstract substitution of a fixpoint. `Prime0` corresponds to non-recursive and `Prime1` to recursive clauses. `NewPrime` is the result of apply one widening operation to the least upper bound of the formers.

- *The following properties should hold at call time:*

  `Prime0` is currently a term which is not a free variable. (`nonvar/1`)

  `Prime1` is currently a term which is not a free variable. (`nonvar/1`)

  `NewPrime` is a free variable. (`var/1`)

  `Prime0` is an abstract substitution (`eterms_asub/1`)

  `Prime1` is an abstract substitution (`eterms_asub/1`)

  `NewPrime` is any term. (`term/1`)

– *The following properties should hold upon exit:*
`NewPrime` is an abstract substitution (`eterms_asub/1`)

eterms_call_to_entry/9: PREDICATE

Usage: `eterms_call_to_entry(Sv,Sg,Hv,Head,K,Fv,Proj,Entry,ExtraInfo)`

It obtains the abstract substitution `Entry` which results from adding the abstraction of the `Sg` = `Head` to `Proj`, later projecting the resulting substitution onto `Hv`.

This is done as follows:

- If `Sg` and `Head` are identical up to renaming it is just renaming `Proj` and adding the `Fv`
- Otherwise, it will
  - obtain the abstract substitution from unifying `Sg` and `Head` calling "unify_term_and_type_term"
  - add to this abstract substitution the variables in Fv as term type.

The meaning of the variables is

- `Sg` is the subgoal being analysed.
- `Head` is the Head of the clause being analysed.
- `Fv` is a list of free variables in the body of the clause being considered.
- `Proj` is the abstract substitution `Call` projected onto `Sv`.
- `Entry` is the Abstract entry substitution (i.e. the abstract subtitution obtained after the abstract unification of `Sg` and `Head` projected onto `Hv + Fv`).
- `ExtraInfo`is a flag "yes" when no unification is required, i.e., Entry=Proj upto names of vars. and ignoring Fv. It is "no" if unification fails.

– *The following properties should hold at call time:*
`Sv` is currently a term which is not a free variable. (`nonvar/1`)
`Sg` is currently a term which is not a free variable. (`nonvar/1`)
`Hv` is currently a term which is not a free variable. (`nonvar/1`)
`Head` is currently a term which is not a free variable. (`nonvar/1`)
`K` is currently a term which is not a free variable. (`nonvar/1`)
`Fv` is currently a term which is not a free variable. (`nonvar/1`)
`Proj` is currently a term which is not a free variable. (`nonvar/1`)
`Entry` is a free variable. (`var/1`)
`ExtraInfo` is a free variable. (`var/1`)
`Sv` is any term. (`term/1`)
`Sg` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)
`Hv` is a list. (`list/1`)
`Head` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)
`K` is any term. (`term/1`)
`Fv` is a list. (`list/1`)
`Proj` is an abstract substitution (`eterms_asub/1`)
`Entry` is any term. (`term/1`)
`ExtraInfo` is any term. (`term/1`)

– *The following properties should hold upon exit:*
`Entry` is an abstract substitution (`eterms_asub/1`)
`eterms_extrainfo(ExtraInfo)` (`eterms_extrainfo/1`)

eterms_exit_to_prime/7: PREDICATE

Usage: `eterms_exit_to_prime(Sg,Hv,Head,Sv,Exit,ExtraInfo,Prime)`

It computes the prime abstract substitution `Prime`, i.e. the result of going from the abstract substitution over the head variables `Exit`, to the abstract substitution over the variables in the subgoal. It will:

- If `Exit` is '$bottom', `Prime` will be also '$bottom'.
- If `ExtraInfo` = yes (`Head` and `Sg` identical up to renaming) it is just renaming Exit %
- Otherwise, it will:
  - projects `Exit` onto `Hv` obtaining `BPrime`.
  - obtain the abstract substitution from unifying `Sg` and `Head` calling "unify_term_and_type_term"

– *The following properties should hold at call time:*

`Sg` is currently a term which is not a free variable. (`nonvar/1`)
`Hv` is currently a term which is not a free variable. (`nonvar/1`)
`Head` is currently a term which is not a free variable. (`nonvar/1`)
`Sv` is currently a term which is not a free variable. (`nonvar/1`)
`Exit` is currently a term which is not a free variable. (`nonvar/1`)
`ExtraInfo` is a free variable. (`var/1`)
`Prime` is a free variable. (`var/1`)
`Sg` is a list. (`list/1`)
`Hv` is a list. (`list/1`)
`Head` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)
`Sv` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)
`Exit` is an abstract substitution (`eterms_asub/1`)
`ExtraInfo` is any term. (`term/1`)
`Prime` is any term. (`term/1`)

– *The following properties should hold upon exit:*

`eterms_extrainfo(ExtraInfo)` (`eterms_extrainfo/1`)
`Prime` is an abstract substitution (`eterms_asub/1`)

replace_names/3: PREDICATE

No further documentation available for this predicate.

normal_asub/2: PREDICATE

No further documentation available for this predicate.

update_names/2: PREDICATE

No further documentation available for this predicate.

generate_subs_exit/4: PREDICATE

No further documentation available for this predicate.

generate_subs/3: PREDICATE

No further documentation available for this predicate.

eterms_project/5: PREDICATE

Usage: `eterms_project(Sg,Vars,HvFv_u,ASub,Proj)`

`Proj` is the result of eliminating from `ASub` all `X:Value` such that `X` is not in `Vars`.

- *The following properties should hold at call time:*

`Sg` is currently a term which is not a free variable.	(`nonvar/1`)
`Vars` is currently a term which is not a free variable.	(`nonvar/1`)
`HvFv_u` is currently a term which is not a free variable.	(`nonvar/1`)
`ASub` is currently a term which is not a free variable.	(`nonvar/1`)
`Proj` is a free variable.	(`var/1`)
`Sg` is any term.	(`term/1`)
`Vars` is a list.	(`list/1`)
`HvFv_u` is a list.	(`list/1`)
`ASub` is an abstract substitution	(`eterms_asub/1`)
`Proj` is any term.	(`term/1`)

- *The following properties should hold upon exit:*

`Proj` is an abstract substitution	(`eterms_asub/1`)

eterms_abs_sort/2: PREDICATE

Usage: `eterms_abs_sort(ASub,ASub_s)`

It sorts the set of `X:Type` in `ASub` ontaining `ASub_s`

- *The following properties should hold at call time:*

`ASub` is currently a term which is not a free variable.	(`nonvar/1`)
`ASub_s` is a free variable.	(`var/1`)
`ASub` is an abstract substitution	(`eterms_asub/1`)

- *The following properties should hold upon exit:*

`ASub_s` is an abstract substitution	(`eterms_asub/1`)

eterms_extend/5: PREDICATE

Usage: `eterms_extend(Sg,Prime,Sv,Call,Succ)`

If `Prime` = '$bottom', `Succ` = '$bottom' otherwise, `Succ` is computed updating the values of `Call` with those in `Prime`

- *The following properties should hold at call time:*

`Sg` is currently a term which is not a free variable.	(`nonvar/1`)
`Prime` is currently a term which is not a free variable.	(`nonvar/1`)
`Sv` is currently a term which is not a free variable.	(`nonvar/1`)
`Call` is currently a term which is not a free variable.	(`nonvar/1`)
`Succ` is a free variable.	(`var/1`)
`Sg` is any term.	(`term/1`)

`Prime` is an abstract substitution (`eterms_asub/1`)
`Sv` is a list. (`list/1`)
`Call` is an abstract substitution (`eterms_asub/1`)
`Succ` is any term. (`term/1`)
– *The following properties should hold upon exit:*
`Succ` is an abstract substitution (`eterms_asub/1`)

eterms_less_or_equal/2: PREDICATE

Usage: `eterms_less_or_equal(ASub0,ASub1)`

Succeeds if `ASub1` is more general or equal to `ASub0`. it's assumed the two abstract substitutions are defined on the same variables

– *The following properties should hold at call time:*
`ASub0` is currently a term which is not a free variable. (`nonvar/1`)
`ASub1` is currently a term which is not a free variable. (`nonvar/1`)
`ASub0` is an abstract substitution (`eterms_asub/1`)
`ASub1` is an abstract substitution (`eterms_asub/1`)

eterms_glb/3: PREDICATE

Usage: `eterms_glb(ASub0,ASub1,Glb)`

`Glb` is the great lower bound of `ASub0` and `ASub1`

– *The following properties should hold at call time:*
`ASub0` is currently a term which is not a free variable. (`nonvar/1`)
`ASub1` is currently a term which is not a free variable. (`nonvar/1`)
`Glb` is a free variable. (`var/1`)
`ASub0` is an abstract substitution (`eterms_asub/1`)
`ASub1` is an abstract substitution (`eterms_asub/1`)
`Glb` is any term. (`term/1`)
– *The following properties should hold upon exit:*
`Glb` is an abstract substitution (`eterms_asub/1`)

eterms_glbnames/3: PREDICATE

No further documentation available for this predicate.

eterms_concrete/3: PREDICATE

No further documentation available for this predicate.

eterms_unknown_entry/3: PREDICATE

Usage: `eterms_unknown_entry(Sg,Qv,Call)`

Gives the "top" value for the variables involved in a literal whose definition is not present, and adds this top value to Call. In this domain the top value is X:term forall X in the set of variables

– *The following properties should hold at call time:*

`Sg` is currently a term which is not a free variable. (`nonvar/1`)

`Qv` is currently a term which is not a free variable. (`nonvar/1`)

`Call` is a free variable. (`var/1`)

`Sg` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)

`Qv` is a list. (`list/1`)

`Call` is any term. (`term/1`)

– *The following properties should hold upon exit:*

`Call` is an abstract substitution (`eterms_asub/1`)

eterms_empty_entry/3: PREDICATE

Usage: `eterms_empty_entry(Sg,Vars,Entry)`

Gives the "empty" value in this domain for a given set of variables `Vars`, resulting in the abstract substitution `Entry`. I.e., obtains the abstraction of a substitution in which all variables `Vars` are unbound: free and unaliased. In this domain the empty value is giving the variable type to each variable

– *The following properties should hold at call time:*

`Sg` is currently a term which is not a free variable. (`nonvar/1`)

`Vars` is currently a term which is not a free variable. (`nonvar/1`)

`Entry` is a free variable. (`var/1`)

`Sg` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)

`Vars` is a list. (`list/1`)

`Entry` is any term. (`term/1`)

– *The following properties should hold upon exit:*

`Entry` is an abstract substitution (`eterms_asub/1`)

eterms_unknown_call/4: PREDICATE

Usage: `eterms_unknown_call(Sg,Vars,Call,Succ)`

Gives the "top" value for the variables involved in a literal whose definition is not present, and adds this top value to `Call`

– *The following properties should hold at call time:*

`Sg` is currently a term which is not a free variable. (`nonvar/1`)

`Vars` is currently a term which is not a free variable. (`nonvar/1`)

`Call` is currently a term which is not a free variable. (`nonvar/1`)

`Succ` is a free variable. (`var/1`)

`Sg` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)

`Vars` is a list. (`list/1`)

`Call` is an abstract substitution (`eterms_asub/1`)

`Succ` is any term. (`term/1`)

– *The following properties should hold upon exit:*

`Succ` is an abstract substitution (`eterms_asub/1`)

variables_are_top_type/2: PREDICATE

Usage: `variables_are_top_type(Fv,ASub)`

It assigns the value top_type to the variables in `Fv` and return the abstract substitution `ASub`

– *The following properties should hold at call time:*

`Fv` is currently a term which is not a free variable. (`nonvar/1`)

`ASub` is a free variable. (`var/1`)

`Fv` is a list. (`list/1`)

– *The following properties should hold upon exit:*

`ASub` is an abstract substitution (`eterms_asub/1`)

eterms_call_to_success_fact/9: PREDICATE

Usage: `eterms_call_to_success_fact(Sg,Hv,Head,K,Sv,Call,Proj,Prime,Succ)`

Specialized version of call_to_entry + exit_to_prime + extend for facts

– *The following properties should hold at call time:*

`Sg` is currently a term which is not a free variable. (`nonvar/1`)

`Hv` is currently a term which is not a free variable. (`nonvar/1`)

`Head` is currently a term which is not a free variable. (`nonvar/1`)

`K` is currently a term which is not a free variable. (`nonvar/1`)

`Sv` is currently a term which is not a free variable. (`nonvar/1`)

`Call` is currently a term which is not a free variable. (`nonvar/1`)

`Proj` is currently a term which is not a free variable. (`nonvar/1`)

`Prime` is a free variable. (`var/1`)

`Succ` is a free variable. (`var/1`)

`Sg` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)

`Hv` is a list. (`list/1`)

`Head` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)

`K` is any term. (`term/1`)

`Sv` is a list. (`list/1`)

`Call` is an abstract substitution (`eterms_asub/1`)

`Proj` is an abstract substitution (`eterms_asub/1`)

`Prime` is any term. (`term/1`)

`Succ` is any term. (`term/1`)

– *The following properties should hold upon exit:*

`Prime` is an abstract substitution (`eterms_asub/1`)

`Succ` is an abstract substitution (`eterms_asub/1`)

eterms_special_builtin/5: PREDICATE

Usage: `eterms_special_builtin(SgKey,Sg,Subgoal,Type,Condvars)`

`Type` is a flag indicating what is the abstraction of builtin `SgKey` and to which variables `Condvars` of the goal `Sg` it affects.

– *The following properties should hold at call time:*

`SgKey` is currently a term which is not a free variable. (`nonvar/1`)
`Sg` is currently a term which is not a free variable. (`nonvar/1`)
`Subgoal` is currently a term which is not a free variable. (`nonvar/1`)
`Type` is a free variable. (`var/1`)
`Condvars` is a free variable. (`var/1`)
`SgKey` is an atom. (`atm/1`)
`Sg` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)
`Subgoal` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)

eterms_success_builtin/6: PREDICATE

Usage: `eterms_success_builtin(Type,Sv_uns,Condvars,HvFv_u,Call,Succ)`

Depending on `Type` it computes the abstraction of a builtin affecting variables `Condvars` and having variables `Sv_uns` with call subs. `Call`.

– *The following properties should hold at call time:*

`Type` is currently a term which is not a free variable. (`nonvar/1`)
`Sv_uns` is currently a term which is not a free variable. (`nonvar/1`)
`Condvars` is currently a term which is not a free variable. (`nonvar/1`)
`HvFv_u` is currently a term which is not a free variable. (`nonvar/1`)
`Call` is currently a term which is not a free variable. (`nonvar/1`)
`Succ` is a free variable. (`var/1`)

keys_same_value/3: PREDICATE

No further documentation available for this predicate.

eterms_arg_call_to_success/9: PREDICATE

No further documentation available for this predicate.

eterms_call_to_success_builtin/6: PREDICATE

Usage: `eterms_call_to_success_builtin(SgKey,Sg,Sv,Call,Proj,Succ)`

Same as above but for each particular builtin.

– *The following properties should hold at call time:*

`SgKey` is currently a term which is not a free variable. (`nonvar/1`)
`Sg` is currently a term which is not a free variable. (`nonvar/1`)
`Sv` is currently a term which is not a free variable. (`nonvar/1`)
`Call` is currently a term which is not a free variable. (`nonvar/1`)
`Proj` is currently a term which is not a free variable. (`nonvar/1`)
`Succ` is a free variable. (`var/1`)
`SgKey` is an atom. (`atm/1`)
`Sg` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)
`Sv` is a list. (`list/1`)

`Call` is an abstract substitution (`eterms_asub/1`)
`Proj` is an abstract substitution (`eterms_asub/1`)
`Succ` is any term. (`term/1`)
– *The following properties should hold upon exit:*
`Succ` is an abstract substitution (`eterms_asub/1`)

eterms_obtain_info/4: PREDICATE
No further documentation available for this predicate.

eterms_input_user_interface/5: PREDICATE
Usage: `eterms_input_user_interface(InputUser,Qv,ASub,Sg,MaybeCallASub)`
Obtains the abstract substitution `ASub` from user supplied information.
– *The following properties should hold at call time:*
`InputUser` is currently a term which is not a free variable. (`nonvar/1`)
`Qv` is currently a term which is not a free variable. (`nonvar/1`)
`ASub` is a free variable. (`var/1`)
`Sg` is currently a term which is not a free variable. (`nonvar/1`)
`MaybeCallASub` is currently a term which is not a free variable. (`nonvar/1`)

eterms_input_interface/4: PREDICATE
No further documentation available for this predicate.

eterms_asub_to_native/5: PREDICATE
Usage: `eterms_asub_to_native(ASub,Qv,OutFlag,OutputUser,Comps)`
Transforms abstract substitution `ASub` to user friendly format.
– *The following properties should hold at call time:*
`ASub` is currently a term which is not a free variable. (`nonvar/1`)
`Qv` is currently a term which is not a free variable. (`nonvar/1`)
`OutFlag` is currently a term which is not a free variable. (`nonvar/1`)
`OutputUser` is a free variable. (`var/1`)
`Comps` is a free variable. (`var/1`)
`ASub` is an abstract substitution (`eterms_asub/1`)
`Qv` is a list. (`list/1`)

eterms_output_interface/2: PREDICATE
Usage: `eterms_output_interface(ASub,Output)`
Transforms abstract substitution `ASub` to a more readable but still close to internal format.
– *The following properties should hold at call time:*
`ASub` is currently a term which is not a free variable. (`nonvar/1`)
`Output` is a free variable. (`var/1`)
`ASub` is an abstract substitution (`eterms_asub/1`)

eterms_collect_auxinfo_asub/3: PREDICATE
No further documentation available for this predicate.

eterms_rename_auxinfo_asub/3: PREDICATE
No further documentation available for this predicate.

eterms_identical_abstract/2: PREDICATE
No further documentation available for this predicate.

getargtypes/6: PREDICATE
No further documentation available for this predicate.

replacetype/4: PREDICATE
No further documentation available for this predicate.

getfunctors/2: PREDICATE
No further documentation available for this predicate.

split_f/4: PREDICATE
No further documentation available for this predicate.

getvalue/2: PREDICATE
No further documentation available for this predicate.

unifytoterm/1: PREDICATE
No further documentation available for this predicate.

abs_eval_arithcomp/4: PREDICATE
No further documentation available for this predicate.

generateSucc0_cond/5: PREDICATE
No further documentation available for this predicate.

abs_eval_arith/3: PREDICATE
No further documentation available for this predicate.

getvalues_comp_cond/3: PREDICATE
No further documentation available for this predicate.

get_list_names_is/2: PREDICATE
No further documentation available for this predicate.

determinate_sel/3: PREDICATE
No further documentation available for this predicate.

replaceintype/5: PREDICATE
No further documentation available for this predicate.

eterms_multi_part_conc/3: PREDICATE
No further documentation available for this predicate.

eterms_part_conc/4: PREDICATE
No further documentation available for this predicate.

obtains_names/4: PREDICATE
No further documentation available for this predicate.

12.3 Documentation on multifiles

aidomain/1: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.init_abstract_domain/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.amgu/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_two_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_entry/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.exit_to_prime/8: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.project/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widencall/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.needs/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widen/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_lub/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_lub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered_gfp/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.identical_abstract/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_sort/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.extend/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.less_or_equal/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.eliminate_equivalent/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_subset/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_fact/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.special_builtin/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.combined_special_builtin0/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.body_succ_builtin/9: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.split_combined_domain/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.obtain_info/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_interface/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_user_interface/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.asub_to_native/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.concrete/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_call/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.empty_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.part_conc/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.multi_part_conc/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.collect_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.rename_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.dom_statistics/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.contains_parameters/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

12.4 Documentation on imports

This module has the following direct dependencies:

- *Application modules:*
  `preprocess_flags`, `domains`, `termsd`, `unfold_builtins`, `apply_assertions_old`.
- *System library modules:*
  `sets`, `sort`, `typeslib`, `hiordlib`, `messages`, `aggregates`, `terms_vars`, `terms_check`, `lists`, `assoc`.
- *Internal (engine) modules:*
  `term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`.
- *Packages:*
  `prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `regtypes`, `basicmodes`, `hiord`, `aidomain`.

13 etermsvar: eterms with variables (abstract domain)

Author(s): Claudio Vaucheret, Francisco Bueno, Alejandro Serrano (etermsvar), Ciao Development Team.

This module implements an (experimental) variant of the `eterms` domain with `vr` elements in the lattice.

13.1 Usage and interface

- **Library usage:**
  `:- use_module(domain(etermsvar)).`
- **Exports:**
  - *Predicates:*
    `etermsvar_init_abstract_domain/1`, `etermsvar_compute_lub/2`, `etermsvar_compute_lub_el/3`, `etermsvar_widencall/3`, `etermsvar_needs/1`, `etermsvar_widen/3`, `etermsvar_call_to_entry/9`, `etermsvar_exit_to_prime/7`, `etermsvar_project/5`, `etermsvar_abs_sort/2`, `etermsvar_extend/5`, `etermsvar_less_or_equal/2`, `etermsvar_glb/3`, `etermsvar_concrete/3`, `etermsvar_unknown_entry/3`, `etermsvar_empty_entry/3`, `etermsvar_unknown_call/4`, `etermsvar_call_to_success_fact/9`, `etermsvar_special_builtin/5`, `etermsvar_success_builtin/6`, `etermsvar_arg_call_to_success/9`, `etermsvar_call_to_success_builtin/6`, `etermsvar_obtain_info/4`, `etermsvar_input_user_interface/5`, `etermsvar_input_interface/4`, `etermsvar_asub_to_native/5`, `etermsvar_output_interface/2`, `etermsvar_collect_auxinfo_asub/3`, `etermsvar_rename_auxinfo_asub/3`, `etermsvar_identical_abstract/2`, `etermsvar_multi_part_conc/3`, `etermsvar_part_conc/4`.
  - *Multifiles:*
    `aidomain/1`, `aidom.init_abstract_domain/2`, `aidom.amgu/5`, `aidom.augment_asub/4`, `aidom.augment_two_asub/4`, `aidom.call_to_entry/10`, `aidom.exit_to_prime/8`, `aidom.project/6`, `aidom.widencall/4`, `aidom.needs/2`, `aidom.widen/4`, `aidom.compute_lub/3`, `aidom.compute_clauses_lub/4`, `aidom.compute_clauses_glb/4`, `aidom.fixpoint_covered/3`, `aidom.fixpoint_covered_gfp/3`, `aidom.identical_abstract/3`, `aidom.abs_sort/3`, `aidom.extend/6`, `aidom.less_or_equal/3`, `aidom.glb/4`, `aidom.eliminate_equivalent/3`, `aidom.abs_subset/3`, `aidom.call_to_success_fact/10`, `aidom.special_builtin/6`, `aidom.combined_special_builtin0/3`, `aidom.body_succ_builtin/9`, `aidom.split_combined_domain/4`, `aidom.success_builtin/7`, `aidom.call_to_success_builtin/7`, `aidom.obtain_info/5`, `aidom.input_interface/5`, `aidom.input_user_interface/6`, `aidom.asub_to_native/6`, `aidom.concrete/4`, `aidom.unknown_call/5`, `aidom.unknown_entry/4`, `aidom.empty_entry/4`, `aidom.part_conc/5`, `aidom.multi_part_conc/4`, `aidom.collect_auxinfo_asub/4`, `aidom.rename_auxinfo_asub/4`, `aidom.dom_statistics/2`, `aidom.contains_parameters/2`.

13.2 Documentation on exports

etermsvar_init_abstract_domain/1: PREDICATE

No further documentation available for this predicate.

etermsvar_compute_lub/2: PREDICATE

Usage: `etermsvar_compute_lub(ListASub,Lub)`

– *The following properties should hold at call time:*

`ListASub` is currently a term which is not a free variable. (`nonvar/1`)

`Lub` is a free variable. (`var/1`)

`ListASub` is a list of `absus`. (`list/2`)

`Lub` is an abstract substitution (`absu/1`)

etermsvar_compute_lub_el/3: PREDICATE

No further documentation available for this predicate.

etermsvar_widencall/3: PREDICATE

No further documentation available for this predicate.

etermsvar_needs/1: PREDICATE

No further documentation available for this predicate.

etermsvar_widen/3: PREDICATE

Usage: `etermsvar_widen(Prime0,Prime1,NewPrime)`

– *The following properties should hold at call time:*

`Prime0` is currently a term which is not a free variable. (`nonvar/1`)

`Prime1` is currently a term which is not a free variable. (`nonvar/1`)

`NewPrime` is a free variable. (`var/1`)

`Prime0` is an abstract substitution (`absu/1`)

`Prime1` is an abstract substitution (`absu/1`)

`NewPrime` is an abstract substitution (`absu/1`)

etermsvar_call_to_entry/9: PREDICATE

Usage: `etermsvar_call_to_entry(Sv,Sg,Hv,Head,K,Fv,Proj,Entry,ExtraInfo)`

– *The following properties should hold at call time:*

`Sv` is currently a term which is not a free variable. (`nonvar/1`)

`Sg` is currently a term which is not a free variable. (`nonvar/1`)

`Hv` is currently a term which is not a free variable. (`nonvar/1`)

`Head` is currently a term which is not a free variable. (`nonvar/1`)

`K` is currently a term which is not a free variable. (`nonvar/1`)

`Fv` is currently a term which is not a free variable. (`nonvar/1`)

`Proj` is currently a term which is not a free variable. (`nonvar/1`)

`Entry` is a free variable. (`var/1`)

`ExtraInfo` is a free variable. (`var/1`)

`Sv` is any term. (`term/1`)

`Sg` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)
`Hv` is a list. (`list/1`)
`Head` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)
`K` is any term. (`term/1`)
`Fv` is a list. (`list/1`)
`Proj` is an abstract substitution (`absu/1`)
`Entry` is an abstract substitution (`absu/1`)
`extrainfo(ExtraInfo)` (`extrainfo/1`)

etermsvar_exit_to_prime/7: PREDICATE

Usage: `etermsvar_exit_to_prime(Sg,Hv,Head,Sv,Exit,ExtraInfo,Prime)`

– *The following properties should hold at call time:*

`Sg` is currently a term which is not a free variable. (`nonvar/1`)
`Hv` is currently a term which is not a free variable. (`nonvar/1`)
`Head` is currently a term which is not a free variable. (`nonvar/1`)
`Sv` is currently a term which is not a free variable. (`nonvar/1`)
`Exit` is currently a term which is not a free variable. (`nonvar/1`)
`ExtraInfo` is a free variable. (`var/1`)
`Prime` is a free variable. (`var/1`)
`Sg` is a list. (`list/1`)
`Hv` is a list. (`list/1`)
`Head` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)
`Sv` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)
`Exit` is an abstract substitution (`absu/1`)
`extrainfo(ExtraInfo)` (`extrainfo/1`)
`Prime` is an abstract substitution (`absu/1`)

etermsvar_project/5: PREDICATE

Usage: `etermsvar_project(Sg,Vars,HvFv_u,Asub,Proj)`

– *The following properties should hold at call time:*

`Sg` is currently a term which is not a free variable. (`nonvar/1`)
`Vars` is currently a term which is not a free variable. (`nonvar/1`)
`HvFv_u` is currently a term which is not a free variable. (`nonvar/1`)
`Asub` is currently a term which is not a free variable. (`nonvar/1`)
`Proj` is a free variable. (`var/1`)
`Sg` is any term. (`term/1`)
`Vars` is a list. (`list/1`)
`HvFv_u` is a list. (`list/1`)
`Asub` is an abstract substitution (`absu/1`)
`Proj` is an abstract substitution (`absu/1`)

etermsvar_abs_sort/2: PREDICATE

Usage: `etermsvar_abs_sort(Asub,Asub_s)`

– *The following properties should hold at call time:*

`Asub` is currently a term which is not a free variable. (`nonvar/1`)

`Asub_s` is a free variable. (`var/1`)

`Asub` is an abstract substitution (`absu/1`)

`Asub_s` is an abstract substitution (`absu/1`)

etermsvar_extend/5: PREDICATE

Usage: `etermsvar_extend(Sg,Prime,Sv,Call,Succ)`

– *The following properties should hold at call time:*

`Sg` is currently a term which is not a free variable. (`nonvar/1`)

`Prime` is currently a term which is not a free variable. (`nonvar/1`)

`Sv` is currently a term which is not a free variable. (`nonvar/1`)

`Call` is currently a term which is not a free variable. (`nonvar/1`)

`Succ` is a free variable. (`var/1`)

`Sg` is any term. (`term/1`)

`Prime` is an abstract substitution (`absu/1`)

`Sv` is a list. (`list/1`)

`Call` is an abstract substitution (`absu/1`)

`Succ` is an abstract substitution (`absu/1`)

etermsvar_less_or_equal/2: PREDICATE

Usage: `etermsvar_less_or_equal(ASub0,ASub1)`

– *The following properties should hold at call time:*

`ASub0` is currently a term which is not a free variable. (`nonvar/1`)

`ASub1` is currently a term which is not a free variable. (`nonvar/1`)

`ASub0` is an abstract substitution (`absu/1`)

`ASub1` is an abstract substitution (`absu/1`)

etermsvar_glb/3: PREDICATE

Usage: `etermsvar_glb(ASub0,ASub1,Glb)`

– *The following properties should hold at call time:*

`ASub0` is currently a term which is not a free variable. (`nonvar/1`)

`ASub1` is currently a term which is not a free variable. (`nonvar/1`)

`Glb` is a free variable. (`var/1`)

`ASub0` is an abstract substitution (`absu/1`)

`ASub1` is an abstract substitution (`absu/1`)

`Glb` is an abstract substitution (`absu/1`)

etermsvar_concrete/3: PREDICATE

No further documentation available for this predicate.

etermsvar_unknown_entry/3: PREDICATE

Usage: `etermsvar_unknown_entry(Sg,Qv,Call)`

– *The following properties should hold at call time:*

`Sg` is currently a term which is not a free variable. (`nonvar/1`)

`Qv` is currently a term which is not a free variable. (`nonvar/1`)

`Call` is a free variable. (`var/1`)

`Sg` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)

`Qv` is a list. (`list/1`)

`Call` is an abstract substitution (`absu/1`)

etermsvar_empty_entry/3: PREDICATE

Usage: `etermsvar_empty_entry(Sg,Vars,Entry)`

– *The following properties should hold at call time:*

`Sg` is currently a term which is not a free variable. (`nonvar/1`)

`Vars` is currently a term which is not a free variable. (`nonvar/1`)

`Entry` is a free variable. (`var/1`)

`Sg` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)

`Vars` is a list. (`list/1`)

`Entry` is an abstract substitution (`absu/1`)

etermsvar_unknown_call/4: PREDICATE

Usage: `etermsvar_unknown_call(Sg,Vars,Call,Succ)`

– *The following properties should hold at call time:*

`Sg` is currently a term which is not a free variable. (`nonvar/1`)

`Vars` is currently a term which is not a free variable. (`nonvar/1`)

`Call` is currently a term which is not a free variable. (`nonvar/1`)

`Succ` is a free variable. (`var/1`)

`Sg` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)

`Vars` is a list. (`list/1`)

`Call` is an abstract substitution (`absu/1`)

`Succ` is an abstract substitution (`absu/1`)

etermsvar_call_to_success_fact/9: PREDICATE

Usage:
`etermsvar_call_to_success_fact(Sg,Hv,Head,K,Sv,Call,Proj,Prime,Succ)`

– *The following properties should hold at call time:*

`Sg` is currently a term which is not a free variable. (`nonvar/1`)
`Hv` is currently a term which is not a free variable. (`nonvar/1`)
`Head` is currently a term which is not a free variable. (`nonvar/1`)
`K` is currently a term which is not a free variable. (`nonvar/1`)
`Sv` is currently a term which is not a free variable. (`nonvar/1`)
`Call` is currently a term which is not a free variable. (`nonvar/1`)
`Proj` is currently a term which is not a free variable. (`nonvar/1`)
`Prime` is a free variable. (`var/1`)
`Succ` is a free variable. (`var/1`)
`Sg` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)
`Hv` is a list. (`list/1`)
`Head` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)
`K` is any term. (`term/1`)
`Sv` is a list. (`list/1`)
`Call` is an abstract substitution (`absu/1`)
`Proj` is an abstract substitution (`absu/1`)
`Prime` is an abstract substitution (`absu/1`)
`Succ` is an abstract substitution (`absu/1`)

etermsvar_special_builtin/5: PREDICATE

Usage: `etermsvar_special_builtin(SgKey,Sg,Subgoal,Type,Condvars)`

– *The following properties should hold at call time:*

`SgKey` is currently a term which is not a free variable. (`nonvar/1`)
`Sg` is currently a term which is not a free variable. (`nonvar/1`)
`Subgoal` is currently a term which is not a free variable. (`nonvar/1`)
`Type` is a free variable. (`var/1`)
`Condvars` is a free variable. (`var/1`)

etermsvar_success_builtin/6: PREDICATE

Usage: `etermsvar_success_builtin(Type,Sv_uns,Condvars,HvFv_u,Call,Succ)`

– *The following properties should hold at call time:*

`Type` is currently a term which is not a free variable. (`nonvar/1`)
`Sv_uns` is currently a term which is not a free variable. (`nonvar/1`)
`Condvars` is currently a term which is not a free variable. (`nonvar/1`)
`HvFv_u` is currently a term which is not a free variable. (`nonvar/1`)
`Call` is currently a term which is not a free variable. (`nonvar/1`)
`Succ` is a free variable. (`var/1`)

etermsvar_arg_call_to_success/9: PREDICATE

No further documentation available for this predicate.

etermsvar_call_to_success_builtin/6: PREDICATE

Usage: `etermsvar_call_to_success_builtin(SgKey,Sg,Sv,Call,Proj,Succ)`

– *The following properties should hold at call time:*

`SgKey` is currently a term which is not a free variable. (`nonvar/1`)

`Sg` is currently a term which is not a free variable. (`nonvar/1`)

`Sv` is currently a term which is not a free variable. (`nonvar/1`)

`Call` is currently a term which is not a free variable. (`nonvar/1`)

`Proj` is currently a term which is not a free variable. (`nonvar/1`)

`Succ` is a free variable. (`var/1`)

etermsvar_obtain_info/4: PREDICATE

No further documentation available for this predicate.

etermsvar_input_user_interface/5: PREDICATE

Usage: `etermsvar_input_user_interface(InputUser,Qv,ASub,Sg,MaybeCallASub)`

– *The following properties should hold at call time:*

`InputUser` is currently a term which is not a free variable. (`nonvar/1`)

`Qv` is currently a term which is not a free variable. (`nonvar/1`)

`ASub` is a free variable. (`var/1`)

`Sg` is currently a term which is not a free variable. (`nonvar/1`)

`MaybeCallASub` is currently a term which is not a free variable. (`nonvar/1`)

etermsvar_input_interface/4: PREDICATE

No further documentation available for this predicate.

etermsvar_asub_to_native/5: PREDICATE

No further documentation available for this predicate.

etermsvar_output_interface/2: PREDICATE

Usage: `etermsvar_output_interface(ASub,Output)`

– *The following properties should hold at call time:*

`ASub` is currently a term which is not a free variable. (`nonvar/1`)

`Output` is a free variable. (`var/1`)

etermsvar_collect_auxinfo_asub/3: PREDICATE

No further documentation available for this predicate.

etermsvar_rename_auxinfo_asub/3: PREDICATE

No further documentation available for this predicate.

etermsvar_identical_abstract/2: PREDICATE
No further documentation available for this predicate.

etermsvar_multi_part_conc/3: PREDICATE
No further documentation available for this predicate.

etermsvar_part_conc/4: PREDICATE
No further documentation available for this predicate.

13.3 Documentation on multifiles

aidomain/1: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.init_abstract_domain/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.amgu/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_two_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_entry/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.exit_to_prime/8: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.project/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widencall/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.needs/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widen/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_lub/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_lub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered_gfp/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.identical_abstract/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_sort/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.extend/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.less_or_equal/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.eliminate_equivalent/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_subset/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_fact/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.special_builtin/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.combined_special_builtin0/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.body_succ_builtin/9: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.split_combined_domain/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.obtain_info/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_interface/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_user_interface/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.asub_to_native/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.concrete/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_call/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.empty_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.part_conc/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.multi_part_conc/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.collect_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.rename_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.dom_statistics/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.contains_parameters/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

13.4 Documentation on imports

This module has the following direct dependencies:

– *Application modules:*

`preprocess_flags`, `domains`, `apply_assertions_old`, `eterms`, `termsd`.

– *System library modules:*

`datafacts_rt`, `sets`, `sort`, `typeslib`, `messages`, `aggregates`, `terms_vars`, `terms_check`, `lists`.

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `regtypes`, `basicmodes`, `datafacts`, `aidomain`.

14 frdef (library)

14.1 Usage and interface

- **Library usage:**
  `:- use_module(domain(frdef)).`
- **Exports:**
  - *Predicates:*
    `frdef_call_to_entry/9`, `frdef_call_to_success_fact/9`, `frdef_compute_lub/2`, `frdef_exit_to_prime/7`, `frdef_extend/5`, `frdef_identical_abstract/2`, `frdef_input_user_interface/5`, `frdef_input_interface/4`, `frdef_less_or_equal/2`, `frdef_glb/3`, `frdef_asub_to_native/5`, `frdef_project/5`, `frdef_abs_sort/2`, `frdef_special_builtin/5`, `frdef_success_builtin/6`, `frdef_unknown_call/4`, `frdef_unknown_entry/3`, `frdef_empty_entry/3`.
  - *Multifiles:*
    `aidomain/1`, `aidom.init_abstract_domain/2`, `aidom.amgu/5`, `aidom.augment_asub/4`, `aidom.augment_two_asub/4`, `aidom.call_to_entry/10`, `aidom.exit_to_prime/8`, `aidom.project/6`, `aidom.widencall/4`, `aidom.needs/2`, `aidom.widen/4`, `aidom.compute_lub/3`, `aidom.compute_clauses_lub/4`, `aidom.compute_clauses_glb/4`, `aidom.fixpoint_covered/3`, `aidom.fixpoint_covered_gfp/3`, `aidom.identical_abstract/3`, `aidom.abs_sort/3`, `aidom.extend/6`, `aidom.less_or_equal/3`, `aidom.glb/4`, `aidom.eliminate_equivalent/3`, `aidom.abs_subset/3`, `aidom.call_to_success_fact/10`, `aidom.special_builtin/6`, `aidom.combined_special_builtin0/3`, `aidom.body_succ_builtin/9`, `aidom.split_combined_domain/4`, `aidom.success_builtin/7`, `aidom.call_to_success_builtin/7`, `aidom.obtain_info/5`, `aidom.input_interface/5`, `aidom.input_user_interface/6`, `aidom.asub_to_native/6`, `aidom.concrete/4`, `aidom.unknown_call/5`, `aidom.unknown_entry/4`, `aidom.empty_entry/4`, `aidom.part_conc/5`, `aidom.multi_part_conc/4`, `aidom.collect_auxinfo_asub/4`, `aidom.rename_auxinfo_asub/4`, `aidom.dom_statistics/2`, `aidom.contains_parameters/2`.

14.2 Documentation on exports

frdef_call_to_entry/9: PREDICATE

No further documentation available for this predicate.

frdef_call_to_success_fact/9: PREDICATE

No further documentation available for this predicate.

frdef_compute_lub/2: PREDICATE

No further documentation available for this predicate.

frdef_exit_to_prime/7: PREDICATE
No further documentation available for this predicate.

frdef_extend/5: PREDICATE
No further documentation available for this predicate.

frdef_identical_abstract/2: PREDICATE
No further documentation available for this predicate.

frdef_input_user_interface/5: PREDICATE
No further documentation available for this predicate.

frdef_input_interface/4: PREDICATE
No further documentation available for this predicate.

frdef_less_or_equal/2: PREDICATE
No further documentation available for this predicate.

frdef_glb/3: PREDICATE
No further documentation available for this predicate.

frdef_asub_to_native/5: PREDICATE
No further documentation available for this predicate.

frdef_project/5: PREDICATE
No further documentation available for this predicate.

frdef_abs_sort/2: PREDICATE
No further documentation available for this predicate.

frdef_special_builtin/5: PREDICATE
No further documentation available for this predicate.

frdef_success_builtin/6: PREDICATE
No further documentation available for this predicate.

frdef_unknown_call/4: PREDICATE
No further documentation available for this predicate.

frdef_unknown_entry/3: PREDICATE
No further documentation available for this predicate.

frdef_empty_entry/3: PREDICATE
No further documentation available for this predicate.

14.3 Documentation on multifiles

aidomain/1: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.init_abstract_domain/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.amgu/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_two_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_entry/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.exit_to_prime/8: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.project/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widencall/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.needs/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widen/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_lub/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_lub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered_gfp/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.identical_abstract/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_sort/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.extend/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.less_or_equal/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.eliminate_equivalent/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_subset/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_fact/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.special_builtin/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.combined_special_builtin0/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.body_succ_builtin/9: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.split_combined_domain/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.obtain_info/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_interface/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_user_interface/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.asub_to_native/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.concrete/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_call/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.empty_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.part_conc/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.multi_part_conc/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.collect_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.rename_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.dom_statistics/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.contains_parameters/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

14.4 Documentation on imports

This module has the following direct dependencies:

– *Application modules:*
`preprocess_flags`, `domains`, `def`, `fr_sets`, `fr_shared`, `fr_top`, `plai_errors`, `share_aux`.

– *System library modules:*
`sets`, `sort`, `lists`, `terms_vars`.

– *Internal (engine) modules:*
`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`.

– *Packages:*
`prelude`, `initial`, `condcomp`, `aidomain`.

15 fr_top (library)

15.1 Usage and interface

- **Library usage:**
  `:- use_module(domain(fr_top)).`
- **Exports:**
  - *Predicates:*
    `fr_call_to_entry/9`, `fr_call_to_success_fact/9`, `fr_compute_lub/2`, `fr_exit_to_prime/7`, `fr_extend/5`, `fr_identical_abstract/2`, `fr_input_user_interface/5`, `fr_input_interface/4`, `fr_less_or_equal/2`, `fr_glb/3`, `fr_output_interface/3`, `fr_project/5`, `fr_abs_sort/2`, `fr_special_builtin/5`, `fr_success_builtin/6`, `fr_asub_to_native/5`, `fr_unknown_call/4`, `fr_unknown_entry/3`, `fr_empty_entry/3`, `get_free_vars/3`.
  - *Multifiles:*
    `aidomain/1`, `aidom.init_abstract_domain/2`, `aidom.amgu/5`, `aidom.augment_asub/4`, `aidom.augment_two_asub/4`, `aidom.call_to_entry/10`, `aidom.exit_to_prime/8`, `aidom.project/6`, `aidom.widencall/4`, `aidom.needs/2`, `aidom.widen/4`, `aidom.compute_lub/3`, `aidom.compute_clauses_lub/4`, `aidom.compute_clauses_glb/4`, `aidom.fixpoint_covered/3`, `aidom.fixpoint_covered_gfp/3`, `aidom.identical_abstract/3`, `aidom.abs_sort/3`, `aidom.extend/6`, `aidom.less_or_equal/3`, `aidom.glb/4`, `aidom.eliminate_equivalent/3`, `aidom.abs_subset/3`, `aidom.call_to_success_fact/10`, `aidom.special_builtin/6`, `aidom.combined_special_builtin0/3`, `aidom.body_succ_builtin/9`, `aidom.split_combined_domain/4`, `aidom.success_builtin/7`, `aidom.call_to_success_builtin/7`, `aidom.obtain_info/5`, `aidom.input_interface/5`, `aidom.input_user_interface/6`, `aidom.asub_to_native/6`, `aidom.concrete/4`, `aidom.unknown_call/5`, `aidom.unknown_entry/4`, `aidom.empty_entry/4`, `aidom.part_conc/5`, `aidom.multi_part_conc/4`, `aidom.collect_auxinfo_asub/4`, `aidom.rename_auxinfo_asub/4`, `aidom.dom_statistics/2`, `aidom.contains_parameters/2`.

15.2 Documentation on exports

fr_call_to_entry/9: PREDICATE

No further documentation available for this predicate.

fr_call_to_success_fact/9: PREDICATE

No further documentation available for this predicate.

fr_compute_lub/2: PREDICATE

No further documentation available for this predicate.

fr_exit_to_prime/7: PREDICATE
No further documentation available for this predicate.

fr_extend/5: PREDICATE
No further documentation available for this predicate.

fr_identical_abstract/2: PREDICATE
No further documentation available for this predicate.

fr_input_user_interface/5: PREDICATE
No further documentation available for this predicate.

fr_input_interface/4: PREDICATE
No further documentation available for this predicate.

fr_less_or_equal/2: PREDICATE
No further documentation available for this predicate.

fr_glb/3: PREDICATE
No further documentation available for this predicate.

fr_output_interface/3: PREDICATE
No further documentation available for this predicate.

fr_project/5: PREDICATE
No further documentation available for this predicate.

fr_abs_sort/2: PREDICATE
No further documentation available for this predicate.

fr_special_builtin/5: PREDICATE
No further documentation available for this predicate.

fr_success_builtin/6: PREDICATE
No further documentation available for this predicate.

fr_asub_to_native/5: PREDICATE
No further documentation available for this predicate.

fr_unknown_call/4: PREDICATE
No further documentation available for this predicate.

fr_unknown_entry/3: PREDICATE
No further documentation available for this predicate.

fr_empty_entry/3: PREDICATE
No further documentation available for this predicate.

get_free_vars/3: PREDICATE
No further documentation available for this predicate.

15.3 Documentation on multifiles

aidomain/1: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.init_abstract_domain/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.amgu/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_two_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_entry/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.exit_to_prime/8: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.project/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widencall/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.needs/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widen/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_lub/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_lub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered_gfp/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.identical_abstract/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_sort/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.extend/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.less_or_equal/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.eliminate_equivalent/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_subset/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_fact/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.special_builtin/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.combined_special_builtin0/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.body_succ_builtin/9: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.split_combined_domain/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.obtain_info/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_interface/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_user_interface/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.asub_to_native/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.concrete/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_call/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.empty_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.part_conc/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.multi_part_conc/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.collect_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.rename_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.dom_statistics/2: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

aidom.contains_parameters/2: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

15.4 Documentation on imports

This module has the following direct dependencies:

- *Application modules:*

  `preprocess_flags`, `domains`, `plai_errors`, `fr_sets`, `fr_shared`, `share_aux`.
- *System library modules:*

  `datafacts_rt`, `sets`, `sort`, `p_unit`.
- *Internal (engine) modules:*

  `term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`.
- *Packages:*

  `prelude`, `initial`, `condcomp`, `datafacts`, `aidomain`.

16 Simple groundness abstract domain

Author(s): Claudio Vaucheret.

This module implements the abstract operations of a simple groundness domain for the PLAI framework of abstract interpretation. An abstract substitution is a list of Var/Mode elements, where Var is a variable and Mode is "any", "g" or "ng".

The abstract domain lattice is:



16.1 Usage and interface

- **Library usage:**

```
:- use_module(domain(gr)).
```

16.2 Documentation on multifiles

aidomain/1: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

aidom.init_abstract_domain/2: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

aidom.amgu/5: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_asub/4: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_two_asub/4: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_entry/10: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

aidom.exit_to_prime/8: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.project/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widencall/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.needs/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widen/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_lub/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_lub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered_gfp/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.identical_abstract/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_sort/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.extend/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.less_or_equal/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.eliminate_equivalent/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_subset/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_fact/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.special_builtin/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.combined_special_builtin0/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.body_succ_builtin/9: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.split_combined_domain/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.obtain_info/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_interface/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_user_interface/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.asub_to_native/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.concrete/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_call/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.empty_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.part_conc/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.multi_part_conc/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.collect_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.rename_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.dom_statistics/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.contains_parameters/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

16.3 Documentation on internals

asub/1: PROPERTY
Usage: `asub(A)`
`A` is a well-formed abstract substitution of the gr domain.

asub_elem/1: PROPERTY
Usage: `asub_elem(E)`
`E` is a single substitution

gr_mode/1: REGTYPE
Usage: `gr_mode(M)`
`M` is g (ground), ng (nonground), or any

extrainfo/1: PROPERTY
Usage: `extrainfo(E)`
`E` is a par (asub,binds)

binds/1: PROPERTY
Usage: `binds(B)`
`B` is a list of bindings

binding/1: PROPERTY
Usage: `binding(B)`
`B` is a triple (X,Term,Vars), where X is a variable, Term is a term and Vars is the set of variables in Term

16.4 Documentation on imports

This module has the following direct dependencies:

– *Application modules:*

`preprocess_flags`, `domains`.

– *System library modules:*

`datafacts_rt`, `native_props`, `messages`, `sort`, `terms_vars`, `terms_check`, `sets`.

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`, `io_basic`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `regtypes`, `basicmodes`, `datafacts`, `nativeprops`, `aidomain`.

17 lsign domain

17.1 Usage and interface

- **Library usage:**
  `:- use_module(domain(lsign)).`
- **Exports:**
  - *Predicates:*
    `lsign_init_abstract_domain/1`, `lsign_call_to_entry/9`, `lsign_call_to_success_fact/9`, `lsign_compute_lub/2`, `lsign_extend/5`, `lsign_eliminate_equivalent/2`, `lsign_exit_to_prime/7`, `lsign_global_info/5`, `lsign_input_user_interface/5`, `lsign_input_interface/4`, `lsign_asub_to_native/5`, `lsign_abs_subset/2`, `lsign_less_or_equal/2`, `lsign_glb/3`, `lsign_project/5`, `lsign_abs_sort/2`, `lsign_special_builtin/5`, `lsign_success_builtin/6`, `lsign_unknown_call/4`, `lsign_unknown_entry/3`, `lsign_empty_entry/3`, `lsign_sum/3`, `lsign_output_interface/2`, `lsign_propagate_fixpoint/8`.
  - *Multifiles:*
    `aidomain/1`, `aidom.init_abstract_domain/2`, `aidom.amgu/5`, `aidom.augment_asub/4`, `aidom.augment_two_asub/4`, `aidom.call_to_entry/10`, `aidom.exit_to_prime/8`, `aidom.project/6`, `aidom.widencall/4`, `aidom.needs/2`, `aidom.widen/4`, `aidom.compute_lub/3`, `aidom.compute_clauses_lub/4`, `aidom.compute_clauses_glb/4`, `aidom.fixpoint_covered/3`, `aidom.fixpoint_covered_gfp/3`, `aidom.identical_abstract/3`, `aidom.abs_sort/3`, `aidom.extend/6`, `aidom.less_or_equal/3`, `aidom.glb/4`, `aidom.eliminate_equivalent/3`, `aidom.abs_subset/3`, `aidom.call_to_success_fact/10`, `aidom.special_builtin/6`, `aidom.combined_special_builtin0/3`, `aidom.body_succ_builtin/9`, `aidom.split_combined_domain/4`, `aidom.success_builtin/7`, `aidom.call_to_success_builtin/7`, `aidom.obtain_info/5`, `aidom.input_interface/5`, `aidom.input_user_interface/6`, `aidom.asub_to_native/6`, `aidom.concrete/4`, `aidom.unknown_call/5`, `aidom.unknown_entry/4`, `aidom.empty_entry/4`, `aidom.part_conc/5`, `aidom.multi_part_conc/4`, `aidom.collect_auxinfo_asub/4`, `aidom.rename_auxinfo_asub/4`, `aidom.dom_statistics/2`, `aidom.contains_parameters/2`.

17.2 Documentation on exports

lsign_init_abstract_domain/1: PREDICATE
No further documentation available for this predicate.

lsign_call_to_entry/9: PREDICATE
No further documentation available for this predicate.

lsign_call_to_success_fact/9: PREDICATE
No further documentation available for this predicate.

lsign_compute_lub/2: PREDICATE
No further documentation available for this predicate.

lsign_extend/5: PREDICATE
No further documentation available for this predicate.

lsign_eliminate_equivalent/2: PREDICATE
No further documentation available for this predicate.

lsign_exit_to_prime/7: PREDICATE
No further documentation available for this predicate.

lsign_global_info/5: PREDICATE
No further documentation available for this predicate.

lsign_input_user_interface/5: PREDICATE
No further documentation available for this predicate.

lsign_input_interface/4: PREDICATE
No further documentation available for this predicate.

lsign_asub_to_native/5: PREDICATE
No further documentation available for this predicate.

lsign_abs_subset/2: PREDICATE
No further documentation available for this predicate.

lsign_less_or_equal/2: PREDICATE
No further documentation available for this predicate.

lsign_glb/3: PREDICATE
No further documentation available for this predicate.

lsign_project/5: PREDICATE
No further documentation available for this predicate.

lsign_abs_sort/2: PREDICATE
No further documentation available for this predicate.

lsign_special_builtin/5: PREDICATE
No further documentation available for this predicate.

lsign_success_builtin/6: PREDICATE
No further documentation available for this predicate.

lsign_unknown_call/4: PREDICATE
No further documentation available for this predicate.

lsign_unknown_entry/3: PREDICATE
No further documentation available for this predicate.

lsign_empty_entry/3: PREDICATE
No further documentation available for this predicate.

lsign_sum/3: PREDICATE
No further documentation available for this predicate.

lsign_output_interface/2: PREDICATE
No further documentation available for this predicate.

lsign_propagate_fixpoint/8: PREDICATE
No further documentation available for this predicate.

17.3 Documentation on multifiles

aidomain/1: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.init_abstract_domain/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.amgu/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_two_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_entry/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.exit_to_prime/8: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.project/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widencall/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.needs/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widen/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_lub/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_lub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered_gfp/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.identical_abstract/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_sort/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.extend/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.less_or_equal/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.eliminate_equivalent/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_subset/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_fact/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.special_builtin/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.combined_special_builtin0/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.body_succ_builtin/9: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.split_combined_domain/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.obtain_info/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_interface/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_user_interface/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.asub_to_native/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.concrete/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_call/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.empty_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.part_conc/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.multi_part_conc/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.collect_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.rename_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.dom_statistics/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.contains_parameters/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

17.4 Documentation on imports

This module has the following direct dependencies:

- *Application modules:*
  `preprocess_flags`, `domains`, `deftools`, `s_grshfr`, `share_aux`, `plai_errors`.
- *System library modules:*
  `sets`, `sort`, `lists`, `lsets`, `messages`, `terms_check`, `terms_vars`.
- *Internal (engine) modules:*
  `term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `io_basic`.
- *Packages:*
  `prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `aidomain`.

18 lsigndiff domain

18.1 Usage and interface

- **Library usage:**
  `:- use_module(domain(lsigndiff)).`
- **Exports:**
  - *Predicates:*
    `difflsign_call_to_entry/9`, `difflsign_call_to_success_fact/9`, `difflsign_compute_lub/2`, `difflsign_exit_to_prime/7`, `difflsign_extend/5`, `difflsign_input_user_interface/5`, `difflsign_input_interface/4`, `difflsign_asub_to_native/5`, `difflsign_less_or_equal/2`, `difflsign_glb/3`, `difflsign_project/5`, `difflsign_abs_sort/2`, `difflsign_special_builtin/5`, `difflsign_success_builtin/6`, `difflsign_unknown_call/4`, `difflsign_unknown_entry/3`, `difflsign_empty_entry/3`.
  - *Multifiles:*
    `aidomain/1`, `aidom.init_abstract_domain/2`, `aidom.amgu/5`, `aidom.augment_asub/4`, `aidom.augment_two_asub/4`, `aidom.call_to_entry/10`, `aidom.exit_to_prime/8`, `aidom.project/6`, `aidom.widencall/4`, `aidom.needs/2`, `aidom.widen/4`, `aidom.compute_lub/3`, `aidom.compute_clauses_lub/4`, `aidom.compute_clauses_glb/4`, `aidom.fixpoint_covered/3`, `aidom.fixpoint_covered_gfp/3`, `aidom.identical_abstract/3`, `aidom.abs_sort/3`, `aidom.extend/6`, `aidom.less_or_equal/3`, `aidom.glb/4`, `aidom.eliminate_equivalent/3`, `aidom.abs_subset/3`, `aidom.call_to_success_fact/10`, `aidom.special_builtin/6`, `aidom.combined_special_builtin0/3`, `aidom.body_succ_builtin/9`, `aidom.split_combined_domain/4`, `aidom.success_builtin/7`, `aidom.call_to_success_builtin/7`, `aidom.obtain_info/5`, `aidom.input_interface/5`, `aidom.input_user_interface/6`, `aidom.asub_to_native/6`, `aidom.concrete/4`, `aidom.unknown_call/5`, `aidom.unknown_entry/4`, `aidom.empty_entry/4`, `aidom.part_conc/5`, `aidom.multi_part_conc/4`, `aidom.collect_auxinfo_asub/4`, `aidom.rename_auxinfo_asub/4`, `aidom.dom_statistics/2`, `aidom.contains_parameters/2`.

18.2 Documentation on exports

difflsign_call_to_entry/9: PREDICATE
No further documentation available for this predicate.

difflsign_call_to_success_fact/9: PREDICATE
No further documentation available for this predicate.

difflsign_compute_lub/2: PREDICATE
No further documentation available for this predicate.

difflsign_exit_to_prime/7: PREDICATE
No further documentation available for this predicate.

difflsign_extend/5: PREDICATE
No further documentation available for this predicate.

difflsign_input_user_interface/5: PREDICATE
No further documentation available for this predicate.

difflsign_input_interface/4: PREDICATE
No further documentation available for this predicate.

difflsign_asub_to_native/5: PREDICATE
No further documentation available for this predicate.

difflsign_less_or_equal/2: PREDICATE
No further documentation available for this predicate.

difflsign_glb/3: PREDICATE
No further documentation available for this predicate.

difflsign_project/5: PREDICATE
No further documentation available for this predicate.

difflsign_abs_sort/2: PREDICATE
No further documentation available for this predicate.

difflsign_special_builtin/5: PREDICATE
No further documentation available for this predicate.

difflsign_success_builtin/6: PREDICATE
No further documentation available for this predicate.

difflsign_unknown_call/4: PREDICATE
No further documentation available for this predicate.

difflsign_unknown_entry/3: PREDICATE
No further documentation available for this predicate.

difflsign_empty_entry/3: PREDICATE
No further documentation available for this predicate.

18.3 Documentation on multifiles

aidomain/1: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.init_abstract_domain/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.amgu/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_two_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_entry/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.exit_to_prime/8: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.project/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widencall/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.needs/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widen/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_lub/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_lub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered_gfp/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.identical_abstract/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_sort/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.extend/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.less_or_equal/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.eliminate_equivalent/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_subset/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_fact/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.special_builtin/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.combined_special_builtin0/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.body_succ_builtin/9: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.split_combined_domain/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.obtain_info/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_interface/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_user_interface/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.asub_to_native/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.concrete/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_call/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.empty_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.part_conc/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.multi_part_conc/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.collect_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.rename_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.dom_statistics/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.contains_parameters/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

18.4 Documentation on imports

This module has the following direct dependencies:

– *Application modules:*
`preprocess_flags`, `domains`, `lsign`, `s_grshfr`, `plai_errors`.

– *System library modules:*
`sets`, `sort`.

– *Internal (engine) modules:*
`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`.

– *Packages:*
`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `aidomain`.

19 detplai (library)

19.1 Usage and interface

- **Library usage:**
  `:- use_module(domain(nfdet/detplai)).`
- **Exports:**
  - *Predicates:*
    `det_init_abstract_domain/1`, `det_call_to_entry/9`, `det_widen/3`, `det_widencall/3`, `det_compute_clauses_lub/3`, `det_eliminate_equivalent/2`, `det_split_combined_domain/3`, `det_special_builtin/5`, `det_combined_special_builtin0/2`, `det_asub_to_native/5`, `det_dom_statistics/1`, `det_obtain_info/4`, `asub/4`, `det_collect_auxinfo_asub/3`, `det_rename_auxinfo_asub/3`.
  - *Regular Types:*
    `det_asub/1`.
  - *Multifiles:*
    `aidomain/1`, `aidom.init_abstract_domain/2`, `aidom.amgu/5`, `aidom.augment_asub/4`, `aidom.augment_two_asub/4`, `aidom.call_to_entry/10`, `aidom.exit_to_prime/8`, `aidom.project/6`, `aidom.widencall/4`, `aidom.needs/2`, `aidom.widen/4`, `aidom.compute_lub/3`, `aidom.compute_clauses_lub/4`, `aidom.compute_clauses_glb/4`, `aidom.fixpoint_covered/3`, `aidom.fixpoint_covered_gfp/3`, `aidom.identical_abstract/3`, `aidom.abs_sort/3`, `aidom.extend/6`, `aidom.less_or_equal/3`, `aidom.glb/4`, `aidom.eliminate_equivalent/3`, `aidom.abs_subset/3`, `aidom.call_to_success_fact/10`, `aidom.special_builtin/6`, `aidom.combined_special_builtin0/3`, `aidom.body_succ_builtin/9`, `aidom.split_combined_domain/4`, `aidom.success_builtin/7`, `aidom.call_to_success_builtin/7`, `aidom.obtain_info/5`, `aidom.input_interface/5`, `aidom.input_user_interface/6`, `aidom.asub_to_native/6`, `aidom.concrete/4`, `aidom.unknown_call/5`, `aidom.unknown_entry/4`, `aidom.empty_entry/4`, `aidom.part_conc/5`, `aidom.multi_part_conc/4`, `aidom.collect_auxinfo_asub/4`, `aidom.rename_auxinfo_asub/4`, `aidom.dom_statistics/2`, `aidom.contains_parameters/2`.

19.2 Documentation on exports

det_init_abstract_domain/1: PREDICATE
No further documentation available for this predicate.

det_call_to_entry/9: PREDICATE
No further documentation available for this predicate.

det_exit_to_prime/7: PREDICATE
No further documentation available for this predicate.

det_project/5: PREDICATE
No further documentation available for this predicate.

det_extend/5: PREDICATE
No further documentation available for this predicate.

det_widen/3: PREDICATE
No further documentation available for this predicate.

det_widencall/3: PREDICATE
No further documentation available for this predicate.

det_compute_lub/2: PREDICATE
No further documentation available for this predicate.

det_compute_clauses_lub/3: PREDICATE
No further documentation available for this predicate.

det_glb/3: PREDICATE
No further documentation available for this predicate.

det_eliminate_equivalent/2: PREDICATE
No further documentation available for this predicate.

det_less_or_equal/2: PREDICATE
No further documentation available for this predicate.

det_identical_abstract/2: PREDICATE
No further documentation available for this predicate.

det_abs_sort/2: PREDICATE
No further documentation available for this predicate.

det_call_to_success_fact/9: PREDICATE
No further documentation available for this predicate.

det_split_combined_domain/3: PREDICATE
No further documentation available for this predicate.

det_special_builtin/5: PREDICATE
No further documentation available for this predicate.

det_combined_special_builtin0/2: PREDICATE
No further documentation available for this predicate.

det_success_builtin/6: PREDICATE
No further documentation available for this predicate.

det_input_interface/4: PREDICATE
No further documentation available for this predicate.

det_input_user_interface/5: PREDICATE
No further documentation available for this predicate.

det_asub_to_native/5: PREDICATE
No further documentation available for this predicate.

det_unknown_call/4: PREDICATE
No further documentation available for this predicate.

det_unknown_entry/3: PREDICATE
No further documentation available for this predicate.

det_empty_entry/3: PREDICATE
No further documentation available for this predicate.

det_dom_statistics/1: PREDICATE
No further documentation available for this predicate.

det_obtain_info/4: PREDICATE
No further documentation available for this predicate.

det_asub/1: REGTYPE

`det_asub(ASub)`

`ASub` is an abstract substitution term used in det. It contains types, modes and determinism information.

Usage: `det_asub(ASub)`

`ASub` is an abstract substitution term used in det.

asub/4: PREDICATE

No further documentation available for this predicate.

det_collect_auxinfo_asub/3: PREDICATE

No further documentation available for this predicate.

det_rename_auxinfo_asub/3: PREDICATE

No further documentation available for this predicate.

19.3 Documentation on multifiles

aidomain/1: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

aidom.init_abstract_domain/2: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

aidom.amgu/5: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_asub/4: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_two_asub/4: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_entry/10: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

aidom.exit_to_prime/8: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.project/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widencall/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.needs/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widen/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_lub/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_lub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered_gfp/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.identical_abstract/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_sort/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.extend/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.less_or_equal/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.eliminate_equivalent/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_subset/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_fact/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.special_builtin/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.combined_special_builtin0/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.body_succ_builtin/9: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.split_combined_domain/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.obtain_info/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_interface/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_user_interface/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.asub_to_native/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.concrete/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_call/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.empty_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.part_conc/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.multi_part_conc/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.collect_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.rename_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.dom_statistics/2: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

aidom.contains_parameters/2: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

19.4 Documentation on imports

This module has the following direct dependencies:

- *Application modules:*

  `preprocess_flags`, `domains`, `eterms`, `sharefree`, `detabs`, `infer_dom`.
- *System library modules:*

  `sets`, `sort`, `idlists`, `lists`.
- *Internal (engine) modules:*

  `term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`.
- *Packages:*

  `prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `regtypes`, `basicmodes`, `aidomain`.

20 nfplai (library)

20.1 Usage and interface

- **Library usage:**
  `:- use_module(domain(nfdet/nfplai)).`
- **Exports:**
  - *Predicates:*
    `nf_init_abstract_domain/1`, `nf_call_to_entry/9`, `nf_widencall/3`, `nf_compute_clauses_lub/3`, `nf_eliminate_equivalent/2`, `nf_split_combined_domain/3`, `nf_special_builtin/5`, `nf_combined_special_builtin0/2`, `nf_asub_to_native/5`, `nf_dom_statistics/1`, `nf_obtain_info/4`, `asub/4`, `nf_collect_auxinfo_asub/3`, `nf_rename_auxinfo_asub/3`.
  - *Regular Types:*
    `nf_par_asub/2`, `nf_asub/1`, `nf_pred_asub/1`, `nf_pred_asub_sl/1`.
  - *Multifiles:*
    `aidomain/1`, `aidom.init_abstract_domain/2`, `aidom.amgu/5`, `aidom.augment_asub/4`, `aidom.augment_two_asub/4`, `aidom.call_to_entry/10`, `aidom.exit_to_prime/8`, `aidom.project/6`, `aidom.widencall/4`, `aidom.needs/2`, `aidom.widen/4`, `aidom.compute_lub/3`, `aidom.compute_clauses_lub/4`, `aidom.compute_clauses_glb/4`, `aidom.fixpoint_covered/3`, `aidom.fixpoint_covered_gfp/3`, `aidom.identical_abstract/3`, `aidom.abs_sort/3`, `aidom.extend/6`, `aidom.less_or_equal/3`, `aidom.glb/4`, `aidom.eliminate_equivalent/3`, `aidom.abs_subset/3`, `aidom.call_to_success_fact/10`, `aidom.special_builtin/6`, `aidom.combined_special_builtin0/3`, `aidom.body_succ_builtin/9`, `aidom.split_combined_domain/4`, `aidom.success_builtin/7`, `aidom.call_to_success_builtin/7`, `aidom.obtain_info/5`, `aidom.input_interface/5`, `aidom.input_user_interface/6`, `aidom.asub_to_native/6`, `aidom.concrete/4`, `aidom.unknown_call/5`, `aidom.unknown_entry/4`, `aidom.empty_entry/4`, `aidom.part_conc/5`, `aidom.multi_part_conc/4`, `aidom.collect_auxinfo_asub/4`, `aidom.rename_auxinfo_asub/4`, `aidom.dom_statistics/2`, `aidom.contains_parameters/2`.

20.2 Documentation on exports

nf_init_abstract_domain/1: PREDICATE
No further documentation available for this predicate.

nf_call_to_entry/9: PREDICATE
No further documentation available for this predicate.

nf_exit_to_prime/7: PREDICATE
No further documentation available for this predicate.

nf_project/5: PREDICATE
No further documentation available for this predicate.

nf_extend/5: PREDICATE
No further documentation available for this predicate.

nf_widen/3: PREDICATE
No further documentation available for this predicate.

nf_widencall/3: PREDICATE
No further documentation available for this predicate.

nf_compute_lub/2: PREDICATE
No further documentation available for this predicate.

nf_compute_clauses_lub/3: PREDICATE
Usage: `nf_compute_clauses_lub(ASubL,Proj,LubL)`
Performs the covering check that decides if the predicate test encoded in `ASubL` covers the types/modes represented in `Proj`. The predicate test is a conjunction of clause tests (corresponding to those clauses that do not fail so far). The modes/types, taken from `Proj`, corresponds to the parent goal, i.e., the one that unifies with the heads the clauses whose tests are represented in `ASubL`. The covering and nonfailure information derived from the covering check is represented in `LubL`

- *The following properties should hold at call time:*
  `nf_pred_asub_sl(ASubL)` (`nf_pred_asub_sl/1`)
  `Proj` is an abstract substitution term used in the combined domain `nf`. It contains types, modes and nonfailure information. (`nf_asub/1`)
  `LubL` is a free variable. (`var/1`)
- *The following properties should hold upon exit:*
  `nf_pred_asub_sl(ASubL)` (`nf_pred_asub_sl/1`)
  `Proj` is an abstract substitution term used in the combined domain `nf`. It contains types, modes and nonfailure information. (`nf_asub/1`)
  `nf_pred_asub_sl(LubL)` (`nf_pred_asub_sl/1`)

nf_glb/3: PREDICATE
No further documentation available for this predicate.

nf_eliminate_equivalent/2: PREDICATE
No further documentation available for this predicate.

nf_less_or_equal/2: PREDICATE
No further documentation available for this predicate.

nf_identical_abstract/2: PREDICATE
No further documentation available for this predicate.

nf_abs_sort/2: PREDICATE
No further documentation available for this predicate.

nf_call_to_success_fact/9: PREDICATE
No further documentation available for this predicate.

nf_split_combined_domain/3: PREDICATE
No further documentation available for this predicate.

nf_special_builtin/5: PREDICATE
No further documentation available for this predicate.

nf_combined_special_builtin0/2: PREDICATE
No further documentation available for this predicate.

nf_success_builtin/6: PREDICATE
No further documentation available for this predicate.

nf_input_interface/4: PREDICATE
No further documentation available for this predicate.

nf_input_user_interface/5: PREDICATE
No further documentation available for this predicate.

nf_asub_to_native/5: PREDICATE
No further documentation available for this predicate.

nf_unknown_call/4: PREDICATE
No further documentation available for this predicate.

nf_unknown_entry/3: PREDICATE

No further documentation available for this predicate.

nf_empty_entry/3: PREDICATE

No further documentation available for this predicate.

nf_dom_statistics/1: PREDICATE

No further documentation available for this predicate.

nf_obtain_info/4: PREDICATE

No further documentation available for this predicate.

nf_par_asub/2: REGTYPE

`nf_par_asub(NfTyp,ASub)`

`ASub` is an abstract substitution term used in the combined domain `nf`. It contains types, modes and nonfailure information of type `NfTyp`.

Usage: `nf_par_asub(NfTyp,ASub)`

`ASub` is an abstract substitution term used in the combined domain `nf`. It contains types, modes and nonfailure information of type `NfTyp`.

Meta-predicate with arguments: `nf_par_asub(pred(1),?)`.

nf_asub/1: REGTYPE

`nf_asub(ASub)`

`ASub` is an abstract substitution term used in the combined domain `nf`. It contains types, modes and nonfailure information.

Usage: `nf_asub(ASub)`

`ASub` is an abstract substitution term used in the combined domain `nf`. It contains types, modes and nonfailure information.

nf_pred_asub/1: REGTYPE

Usage: `nf_pred_asub(ASub)`

`ASub` is a compact representation for a set of abstract substitutions used in the combined domain `nf`. Each of the substitutions in that set has the same modes and types. However, the nonfailure information gathers together the clause tests of those abstract substitutions as a list, meaning the disjunction of all of them (named a `predicate test`, which is needed for performing the `covering check`).

nf_pred_asub_sl/1: REGTYPE

A regular type, defined as follows:

```
nf_pred_asub_sl([Asub]) :-
    nf_pred_asub(Asub).
```

asub/4: PREDICATE
No further documentation available for this predicate.

nf_collect_auxinfo_asub/3: PREDICATE
No further documentation available for this predicate.

nf_rename_auxinfo_asub/3: PREDICATE
No further documentation available for this predicate.

20.3 Documentation on multifiles

aidomain/1: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.init_abstract_domain/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.amgu/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_two_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_entry/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.exit_to_prime/8: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.project/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widencall/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.needs/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widen/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_lub/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_lub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered_gfp/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.identical_abstract/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_sort/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.extend/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.less_or_equal/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.eliminate_equivalent/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_subset/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_fact/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.special_builtin/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.combined_special_builtin0/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.body_succ_builtin/9: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.split_combined_domain/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.obtain_info/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_interface/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_user_interface/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.asub_to_native/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.concrete/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_call/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.empty_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.part_conc/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.multi_part_conc/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.collect_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.rename_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.dom_statistics/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.contains_parameters/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

20.4 Documentation on imports

This module has the following direct dependencies:

– *Application modules:*

`preprocess_flags`, `domains`, `eterms`, `sharefree`, `nfabs`, `infer_dom`.

– *System library modules:*

`sets`, `sort`, `idlists`, `lists`.

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `regtypes`, `basicmodes`, `hiord`, `aidomain`.

21 Interval Domain

Author(s): Isabel Garcia-Contreras, Jose F. Morales.

Stability: [**devel**] Currently the subject of active development and/or research. Functionality may be limited and API and/or functionality may change without warning or deprecation period. Not recommended yet for use in production.

A simple *intervals* abstract domain (non relational) derived from `nonrel_base.pl`.

This domain only uses closed intervals as abstractions, over-approximating the necessary builtins.

21.1 Usage and interface

- **Library usage:**

```
:- use_module(domain(nonrel_intervals)).
```

21.2 Documentation on multifiles

aidomain/1: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

aidom.init_abstract_domain/2: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

aidom.amgu/5: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_asub/4: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_two_asub/4: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_entry/10: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

aidom.exit_to_prime/8: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.project/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widencall/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.needs/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widen/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_lub/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_lub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered_gfp/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.identical_abstract/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_sort/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.extend/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.less_or_equal/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.eliminate_equivalent/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_subset/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_fact/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.special_builtin/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.combined_special_builtin0/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.body_succ_builtin/9: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.split_combined_domain/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.obtain_info/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_interface/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_user_interface/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.asub_to_native/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.concrete/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_call/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.empty_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.part_conc/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.multi_part_conc/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.collect_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.rename_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.dom_statistics/2: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

aidom.contains_parameters/2: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

21.3 Documentation on internals

nonrel_top/2: PREDICATE

Usage: `nonrel_top(AbsInt,X)`

`X` is the representation of "top" in the abstract domain.

(implement in derived domain)

nonrel_bot/2: PREDICATE

Usage: `nonrel_bot(AbsInt,X)`

`X` is the representation of "bot" in the abstract domain.

(implement in derived domain)

nonrel_var_elem/2: PREDICATE

Usage: `nonrel_var_elem(AbsInt,X)`

`X` is the abstraction of a free variable in the abstract domain.

(implement in derived domain)

nonrel_less_or_equal_elem/3: PREDICATE

Usage: `nonrel_less_or_equal_elem(AbsInt,E1,E2)`

Succeeds if `E1` is smaller than `E2`.

(implement in derived domain)

– *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`E1` is currently a term which is not a free variable. (`nonvar/1`)

`E2` is currently a term which is not a free variable. (`nonvar/1`)

nonrel_compute_glb_elem/4: PREDICATE

Usage: `nonrel_compute_glb_elem(AbsInt,E1,E2,EG)`

`EG` is the *greatest lower bound* of `E1` and `E2`.

(implement in derived domain)

– *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`E1` is currently a term which is not a free variable. (`nonvar/1`)

`E2` is currently a term which is not a free variable. (`nonvar/1`)

nonrel_compute_lub_elem/4: PREDICATE

Usage: `nonrel_compute_lub_elem(AbsInt,E1,E2,EL)`

`EL` is the *least upper bound* of `E1` and `E2`.

(implement in derived domain)

– *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`E1` is currently a term which is not a free variable. (`nonvar/1`)

`E2` is currently a term which is not a free variable. (`nonvar/1`)

nonrel_widen_elem/4: PREDICATE

Usage: `nonrel_widen_elem(AbsInt,E1,E2,EW)`

`EW` is the *widening* of `E1` and `E2`.

(implement in derived domain)

– *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`E1` is currently a term which is not a free variable. (`nonvar/1`)

`E2` is currently a term which is not a free variable. (`nonvar/1`)

nonrel_amgu/5: PREDICATE

Usage: `nonrel_amgu(AbsInt,Term1,Term2,ASub0,NASub)`

`NASub` is the abstract unification of `Term1` and `Term2`, with `ASub0` an abstract substitution that represents the state of both terms.

(implement in derived domain)

– *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`Term1` is currently a term which is not a free variable. (`nonvar/1`)

`Term2` is currently a term which is not a free variable. (`nonvar/1`)

`ASub0` is currently a term which is not a free variable. (`nonvar/1`)

`NASub` is a free variable. (`var/1`)

nonrel_unknown_entry/4: PREDICATE

Usage: `nonrel_unknown_entry(AbsInt,Sg,Vars,Call)`

Gives the "top" value for a given set of variables `Vars`, resulting in abstract constraint `Call`.

– *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable.	(`nonvar/1`)
`Sg` is currently a term which is not a free variable.	(`nonvar/1`)
`Vars` is currently a term which is not a free variable.	(`nonvar/1`)
`Call` is a free variable.	(`var/1`)
`AbsInt` is an atom.	(`atm/1`)
`Sg` is a term which represents a goal, i.e., an atom or a structure.	(`cgoal/1`)
`Vars` is a list.	(`list/1`)
`Call` is any term.	(`term/1`)

nonrel_abs_sort/2: PREDICATE

Usage: `nonrel_abs_sort(Asub,Asub_s)`

It sorts the set of `X`/`Values` in `Asub` obtaining `Asub_s`

– *The following properties should hold at call time:*

`Asub` is currently a term which is not a free variable.	(`nonvar/1`)
`Asub_s` is a free variable.	(`var/1`)
`Asub` is any term.	(`term/1`)
`Asub_s` is any term.	(`term/1`)

nonrel_project/5: PREDICATE

Usage: `nonrel_project(Sg,Vars,HvFv_u,ASub,Proj)`

`Proj` is the result of eliminating from `ASub` all `X`/`Value` such that `X` is not in `Vars`

– *The following properties should hold at call time:*

`Sg` is currently a term which is not a free variable.	(`nonvar/1`)
`Vars` is currently a term which is not a free variable.	(`nonvar/1`)
`HvFv_u` is currently a term which is not a free variable.	(`nonvar/1`)
`ASub` is currently a term which is not a free variable.	(`nonvar/1`)
`Proj` is a free variable.	(`var/1`)
`Sg` is any term.	(`term/1`)
`Vars` is a list.	(`list/1`)
`HvFv_u` is a list.	(`list/1`)
`ASub` is any term.	(`term/1`)
`Proj` is any term.	(`term/1`)

nonrel_call_to_entry/10: PREDICATE

Usage:
`nonrel_call_to_entry(AbsInt,Sv,Sg,Hv,Head,K,Fv,Proj,Entry,ExtraInfo)`

It obtains the abstract substitution `Entry` which results from adding the abstraction of `Sg` = `Head` to `Proj`, later projecting the resulting substitution onto `Hv`.

In the general case, the steps are:

- Add to `Proj` the variables of `Hv` with a "top" value.
- Perform the abstract unification of `Sg` and `Head`.
- Add to the unification the variables of `Fv` with a "top" value.
- Project to the variables in `Hv` and `Fv`.

– *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable.	(`nonvar/1`)
`Sv` is currently a term which is not a free variable.	(`nonvar/1`)
`Sg` is currently a term which is not a free variable.	(`nonvar/1`)
`Hv` is currently a term which is not a free variable.	(`nonvar/1`)
`Head` is currently a term which is not a free variable.	(`nonvar/1`)
`K` is currently a term which is not a free variable.	(`nonvar/1`)
`Fv` is currently a term which is not a free variable.	(`nonvar/1`)
`Proj` is currently a term which is not a free variable.	(`nonvar/1`)
`Entry` is a free variable.	(`var/1`)
`ExtraInfo` is a free variable.	(`var/1`)
`AbsInt` is an atom.	(`atm/1`)
`Sv` is a list.	(`list/1`)
`Sg` is a term which represents a goal, i.e., an atom or a structure.	(`cgoal/1`)
`Hv` is a list.	(`list/1`)
`Head` is a term which represents a goal, i.e., an atom or a structure.	(`cgoal/1`)
`K` is any term.	(`term/1`)
`Fv` is a list.	(`list/1`)
`Proj` is any term.	(`term/1`)
`Entry` is any term.	(`term/1`)
`ExtraInfo` is any term.	(`term/1`)

nonrel_exit_to_prime/8: PREDICATE

Usage: `nonrel_exit_to_prime(AbsInt,Sg,Hv,Head,Sv,Exit,ExtraInfo,Prime)`

– *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable.	(`nonvar/1`)
`Sg` is currently a term which is not a free variable.	(`nonvar/1`)
`Hv` is currently a term which is not a free variable.	(`nonvar/1`)
`Head` is currently a term which is not a free variable.	(`nonvar/1`)
`Sv` is currently a term which is not a free variable.	(`nonvar/1`)
`Exit` is currently a term which is not a free variable.	(`nonvar/1`)
`ExtraInfo` is a free variable.	(`var/1`)
`Prime` is a free variable.	(`var/1`)
`AbsInt` is an atom.	(`atm/1`)
`Sg` is a list.	(`list/1`)
`Hv` is a list.	(`list/1`)
`Head` is a term which represents a goal, i.e., an atom or a structure.	(`cgoal/1`)
`Sv` is a term which represents a goal, i.e., an atom or a structure.	(`cgoal/1`)
`Exit` is any term.	(`term/1`)
`ExtraInfo` is any term.	(`term/1`)
`Prime` is any term.	(`term/1`)

nonrel_compute_lub/3: PREDICATE

Usage: `nonrel_compute_lub(AbsInt,ListASub,Lub)`

`Lub` is the *least upper bound* of the list of abstract substitutions `ListASub`.

– *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable.	(`nonvar/1`)
`ListASub` is currently a term which is not a free variable.	(`nonvar/1`)
`Lub` is a free variable.	(`var/1`)
`AbsInt` is an atom.	(`atm/1`)
`ListASub` is a list.	(`list/1`)
`Lub` is any term.	(`term/1`)

nonrel_extend/6: PREDICATE

Usage: `nonrel_extend(AbsInt,Sg,Prime,Sv,Call,Succ)`

– *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable.	(`nonvar/1`)
`Sg` is currently a term which is not a free variable.	(`nonvar/1`)
`Prime` is currently a term which is not a free variable.	(`nonvar/1`)
`Call` is currently a term which is not a free variable.	(`nonvar/1`)
`Succ` is a free variable.	(`var/1`)
`AbsInt` is an atom.	(`atm/1`)
`Sg` is any term.	(`term/1`)
`Prime` is any term.	(`term/1`)
`Sv` is a list.	(`list/1`)
`Call` is any term.	(`term/1`)
`Succ` is any term.	(`term/1`)

nonrel_call_to_success_fact/10: PREDICATE

Usage:
`nonrel_call_to_success_fact(AbsInt,Sg,Hv,Head,K,Sv,Call,Proj,Prime,Succ)`

Specialized version of `call_to_entry/9` + `exit_to_prime/7` + `extend/4` for facts

– *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable.	(`nonvar/1`)
`Sg` is currently a term which is not a free variable.	(`nonvar/1`)
`Hv` is currently a term which is not a free variable.	(`nonvar/1`)
`Head` is currently a term which is not a free variable.	(`nonvar/1`)
`K` is currently a term which is not a free variable.	(`nonvar/1`)
`Sv` is currently a term which is not a free variable.	(`nonvar/1`)
`Call` is currently a term which is not a free variable.	(`nonvar/1`)
`Proj` is currently a term which is not a free variable.	(`nonvar/1`)
`Prime` is a free variable.	(`var/1`)
`Succ` is a free variable.	(`var/1`)
`AbsInt` is an atom.	(`atm/1`)

`Sg` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)
`Hv` is a list. (`list/1`)
`Head` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)
`K` is a list. (`list/1`)
`Sv` is any term. (`term/1`)
`Call` is any term. (`term/1`)
`Proj` is any term. (`term/1`)
`Prime` is any term. (`term/1`)
`Succ` is any term. (`term/1`)

nonrel_special_builtin/6: PREDICATE

Usage: `nonrel_special_builtin(AbsInt,SgKey,Sg,Subgoal,Type,Condvars)`

This predicate needs to be implemented by the user.

– *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)
`SgKey` is currently a term which is not a free variable. (`nonvar/1`)
`Sg` is currently a term which is not a free variable. (`nonvar/1`)
`Subgoal` is currently a term which is not a free variable. (`nonvar/1`)
`Type` is a free variable. (`var/1`)
`Condvars` is a free variable. (`var/1`)
`AbsInt` is an atom. (`atm/1`)
`SgKey` is a predicate name. (`predname/1`)
`Sg` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)
`Subgoal` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)
`Type` is an atom. (`atm/1`)
`Condvars` is any term. (`term/1`)

nonrel_success_builtin/7: PREDICATE

Usage: `nonrel_success_builtin(AbsInt,Sv_uns,Type,Condv,HvFv_u,Call,Succ)`

Obtains the success for some particular builtins.

– *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)
`Sv_uns` is currently a term which is not a free variable. (`nonvar/1`)
`Type` is currently a term which is not a free variable. (`nonvar/1`)
`Condv` is currently a term which is not a free variable. (`nonvar/1`)
`HvFv_u` is currently a term which is not a free variable. (`nonvar/1`)
`Call` is currently a term which is not a free variable. (`nonvar/1`)
`Succ` is a free variable. (`var/1`)
`AbsInt` is an atom. (`atm/1`)
`Sv_uns` is any term. (`term/1`)

`Type` is an atom. (`atm/1`)
`Condv` is any term. (`term/1`)
`HvFv_u` is any term. (`term/1`)
`Call` is any term. (`term/1`)
`Succ` is any term. (`term/1`)

nonrel_call_to_success_builtin/7: PREDICATE

Usage: `nonrel_call_to_success_builtin(AbsInt,SgKey,Sg,Sv,Call,Proj,Succ)`

Handles those builtins for which computing `Proj` is easier than `Succ`. Currently only builtins `=/2` and `==/2` are implemented. More builtins can be added by the user.

– *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)
`SgKey` is currently a term which is not a free variable. (`nonvar/1`)
`Sg` is currently a term which is not a free variable. (`nonvar/1`)
`Sv` is currently a term which is not a free variable. (`nonvar/1`)
`Call` is currently a term which is not a free variable. (`nonvar/1`)
`Proj` is currently a term which is not a free variable. (`nonvar/1`)
`Succ` is a free variable. (`var/1`)
`AbsInt` is an atom. (`atm/1`)
`SgKey` is a predicate name. (`predname/1`)
`Sg` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)
`Sv` is a list. (`list/1`)
`Call` is any term. (`term/1`)
`Proj` is any term. (`term/1`)
`Succ` is any term. (`term/1`)

nonrel_input_user_interface/6: PREDICATE

Usage:
`nonrel_input_user_interface(AbsInt,InputUser,Qv,ASub,Sg,MaybeCallASub)`

Obtains the abstract substitution from the native properties found in the user supplied info.

– *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)
`InputUser` is currently a term which is not a free variable. (`nonvar/1`)
`Qv` is currently a term which is not a free variable. (`nonvar/1`)
`ASub` is currently a term which is not a free variable. (`nonvar/1`)
`Sg` is currently a term which is not a free variable. (`nonvar/1`)
`MaybeCallASub` is currently a term which is not a free variable. (`nonvar/1`)

nonrel_input_interface/5: PREDICATE

Usage: `nonrel_input_interface(AbsInt,Prop,Kind,Struc0,Struc1)`

Adds native property `Prop` to the structure accumulating the properties relevant to this domain.

– *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)
`Prop` is currently a term which is not a free variable. (`nonvar/1`)
`Struc0` is currently a term which is not a free variable. (`nonvar/1`)
`Struc1` is currently a term which is not a free variable. (`nonvar/1`)

nonrel_asub_to_native/6: PREDICATE

Usage: `nonrel_asub_to_native(AbsInt,ASub,Qv,OutFlag,ASub_user,Comps)`

It translates an internal abstract constraint into something friendly for the user.

– *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)
`ASub` is currently a term which is not a free variable. (`nonvar/1`)
`Qv` is currently a term which is not a free variable. (`nonvar/1`)
`OutFlag` is currently a term which is not a free variable. (`nonvar/1`)
`ASub_user` is a free variable. (`var/1`)
`Comps` is a free variable. (`var/1`)
`AbsInt` is an atom. (`atm/1`)
`ASub` is any term. (`term/1`)
`Qv` is any term. (`term/1`)
`OutFlag` is any term. (`term/1`)
`ASub_user` is any term. (`term/1`)
`Comps` is any term. (`term/1`)

nonrel_unknown_call/5: PREDICATE

Usage: `nonrel_unknown_call(AbsInt,Sg,Vars,Call,Succ)`

Gives the "top" value for the variables involved in a literal whose definition is not present, and adds this top value to `Call`

– *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)
`Sg` is currently a term which is not a free variable. (`nonvar/1`)
`Vars` is currently a term which is not a free variable. (`nonvar/1`)
`Call` is currently a term which is not a free variable. (`nonvar/1`)
`Succ` is a free variable. (`var/1`)
`AbsInt` is an atom. (`atm/1`)
`Sg` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)
`Vars` is a list. (`list/1`)
`Call` is any term. (`term/1`)
`Succ` is any term. (`term/1`)

nonrel_less_or_equal/3: PREDICATE

Usage: `nonrel_less_or_equal(AbsInt,ASub0,ASub1)`

Succeeds if `ASub1` is more general or equal to `ASub0`. it is assumed the two abstract substitutions are defined on the same variables

– *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`ASub0` is currently a term which is not a free variable. (`nonvar/1`)

`ASub1` is currently a term which is not a free variable. (`nonvar/1`)

`AbsInt` is an atom. (`atm/1`)

`ASub0` is any term. (`term/1`)

`ASub1` is any term. (`term/1`)

nonrel_glb/4: PREDICATE

Usage: `nonrel_glb(AbsInt,ASub0,ASub1,Glb)`

`Glb` is the great lower bound of `ASub0` and `ASub1`, two substitutions that describe the same set of variables.

– *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`ASub0` is currently a term which is not a free variable. (`nonvar/1`)

`ASub1` is currently a term which is not a free variable. (`nonvar/1`)

`Glb` is a free variable. (`var/1`)

`AbsInt` is an atom. (`atm/1`)

`ASub0` is a list. (`list/1`)

`ASub1` is a list. (`list/1`)

`Glb` is a free variable. (`var/1`)

nonrel_identical_abstract/2: PREDICATE

Usage: `nonrel_identical_abstract(ASub1,ASub2)`

– *The following properties should hold at call time:*

`ASub1` is currently a term which is not a free variable. (`nonvar/1`)

`ASub2` is currently a term which is not a free variable. (`nonvar/1`)

nonrel_widen/4: PREDICATE

Usage: `nonrel_widen(AbsInt,Asub1,ASub2,WAsub)`

– *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`Asub1` is currently a term which is not a free variable. (`nonvar/1`)

`ASub2` is currently a term which is not a free variable. (`nonvar/1`)

`WAsub` is a free variable. (`var/1`)

nonrel_widencall/4: PREDICATE

Usage: `nonrel_widencall(AbsInt,Asub1,ASub2,WAsub)`

– *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`Asub1` is currently a term which is not a free variable. (`nonvar/1`)

`ASub2` is currently a term which is not a free variable. (`nonvar/1`)

`WAsub` is a free variable. (`var/1`)

21.4 Documentation on imports

This module has the following direct dependencies:

– *Application modules:*

`preprocess_flags`, `domains`.

– *System library modules:*

`sets`, `sort`, `terms_check`, `terms_vars`.

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `regtypes`, `basicmodes`, `aidomain`.

22 PD domain

This abstract domain is the domain with one value, top. PD stands for Partial Deduction.

22.1 Usage and interface

- **Library usage:**
  `:- use_module(domain(pd)).`

22.2 Documentation on multifiles

aidomain/1: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.init_abstract_domain/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.amgu/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_two_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_entry/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.exit_to_prime/8: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.project/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widencall/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.needs/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widen/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_lub/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_lub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered_gfp/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.identical_abstract/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_sort/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.extend/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.less_or_equal/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.eliminate_equivalent/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_subset/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_fact/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.special_builtin/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.combined_special_builtin0/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.body_succ_builtin/9: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.split_combined_domain/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.obtain_info/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_interface/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_user_interface/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.asub_to_native/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.concrete/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_call/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.empty_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.part_conc/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.multi_part_conc/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.collect_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.rename_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.dom_statistics/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.contains_parameters/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

22.3 Documentation on imports

This module has the following direct dependencies:

– *Application modules:*

`sharefree`, `preprocess_flags`, `domains`.

– *System library modules:*

`sets`, `sort`.

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `regtypes`, `basicmodes`, `aidomain`.

23 PD domain with bottom

This abstract domain is the domain with only two values, top and bottom. This simple improvement over the `pd` domain provides improvements, both in specialization time and quality of the specialized program if abstract specialization is then performed. PDB stands for Partial Deduction + Bottom.

23.1 Usage and interface

- **Library usage:**
  `:- use_module(domain(pdb)).`

23.2 Documentation on multifiles

aidomain/1: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.init_abstract_domain/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.amgu/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_two_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_entry/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.exit_to_prime/8: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.project/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widencall/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.needs/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widen/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_lub/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_lub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered_gfp/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.identical_abstract/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_sort/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.extend/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.less_or_equal/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.eliminate_equivalent/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_subset/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_fact/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.special_builtin/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.combined_special_builtin0/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.body_succ_builtin/9: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.split_combined_domain/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.obtain_info/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_interface/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_user_interface/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.asub_to_native/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.concrete/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_call/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.empty_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.part_conc/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.multi_part_conc/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.collect_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.rename_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.dom_statistics/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.contains_parameters/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

23.3 Documentation on imports

This module has the following direct dependencies:

– *Application modules:*

`sharefree`, `preprocess_flags`, `domains`.

– *System library modules:*

`sets`, `sort`.

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `regtypes`, `basicmodes`, `aidomain`.

24 polyhedra (library)

24.1 Usage and interface

- **Library usage:**
  `:- use_module(domain(polyhedra)).`
- **Exports:**
  - *Predicates:*
    `polyhedra_initialize/0`, `polyhedra_finalize/0`, `less_or_equal/2`, `input_user_interface/5`.
  - *Multifiles:*
    `aidomain/1`, `aidom.init_abstract_domain/2`, `aidom.amgu/5`, `aidom.augment_asub/4`, `aidom.augment_two_asub/4`, `aidom.call_to_entry/10`, `aidom.exit_to_prime/8`, `aidom.project/6`, `aidom.widencall/4`, `aidom.needs/2`, `aidom.widen/4`, `aidom.compute_lub/3`, `aidom.compute_clauses_lub/4`, `aidom.compute_clauses_glb/4`, `aidom.fixpoint_covered/3`, `aidom.fixpoint_covered_gfp/3`, `aidom.identical_abstract/3`, `aidom.abs_sort/3`, `aidom.extend/6`, `aidom.less_or_equal/3`, `aidom.glb/4`, `aidom.eliminate_equivalent/3`, `aidom.abs_subset/3`, `aidom.call_to_success_fact/10`, `aidom.special_builtin/6`, `aidom.combined_special_builtin0/3`, `aidom.body_succ_builtin/9`, `aidom.split_combined_domain/4`, `aidom.success_builtin/7`, `aidom.call_to_success_builtin/7`, `aidom.obtain_info/5`, `aidom.input_interface/5`, `aidom.input_user_interface/6`, `aidom.asub_to_native/6`, `aidom.concrete/4`, `aidom.unknown_call/5`, `aidom.unknown_entry/4`, `aidom.empty_entry/4`, `aidom.part_conc/5`, `aidom.multi_part_conc/4`, `aidom.collect_auxinfo_asub/4`, `aidom.rename_auxinfo_asub/4`, `aidom.dom_statistics/2`, `aidom.contains_parameters/2`.

24.2 Documentation on exports

polyhedra_initialize/0: PREDICATE

No further documentation available for this predicate.

polyhedra_finalize/0: PREDICATE

No further documentation available for this predicate.

less_or_equal/2: PREDICATE

No further documentation available for this predicate.

input_user_interface/5: PREDICATE

No further documentation available for this predicate.

24.3 Documentation on multifiles

aidomain/1: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.init_abstract_domain/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.amgu/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_two_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_entry/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.exit_to_prime/8: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.project/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widencall/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.needs/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widen/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_lub/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_lub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered_gfp/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.identical_abstract/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_sort/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.extend/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.less_or_equal/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.eliminate_equivalent/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_subset/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_fact/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.special_builtin/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.combined_special_builtin0/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.body_succ_builtin/9: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.split_combined_domain/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.obtain_info/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_interface/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_user_interface/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.asub_to_native/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.concrete/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_call/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.empty_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.part_conc/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.multi_part_conc/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.collect_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.rename_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.dom_statistics/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.contains_parameters/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

24.4 Documentation on imports

This module has the following direct dependencies:

- *Application modules:*
  `ppl_interface`, `preprocess_flags`, `domains`.
- *System library modules:*
  `datafacts_rt`, `sets`, `lists`, `streams`, `write`, `sort`, `terms_vars`.
- *Internal (engine) modules:*
  `term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `runtime_control`.
- *Packages:*
  `prelude`, `initial`, `condcomp`, `datafacts`, `aidomain`.

25 ptypes: types with topological class widening (abstract domain)

Author(s): Claudio Vaucheret, Francisco Bueno, Ciao Development Team.

This module implements a types domain (based on `termsd.pl`) using the topological clash widening operator (`hentenwid/3`).

25.1 Usage and interface

- **Library usage:**

```
:- use_module(domain(ptypes)).
```

25.2 Documentation on multifiles

aidomain/1: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

aidom.init_abstract_domain/2: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

aidom.amgu/5: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_asub/4: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_two_asub/4: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_entry/10: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

aidom.exit_to_prime/8: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

aidom.project/6: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

aidom.widencall/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.needs/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widen/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_lub/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_lub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered_gfp/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.identical_abstract/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_sort/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.extend/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.less_or_equal/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.eliminate_equivalent/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_subset/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_fact/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.special_builtin/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.combined_special_builtin0/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.body_succ_builtin/9: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.split_combined_domain/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.obtain_info/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_interface/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_user_interface/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.asub_to_native/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.concrete/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_call/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.empty_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.part_conc/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.multi_part_conc/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.collect_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.rename_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.dom_statistics/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.contains_parameters/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

25.3 Documentation on imports

This module has the following direct dependencies:

– *Application modules:*
`preprocess_flags`, `termsd`, `domains`.

– *System library modules:*
`typeslib`, `sets`, `sort`.

– *Internal (engine) modules:*
`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`.

– *Packages:*
`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `regtypes`, `basicmodes`, `aidomain`.

26 sharing+freeness (abstract domain)

Author(s): Maria Garcia de la Banda, Francisco Bueno.

26.1 Usage and interface

- **Library usage:**
  `:- use_module(domain(sharefree)).`
- **Exports:**
  - *Predicates:*
    needs/1, project_freeness/3, call_to_entry/9, exit_to_prime/7, abs_sort/2, compute_lub/2, compute_lub_el/3, compute_lub_sh/3, extend/5, call_to_success_fact/9, call_to_prime_fact/6, unknown_entry/3, empty_entry/3, asub_to_native/5, obtain_info/4, obtain_info/3, special_builtin/5, success_builtin/6, call_to_success_builtin/6, take_coupled/3, split_coupled/4, all_terms_identical/2, update_lambda_sf/5, update_lambda_non_free/5, partition_sf/4, prune/5, prune/4, covering/3, eliminate_non_element/4, product/8, insert_each/3, obtain_freeness/2, obtain_prime_var_var/3, sh_free_vars_compatible/2, make_dependence/5, unknown_call/4, values_equal/3, values_differ/3, change_values/4, change_values_if_not_g/4, change_values_if_f/4, member_value_freeness_differ/3, project_freeness_n/3, propagate_non_freeness/5, add_environment_vars/3.
  - *Multifiles:*
    aidomain/1, aidom.init_abstract_domain/2, aidom.amgu/5, aidom.augment_asub/4, aidom.augment_two_asub/4, aidom.call_to_entry/10, aidom.exit_to_prime/8, aidom.project/6, aidom.widencall/4, aidom.needs/2, aidom.widen/4, aidom.compute_lub/3, aidom.compute_clauses_lub/4, aidom.compute_clauses_glb/4, aidom.fixpoint_covered/3, aidom.fixpoint_covered_gfp/3, aidom.identical_abstract/3, aidom.abs_sort/3, aidom.extend/6, aidom.less_or_equal/3, aidom.glb/4, aidom.eliminate_equivalent/3, aidom.abs_subset/3, aidom.call_to_success_fact/10, aidom.special_builtin/6, aidom.combined_special_
    builtin0/3, aidom.body_succ_builtin/9, aidom.split_combined_domain/4, aidom.success_builtin/7, aidom.call_to_success_builtin/7, aidom.obtain_info/5, aidom.input_interface/5, aidom.input_user_interface/6, aidom.asub_to_native/6, aidom.concrete/4, aidom.unknown_call/5, aidom.unknown_entry/4, aidom.empty_entry/4, aidom.part_conc/5, aidom.multi_part_conc/4, aidom.collect_auxinfo_asub/4, aidom.rename_auxinfo_asub/4, aidom.dom_statistics/2, aidom.contains_parameters/2.

26.2 Documentation on exports

needs/1: PREDICATE

No further documentation available for this predicate.

project/5: PREDICATE

No further documentation available for this predicate.

project_freeness/3: PREDICATE
No further documentation available for this predicate.

call_to_entry/9: PREDICATE
No further documentation available for this predicate.

exit_to_prime/7: PREDICATE
No further documentation available for this predicate.

abs_sort/2: PREDICATE
No further documentation available for this predicate.

compute_lub/2: PREDICATE
No further documentation available for this predicate.

compute_lub_el/3: PREDICATE
No further documentation available for this predicate.

compute_lub_sh/3: PREDICATE
No further documentation available for this predicate.

glb/3: PREDICATE
No further documentation available for this predicate.

extend/5: PREDICATE
No further documentation available for this predicate.

call_to_success_fact/9: PREDICATE
No further documentation available for this predicate.

call_to_prime_fact/6: PREDICATE
No further documentation available for this predicate.

unknown_entry/3: PREDICATE
No further documentation available for this predicate.

empty_entry/3: PREDICATE

Usage: `empty_entry(Sg,Vars,Entry)`

Gives the "empty" value in this domain for a given set of variables `Vars`, resulting in the abstract substitution `Entry`. I.e., obtains the abstraction of a substitution in which all variables `Vars` are unbound: free and unaliased. In Sh is the list of singleton lists of variables and in Fr is X/f forall X in the set of variables

– *The following properties should hold at call time:*

`Sg` is currently a term which is not a free variable. (`nonvar/1`)

`Vars` is currently a term which is not a free variable. (`nonvar/1`)

`Entry` is a free variable. (`var/1`)

`Sg` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)

`Vars` is a list. (`list/1`)

`Entry` is an abstract substitution (`absu/1`)

input_user_interface/5: PREDICATE

No further documentation available for this predicate.

input_interface/4: PREDICATE

No further documentation available for this predicate.

asub_to_native/5: PREDICATE

No further documentation available for this predicate.

obtain_info/4: PREDICATE

No further documentation available for this predicate.

obtain_info/3: PREDICATE

No further documentation available for this predicate.

less_or_equal/2: PREDICATE

No further documentation available for this predicate.

special_builtin/5: PREDICATE

No further documentation available for this predicate.

success_builtin/6: PREDICATE

No further documentation available for this predicate.

call_to_success_builtin/6: PREDICATE
No further documentation available for this predicate.

take_coupled/3: PREDICATE
No further documentation available for this predicate.

split_coupled/4: PREDICATE
No further documentation available for this predicate.

all_terms_identical/2: PREDICATE
No further documentation available for this predicate.

update_lambda_sf/5: PREDICATE
No further documentation available for this predicate.

update_lambda_non_free/5: PREDICATE
No further documentation available for this predicate.

partition_sf/4: PREDICATE
No further documentation available for this predicate.

prune/5: PREDICATE
No further documentation available for this predicate.

prune/4: PREDICATE
No further documentation available for this predicate.

covering/3: PREDICATE
No further documentation available for this predicate.

eliminate_non_element/4: PREDICATE
No further documentation available for this predicate.

product/8: PREDICATE
No further documentation available for this predicate.

insert_each/3: PREDICATE
No further documentation available for this predicate.

obtain_freeness/2: PREDICATE
No further documentation available for this predicate.

obtain_prime_var_var/3: PREDICATE
No further documentation available for this predicate.

sh_free_vars_compatible/2: PREDICATE
No further documentation available for this predicate.

make_dependence/5: PREDICATE
No further documentation available for this predicate.

unknown_call/4: PREDICATE
No further documentation available for this predicate.

values_equal/3: PREDICATE
No further documentation available for this predicate.

values_differ/3: PREDICATE
No further documentation available for this predicate.

change_values/4: PREDICATE
No further documentation available for this predicate.

change_values_if_not_g/4: PREDICATE
No further documentation available for this predicate.

change_values_if_f/4: PREDICATE
No further documentation available for this predicate.

member_value_freeness_differ/3: PREDICATE
No further documentation available for this predicate.

project_freeness_n/3: PREDICATE
No further documentation available for this predicate.

propagate_non_freeness/5: PREDICATE
No further documentation available for this predicate.

add_environment_vars/3: PREDICATE
No further documentation available for this predicate.

26.3 Documentation on multifiles

aidomain/1: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.init_abstract_domain/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.amgu/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_two_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_entry/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.exit_to_prime/8: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.project/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widencall/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.needs/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widen/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_lub/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_lub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered_gfp/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.identical_abstract/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_sort/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.extend/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.less_or_equal/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.eliminate_equivalent/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_subset/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_fact/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.special_builtin/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.combined_special_builtin0/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.body_succ_builtin/9: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.split_combined_domain/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.obtain_info/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_interface/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_user_interface/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.asub_to_native/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.concrete/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_call/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.empty_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.part_conc/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.multi_part_conc/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.collect_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.rename_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.dom_statistics/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.contains_parameters/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

26.4 Documentation on imports

This module has the following direct dependencies:

– *Application modules:*

`preprocess_flags`, `domains`, `sharefree_amgu`, `s_grshfr`, `share_aux`, `sharing`, `s_eqs`.

– *System library modules:*

`datafacts_rt`, `sets`, `sort`, `lists`, `lsets`, `terms_check`, `terms_vars`.

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`, `io_basic`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `regtypes`, `isomodes`, `datafacts`, `aidomain`.

27 amgu-based sharing+freeness domain

Author(s): Jorge Navas.

27.1 Usage and interface

- **Library usage:**
  `:- use_module(domain(sharefree_amgu)).`
- **Exports:**
  - *Predicates:*
    `call_to_entry/9`, `exit_to_prime/7`, `amgu/4`, `augment_asub0/3`, `call_to_success_fact/9`, `sharefree_delete_variables/3`, `call_to_prime_fact/6`.
  - *Multifiles:*
    `aidomain/1`, `aidom.init_abstract_domain/2`, `aidom.amgu/5`, `aidom.augment_asub/4`, `aidom.augment_two_asub/4`, `aidom.call_to_entry/10`, `aidom.exit_to_prime/8`, `aidom.project/6`, `aidom.widencall/4`, `aidom.needs/2`, `aidom.widen/4`, `aidom.compute_lub/3`, `aidom.compute_clauses_lub/4`, `aidom.compute_clauses_glb/4`, `aidom.fixpoint_covered/3`, `aidom.fixpoint_covered_gfp/3`, `aidom.identical_abstract/3`, `aidom.abs_sort/3`, `aidom.extend/6`, `aidom.less_or_equal/3`, `aidom.glb/4`, `aidom.eliminate_equivalent/3`, `aidom.abs_subset/3`, `aidom.call_to_success_fact/10`, `aidom.special_builtin/6`, `aidom.combined_special_builtin0/3`, `aidom.body_succ_builtin/9`, `aidom.split_combined_domain/4`, `aidom.success_builtin/7`, `aidom.call_to_success_builtin/7`, `aidom.obtain_info/5`, `aidom.input_interface/5`, `aidom.input_user_interface/6`, `aidom.asub_to_native/6`, `aidom.concrete/4`, `aidom.unknown_call/5`, `aidom.unknown_entry/4`, `aidom.empty_entry/4`, `aidom.part_conc/5`, `aidom.multi_part_conc/4`, `aidom.collect_auxinfo_asub/4`, `aidom.rename_auxinfo_asub/4`, `aidom.dom_statistics/2`, `aidom.contains_parameters/2`.

27.2 Documentation on exports

call_to_entry/9: PREDICATE
No further documentation available for this predicate.

exit_to_prime/7: PREDICATE
No further documentation available for this predicate.

amgu/4: PREDICATE
No further documentation available for this predicate.

augment_asub/3: PREDICATE
No further documentation available for this predicate.

augment_asub0/3: PREDICATE
No further documentation available for this predicate.

call_to_success_fact/9: PREDICATE
No further documentation available for this predicate.

sharefree_delete_variables/3: PREDICATE
No further documentation available for this predicate.

call_to_prime_fact/6: PREDICATE
No further documentation available for this predicate.

special_builtin/5: PREDICATE
No further documentation available for this predicate.

success_builtin/6: PREDICATE
No further documentation available for this predicate.

call_to_success_builtin/6: PREDICATE
No further documentation available for this predicate.

27.3 Documentation on multifiles

aidomain/1: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.init_abstract_domain/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.amgu/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_two_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_entry/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.exit_to_prime/8: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.project/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widencall/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.needs/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widen/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_lub/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_lub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered_gfp/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.identical_abstract/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_sort/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.extend/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.less_or_equal/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.eliminate_equivalent/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_subset/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_fact/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.special_builtin/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.combined_special_builtin0/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.body_succ_builtin/9: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.split_combined_domain/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.obtain_info/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_interface/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_user_interface/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.asub_to_native/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.concrete/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_call/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.empty_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.part_conc/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.multi_part_conc/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.collect_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.rename_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.dom_statistics/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.contains_parameters/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

27.4 Documentation on imports

This module has the following direct dependencies:

- *Application modules:*

  `sharefree`, `preprocess_flags`, `domains`, `share_amgu_sets`, `s_grshfr`, `share_aux`, `sharing`, `sharing_amgu`, `sharefree_amgu_aux`.
- *System library modules:*

  `sets`, `sort`, `terms_vars`, `lists`, `lsets`, `terms_check`.
- *Internal (engine) modules:*

  `term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`.
- *Packages:*

  `prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `isomodes`, `aidomain`.

28 CLIQUE-Sharing+Freeness domain

Author(s): Jorge Navas.

28.1 Usage and interface

- **Library usage:**
  `:- use_module(domain(sharefree_clique)).`
- **Exports:**
  - *Predicates:*
    `call_to_entry/9`, `exit_to_prime/7`, `identical_abstract/2`, `call_to_success_fact/9`, `compute_lub_el/3`, `unknown_call/4`, `empty_entry/3`.
  - *Multifiles:*
    `aidomain/1`, `aidom.init_abstract_domain/2`, `aidom.amgu/5`, `aidom.augment_asub/4`, `aidom.augment_two_asub/4`, `aidom.call_to_entry/10`, `aidom.exit_to_prime/8`, `aidom.project/6`, `aidom.widencall/4`, `aidom.needs/2`, `aidom.widen/4`, `aidom.compute_lub/3`, `aidom.compute_clauses_lub/4`, `aidom.compute_clauses_glb/4`, `aidom.fixpoint_covered/3`, `aidom.fixpoint_covered_gfp/3`, `aidom.identical_abstract/3`, `aidom.abs_sort/3`, `aidom.extend/6`, `aidom.less_or_equal/3`, `aidom.glb/4`, `aidom.eliminate_equivalent/3`, `aidom.abs_subset/3`, `aidom.call_to_success_fact/10`, `aidom.special_builtin/6`, `aidom.combined_special_builtin0/3`, `aidom.body_succ_builtin/9`, `aidom.split_combined_domain/4`, `aidom.success_builtin/7`, `aidom.call_to_success_builtin/7`, `aidom.obtain_info/5`, `aidom.input_interface/5`, `aidom.input_user_interface/6`, `aidom.asub_to_native/6`, `aidom.concrete/4`, `aidom.unknown_call/5`, `aidom.unknown_entry/4`, `aidom.empty_entry/4`, `aidom.part_conc/5`, `aidom.multi_part_conc/4`, `aidom.collect_auxinfo_asub/4`, `aidom.rename_auxinfo_asub/4`, `aidom.dom_statistics/2`, `aidom.contains_parameters/2`.

28.2 Documentation on exports

call_to_entry/9: PREDICATE

No further documentation available for this predicate.

exit_to_prime/7: PREDICATE

No further documentation available for this predicate.

extend/5: PREDICATE

No further documentation available for this predicate.

project/5: PREDICATE

No further documentation available for this predicate.

abs_sort/2: PREDICATE
No further documentation available for this predicate.

identical_abstract/2: PREDICATE
No further documentation available for this predicate.

less_or_equal/2: PREDICATE
No further documentation available for this predicate.

call_to_success_fact/9: PREDICATE
No further documentation available for this predicate.

compute_lub_el/3: PREDICATE
No further documentation available for this predicate.

glb/3: PREDICATE
No further documentation available for this predicate.

input_user_interface/5: PREDICATE
No further documentation available for this predicate.

input_interface/4: PREDICATE
No further documentation available for this predicate.

unknown_call/4: PREDICATE
No further documentation available for this predicate.

empty_entry/3: PREDICATE
No further documentation available for this predicate.

special_builtin/5: PREDICATE
No further documentation available for this predicate.

28.3 Documentation on multifiles

aidomain/1: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.init_abstract_domain/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.amgu/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_two_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_entry/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.exit_to_prime/8: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.project/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widencall/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.needs/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widen/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_lub/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_lub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered_gfp/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.identical_abstract/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_sort/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.extend/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.less_or_equal/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.eliminate_equivalent/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_subset/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_fact/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.special_builtin/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.combined_special_builtin0/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.body_succ_builtin/9: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.split_combined_domain/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.obtain_info/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_interface/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_user_interface/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.asub_to_native/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.concrete/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_call/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.empty_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.part_conc/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.multi_part_conc/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.collect_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.rename_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.dom_statistics/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.contains_parameters/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

28.4 Documentation on imports

This module has the following direct dependencies:

- *Application modules:*
  `sharefree`, `preprocess_flags`, `domains`, `share_amgu_sets`, `sharing_clique`, `share_clique_aux`, `s_grshfr`, `sharefree_amgu`, `sharefree_clique_aux`, `sharefree_amgu_aux`, `share_aux`.
- *System library modules:*
  `sets`, `sort`, `lsets`, `terms_check`, `lists`, `terms_vars`.
- *Internal (engine) modules:*
  `term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`.
- *Packages:*
  `prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `isomodes`, `aidomain`.

29 CLIQUE-Sharing+Freeness+Def domain

Author(s): Jorge Navas.

29.1 Usage and interface

- **Library usage:**
  `:- use_module(domain(sharefree_clique_def)).`

29.2 Documentation on multifiles

aidomain/1: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.init_abstract_domain/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.amgu/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_two_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_entry/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.exit_to_prime/8: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.project/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widencall/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.needs/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widen/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_lub/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_lub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered_gfp/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.identical_abstract/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_sort/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.extend/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.less_or_equal/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.eliminate_equivalent/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_subset/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_fact/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.special_builtin/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.combined_special_builtin0/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.body_succ_builtin/9: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.split_combined_domain/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.obtain_info/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_interface/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_user_interface/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.asub_to_native/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.concrete/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_call/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.empty_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.part_conc/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.multi_part_conc/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.collect_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.rename_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.dom_statistics/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.contains_parameters/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

29.3 Documentation on imports

This module has the following direct dependencies:

– *Application modules:*

`preprocess_flags`, `domains`, `s_grshfr`, `share_clique_aux`, `share_aux`, `sharefree_clique`, `def`.

– *System library modules:*

`sets`, `sort`, `messages`.

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `isomodes`, `aidomain`.

30 sharing+freeness+nonvar (abstract domain)

Author(s): Maria Garcia de la Banda.

30.1 Usage and interface

- **Library usage:**
  `:- use_module(domain(sharefree_non_var)).`

30.2 Documentation on multifiles

aidomain/1: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.init_abstract_domain/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.amgu/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_two_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_entry/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.exit_to_prime/8: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.project/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widencall/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.needs/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widen/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_lub/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_lub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered_gfp/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.identical_abstract/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_sort/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.extend/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.less_or_equal/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.eliminate_equivalent/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_subset/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_fact/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.special_builtin/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.combined_special_builtin0/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.body_succ_builtin/9: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.split_combined_domain/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.obtain_info/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_interface/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_user_interface/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.asub_to_native/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.concrete/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_call/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.empty_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.part_conc/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.multi_part_conc/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.collect_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.rename_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.dom_statistics/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.contains_parameters/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

30.3 Documentation on imports

This module has the following direct dependencies:

– *Application modules:*

`preprocess_flags`, `domains`, `sharefree`, `sharing`, `s_grshfr`, `s_eqs`, `share_aux`, `plai_errors`.

– *System library modules:*

`sets`, `sort`, `terms_vars`, `lists`, `lsets`, `terms_check`.

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `isomodes`, `aidomain`.

31 shareson (library)

31.1 Usage and interface

- **Library usage:**
  `:- use_module(domain(shareson)).`

31.2 Documentation on multifiles

aidomain/1: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.init_abstract_domain/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.amgu/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_two_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_entry/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.exit_to_prime/8: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.project/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widencall/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.needs/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widen/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_lub/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_lub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered_gfp/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.identical_abstract/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_sort/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.extend/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.less_or_equal/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.eliminate_equivalent/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_subset/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_fact/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.special_builtin/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.combined_special_builtin0/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.body_succ_builtin/9: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.split_combined_domain/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.obtain_info/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_interface/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_user_interface/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.asub_to_native/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.concrete/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_call/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.empty_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.part_conc/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.multi_part_conc/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.collect_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.rename_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.dom_statistics/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.contains_parameters/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

31.3 Documentation on imports

This module has the following direct dependencies:

– *Application modules:*
`preprocess_flags`, `domains`, `sharing`, `sondergaard`, `s_grshfr`, `share_aux`, `plai_errors`.

– *System library modules:*
`sets`, `sort`, `llists`, `lsets`, `terms_vars`.

– *Internal (engine) modules:*
`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`.

– *Packages:*
`prelude`, `initial`, `condcomp`, `aidomain`.

32 sharing (abstract domain)

Author(s): Kalyan Muthukumar, Maria Garcia de la Banda, Francisco Bueno.

32.1 Usage and interface

- **Library usage:**
  `:- use_module(domain(sharing)).`
- **Exports:**
  - *Predicates:*
    `project/5`, `project_share/3`, `call_to_entry/9`, `exit_to_prime/7`, `abs_sort/2`, `compute_lub/2`, `lub/3`, `glb/3`, `extend/5`, `call_to_success_fact/9`, `call_to_prime_fact/6`, `pos/4`, `script_p_star/3`, `script_p/3`, `unknown_entry/3`, `empty_entry/3`, `asub_to_native/5`, `input_user_interface/5`, `input_interface/4`, `unknown_call/4`, `less_or_equal/2`, `special_builtin/5`, `success_builtin/6`, `call_to_success_builtin/6`.
  - *Multifiles:*
    `aidomain/1`, `aidom.init_abstract_domain/2`, `aidom.amgu/5`, `aidom.augment_asub/4`, `aidom.augment_two_asub/4`, `aidom.call_to_entry/10`, `aidom.exit_to_prime/8`, `aidom.project/6`, `aidom.widencall/4`, `aidom.needs/2`, `aidom.widen/4`, `aidom.compute_lub/3`, `aidom.compute_clauses_lub/4`, `aidom.compute_clauses_glb/4`, `aidom.fixpoint_covered/3`, `aidom.fixpoint_covered_gfp/3`, `aidom.identical_abstract/3`, `aidom.abs_sort/3`, `aidom.extend/6`, `aidom.less_or_equal/3`, `aidom.glb/4`, `aidom.eliminate_equivalent/3`, `aidom.abs_subset/3`, `aidom.call_to_success_fact/10`, `aidom.special_builtin/6`, `aidom.combined_special_builtin0/3`, `aidom.body_succ_builtin/9`, `aidom.split_combined_domain/4`, `aidom.success_builtin/7`, `aidom.call_to_success_builtin/7`, `aidom.obtain_info/5`, `aidom.input_interface/5`, `aidom.input_user_interface/6`, `aidom.asub_to_native/6`, `aidom.concrete/4`, `aidom.unknown_call/5`, `aidom.unknown_entry/4`, `aidom.empty_entry/4`, `aidom.part_conc/5`, `aidom.multi_part_conc/4`, `aidom.collect_auxinfo_asub/4`, `aidom.rename_auxinfo_asub/4`, `aidom.dom_statistics/2`, `aidom.contains_parameters/2`.

32.2 Documentation on exports

project/5: PREDICATE

No further documentation available for this predicate.

project_share/3: PREDICATE

No further documentation available for this predicate.

call_to_entry/9: PREDICATE

No further documentation available for this predicate.

exit_to_prime/7: PREDICATE
No further documentation available for this predicate.

abs_sort/2: PREDICATE
No further documentation available for this predicate.

compute_lub/2: PREDICATE
No further documentation available for this predicate.

lub/3: PREDICATE
No further documentation available for this predicate.

glb/3: PREDICATE
No further documentation available for this predicate.

extend/5: PREDICATE
No further documentation available for this predicate.

call_to_success_fact/9: PREDICATE
No further documentation available for this predicate.

call_to_prime_fact/6: PREDICATE
No further documentation available for this predicate.

pos/4: PREDICATE
No further documentation available for this predicate.

script_p_star/3: PREDICATE
No further documentation available for this predicate.

script_p/3: PREDICATE
No further documentation available for this predicate.

unknown_entry/3: PREDICATE
No further documentation available for this predicate.

empty_entry/3: PREDICATE

Usage: `empty_entry(Sg,Vars,Entry)`

Gives the "empty" value in this domain for a given set of variables `Vars`, resulting in the abstract substitution `Entry`. I.e., obtains the abstraction of a substitution in which all variables `Vars` are unbound: free and unaliased. In this domain is the list of singleton lists of variables

– *The following properties should hold at call time:*

`Sg` is currently a term which is not a free variable.	(`nonvar/1`)
`Vars` is currently a term which is not a free variable.	(`nonvar/1`)
`Entry` is a free variable.	(`var/1`)
`Sg` is a term which represents a goal, i.e., an atom or a structure.	(`cgoal/1`)
`Vars` is a list.	(`list/1`)
`Entry` is an abstract substitution	(`absu/1`)

asub_to_native/5: PREDICATE

No further documentation available for this predicate.

input_user_interface/5: PREDICATE

No further documentation available for this predicate.

input_interface/4: PREDICATE

No further documentation available for this predicate.

unknown_call/4: PREDICATE

No further documentation available for this predicate.

less_or_equal/2: PREDICATE

No further documentation available for this predicate.

special_builtin/5: PREDICATE

No further documentation available for this predicate.

success_builtin/6: PREDICATE

No further documentation available for this predicate.

call_to_success_builtin/6: PREDICATE

No further documentation available for this predicate.

32.3 Documentation on multifiles

aidomain/1: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.init_abstract_domain/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.amgu/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_two_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_entry/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.exit_to_prime/8: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.project/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widencall/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.needs/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widen/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_lub/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_lub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered_gfp/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.identical_abstract/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_sort/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.extend/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.less_or_equal/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.eliminate_equivalent/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_subset/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_fact/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.special_builtin/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.combined_special_builtin0/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.body_succ_builtin/9: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.split_combined_domain/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.obtain_info/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_interface/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_user_interface/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.asub_to_native/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.concrete/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_call/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.empty_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.part_conc/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.multi_part_conc/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.collect_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.rename_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.dom_statistics/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.contains_parameters/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

32.4 Documentation on imports

This module has the following direct dependencies:

- *Application modules:*
  `preprocess_flags`, `domains`, `sharing_amgu`, `s_grshfr`, `eterms`, `share_aux`.
- *System library modules:*
  `sets`, `sort`, `lsets`, `terms_check`, `terms_vars`, `lists`, `typeslib`.
- *Internal (engine) modules:*
  `term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`.
- *Packages:*
  `prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `regtypes`, `isomodes`, `aidomain`.

33 amgu-based sharing domain

Author(s): Jorge Navas.

33.1 Usage and interface

- **Library usage:**
  `:- use_module(domain(sharing_amgu)).`
- **Exports:**
  - *Predicates:*
    `call_to_entry/9`, `augment_asub/3`, `augment_two_asub/3`.
  - *Multifiles:*
    `aidomain/1`, `aidom.init_abstract_domain/2`, `aidom.amgu/5`, `aidom.augment_asub/4`, `aidom.augment_two_asub/4`, `aidom.call_to_entry/10`, `aidom.exit_to_prime/8`, `aidom.project/6`, `aidom.widencall/4`, `aidom.needs/2`, `aidom.widen/4`, `aidom.compute_lub/3`, `aidom.compute_clauses_lub/4`, `aidom.compute_clauses_glb/4`, `aidom.fixpoint_covered/3`, `aidom.fixpoint_covered_gfp/3`, `aidom.identical_abstract/3`, `aidom.abs_sort/3`, `aidom.extend/6`, `aidom.less_or_equal/3`, `aidom.glb/4`, `aidom.eliminate_equivalent/3`, `aidom.abs_subset/3`, `aidom.call_to_success_fact/10`, `aidom.special_builtin/6`, `aidom.combined_special_builtin0/3`, `aidom.body_succ_builtin/9`, `aidom.split_combined_domain/4`, `aidom.success_builtin/7`, `aidom.call_to_success_builtin/7`, `aidom.obtain_info/5`, `aidom.input_interface/5`, `aidom.input_user_interface/6`, `aidom.asub_to_native/6`, `aidom.concrete/4`, `aidom.unknown_call/5`, `aidom.unknown_entry/4`, `aidom.empty_entry/4`, `aidom.part_conc/5`, `aidom.multi_part_conc/4`, `aidom.collect_auxinfo_asub/4`, `aidom.rename_auxinfo_asub/4`, `aidom.dom_statistics/2`, `aidom.contains_parameters/2`.

33.2 Documentation on exports

call_to_entry/9: PREDICATE

No further documentation available for this predicate.

amgu/4: PREDICATE

No further documentation available for this predicate.

augment_asub/3: PREDICATE

No further documentation available for this predicate.

augment_two_asub/3: PREDICATE

No further documentation available for this predicate.

33.3 Documentation on multifiles

aidomain/1: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.init_abstract_domain/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.amgu/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_two_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_entry/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.exit_to_prime/8: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.project/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widencall/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.needs/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widen/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_lub/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_lub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered_gfp/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.identical_abstract/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_sort/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.extend/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.less_or_equal/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.eliminate_equivalent/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_subset/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_fact/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.special_builtin/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.combined_special_builtin0/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.body_succ_builtin/9: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.split_combined_domain/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.obtain_info/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_interface/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_user_interface/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.asub_to_native/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.concrete/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_call/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.empty_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.part_conc/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.multi_part_conc/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.collect_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.rename_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.dom_statistics/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.contains_parameters/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

33.4 Documentation on imports

This module has the following direct dependencies:

- *Application modules:*
  `preprocess_flags`, `domains`, `sharing`, `s_grshfr`, `share_amgu_sets`, `share_amgu_aux`.
- *System library modules:*
  `sets`, `sort`, `terms_vars`, `lsets`, `lists`, `terms_check`.
- *Internal (engine) modules:*
  `term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`.
- *Packages:*
  `prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `isomodes`, `aidomain`.

34 CLIQUE-Sharing domain

Author(s): Jorge Navas.

34.1 Usage and interface

- **Library usage:**
  `:- use_module(domain(sharing_clique)).`
- **Exports:**
  - *Predicates:*
    `call_to_entry/9`, `exit_to_prime/7`, `extend/5`, `asub_gt/2`, `prune_success/5`, `sharing_possible/4`, `powerset_with_empty_set/2`, `augment_asub/3`, `abs_sort/2`, `identical_abstract/2`, `eliminate_equivalent/2`, `less_or_equal/2`, `clique_part_less_or_equal/2`, `sharing_part_less_or_equal/3`, `call_to_success_fact/9`, `call_to_prime_fact/6`, `compute_lub/2`, `share_clique_lub_cl/3`, `glb/3`, `may_be_var/2`, `myappend/3`, `asub_to_native/5`, `unknown_call/4`, `unknown_entry/3`, `widen/4`, `widen/5`, `success_builtin/6`, `call_to_success_builtin/6`, `clique_make_decomposition/5`, `eliminate_couples_clique/4`, `share_make_reduction/5`, `projected_gvars_clique/3`, `compute_upper_amgu/2`.
  - *Multifiles:*
    `aidomain/1`, `aidom.init_abstract_domain/2`, `aidom.amgu/5`, `aidom.augment_asub/4`, `aidom.augment_two_asub/4`, `aidom.call_to_entry/10`, `aidom.exit_to_prime/8`, `aidom.project/6`, `aidom.widencall/4`, `aidom.needs/2`, `aidom.widen/4`, `aidom.compute_lub/3`, `aidom.compute_clauses_lub/4`, `aidom.compute_clauses_glb/4`, `aidom.fixpoint_covered/3`, `aidom.fixpoint_covered_gfp/3`, `aidom.identical_abstract/3`, `aidom.abs_sort/3`, `aidom.extend/6`, `aidom.less_or_equal/3`, `aidom.glb/4`, `aidom.eliminate_equivalent/3`, `aidom.abs_subset/3`, `aidom.call_to_success_fact/10`, `aidom.special_builtin/6`, `aidom.combined_special_builtin0/3`, `aidom.body_succ_builtin/9`, `aidom.split_combined_domain/4`, `aidom.success_builtin/7`, `aidom.call_to_success_builtin/7`, `aidom.obtain_info/5`, `aidom.input_interface/5`, `aidom.input_user_interface/6`, `aidom.asub_to_native/6`, `aidom.concrete/4`, `aidom.unknown_call/5`, `aidom.unknown_entry/4`, `aidom.empty_entry/4`, `aidom.part_conc/5`, `aidom.multi_part_conc/4`, `aidom.collect_auxinfo_asub/4`, `aidom.rename_auxinfo_asub/4`, `aidom.dom_statistics/2`, `aidom.contains_parameters/2`.

34.2 Documentation on exports

call_to_entry/9: PREDICATE

No further documentation available for this predicate.

exit_to_prime/7: PREDICATE

No further documentation available for this predicate.

amgu/4: PREDICATE
No further documentation available for this predicate.

extend/5: PREDICATE
No further documentation available for this predicate.

asub_gt/2: PREDICATE
No further documentation available for this predicate.

prune_success/5: PREDICATE
No further documentation available for this predicate.

sharing_possible/4: PREDICATE
No further documentation available for this predicate.

powerset_with_empty_set/2: PREDICATE
No further documentation available for this predicate.

augment_asub/3: PREDICATE
No further documentation available for this predicate.

project/5: PREDICATE
No further documentation available for this predicate.

abs_sort/2: PREDICATE
No further documentation available for this predicate.

identical_abstract/2: PREDICATE
No further documentation available for this predicate.

eliminate_equivalent/2: PREDICATE
No further documentation available for this predicate.

less_or_equal/2: PREDICATE
No further documentation available for this predicate.

clique_part_less_or_equal/2: PREDICATE
No further documentation available for this predicate.

sharing_part_less_or_equal/3: PREDICATE
No further documentation available for this predicate.

call_to_success_fact/9: PREDICATE
No further documentation available for this predicate.

call_to_prime_fact/6: PREDICATE
No further documentation available for this predicate.

compute_lub/2: PREDICATE
No further documentation available for this predicate.

share_clique_lub_cl/3: PREDICATE
No further documentation available for this predicate.

glb/3: PREDICATE
No further documentation available for this predicate.

input_user_interface/5: PREDICATE
No further documentation available for this predicate.

input_interface/4: PREDICATE
No further documentation available for this predicate.

may_be_var/2: PREDICATE
No further documentation available for this predicate.

myappend/3: PREDICATE
No further documentation available for this predicate.

asub_to_native/5: PREDICATE
No further documentation available for this predicate.

unknown_call/4: PREDICATE
No further documentation available for this predicate.

empty_entry/3: PREDICATE
No further documentation available for this predicate.

unknown_entry/3: PREDICATE
No further documentation available for this predicate.

widen/4: PREDICATE
No further documentation available for this predicate.

widen/5: PREDICATE
No further documentation available for this predicate.

special_builtin/5: PREDICATE
No further documentation available for this predicate.

success_builtin/6: PREDICATE
No further documentation available for this predicate.

call_to_success_builtin/6: PREDICATE
No further documentation available for this predicate.

clique_make_decomposition/5: PREDICATE
No further documentation available for this predicate.

eliminate_couples_clique/4: PREDICATE
No further documentation available for this predicate.

share_make_reduction/5: PREDICATE
No further documentation available for this predicate.

projected_gvars_clique/3: PREDICATE
No further documentation available for this predicate.

compute_upper_amgu/2: PREDICATE
No further documentation available for this predicate.

34.3 Documentation on multifiles

aidomain/1: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.init_abstract_domain/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.amgu/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_two_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_entry/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.exit_to_prime/8: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.project/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widencall/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.needs/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widen/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_lub/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_lub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered_gfp/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.identical_abstract/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_sort/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.extend/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.less_or_equal/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.eliminate_equivalent/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_subset/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_fact/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.special_builtin/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.combined_special_builtin0/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.body_succ_builtin/9: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.split_combined_domain/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.obtain_info/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_interface/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_user_interface/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.asub_to_native/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.concrete/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_call/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.empty_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.part_conc/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.multi_part_conc/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.collect_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.rename_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.dom_statistics/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.contains_parameters/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

34.4 Documentation on imports

This module has the following direct dependencies:

- *Application modules:*
  `preprocess_flags`, `domains`, `share_amgu_sets`, `s_grshfr`, `share_clique_aux`, `share_aux`, `share_clique_1_aux`, `sharing`, `share_amgu_aux`.
- *System library modules:*
  `sets`, `sort`, `lsets`, `lists`, `terms_vars`, `terms_check`, `aggregates`, `messages`.
- *Internal (engine) modules:*
  `term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`.
- *Packages:*
  `prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `isomodes`, `aidomain`.

35 1-CLIQUE-Sharing domain

Author(s): Jorge Navas.

35.1 Usage and interface

- **Library usage:**
  `:- use_module(domain(sharing_clique_1)).`

35.2 Documentation on multifiles

aidomain/1: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.init_abstract_domain/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.amgu/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_two_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_entry/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.exit_to_prime/8: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.project/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widencall/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.needs/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widen/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_lub/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_lub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered_gfp/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.identical_abstract/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_sort/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.extend/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.less_or_equal/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.eliminate_equivalent/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_subset/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_fact/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.special_builtin/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.combined_special_builtin0/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.body_succ_builtin/9: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.split_combined_domain/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.obtain_info/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_interface/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_user_interface/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.asub_to_native/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.concrete/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_call/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.empty_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.part_conc/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.multi_part_conc/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.collect_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.rename_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.dom_statistics/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.contains_parameters/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

35.3 Documentation on imports

This module has the following direct dependencies:

– *Application modules:*

`sharing_clique`, `preprocess_flags`, `domains`, `share_aux`, `share_amgu_sets`, `share_amgu_aux`, `s_grshfr`, `sharing`, `share_clique_aux`, `share_clique_1_aux`.

– *System library modules:*

`sets`, `sort`, `terms_check`, `terms_vars`, `lsets`, `lists`.

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `isomodes`, `aidomain`.

36 CLIQUE-Sharing+Def domain

Author(s): Jorge Navas.

36.1 Usage and interface

- **Library usage:**
  `:- use_module(domain(sharing_clique_def)).`

36.2 Documentation on multifiles

aidomain/1: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.init_abstract_domain/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.amgu/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_two_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_entry/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.exit_to_prime/8: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.project/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widencall/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.needs/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widen/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_lub/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_lub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered_gfp/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.identical_abstract/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_sort/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.extend/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.less_or_equal/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.eliminate_equivalent/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_subset/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_fact/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.special_builtin/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.combined_special_builtin0/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.body_succ_builtin/9: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.split_combined_domain/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.obtain_info/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_interface/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_user_interface/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.asub_to_native/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.concrete/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_call/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.empty_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.part_conc/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.multi_part_conc/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.collect_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.rename_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.dom_statistics/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.contains_parameters/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

36.3 Documentation on imports

This module has the following direct dependencies:

– *Application modules:*

`sharing_clique`, `preprocess_flags`, `domains`, `def`, `share_clique_aux`, `s_grshfr`, `share_aux`.

– *System library modules:*

`sets`, `sort`, `messages`.

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `isomodes`, `aidomain`.

37 shfret (library)

37.1 Usage and interface

- **Library usage:**
  `:- use_module(domain(shfret)).`
- **Exports:**
  - *Predicates:*
    shfret_init_abstract_domain/1, shfret_call_to_entry/9, shfret_exit_to_prime/7, shfret_project/5, shfret_extend/5, shfret_widen/3, shfret_widencall/3, shfret_compute_lub/2, shfret_glb/3, shfret_eliminate_equivalent/2, shfret_less_or_equal/2, shfret_identical_abstract/2, shfret_abs_sort/2, shfret_call_to_success_fact/9, shfret_combined_special_builtin0/2, shfret_split_combined_domain/3, shfret_input_interface/4, shfret_input_user_interface/5, shfret_asub_to_native/5, shfret_unknown_call/4, shfret_unknown_entry/3, shfret_empty_entry/3.
  - *Multifiles:*
    aidomain/1, aidom.init_abstract_domain/2, aidom.amgu/5, aidom.augment_asub/4, aidom.augment_two_asub/4, aidom.call_to_entry/10, aidom.exit_to_prime/8, aidom.project/6, aidom.widencall/4, aidom.needs/2, aidom.widen/4, aidom.compute_lub/3, aidom.compute_clauses_lub/4, aidom.compute_clauses_glb/4, aidom.fixpoint_covered/3, aidom.fixpoint_covered_gfp/3, aidom.identical_abstract/3, aidom.abs_sort/3, aidom.extend/6, aidom.less_or_equal/3, aidom.glb/4, aidom.eliminate_equivalent/3, aidom.abs_subset/3, aidom.call_to_success_fact/10, aidom.special_builtin/6, aidom.combined_special_builtin0/3, aidom.body_succ_builtin/9, aidom.split_combined_domain/4, aidom.success_builtin/7, aidom.call_to_success_builtin/7, aidom.obtain_info/5, aidom.input_interface/5, aidom.input_user_interface/6, aidom.asub_to_native/6, aidom.concrete/4, aidom.unknown_call/5, aidom.unknown_entry/4, aidom.empty_entry/4, aidom.part_conc/5, aidom.multi_part_conc/4, aidom.collect_auxinfo_asub/4, aidom.rename_auxinfo_asub/4, aidom.dom_statistics/2, aidom.contains_parameters/2.

37.2 Documentation on exports

shfret_init_abstract_domain/1: PREDICATE
No further documentation available for this predicate.

shfret_call_to_entry/9: PREDICATE
No further documentation available for this predicate.

shfret_exit_to_prime/7: PREDICATE
No further documentation available for this predicate.

shfret_project/5: PREDICATE
No further documentation available for this predicate.

shfret_extend/5: PREDICATE
No further documentation available for this predicate.

shfret_widen/3: PREDICATE
No further documentation available for this predicate.

shfret_widencall/3: PREDICATE
No further documentation available for this predicate.

shfret_compute_lub/2: PREDICATE
No further documentation available for this predicate.

shfret_glb/3: PREDICATE
No further documentation available for this predicate.

shfret_eliminate_equivalent/2: PREDICATE
No further documentation available for this predicate.

shfret_less_or_equal/2: PREDICATE
No further documentation available for this predicate.

shfret_identical_abstract/2: PREDICATE
No further documentation available for this predicate.

shfret_abs_sort/2: PREDICATE
No further documentation available for this predicate.

shfret_call_to_success_fact/9: PREDICATE
No further documentation available for this predicate.

shfret_combined_special_builtin0/2: PREDICATE
No further documentation available for this predicate.

shfret_split_combined_domain/3: PREDICATE
No further documentation available for this predicate.

shfret_input_interface/4: PREDICATE
No further documentation available for this predicate.

shfret_input_user_interface/5: PREDICATE
No further documentation available for this predicate.

shfret_asub_to_native/5: PREDICATE
No further documentation available for this predicate.

shfret_unknown_call/4: PREDICATE
No further documentation available for this predicate.

shfret_unknown_entry/3: PREDICATE
No further documentation available for this predicate.

shfret_empty_entry/3: PREDICATE
No further documentation available for this predicate.

37.3 Documentation on multifiles

aidomain/1: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.init_abstract_domain/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.amgu/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_two_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_entry/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.exit_to_prime/8: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.project/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widencall/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.needs/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widen/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_lub/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_lub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered_gfp/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.identical_abstract/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_sort/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.extend/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.less_or_equal/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.eliminate_equivalent/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_subset/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_fact/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.special_builtin/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.combined_special_builtin0/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.body_succ_builtin/9: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.split_combined_domain/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.obtain_info/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_interface/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_user_interface/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.asub_to_native/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.concrete/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_call/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.empty_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.part_conc/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.multi_part_conc/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.collect_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.rename_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.dom_statistics/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.contains_parameters/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

37.4 Documentation on imports

This module has the following direct dependencies:

- *Application modules:*
  `preprocess_flags`, `domains`, `eterms`, `sharefree`.
- *System library modules:*
  `sets`, `sort`, `lists`.
- *Internal (engine) modules:*
  `term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`.
- *Packages:*
  `prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `regtypes`, `basicmodes`, `aidomain`.

38 amgu-based sharing+freeness+linearity domain

Author(s): Jorge Navas.

38.1 Usage and interface

- **Library usage:**
  `:- use_module(domain(shfrlin_amgu)).`

38.2 Documentation on multifiles

aidomain/1: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.init_abstract_domain/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.amgu/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_two_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_entry/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.exit_to_prime/8: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.project/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widencall/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.needs/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widen/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_lub/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_lub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered_gfp/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.identical_abstract/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_sort/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.extend/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.less_or_equal/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.eliminate_equivalent/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_subset/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_fact/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.special_builtin/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.combined_special_builtin0/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.body_succ_builtin/9: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.split_combined_domain/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.obtain_info/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_interface/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_user_interface/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.asub_to_native/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.concrete/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_call/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.empty_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.part_conc/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.multi_part_conc/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.collect_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.rename_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.dom_statistics/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.contains_parameters/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

38.3 Documentation on imports

This module has the following direct dependencies:

– *Application modules:*

`preprocess_flags`, `domains`, `sharefree`, `sharefree_amgu`, `share_aux`, `sharefree_amgu_aux`, `s_grshfr`, `shfrlin_amgu_aux`.

– *System library modules:*

`sets`, `sort`, `terms_vars`, `lists`, `terms_check`.

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `isomodes`, `aidomain`.

39 shfrson (library)

39.1 Usage and interface

- **Library usage:**
  `:- use_module(domain(shfrson)).`

39.2 Documentation on multifiles

aidomain/1: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.init_abstract_domain/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.amgu/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_two_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_entry/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.exit_to_prime/8: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.project/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widencall/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.needs/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widen/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_lub/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_lub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered_gfp/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.identical_abstract/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_sort/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.extend/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.less_or_equal/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.eliminate_equivalent/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_subset/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_fact/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.special_builtin/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.combined_special_builtin0/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.body_succ_builtin/9: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.split_combined_domain/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.obtain_info/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_interface/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_user_interface/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.asub_to_native/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.concrete/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_call/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.empty_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.part_conc/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.multi_part_conc/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.collect_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.rename_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.dom_statistics/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.contains_parameters/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

39.3 Documentation on imports

This module has the following direct dependencies:

– *Application modules:*

`preprocess_flags`, `domains`, `sharefree`, `sondergaard`, `s_grshfr`, `share_aux`, `plai_errors`.

– *System library modules:*

`sets`, `sort`, `llists`, `terms_vars`.

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `aidomain`.

40 sondergaard (library)

40.1 Usage and interface

- **Library usage:**
  `:- use_module(domain(sondergaard)).`
- **Exports:**
  - *Predicates:*
    `project/5`, `call_to_entry/9`, `exit_to_prime/7`, `abs_sort/2`, `compute_lub/2`, `lub/3`, `glb/3`, `extend/5`, `call_to_success_fact/9`, `call_to_prime_fact/6`, `unknown_call/4`, `unknown_entry/3`, `empty_entry/3`, `asub_to_native/5`, `less_or_equal/2`, `special_builtin/5`, `success_builtin/6`, `call_to_success_builtin/6`, `share_to_son/3`, `son_to_share/4`, `propagate_to_sh/4`, `propagate_to_son/4`.
  - *Multifiles:*
    `aidomain/1`, `aidom.init_abstract_domain/2`, `aidom.amgu/5`, `aidom.augment_asub/4`, `aidom.augment_two_asub/4`, `aidom.call_to_entry/10`, `aidom.exit_to_prime/8`, `aidom.project/6`, `aidom.widencall/4`, `aidom.needs/2`, `aidom.widen/4`, `aidom.compute_lub/3`, `aidom.compute_clauses_lub/4`, `aidom.compute_clauses_glb/4`, `aidom.fixpoint_covered/3`, `aidom.fixpoint_covered_gfp/3`, `aidom.identical_abstract/3`, `aidom.abs_sort/3`, `aidom.extend/6`, `aidom.less_or_equal/3`, `aidom.glb/4`, `aidom.eliminate_equivalent/3`, `aidom.abs_subset/3`, `aidom.call_to_success_fact/10`, `aidom.special_builtin/6`, `aidom.combined_special_builtin0/3`, `aidom.body_succ_builtin/9`, `aidom.split_combined_domain/4`, `aidom.success_builtin/7`, `aidom.call_to_success_builtin/7`, `aidom.obtain_info/5`, `aidom.input_interface/5`, `aidom.input_user_interface/6`, `aidom.asub_to_native/6`, `aidom.concrete/4`, `aidom.unknown_call/5`, `aidom.unknown_entry/4`, `aidom.empty_entry/4`, `aidom.part_conc/5`, `aidom.multi_part_conc/4`, `aidom.collect_auxinfo_asub/4`, `aidom.rename_auxinfo_asub/4`, `aidom.dom_statistics/2`, `aidom.contains_parameters/2`.

40.2 Documentation on exports

project/5: PREDICATE

No further documentation available for this predicate.

call_to_entry/9: PREDICATE

No further documentation available for this predicate.

exit_to_prime/7: PREDICATE

No further documentation available for this predicate.

abs_sort/2: PREDICATE
No further documentation available for this predicate.

compute_lub/2: PREDICATE
No further documentation available for this predicate.

lub/3: PREDICATE
No further documentation available for this predicate.

glb/3: PREDICATE
No further documentation available for this predicate.

extend/5: PREDICATE
No further documentation available for this predicate.

call_to_success_fact/9: PREDICATE
No further documentation available for this predicate.

call_to_prime_fact/6: PREDICATE
No further documentation available for this predicate.

unknown_call/4: PREDICATE
No further documentation available for this predicate.

unknown_entry/3: PREDICATE
No further documentation available for this predicate.

empty_entry/3: PREDICATE
No further documentation available for this predicate.

asub_to_native/5: PREDICATE
No further documentation available for this predicate.

input_user_interface/5: PREDICATE
No further documentation available for this predicate.

input_interface/4: PREDICATE
No further documentation available for this predicate.

less_or_equal/2: PREDICATE
No further documentation available for this predicate.

special_builtin/5: PREDICATE
No further documentation available for this predicate.

success_builtin/6: PREDICATE
No further documentation available for this predicate.

call_to_success_builtin/6: PREDICATE
No further documentation available for this predicate.

share_to_son/3: PREDICATE
No further documentation available for this predicate.

son_to_share/4: PREDICATE
No further documentation available for this predicate.

propagate_to_sh/4: PREDICATE
No further documentation available for this predicate.

propagate_to_son/4: PREDICATE
No further documentation available for this predicate.

40.3 Documentation on multifiles

aidomain/1: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.init_abstract_domain/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.amgu/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_two_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_entry/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.exit_to_prime/8: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.project/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widencall/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.needs/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widen/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_lub/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_lub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered_gfp/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.identical_abstract/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_sort/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.extend/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.less_or_equal/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.eliminate_equivalent/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_subset/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_fact/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.special_builtin/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.combined_special_builtin0/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.body_succ_builtin/9: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.split_combined_domain/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.obtain_info/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_interface/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_user_interface/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.asub_to_native/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.concrete/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_call/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.empty_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.part_conc/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.multi_part_conc/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.collect_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.rename_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.dom_statistics/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.contains_parameters/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

40.4 Documentation on imports

This module has the following direct dependencies:

- *Application modules:*
  `preprocess_flags`, `domains`, `sharing`, `s_grshfr`, `share_aux`.
- *System library modules:*
  `sets`, `sort`, `lists`, `llists`, `lsets`, `terms_check`, `terms_vars`.
- *Internal (engine) modules:*
  `term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`.
- *Packages:*
  `prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `aidomain`.

41 svterms: eterms + same value (abstract domain)

41.1 Usage and interface

- **Library usage:**
  `:- use_module(domain(svterms)).`
- **Exports:**
  - *Predicates:*
    svterms_concrete/3, svterms_compute_lub/2, svterms_compute_lub_el/3, svterms_needs/1, svterms_widencall/3, svterms_widen/3, svterms_init_abstract_domain/1, svterms_call_to_entry/9, svterms_exit_to_prime/7, svterms_project/5, svterms_abs_sort/2, svterms_extend/5, svterms_less_or_equal/2, svterms_glb/3, svterms_unknown_entry/3, svterms_empty_entry/3, svterms_unknown_call/4, svterms_call_to_success_fact/9, svterms_special_builtin/5, svterms_success_builtin/6, svterms_call_to_success_builtin/6, svterms_input_user_interface/5, svterms_input_interface/4, svterms_asub_to_native/5, svterms_output_interface/2, svterms_collect_auxinfo_asub/3, svterms_rename_auxinfo_asub/3, svterms_identical_abstract/2.
  - *Multifiles:*
    aidomain/1, aidom.init_abstract_domain/2, aidom.amgu/5, aidom.augment_asub/4, aidom.augment_two_asub/4, aidom.call_to_entry/10, aidom.exit_to_prime/8, aidom.project/6, aidom.widencall/4, aidom.needs/2, aidom.widen/4, aidom.compute_lub/3, aidom.compute_clauses_lub/4, aidom.compute_clauses_glb/4, aidom.fixpoint_covered/3, aidom.fixpoint_covered_gfp/3, aidom.identical_abstract/3, aidom.abs_sort/3, aidom.extend/6, aidom.less_or_equal/3, aidom.glb/4, aidom.eliminate_equivalent/3, aidom.abs_subset/3, aidom.call_to_success_fact/10, aidom.special_builtin/6, aidom.combined_special_
    builtin0/3, aidom.body_succ_builtin/9, aidom.split_combined_domain/4, aidom.success_builtin/7, aidom.call_to_success_builtin/7, aidom.obtain_info/5, aidom.input_interface/5, aidom.input_user_interface/6, aidom.asub_to_native/6, aidom.concrete/4, aidom.unknown_call/5, aidom.unknown_entry/4, aidom.empty_entry/4, aidom.part_conc/5, aidom.multi_part_conc/4, aidom.collect_auxinfo_asub/4, aidom.rename_auxinfo_asub/4, aidom.dom_statistics/2, aidom.contains_parameters/2.

41.2 Documentation on exports

svterms_concrete/3: PREDICATE

No further documentation available for this predicate.

svterms_compute_lub/2: PREDICATE

No further documentation available for this predicate.

svterms_compute_lub_el/3: PREDICATE
No further documentation available for this predicate.

svterms_needs/1: PREDICATE
No further documentation available for this predicate.

svterms_widencall/3: PREDICATE
No further documentation available for this predicate.

svterms_widen/3: PREDICATE
No further documentation available for this predicate.

svterms_init_abstract_domain/1: PREDICATE
No further documentation available for this predicate.

svterms_call_to_entry/9: PREDICATE
No further documentation available for this predicate.

svterms_exit_to_prime/7: PREDICATE
No further documentation available for this predicate.

svterms_project/5: PREDICATE
No further documentation available for this predicate.

svterms_abs_sort/2: PREDICATE
No further documentation available for this predicate.

svterms_extend/5: PREDICATE
No further documentation available for this predicate.

svterms_less_or_equal/2: PREDICATE
No further documentation available for this predicate.

svterms_glb/3: PREDICATE
No further documentation available for this predicate.

svterms_unknown_entry/3: PREDICATE
No further documentation available for this predicate.

svterms_empty_entry/3: PREDICATE
No further documentation available for this predicate.

svterms_unknown_call/4: PREDICATE
No further documentation available for this predicate.

svterms_call_to_success_fact/9: PREDICATE
No further documentation available for this predicate.

svterms_special_builtin/5: PREDICATE
No further documentation available for this predicate.

svterms_success_builtin/6: PREDICATE
No further documentation available for this predicate.

svterms_call_to_success_builtin/6: PREDICATE
No further documentation available for this predicate.

svterms_input_user_interface/5: PREDICATE
No further documentation available for this predicate.

svterms_input_interface/4: PREDICATE
No further documentation available for this predicate.

svterms_asub_to_native/5: PREDICATE
No further documentation available for this predicate.

svterms_output_interface/2: PREDICATE
No further documentation available for this predicate.

svterms_collect_auxinfo_asub/3: PREDICATE
No further documentation available for this predicate.

svterms_rename_auxinfo_asub/3: PREDICATE
No further documentation available for this predicate.

svterms_identical_abstract/2: PREDICATE
No further documentation available for this predicate.

41.3 Documentation on multifiles

aidomain/1: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.init_abstract_domain/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.amgu/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_two_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_entry/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.exit_to_prime/8: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.project/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widencall/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.needs/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widen/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_lub/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_lub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered_gfp/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.identical_abstract/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_sort/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.extend/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.less_or_equal/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.eliminate_equivalent/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_subset/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_fact/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.special_builtin/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.combined_special_builtin0/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.body_succ_builtin/9: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.split_combined_domain/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.obtain_info/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_interface/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_user_interface/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.asub_to_native/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.concrete/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_call/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.empty_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.part_conc/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.multi_part_conc/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.collect_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.rename_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.dom_statistics/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.contains_parameters/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

41.4 Documentation on imports

This module has the following direct dependencies:

– *Application modules:*

`preprocess_flags`, `domains`, `eterms`.

– *System library modules:*

`sets`, `sort`, `aggregates`, `terms_vars`, `terms_check`, `lists`, `assoc`, `typeslib`.

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `regtypes`, `basicmodes`, `aidomain`.

42 termsd: types with shortening (abstract domain)

Author(s): Claudio Vaucheret, Francisco Bueno, Ciao Development Team.

This module implements the abstract operations of the type domains with widening based on shortening (`shortening_el/3`). An abstract sustitution is a list of `Var:Type` elements, where `Var` is a variable and `Type` is a pure type term [DZ92].

42.1 Usage and interface

- **Library usage:**
  `:- use_module(domain(termsd)).`
- **Exports:**
  - *Predicates:*
    `terms_input_interface/4`, `terms_concrete/3`, `terms_compute_lub/2`, `terms_compute_lub_el/3`, `terms_widencall/3`, `terms_needs/1`, `terms_widen/3`, `terms_init_abstract_domain/1`, `terms_call_to_entry/9`, `variables_are_variable_type/2`, `terms_exit_to_prime/7`, `unify_term_and_type_term/5`, `generate_a_type_assignment/3`, `get_var_types_by_unification/3`, `compute_type/3`, `find_list_entry/3`, `terms_project/5`, `terms_abs_sort/2`, `terms_extend/5`, `terms_less_or_equal/2`, `terms_glb/3`, `terms_unknown_entry/3`, `terms_empty_entry/3`, `terms_unknown_call/4`, `substitution/3`, `variables_are_top_type/2`, `terms_call_to_success_fact/9`, `terms_special_builtin/5`, `terms_success_builtin/6`, `terms_call_to_success_builtin/6`, `precondition_builtin/2`, `postcondition_builtin/4`, `terms_input_user_interface/5`, `terms_asub_to_native/5`, `terms_internal_to_native/3`, `terms_output_interface/2`, `terms_collect_auxinfo_asub/3`, `terms_rename_auxinfo_asub/3`, `terms_identical_abstract/2`.
  - *Multifiles:*
    `aidomain/1`, `aidom.init_abstract_domain/2`, `aidom.amgu/5`, `aidom.augment_asub/4`, `aidom.augment_two_asub/4`, `aidom.call_to_entry/10`, `aidom.exit_to_prime/8`, `aidom.project/6`, `aidom.widencall/4`, `aidom.needs/2`, `aidom.widen/4`, `aidom.compute_lub/3`, `aidom.compute_clauses_lub/4`, `aidom.compute_clauses_glb/4`, `aidom.fixpoint_covered/3`, `aidom.fixpoint_covered_gfp/3`, `aidom.identical_abstract/3`, `aidom.abs_sort/3`, `aidom.extend/6`, `aidom.less_or_equal/3`, `aidom.glb/4`, `aidom.eliminate_equivalent/3`, `aidom.abs_subset/3`, `aidom.call_to_success_fact/10`, `aidom.special_builtin/6`, `aidom.combined_special_builtin0/3`, `aidom.body_succ_builtin/9`, `aidom.split_combined_domain/4`, `aidom.success_builtin/7`, `aidom.call_to_success_builtin/7`, `aidom.obtain_info/5`, `aidom.input_interface/5`, `aidom.input_user_interface/6`, `aidom.asub_to_native/6`, `aidom.concrete/4`, `aidom.unknown_call/5`, `aidom.unknown_entry/4`, `aidom.empty_entry/4`, `aidom.part_conc/5`, `aidom.multi_part_conc/4`, `aidom.collect_auxinfo_asub/4`, `aidom.rename_auxinfo_asub/4`, `aidom.dom_statistics/2`, `aidom.contains_parameters/2`.

42.2 Documentation on exports

terms_input_interface/4: PREDICATE

No further documentation available for this predicate.

terms_concrete/3: PREDICATE

No further documentation available for this predicate.

terms_compute_lub/2: PREDICATE

Usage: `terms_compute_lub(ListASub,Lub)`

It computes the least upper bound of a set of abstract substitutions. For each two abstract substitutions `ASub1` and `ASub2` in `ListASub`, obtaining the lub is foreach X:Type1 in `ASub1` and X:Type2 in `ASub2`, X:TypeUnion is in Lub, and TypeUnion is the deterministic union of Type1 an Type2.

– *The following properties should hold at call time:*

`ListASub` is currently a term which is not a free variable. (`nonvar/1`)

`Lub` is a free variable. (`var/1`)

`ListASub` is a list of `termsd_asub`s. (`list/2`)

– *The following properties should hold upon exit:*

`Lub` is an abstract substitution (`termsd_asub/1`)

terms_compute_lub_el/3: PREDICATE

No further documentation available for this predicate.

terms_widencall/3: PREDICATE

No further documentation available for this predicate.

terms_needs/1: PREDICATE

No further documentation available for this predicate.

terms_widen/3: PREDICATE

Usage: `terms_widen(Prime0,Prime1,NewPrime)`

Induction step on the abstract substitution of a fixpoint. `Prime0` corresponds to non-recursive and `Prime1` to recursive clauses. `NewPrime` is the result of apply one widening operation to the least upper bound of the formers. Widening operations implemented are "shortening" and "restricted shortening" [GdW94, SG94].

– *The following properties should hold at call time:*

`Prime0` is currently a term which is not a free variable. (`nonvar/1`)

`Prime1` is currently a term which is not a free variable. (`nonvar/1`)

`NewPrime` is a free variable. (`var/1`)

`Prime0` is an abstract substitution (`termsd_asub/1`)

`Prime1` is an abstract substitution (`termsd_asub/1`)

`NewPrime` is any term. (`term/1`)

– *The following properties should hold upon exit:*

`NewPrime` is an abstract substitution (`termsd_asub/1`)

terms_init_abstract_domain/1: PREDICATE

No further documentation available for this predicate.

terms_call_to_entry/9: PREDICATE

Usage: `terms_call_to_entry(Sv,Sg,Hv,Head,K,Fv,Proj,Entry,ExtraInfo)`

It obtains the abstract substitution `Entry` which results from adding the abstraction of the `Sg` = `Head` to `Proj`, later projecting the resulting substitution onto `Hv`.

This is done as follows:

- If `Sg` and `Head` are identical up to renaming it is just renaming `Proj` and adding the `Fv`
- Otherwise, it will:
  - obtain the abstract substitution from unifying `Sg` and `Head` calling "unify_term_and_type_term"
  - add to this abstract substituion the variables in `Fv` as term type.

The meaning of the variables is:

- `Sg` is the subgoal being analysed.
- `Head` is the Head of the clause being analysed.
- `Fv` is a list of free variables in the body of the clause being considered.
- `Proj` is the abstract substitution `Call` projected onto `Sv`.
- `Entry` is the Abstract entry substitution (i.e. the abstract subtitution obtained after the abstract unification of `Sg` and `Head` projected onto `Hv + Fv`).
- `ExtraInfo` is a flag `yes` when no unification is required, i.e., `Entry=Proj` upto names of vars. and ignoring `Fv`. It is `no` if unification fails.

– *The following properties should hold at call time:*

`Sv` is currently a term which is not a free variable. (`nonvar/1`)
`Sg` is currently a term which is not a free variable. (`nonvar/1`)
`Hv` is currently a term which is not a free variable. (`nonvar/1`)
`Head` is currently a term which is not a free variable. (`nonvar/1`)
`K` is currently a term which is not a free variable. (`nonvar/1`)
`Fv` is currently a term which is not a free variable. (`nonvar/1`)
`Proj` is currently a term which is not a free variable. (`nonvar/1`)
`Entry` is a free variable. (`var/1`)
`ExtraInfo` is a free variable. (`var/1`)
`Sv` is any term. (`term/1`)
`Sg` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)
`Hv` is a list. (`list/1`)
`Head` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)
`K` is any term. (`term/1`)
`Fv` is a list. (`list/1`)
`Proj` is an abstract substitution (`termsd_asub/1`)
`Entry` is any term. (`term/1`)
`ExtraInfo` is any term. (`term/1`)

– *The following properties should hold upon exit:*

`Entry` is an abstract substitution (`termsd_asub/1`)
`termsd_extrainfo(ExtraInfo)` (`termsd_extrainfo/1`)

variables_are_variable_type/2: PREDICATE

Usage: `variables_are_variable_type(Fv,ASub)`

(at the moment) assigns the value top_type to the variables in `Fv` but in the future it must assign the value `var`

– *The following properties should hold at call time:*

`Fv` is currently a term which is not a free variable. (`nonvar/1`)

`ASub` is a free variable. (`var/1`)

`Fv` is a list. (`list/1`)

– *The following properties should hold upon exit:*

`ASub` is an abstract substitution (`termsd_asub/1`)

terms_exit_to_prime/7: PREDICATE

Usage: `terms_exit_to_prime(Sg,Hv,Head,Sv,Exit,ExtraInfo,Prime)`

It computes the prime abstract substitution `Prime`, i.e. the result of going from the abstract substitution over the head variables `Exit`, to the abstract substitution over the variables in the subgoal. It will:

- If `Exit` is '$bottom', `Prime` will be also '$bottom'.
- If `ExtraInfo` = yes (`Head` and `Sg` identical up to renaming) it is just renaming Exit %
- Otherwise, it will:
  - projects `Exit` onto `Hv` obtaining `BPrime`.
  - obtain the abstract substitution from unifying `Sg` and `Head` calling "unify_term_and_type_term"

– *The following properties should hold at call time:*

`Sg` is currently a term which is not a free variable. (`nonvar/1`)

`Hv` is currently a term which is not a free variable. (`nonvar/1`)

`Head` is currently a term which is not a free variable. (`nonvar/1`)

`Sv` is currently a term which is not a free variable. (`nonvar/1`)

`Exit` is currently a term which is not a free variable. (`nonvar/1`)

`ExtraInfo` is currently a term which is not a free variable. (`nonvar/1`)

`Prime` is a free variable. (`var/1`)

`Sg` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)

`Hv` is a list. (`list/1`)

`Head` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)

`Sv` is a list. (`list/1`)

`Exit` is an abstract substitution (`termsd_asub/1`)

`termsd_extrainfo(ExtraInfo)` (`termsd_extrainfo/1`)

`Prime` is any term. (`term/1`)

– *The following properties should hold upon exit:*

`Prime` is an abstract substitution (`termsd_asub/1`)

unify_term_and_type_term/5: PREDICATE

Usage: `unify_term_and_type_term(Term1,Tv,Term2,ASub,NewASub)`

It unifies the term `Term1` to the type term `Term2` obtaining the the abstract substitution TypeAss which is sorted and projeted on `Tv`

– *The following properties should hold at call time:*

`Term1` is currently a term which is not a free variable. (`nonvar/1`)

`Tv` is currently a term which is not a free variable. (`nonvar/1`)

`Term2` is currently a term which is not a free variable. (`nonvar/1`)

`ASub` is currently a term which is not a free variable. (`nonvar/1`)

`NewASub` is a free variable. (`var/1`)

`Term1` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)

`Tv` is a list. (`list/1`)

`Term2` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)

`ASub` is an abstract substitution (`termsd_asub/1`)

`NewASub` is any term. (`term/1`)

– *The following properties should hold upon exit:*

`NewASub` is an abstract substitution (`termsd_asub/1`)

generate_a_type_assignment/3: PREDICATE

No further documentation available for this predicate.

get_var_types_by_unification/3: PREDICATE

No further documentation available for this predicate.

compute_type/3: PREDICATE

Usage: `compute_type(Term,Type,Types)`

Given the term `Term` and a type `Type`, computes the type corresponding to each variable in `Term`, and store it in the data structure `Types`. `Types` have the structure [vt(Var1, TypeList1), ..., vt(VarN, TypeListN)|_], where TypeListN is the list of types corresponding to variable VarN.

– *The following properties should hold at call time:*

`Type` is currently a term which is not a free variable. (`nonvar/1`)

find_list_entry/3: PREDICATE

No further documentation available for this predicate.

terms_project/5: PREDICATE

Usage: `terms_project(Sg,Vars,HvFv_u,Asub,Proj)`

`Proj` is the result of eliminating from `Asub` all `X`:`Value` such that `X` is not in `Vars`.

`HvFv_u` may be a list or `not_provided_HvFv_u` and is not used by this predicate.

– *The following properties should hold at call time:*

`Sg` is currently a term which is not a free variable. (`nonvar/1`)
`Vars` is currently a term which is not a free variable. (`nonvar/1`)
`HvFv_u` is currently a term which is not a free variable. (`nonvar/1`)
`Asub` is currently a term which is not a free variable. (`nonvar/1`)
`Proj` is a free variable. (`var/1`)
`Sg` is any term. (`term/1`)
`Vars` is a list. (`list/1`)
`HvFv_u` is any term. (`term/1`)
`Asub` is an abstract substitution (`termsd_asub/1`)
`Proj` is any term. (`term/1`)

– *The following properties should hold upon exit:*

`Proj` is an abstract substitution (`termsd_asub/1`)

terms_abs_sort/2: PREDICATE

Usage: `terms_abs_sort(Asub,Asub_s)`

It sorts the set of `X:Type` in `Asub` containing `Asub_s`

– *The following properties should hold at call time:*

`Asub` is currently a term which is not a free variable. (`nonvar/1`)
`Asub_s` is a free variable. (`var/1`)
`Asub` is an abstract substitution (`termsd_asub/1`)

– *The following properties should hold upon exit:*

`Asub_s` is an abstract substitution (`termsd_asub/1`)

terms_extend/5: PREDICATE

Usage: `terms_extend(Sg,Prime,Sv,Call,Succ)`

If `Prime` = '$bottom', `Succ` = '$bottom' otherwise, `Succ` is computed updating the values of `Call` with those in `Prime`

– *The following properties should hold at call time:*

`Sg` is currently a term which is not a free variable. (`nonvar/1`)
`Prime` is currently a term which is not a free variable. (`nonvar/1`)
`Sv` is currently a term which is not a free variable. (`nonvar/1`)
`Call` is currently a term which is not a free variable. (`nonvar/1`)
`Succ` is a free variable. (`var/1`)
`Sg` is any term. (`term/1`)
`Prime` is an abstract substitution (`termsd_asub/1`)
`Sv` is a list. (`list/1`)
`Call` is an abstract substitution (`termsd_asub/1`)
`Succ` is any term. (`term/1`)

– *The following properties should hold upon exit:*

`Succ` is an abstract substitution (`termsd_asub/1`)

terms_less_or_equal/2: PREDICATE

Usage: `terms_less_or_equal(ASub0,ASub1)`

Succeeds if `ASub1` is more general or equal to `ASub0`. it's assumed the two abstract substitutions are defined on the same variables

– *The following properties should hold at call time:*

`ASub0` is currently a term which is not a free variable. (`nonvar/1`)

`ASub1` is currently a term which is not a free variable. (`nonvar/1`)

`ASub0` is an abstract substitution (`termsd_asub/1`)

`ASub1` is an abstract substitution (`termsd_asub/1`)

terms_glb/3: PREDICATE

Usage: `terms_glb(ASub0,ASub1,Glb)`

`Glb` is the great lower bound of `ASub0` and `ASub1`

– *The following properties should hold at call time:*

`ASub0` is currently a term which is not a free variable. (`nonvar/1`)

`ASub1` is currently a term which is not a free variable. (`nonvar/1`)

`Glb` is a free variable. (`var/1`)

`ASub0` is an abstract substitution (`termsd_asub/1`)

`ASub1` is an abstract substitution (`termsd_asub/1`)

`Glb` is any term. (`term/1`)

– *The following properties should hold upon exit:*

`Glb` is an abstract substitution (`termsd_asub/1`)

terms_unknown_entry/3: PREDICATE

Usage: `terms_unknown_entry(Sg,Qv,Call)`

Gives the "top" value for the variables involved in a literal whose definition is not present, and adds this top value to Call. In this domain the top value is X:term forall X in the set of variables

– *The following properties should hold at call time:*

`Sg` is currently a term which is not a free variable. (`nonvar/1`)

`Qv` is currently a term which is not a free variable. (`nonvar/1`)

`Call` is a free variable. (`var/1`)

`Sg` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)

`Qv` is a list. (`list/1`)

`Call` is any term. (`term/1`)

– *The following properties should hold upon exit:*

`Call` is an abstract substitution (`termsd_asub/1`)

terms_empty_entry/3: PREDICATE

Usage: `terms_empty_entry(Sg,Vars,Entry)`

Gives the "empty" value in this domain for a given set of variables `Vars`, resulting in the abstract substitution `Entry`. I.e., obtains the abstraction of a substitution in which all variables `Vars` are unbound: free and unaliased. In this domain the empty value is giving the variable type to each variable

– *The following properties should hold at call time:*

`Sg` is currently a term which is not a free variable. (`nonvar/1`)

`Vars` is currently a term which is not a free variable. (`nonvar/1`)

`Entry` is a free variable. (`var/1`)

`Sg` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)

`Vars` is a list. (`list/1`)

`Entry` is any term. (`term/1`)

– *The following properties should hold upon exit:*

`Entry` is an abstract substitution (`termsd_asub/1`)

terms_unknown_call/4: PREDICATE

Usage: `terms_unknown_call(Sg,Vars,Call,Succ)`

Gives the "top" value for the variables involved in a literal whose definition is not present, and adds this top value to `Call`

– *The following properties should hold at call time:*

`Sg` is currently a term which is not a free variable. (`nonvar/1`)

`Vars` is currently a term which is not a free variable. (`nonvar/1`)

`Call` is currently a term which is not a free variable. (`nonvar/1`)

`Succ` is a free variable. (`var/1`)

`Sg` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)

`Vars` is a list. (`list/1`)

`Call` is an abstract substitution (`termsd_asub/1`)

`Succ` is any term. (`term/1`)

– *The following properties should hold upon exit:*

`Succ` is an abstract substitution (`termsd_asub/1`)

substitution/3: PREDICATE

No further documentation available for this predicate.

variables_are_top_type/2: PREDICATE

Usage: `variables_are_top_type(Fv,ASub)`

It assigns the value top_type to the variables in `Fv` and return the abstract substitution `ASub`

– *The following properties should hold at call time:*

`Fv` is currently a term which is not a free variable. (`nonvar/1`)

`ASub` is a free variable. (`var/1`)

`Fv` is a list. (`list/1`)

– *The following properties should hold upon exit:*

`ASub` is an abstract substitution (`termsd_asub/1`)

terms_call_to_success_fact/9: PREDICATE

Usage: `terms_call_to_success_fact(Sg,Hv,Head,K,Sv,Call,Proj,Prime,Succ)`

Specialized version of call_to_entry + exit_to_prime + extend for facts

– *The following properties should hold at call time:*

`Sg` is currently a term which is not a free variable.	(`nonvar/1`)
`Hv` is currently a term which is not a free variable.	(`nonvar/1`)
`Head` is currently a term which is not a free variable.	(`nonvar/1`)
`K` is currently a term which is not a free variable.	(`nonvar/1`)
`Sv` is currently a term which is not a free variable.	(`nonvar/1`)
`Call` is currently a term which is not a free variable.	(`nonvar/1`)
`Proj` is currently a term which is not a free variable.	(`nonvar/1`)
`Prime` is a free variable.	(`var/1`)
`Succ` is a free variable.	(`var/1`)
`Sg` is a term which represents a goal, i.e., an atom or a structure.	(`cgoal/1`)
`Hv` is a list.	(`list/1`)
`Head` is a term which represents a goal, i.e., an atom or a structure.	(`cgoal/1`)
`K` is any term.	(`term/1`)
`Sv` is a list.	(`list/1`)
`Call` is an abstract substitution	(`termsd_asub/1`)
`Proj` is an abstract substitution	(`termsd_asub/1`)
`Prime` is any term.	(`term/1`)
`Succ` is any term.	(`term/1`)

– *The following properties should hold upon exit:*

`Prime` is an abstract substitution	(`termsd_asub/1`)
`Succ` is an abstract substitution	(`termsd_asub/1`)

terms_special_builtin/5: PREDICATE

Usage: `terms_special_builtin(SgKey,Sg,Subgoal,Type,Condvars)`

`Type` is a flag indicating what is the abstraction of builtin `SgKey` and to which variables `Condvars` of the goal `Sg` it affects.

– *The following properties should hold at call time:*

`SgKey` is currently a term which is not a free variable.	(`nonvar/1`)
`Sg` is currently a term which is not a free variable.	(`nonvar/1`)
`Subgoal` is currently a term which is not a free variable.	(`nonvar/1`)
`Type` is a free variable.	(`var/1`)
`Condvars` is a free variable.	(`var/1`)

terms_success_builtin/6: PREDICATE

No further documentation available for this predicate.

terms_call_to_success_builtin/6: PREDICATE

No further documentation available for this predicate.

precondition_builtin/2: PREDICATE

No further documentation available for this predicate.

postcondition_builtin/4: PREDICATE

No further documentation available for this predicate.

terms_input_user_interface/5: PREDICATE

Usage: `terms_input_user_interface(InputUser,Qv,ASub,Sg,MaybeCallASub)`

Obtains the abstract substitution ASub from user supplied information.

– *The following properties should hold at call time:*

`Qv` is currently a term which is not a free variable. (`nonvar/1`)

`ASub` is a free variable. (`var/1`)

`Sg` is currently a term which is not a free variable. (`nonvar/1`)

`MaybeCallASub` is currently a term which is not a free variable. (`nonvar/1`)

terms_asub_to_native/5: PREDICATE

Usage: `terms_asub_to_native(ASub,Qv,OutFlag,OutputUser,Comps)`

Transforms abstract substitution `ASub` to user friendly format. Record relevant symbols for output if `OutFlag` is `yes`.

– *The following properties should hold at call time:*

`ASub` is currently a term which is not a free variable. (`nonvar/1`)

`Qv` is currently a term which is not a free variable. (`nonvar/1`)

`OutFlag` is currently a term which is not a free variable. (`nonvar/1`)

`OutputUser` is a free variable. (`var/1`)

`Comps` is a free variable. (`var/1`)

terms_internal_to_native/3: PREDICATE

No further documentation available for this predicate.

terms_output_interface/2: PREDICATE

No further documentation available for this predicate.

terms_collect_auxinfo_asub/3: PREDICATE

No further documentation available for this predicate.

terms_rename_auxinfo_asub/3: PREDICATE

No further documentation available for this predicate.

terms_identical_abstract/2: PREDICATE

No further documentation available for this predicate.

42.3 Documentation on multifiles

aidomain/1: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.init_abstract_domain/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.amgu/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_two_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_entry/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.exit_to_prime/8: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.project/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widencall/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.needs/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widen/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_lub/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_lub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered_gfp/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.identical_abstract/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_sort/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.extend/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.less_or_equal/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.eliminate_equivalent/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_subset/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_fact/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.special_builtin/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.combined_special_builtin0/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.body_succ_builtin/9: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.split_combined_domain/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.obtain_info/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_interface/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_user_interface/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.asub_to_native/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.concrete/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_call/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.empty_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.part_conc/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.multi_part_conc/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.collect_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.rename_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.dom_statistics/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.contains_parameters/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

42.4 Documentation on imports

This module has the following direct dependencies:

- *Application modules:*
  `preprocess_flags`, `domains`.
- *System library modules:*
  `sets`, `sort`, `messages`, `terms_vars`, `terms_check`, `lists`, `typeslib`, `p_unit`, `assoc`.
- *Internal (engine) modules:*
  `term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`.
- *Packages:*
  `prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `regtypes`, `basicmodes`, `aidomain`.

43 top_path_sharing (library)

43.1 Usage and interface

- **Library usage:**
  `:- use_module(domain(top_path_sharing)).`
- **Exports:**
  - *Predicates:*
    `path_to_shfr/3`.
  - *Multifiles:*
    `aidomain/1`, `aidom.init_abstract_domain/2`, `aidom.amgu/5`, `aidom.augment_asub/4`, `aidom.augment_two_asub/4`, `aidom.call_to_entry/10`, `aidom.exit_to_prime/8`, `aidom.project/6`, `aidom.widencall/4`, `aidom.needs/2`, `aidom.widen/4`, `aidom.compute_lub/3`, `aidom.compute_clauses_lub/4`, `aidom.compute_clauses_glb/4`, `aidom.fixpoint_covered/3`, `aidom.fixpoint_covered_gfp/3`, `aidom.identical_abstract/3`, `aidom.abs_sort/3`, `aidom.extend/6`, `aidom.less_or_equal/3`, `aidom.glb/4`, `aidom.eliminate_equivalent/3`, `aidom.abs_subset/3`, `aidom.call_to_success_fact/10`, `aidom.special_builtin/6`, `aidom.combined_special_builtin0/3`, `aidom.body_succ_builtin/9`, `aidom.split_combined_domain/4`, `aidom.success_builtin/7`, `aidom.call_to_success_builtin/7`, `aidom.obtain_info/5`, `aidom.input_interface/5`, `aidom.input_user_interface/6`, `aidom.asub_to_native/6`, `aidom.concrete/4`, `aidom.unknown_call/5`, `aidom.unknown_entry/4`, `aidom.empty_entry/4`, `aidom.part_conc/5`, `aidom.multi_part_conc/4`, `aidom.collect_auxinfo_asub/4`, `aidom.rename_auxinfo_asub/4`, `aidom.dom_statistics/2`, `aidom.contains_parameters/2`.

43.2 Documentation on exports

path_to_shfr/3: PREDICATE
No further documentation available for this predicate.

43.3 Documentation on multifiles

aidomain/1: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.init_abstract_domain/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.amgu/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_two_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_entry/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.exit_to_prime/8: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.project/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widencall/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.needs/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.widen/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_lub/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_lub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered_gfp/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.identical_abstract/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_sort/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.extend/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.less_or_equal/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.eliminate_equivalent/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_subset/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_fact/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.special_builtin/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.combined_special_builtin0/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.body_succ_builtin/9: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.split_combined_domain/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.obtain_info/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_interface/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_user_interface/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.asub_to_native/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.concrete/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_call/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.empty_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.part_conc/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.multi_part_conc/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.collect_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.rename_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.dom_statistics/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.contains_parameters/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

43.4 Documentation on imports

This module has the following direct dependencies:

- *Application modules:*
  `preprocess_flags`, `domains`, `s_eqs`, `share_aux`, `plai_errors`.
- *System library modules:*
  `sets`, `sort`, `idlists`, `keys`, `lists`, `lsets`, `terms_check`, `terms_vars`.
- *Internal (engine) modules:*
  `term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `io_basic`.
- *Packages:*
  `prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `aidomain`.

44 Available program transformations

44.0.1 Program specialization

- `simp` This transformation tries to explote analysis information in order to *simplify* the program as much as possible. It includes optimizations such as abstract executability of literals, removal of useless clauses, and unfolding of literals for predicates which are defined by just a fact or a single clause with just one literal in its body (a *bridge*). It also propagates failure backwards in a clause as long as such propagation is safe.
- `spec` This transformation performs the same optimizations as `simp` but it also performs multiple specialization when this improves the possibilities of optimization. The starting point for this transformation is not a program annotated with analysis information, as in the case above, but rather an *expanded program* which corresponds to the analysis graph computed by multi-variant abstract interpretation. A minimization algorithm is used in order to guarantee that the resulting program is minimal in the sense that further collapsing versions would represent losing opportunities for optimization.
- `vers` This transformation has in common with `spec` that it takes as starting point the *expanded program* which corresponds to the analysis graph computed by abstract interpretation. However, this transformation performs no optimizations and does not minimize the program. As a result, it generates the expanded program.

44.0.2 Partial evaluation

- `codegen` This generates the specialized program resulting from partial evaluation, obtained by unfolding goals during analysis. The kind of unfolding performed is governed by the `comp_rule` flag, as follows:
  - `leftmost` unfolds the leftmost clause literal;
  - `eval_builtin` selects for unfolding first builtins which can be evaluated;
  - `local_emb` tries to select first atoms which do not endanger the embedding ordering or evaluable builtins whenever possible;
  - `jump_builtin` selects the leftmost goal but can 'jump' over (ignore) builtins when they are not evaluable. A main difference with the other computation rules is that unfolding is performed 'in situ', i.e., without reordering the atoms in the clause.
  - `safe_jb` same as `jump_builtin` with the difference that it only jumps over a call to a builtin iff the call is safe [APG06] (i.e., it is error free, binding insensitive and side effect free).
  - `bind_ins_jb` same as `safe_jb` with the difference that it only jumps over a call to a builtin iff the call is binding insensitive and side effect free.
  - `no_sideff_jb` same as `bind_ins_jb` with the difference that it only jumps over a call to a builtin iff it is side effect free.

  Unfolding is performed continuously on the already unfolded clauses, until a condition for stopping the process is satisfied. This condition is stablished by the local control policy, governed by the `local_control` flag, as follows:
  - `inst` allows goal instantiation but no actual unfolding is performed.
  - `orig` returns the clauses in the original program for the corresponding predicate.
  - `det` allows unfolding while derivations are deterministic and stops them when a non-deterministic branch is required. Note that this may not be terminating.
  - `det_la` same as `det`, but with look-ahead. It can perform a number of non-deterministic steps in the hope that the computation will turn deterministic. This number is determined by flag `unf_depth`.
  - `depth` always performs the same number of unfolding steps for every call pattern. The number is determined by flag `unf_depth`.
  - `first_sol` explores the SLD tree width-first and keeps on unfolding until a first solution is found. It can be non-terminating.
  - `first_sol_d` same as above, but allows terminating when a given depth bound is reached without obtaining any solution. The bound is determined by `unf_depth`.
  - `all_sol` tries to generate all solutions by exploring the whole SLD tree. This strategy only terminates if the SLD is finite.
  - `hom_emb` keeps on unfolding until the selected atom is homeomorphically embedded in an atom previously selected for unfolding.

45 Available fixpoints

45.0.1 Analysis with PLAI

Most of the analyses of CiaoPP are performed with the PLAI (Programming in Logic with Abstract Interpretation) framework [BGH94]. This framework is based on the computation of a fixed point for the information being inferred. Such a fixed point computation is governed by flag `fixpoint`, whose values are:

- `plai` for the classical fixed point computation [MH89a];
- `dd` for an incremental fixed point computation [HPMS00];
- `di` for the *depth independent* fixed point algorithm of [PH96];
- `check_di` .

45.0.2 Inter-modular analysis

In inter-modular analysis CiaoPP takes into account the results of analyzing a module when other modules in the same program are analyzed. Thus, it collects analysis results (success patterns) for calls to predicates in other modules to improve the analysis of a given module. It also collects calls (call patterns) that are issued by the given module to other modules to reconsider them during analysis of such other modules.

Such flow of analysis information between modules while being analyzed can be performed when analyzing one single module. The information flow then affects only the modules imported by it. New call patterns will be taken into account when/if it is the turn for such imported modules to be analyzed. Improved success patterns will only be reused when/if the importing module is reanalyzed. However, CiaoPP can also iterate continuously over the set of modules of a given program, transferring the information from one module to others, and deciding which modules to analyze at which moment. This will be done until an inter-modular fixed point is reached in the analysis of the whole program (whereas analysis is performed one-module-at-a-time, anyway).

Inter-modular analysis is enabled with flag `intermod`. During inter-modular analysis there are several possible choices for selecting success patterns and call patterns. For example, when a success pattern is required for a given call pattern to an imported predicate, and there exist several that could be used, but none of them fit exactly with the given call pattern. Also, if, in that same case, there are no success patterns that fit (in which case CiaoPP has to make an *initial guess*). Finally, when there are new call patterns to a given module obtained during analysis of the modules that import it, which of them to use as entry points should be decided. All these features are governed by the following flags:

- `intermod` to activate inter-modular analysis.
  - `off` disables inter-modular analysis. This is the default value.
  - `on` enables inter-modular analysis.
  - `auto` allows the analysis of a modular program, using `intermod:auto_analyze/2-3` with the main module of the program, iterating through the module graph until an inter-modular fixed point is reached. This value is set automatically by CiaoPP, and it should not be set by the user.
- `success_policy` to obtain success information for given call patterns to imported predicates.
  - `best` selects the success pattern which corresponds to the best over-approximation of the sought call pattern; if there are several non-comparable best over-approximations, one of them is chosen randomly.
  - `first` selects the first success pattern which corresponds to a call pattern which is an over-approximation of the sought call pattern.
  - `all` computes the greatest lower bound of the success patterns that correspond to over-approximating call patterns.
  - `top` selects `Top` (no information) as answer pattern for any call pattern.
  - `botfirst` selects the first success pattern which corresponds to a call pattern which is an under-approximation of the sought call pattern.
  - `botbest` selects the success pattern which corresponds to the best under-approximation of the sought call pattern; if there are several non-comparable best under-approximations, one of them is chosen randomly.
  - `botall` computes the least upper bound of the success patterns that correspond to

46 Other commands



47 Display information about CiaoPP files

Author(s): Isabel Garcia-Contreras.

Stability: [**devel**] Currently the subject of active development and/or research. Functionality may be limited and API and/or functionality may change without warning or deprecation period. Not recommended yet for use in production.

This program outputs information about CiaoPP files.

47.1 Usage

```
ciaopp-dump <action> [<opts>] <files>

where the possible options are:

  -h
     Print this information

  show <path>
     Print info of the dump file or registry directory located in <path>.

  cmp <path1> <path2> <domain>
     Compares the analysis results of path1 and path2.
     May be directories or .dump files.

  fmt <filename>[.dump]
     Outputs the analysis result in dot format.

  ctcheck <modulename>.pl <filename>[.dump] <domain>
     Checks assertions agains the analysis in <filename>.dump with <domain>.

  report reach <file>[.dump]
     Deadcode and failure report of a CiaoPP analysis dumped with the
     incremental option, and analyzed with the pp_flag fact_info=on.

  stats [--print-header] <filenames>[.dump]
     Counts simple characteristics of analysis in the files.

     --print-header: prints the names of the characteristics displayed

  syntactic [--print-header] <filenames>[.pl]
     Counts simple syntactic characteristics of the source in the files.

     --print-header: prints the names of the characteristics displayed
```

48 CiaoPP batch processing

Author(s): Isabel Garcia-Contreras.

This is the command line interface for the batch analysis `ciaopp_batch(ciaopp_batch)` library.

Usage: `ciaopp-batch AbsInt [Paths]`

Analyze a list of directories:

```
?- use_module(ciaopp_batch(ciaopp_batch)).
?- analysis_start([Dir1, Dir2], []).
```

To see more options see page ⟨undefined⟩ [Analysis management predicates], page ⟨undefined⟩.

Generate a report of an analyzed directory:

The following command generates a directory `allure-results` in the directory from which the command is run. The diretory will contain an `xml` file for each of the domains that the directory was analyzed for.

```
$ ciaopp_batch_report Dir
```

Visualize a report:

The analysis report in xml can be processed with the allure tool. Once the tool is installed, visualize the results by running in the same directory as the results were generated

```
$ allure serve
```

49 XML report for ciaopp-batch output

Author(s): Isabel Garcia-Contreras.

This command generates a report in xml format compatible with junit xml (). It can then be used to visualize the results of launching ciaopp_batch with the allure tool (see), as well as in gitlab (.

50 PART II - The Assertion Language and Its Use

Author(s): The Ciao Development Team.

51 Using assertions for preprocessing programs

Author(s): Francisco Bueno.

This chapter explains the use of assertions to specify a program behaviour and properties expected to hold of the program. It also clarifies the role of assertion-related declarations so that a program can be statically preprocessed with CiaoPP.

CiaoPP starts a preprocessing session from a piece of code, annotated with assertions. The code can be either a complete self-contained program or part of a larger program (e.g., a module, or a user file which is only partial). The assertions annotating the code describe some properties which the programmer requires to hold of the program. Assertions are used also to describe to the static analyzer some properties of the interface of the code being preprocessed at a given session with other parts of the program that code belongs to. In addition, assertions can be used to provide information to the static analyzer, in order to guide it, and also to control specialization and other program transformations.

This chapter explains the use of assertions in describing to CiaoPP: (1) the program specification, (2) the program interface, and (3) additional information that might help static preprocessing of the program.

In the following, the Ciao assertion language is briefly described and heavily used. In Chapter 52 [The Ciao assertion language], page 335, a complete reference description of assertions is provided. More detailed explanations of the language can be found in [PBH00].

This chapter also introduces and uses properties, and among them (regular) types. See Chapter 55 [Basic data types and properties], page 357, for a concrete reference of (some of) the Ciao properties. See Chapter 54 [Declaring regular types], page 351, for a presentation of the Ciao type language and an explanation on how you can write your own properties and types.

Most of the predicates used below which are not defined belong to the *ISO-Prolog* standard [DEDC96]. The builtin (or primitive) constraints used have also become more or less de-facto standard. For detailed descriptions of particular constraint logic programming builtins refer for example to the CHIP [COS96], PrologIV [PRO], and Ciao [BCC04] manuals.

51.1 Assertions

Predicate assertions can be used to declare properties of the execution states at the time of calling a predicate and upon predicate success. Also, properties of the computation of the calls to a predicate can be declared.

Assertions may be qualified by keywords `check` or `trust`. Assertions qualified with the former—or not qualifed—are known as check assertions; those qualified with the latter are known as trust assertions. Check assertions state the programmer's intention about the program and are used by the debugger to check for program inconsistencies. On the contrary, trust assertions are "trusted" by CiaoPP tools.

- The specification of a program is made of all check assertions for the program predicates.

51.1.1 Properties of success states

They are similar in nature to the *postconditions* used in program verification. They can be expressed in our assertion language using the basic assertion:

```
:- success Goal => Postcond.
```

This assertion should be interpreted as, "for any call of the form `Goal` which succeeds, on success `Postcond` should also hold" .

Note that, in contrast to other programming paradigms, calls to a predicate may either succeed or fail. The postcondition stated in a `success` assertion only refers to successful executions.

51.1.2 Restricting assertions to a subset of calls

Sometimes we are interested in properties which refer not to all invocations of a predicate, but rather to a subset of them. With this aim we allow the addition of preconditions (`Precond`) to predicate assertions as follows: '`Goal : Precond`'.

For example, `success` assertions can be restricted and we obtain an assertion of the form:

```
:- success Goal : Precond => Postcond.
```

which should be interpreted as, "for any call of the form `Goal` for which `Precond` holds, if the call succeeds then on success `Postcond` should also hold".

51.1.3 Properties of call states

It is also possible to use assertions to describe properties about the calls for a predicate which may appear at run-time. An assertion of the form:

```
:- calls Goal : Cond.
```

must be interpreted as, "all calls of the form `Goal` should satisfy `Cond`".

51.1.4 Properties of the computation

Many other properties which refer to the computation of the predicate (rather than the input-output behaviour) are not easily expressible using `calls` and `success` predicate assertions only. Examples of properties of the computation which we may be interested in are: non-failure, termination, determinacy, non-suspension, etc.

This sort of properties are expressed by an assertion of the form:

```
:- comp Goal : Precond + Comp-prop.
```

which must be interpreted as, "for any call of the form `Goal` for which `Precond` holds, `Comp-prop` should also hold for the computation of `Goal`". Again, the field '`: Precond`' is optional.

51.1.5 Compound assertions

In order to facilitate the writing of assertions, a compound predicate assertion can be used as syntactic sugar for the above mentioned basic assertions. Each compound assertion is translated into one or several basic assertions, depending on how many of the fields in the compound assertion are given. The compound assertion is as follows.

```
:- pred Pred : Precond => Postcond + Comp-prop.
```

Each such compound assertion corresponds to: a `success` assertion of the form:

```
:- success Pred : Precond => Postcond.
```

if the `pred` assertion has a `=>` field (and a `:` field). It also corresponds to a `comp` assertion of the form:

```
:- comp Pred : Precond + Comp-prop.
```

if the `pred` assertion has a `+` field (and a `:` field).

All compound assertions given for the same predicate correspond to a single `calls` assertion. This `calls` assertion states as properties of the calls to the predicate a disjunction of the properties stated by the different compound assertions in their `:` field. Thus, it is of the form:

```
:- calls Pred : ( Precond1 ; ... ; Precondn ).
```

for all the `Precondi` in the `:` fields of (all) the different `pred` assertions.

Note that when compound assertions are used, `calls` assertions are always implicitly generated. If you do not want the `calls` assertion to be generated (for example because the set of assertions available does not cover all possible uses of the predicate) basic `success` or `comp` assertions rather than compound (`pred`) assertions should be used.

51.1.6 Examples of compound assertions

Consider the classical qsort program for sorting lists. We can use the following assertion in order to require that the output of procedure `qsort` be a list:

```
:- success qsort(A,B) => list(B).
```

Alternatively, we may require that if `qsort` is called with a list in the first argument position and the call succeeds, then on success the second argument position should also be a list. This is declared as follows:

```
:- success qsort(A,B) : list(A) => list(B).
```

The difference with respect to the previous assertion is that `B` is only expected to be a list on success of predicate `qsort/2` if `A` was a list at the call.

In addition, we may also require that in all calls to predicate `qsort` the first argument should be a list. The following assertion will do:

```
:- calls qsort(A,B) : list(A).
```

The `qsort` procedure should be able to sort all lists. Thus, we also require that all calls to it that have a list in the first argument and a variable in the second argument do not fail:

```
:- comp qsort(A,B) : (list(A) , var(B)) + not_fails.
```

Instead of the above basic assertions, the following compound one could be given:

```
:- pred qsort(A,B) : (list(A) , var(B)) => list(B) + not_fails.
```

which will be equivalent to:

```
:- calls qsort(A,B) : (list(A), var(B)).
:- success qsort(A,B) : (list(A), var(B)) => list(B).
:- comp qsort(A,B) : (list(A) , var(B)) + not_fails.
```

This will not allow to call `qsort` with anything else than a variable as second argument. If this use of `qsort` is expected, one should have added the assertion:

```
:- pred qsort(A,B) : list(A) => list(B).
```

which, together with the above one, will imply:

```
:- calls qsort(A,B) : ((list(A), var(B)) ; list(A)).
```

Then it is only required that `A` be a list.

51.2 Properties

Whereas each kind of assertion indicates *when*, i.e., in which states or sequences of states, to check the given properties, the properties themselves define *what* to check. Properties are used to say things such as "X is a list of integers," "Y is ground," "p(X) does not fail," etc. and in Ciao they are logic predicates, in the sense that the evaluation of each property either succeeds or fails. The failure or success of properties typically needs to be determined at the time when the assertions in which they appear are checked. Assertions can be checked both at compile-time by CiaoPP and at run-time by Ciao itself (after the instrumentation of the program by CiaoPP). In this section we will concentrate exclusively on run-time checking.

A property may be a predefined predicate in the language (such as `integer(X)`) or constraint (such as `X>5`). Properties may include extra-logical predicates such as `var(X)`). Also, expressions built using conjunctions of properties,[1] or, in principle, any predicate defined by the user, using the full underlying (C)LP language. As an example, consider defining the predicate `sorted(B)` and using it as a postcondition to check that a more involved sorting algorithm such as `qsort(A,B)` produces correct results.

[1] Although disjunctions are also supported, we restrict our attention to only conjunctions.

While user-defined properties allow for properties that are as general as allowed by the full source language syntax, some limitations are useful in practice. Essentially, the behaviour of the program should not change in a fundamental way depending on whether the run-time tests are being performed or not. For example, turning on run-time checking should not introduce non-termination in a program which terminates without run-time checking. To this end, it is required that the user ensure that the execution of properties terminate for any possible initial state. Also, checking a property should not change the answers computed by the program or produce unexpected side-effects. Regarding computed answers, in principle properties are not allowed to further instantiate their arguments or add new constraints. Regarding side-effects, it is required that the code defining the property does not perform input/output, add/delete clauses, etc. which may interfere with the program behaviour. It is the user's responsibility to only use predicates meeting these conditions as properties. The user is required to identify in a special way the predicates which he or she has determined to be legal properties. This is done by means of a declaration of the form

```
:- prop Spec.
```

where `Spec` is a predicate specification in the form `PredName/Arity`.

Given the classes of assertions presented previously, there are two fundamental classes of properties. The properties used in the `Cond` of calls assertions, `Postcond` of success assertions, and `Precond` of success and comp assertions refer to a particular execution state and we refer to them as *properties of execution states*. The properties used in the `Comp-prop` part of comp assertions refer to a sequence of states and we refer to them as *properties of computations*.

Basic properties, including instantiation and compatibility state properties, types, and properties of computations (all discussed in Chapter 54 [Declaring regular types], page 351) are documented in Chapter 55 [Basic data types and properties], page 357.

51.3 Preprocessing units

The preprocessing unit is the piece of code that is made available to CiaoPP at a given preprocessing session. Normally, this is a file, but not all the code of a program is necessarily contained in one single file: in order to statically manipulate the code in a file, CiaoPP needs to know the interactions of this code with other pieces of the program—probably scattered over other files—, as well as what the user's interaction with the code will be upon execution. This is also done through the use of assertions.

If the preprocessing unit is self-contained the only interaction of its code (apart from calling the builtin predicates of the language) is with the user. The user's interaction with the program consists in querying the program. The predicates that may be directly queried by the user are entry points to the preprocessing unit.

Entry points can be declared in two ways: using a module declaration specifying the entry points, or using one entry declaration for each entry point. If entry declarations are used, instead of, or in addition to, the module declaration, they can also state properties which will hold at the time the predicate is called.

However, if the preprocessing unit is not self-contained, but only part of a larger program, then other interactions may occur. The interactions of the preprocessing unit include: the user's queries, calls from other parts of the program to the unit code, calls to the unit code from unit code which does not appear explicitely in the unit text, and calls from the unit code to other parts of the program.

First, other parts of the program can call predicates defined in the preprocessing unit. CiaoPP needs to know this information. It must be declared by specifying additional entry points, together with those corresponding to the user's queries.

Second, the preprocessing unit itself may contain meta-calls which may call any unspecified predicate. All predicates that may be called in such a way should be declared also as entry points.

Additional entry points also occur when there are predicates defined in the preprocessing unit which can be dynamically modified. In this case the code dynamically added can contain new predicate calls. These calls should be declared also as entry points.

Note that *all* entry points to the preprocessing unit should be declared: entry points including query calls that the user may issue to the program, or another part of the program can issue to the unit, but also *dynamic calls*: goals that may be run within the unit which do not appear explicitely in the unit text, i.e., from meta-predicates or from dynamic clauses which may be asserted during execution. In all cases, *entry* declarations are used to declare entry points.[2]

Third, the unit code may call predicates defined in other parts of the program. The code defining such predicates is termed *foreign code*, since it is foreign to the preprocessing unit. It is important that CiaoPP knows information about how calls to foreign code will succeed (if they succeed), in order to improve its accuracy. This can be done using *trust* declarations.

Also, trust declarations can be used to provide the preprocessor with extra information. They can be used to describe calls to predicates defined within the preprocessing unit, in addition to those describing foreign code. This can improve the information available to the preprocessor and thus help it in its task. Trust declarations state properties that the programmer knows to hold of the program.

The builtin predicates is one particular case of predicates the definitions of which are never contained in the program itself. Therefore, preprocessing units never contain code to define the builtins that they use. However, the Ciao Program Precompiler makes no assumptions on the underlying language (except that it is constraint logic programming). Thus, all information on the behaviour of the language builtins should be made available to it by means of assertions (although this does not concern the application programmer who is going to preprocess a unit, rather it concerns the system programmer when installing the Ciao Program Precompiler).

The rest of this document summarizes how assertions can be used to declare the preprocessing unit interactions. It shows the use of entry and trust declarations in preprocessing programs with CiaoPP.[3]

51.4 Foreign code

A program preprocessing unit may make use of predicates defined in other parts of the program. Such predicates are foreign to the preprocessing unit, i.e., their code is not in the unit itself. In this case, CiaoPP needs to know which is the effect that such predicates may cause on the execution of the predicates defined in the unit. For this purpose, trust declarations are used.

Foreign code includes predicates defined in other modules which are used by the preprocessing unit, predicates defined in other files which do not form part of the preprocessing unit but which are called by it, builtin predicates[4] used by the code in the preprocessing unit, and code written in a foreign language which will be linked with the program. All foreign calls (except to builtin predicates) need to be declared.[5]

---

[2] When the language supports a module system, entry points are implicitely declared by the exported predicates. In this case entry declarations are only used for local predicates if there are dynamic calls.

[3] This manual concentrates on one particular use of the declarations for solving problems related to compile-time program analysis. However, there are other possible solutions. For a complete discussion of these see [BCHP96].

[4] However, builtin predicates are usually taken care of by the system programmer, and the preprocessor, once installed, already "knows" them.

[5] However, if the language supports a module system, and the preprocessor is used in modular analysis operation mode, trust declarations are imported from other modules and do not need to be declared in the preprocessing unit.

- The effect of calls to foreign predicates may be declared by using trust declarations for such predicates.

Trust declarations have the following form:

```
:- trust success Goal : ( Prop, ..., Prop )
                     => ( Prop, ..., Prop ).
```

where `Goal` is an atom of the foreign predicate, with all arguments single distinct variables, and `Prop` is an atom which declares a property of one (or several) of the goal variables.

The first list of properties states the information at the time of calling the goal and the second one at the time of success of the goal. Thus, such a trust assertion declares that for any call to the predicate where the properties in the first list hold, those of the second will also hold upon success of the call.

Simplified versions of trust assertions can also be used, much the same as with entry declarations. See ⟨undefined⟩ [Assertions], page ⟨undefined⟩.

Trust declarations are a means to provide the preprocessor with extra information about the program states. This information is guaranteed to hold, and for this reason the preprocessor *trusts* it. Therefore, it should be used with great care, since if it is wrong the precompilation of your program will possibly be wrong.

51.4.1 Examples of trust assertions

The following annotations describe the behavior of the predicate `p/2` for two possible call patterns:

```
:- trust success p/2 : def * free => def * def.
:- trust success p/2 : free * def => free * def.
```

This would allow performing the analysis even if the code for `p/2` is not present. In that case the corresponding success information in the annotation can be used ("trusted") as success substitution.

In addition, trust declarations can be used to improve the results of compile-time program analysis when they are imprecise. This may improve the accuracy of the debugging, possibly allowing it to find more bugs.

51.5 Dynamic predicates

Predicate definitions can be augmented, reduced, and modified during program execution. This is done through the database manipulation builtins, which include `assert`, `retract`, `abolish`, and `clause`. These builtins (with the exception of `clause`) dynamically manipulate the program itself by adding to or removing clauses from it. Predicates that can be affected by such builtins are called dynamic predicates.

There are at least two possible classes of dynamic predicates which behave differently from the point of view of static manipulation. First, clauses can be asserted and/or retracted to maintain an information database that the program uses. In this case, usually only facts are asserted. Second, full clauses can be asserted for predicates which are also called within the program.

The first class of dynamic predicates are declared by data declarations. The second class by dynamic declarations. The form of both declarations is as follows:

```
:- data Spec, ..., Spec.
:- dynamic Spec, ..., Spec.
```

where `Spec` is a predicate specification in the form `PredName/Arity`.

- Dynamic predicates which are called must be declared by using a dynamic declaration.

Of course, the preprocessor cannot know of the effect that dynamic clauses added to the definition of a predicate may cause in the execution of that predicate. However, this effect can be described to the preprocessor by adding trust declarations for the dynamic predicates.

- The effect of calls to predicates which are dynamically modified may be declared by using trust declarations for such predicates.

51.6 Entry points

In a preprocessing session (at least) one entry point to the preprocessing unit is required. It plays a role during preprocessing similar to that of the query that is given to the program to run. Several entry points may be given. Entry points are given to the preprocessor by means of entry or module declarations.

If the preprocessing unit is a module, only the exported predicates can be queried. If the preprocessing unit is not a module, all of its predicates can be queried: all the unit predicates may be entry points to it. Entry declarations can then be used by the programmer to specify additional information about the properties that hold of the arguments of a predicate call when that predicate is queried.

Note that if the unit is not a module all of its predicates are considered entry points to the preprocessor. However, if the unit incorporates some entry declarations the preprocessor will act as if the predicates declared were the only entry points (the preprocessing session being valid for a particular use of the unit code—that specified by the entry declarations given).

- All predicates that can be queried by the user and all predicates that can be called from parts of the program which do not explicitely appear in the preprocessing unit should (but need not) be declared as entry points by using entry declarations.

The entry declaration has the following form:

```
:- entry Goal : ( Prop, ..., Prop ).
```

where `Goal` is an atom of the predicate that may be called, with all arguments single distinct variables, and `Prop` is an atom which declares a property of one (or several) of the goal variables. The list of properties is optional.

There are alternative formats in which the properties can be given: as the arguments of `Goal` itself, or as keywords of the declaration. For a complete reference of the syntax of assertions, see ⟨undefined⟩ [Assertions], page ⟨undefined⟩.

51.6.1 Examples of entry declarations

Consider the following program:

```
append([], L, L).
append([H|T], L, [H|R]) :- append(T, L, R).
```

It may be called in a classical way with the first two arguments bound to lists, and the third argument a free variable. This can be annotated in any of the following three ways:

```
:- entry append(X,Y,Z) : ( list(X), list(Y), var(Z) ).
:- entry append/3 : list * list * var.
:- entry append(list,list,var).
```

Assume you have the following program:

```
p(X,Y):- q(X,Y,Z).
q(X,Y,Z):- X = f(Y,Z), Y + Z = 3.
```

Assume that `p/2` is the only entry point. If you include the following declaration:

```
:- entry p/2.
```

or, equivalently,

```
:- entry p(X,Y).
```

the code will be preprocessed as if goal `p(X,Y)` was called with the most general call pattern (i.e., as if `X` and `Y` may have any two values, or no value at all—the variables being free).

However, if you know that `p/2` will always be called with the first argument uniquely defined and the second unconstrained, you can then provide more accurate information by introducing one of the following declarations:

```
:- entry p(X,Y) : ( def(X), free(Y) ).
:- entry p(def,free).
```

Now assume that `p/2` will always be called with the first argument bound to the compound term `f(A,B)` where `A` is definite and `B` is unconstrained, and the second argument of `p/2` is unconstrained. The entry declaration for this call pattern is:

```
:- entry p(X,Y) : ( X=f(A,B), def(A), free(B), free(Y) ).
```

If both call patterns are possible, the most accurate approach is to include both entry declarations in the preprocessing unit. The preprocessor will then analyze the program for each declaration. Another alternative is to include an entry declaration which approximates both call patterns, such as one of the following two:

```
:- entry p(X,Y) : free(Y).
:- entry p(X,free).
```

which state that `Y` is known to be free, but nothing is known of `X` (since it may or may not be definite).

51.7 Modules

Modules provide for encapsulation of code, in such a way that (some) predicates defined in a module can be used by other parts of the program (possibly other modules), but other (auxiliary) predicates can not. The predicates that can be used are exported by the module defining them and imported by the module(s) which use(s) them. Thus, modules provide for a natural declaration of the allowed entry points to a piece of a program.

A module is identified by a module declaration at the beginning of the file defining that module. The module declaration has the following form:

```
:- module(Name, [ Spec,...,Spec ] ).
```

where the module is named `Name` and it exports the predicates in the different `Spec`'s.

Note that such a module declaration is equivalent, for the purpose of static preprocessing, to as many entry declarations of the form:

```
:- entry Spec.
```

as there are exported `Spec`'s.

51.8 Dynamic calls

In addition to entry points there are other calls that may occur from within a piece of code which do not explicitely appear in the code itself. Among these are metacalls, callbacks, and calls from clauses which are asserted during program execution.

Metacalls are literals which call one of their arguments at run-time, converting at the time of the call a term into a goal. Predicates in this class are not only `call`, but also `bagof`, `findall`, `setof`, negation by failure, and `once` (single solution).

Metacalls may be static, and this kind of calls need not be declared. A static metacall is, for example, `once(p(X))`, where the predicate being called is statically identifiable (since it appears in the code). On the other hand, metacalls of the form `call(Y)` are dynamic, since the predicate being called will only be determined at runtime.[6]

Callbacks are also metacalls. A callback occurs when a piece of a program uses a different program module (or object) in such a way that it provides to that module the call that it should issue upon return. Callbacks, much the same as metacalls, can be either dynamic or static. Only the predicates of the preprocessing unit which can be dynamically called-back need be declared.

Clauses that are asserted during program execution correspond to code which is dynamically created; thus, the preprocessor cannot be aware of such code during a (compile-time) preprocessing session. The calls that may appear from the body of a clause which is dynamically created and asserted are also dynamic calls.

- All dynamic calls must be declared by using entry declarations for the predicates that can be called in a dynamic way.

51.8.1 Examples of dynamic calls

Consider a program where you use the `bagof` predicate to collect all solutions to a goal, and the program call looks like:

```
p(X,...) :- ..., bagof(P,X,L), ...
```

However, you know that, upon execution, only the predicates `p/2` and `q/3` will be called by `bagof`, i.e., `X` will only be bound to terms with functors `p/2` and `q/3`. Moreover, such terms will have all of their arguments constrained to definite values. This information should be given to the preprocessor using the declarations:

```
:- entry p(def,def).
:- entry q(def,def,def).
```

Assume you have a graphics library predicate `menu_create/5` which creates a graphic menu. The call must specify, among other things, the name of the menu, the menu items, and the menu handler, i.e., a predicate which should be called upon the selection of a menu item. The predicate is used as:

```
top :- ..., menu_create(Menu,0,Items,Callback,[]), ...
```

but the program is coded so that there are only two menu handlers: `app_menu/2` and `edit_menu/2`. The first one handles menu items of the type `app_item` and the second one items of the type `edit_item`. This should be declared with:

```
:- entry app_menu(gnd,app_item).
:- entry edit_menu(gnd,edit_item).
```

[6] However, sometimes analysis techniques can be used to transform dynamic metacalls into static ones.

Let a program have a dynamic predicate `dyn_calls/1` to which the program asserts clauses, such that these clauses do only have in their bodies calls to predicates `p/2` and `q/3`. This should be declared with:

```
:- entry p/2.
:- entry q/3.
```

Moreover, if the programmer knows that every call to `dyn_calls/1` which can appear in the program is such that upon its execution the calls to `p/2` and `q/3` have all of their arguments constrained to definite values, then the two entry declarations at the beginning of the examples may be used.

51.9 An overview

To process programs with the Ciao Program Precompiler the following guidelines might be useful:

1. Add

   ```
   :- use_package(assertions).
   ```

   to your program.
2. Declare your specification of the program using calls, success, comp, or pred assertions.
3. Use entry declarations to declare all entry points to your program.
4. The preprocessor will notify you during the session of certain program points where a meta-call appears that may call unknown (at compile-time) predicates.

   Add entry declarations for all the predicates that may be dynamically called at such program points.
5. Use data or dynamic declarations to declare all predicates that may be dynamically modified.
6. Add entry declarations for the dynamic calls that may occur from the code that the program may dynamically assert.
7. Optionally, you can interact with the preprocessor using trust assertions.

   For example, the preprocessor will notify you during the session of certain program points where a call appears to an unknown (at compile-time) predicate.

   Add trust declarations for such predicates.

52 The Ciao assertion language

Author(s): Manuel Hermenegildo, Francisco Bueno, German Puebla.

The `assertions` package adds a number of new declaration definitions and new operator definitions which allow including program assertions in user programs. Such assertions can be used to describe predicates, properties, modules, applications, etc. These descriptions can contain formal specifications (such as sets of preconditions, post-conditions, or descriptions of computations) as well as machine-readable textual comments.

This module is part of the `assertions` library. It defines the basic code-related assertions, i.e., those intended to be used mainly by compilation-related tools, such as the static analyzer or the run-time test generator.

Here we document mainly the use of assertions for providing specifications for predicates and other program elements, as well as the locations within assertions where machine-readable documentation strings can be placed. The commands that can be used in the documentation strings and other directives that can be used to provide additional machine-readable comments are described in the autodocumenter (`lpdoc` [Knu84, Her99]) manual.

There are two kinds of assertions: predicate assertions and program point assertions. Predicate assertions are placed as directives in the source code, i.e., preceded by "`:-`". Program point assertions are placed as literals in clause bodies. Additional documentation on the syntax and fields of predicate assertions can be found in the Chapter 53 [Types and properties related to assertions], page 345 module.

52.1 Getting more information

This documentation is intended to provide information at a "reference manual" level. For more tutorial introductions to the assertion language and more examples please see [BCHP96, HPB99, PBH00, HPBLG05, HBC12] and the `ciaopp` tutorial. % The assertion language as implemented in this library essentially follows these documents, although, due to its evolution, it may differ in some details. The purpose of this manual is to document precisely what the implementation of the library supports at any given point in time.

52.2 Some attention points

- **Formatting commands within text strings:** many of the predicates defined in these modules include arguments intended for providing textual information. This includes titles, descriptions, comments, etc. The type of this argument is a character string. In order for the automatic generation of documentation to work correctly, this character string should adhere to certain conventions. See the description of the `docstring/1` type/grammar for details.
- **Referring to variables:** In order for the automatic documentation system to work correctly, variable names (for example, when referring to arguments in the head patterns of *pred* declarations) must be surrounded by an `@var` command. For example, `@var{VariableName}` should be used for referring to the variable "VariableName", which will appear then formatted as follows: `VariableName`. See the description of the `docstring/1` type/grammar for details.

52.3 Usage and interface

- **Library usage:**

  `:- use_package(assertions).` or `:- module(...,...,[assertions]).`. Use the `assertions_basic` package to disable the implicit use of the `basic_props` module.
- **Exports:**
  - *Predicates:*

    `check/1`, `trust/1`, `true/1`, `false/1`.
- **New operators defined:**

  `=>/2` [975,xfx], `::/2` [978,xfx], `decl/1` [1150,fx], `decl/2` [1150,xfx], `pred/1` [1150,fx], `pred/2` [1150,xfx], `prop/1` [1150,fx], `prop/2` [1150,xfx], `modedef/1` [1150,fx], `calls/1` [1150,fx], `calls/2` [1150,xfx], `success/1` [1150,fx], `success/2` [1150,xfx], `comp/1` [1150,fx], `comp/2` [1150,xfx], `entry/1` [1150,fx], `exit/1` [1150,fx], `exit/2` [1150,xfx], `test/1` [1150,fx], `test/2` [1150,xfx], `texec/1` [1150,fx], `texec/2` [1150,xfx].
- **New declarations defined:**

  `pred/1`, `pred/2`, `calls/1`, `calls/2`, `success/1`, `success/2`, `comp/1`, `comp/2`, `prop/1`, `prop/2`, `test/1`, `test/2`, `texec/1`, `texec/2`, `entry/1`, `exit/1`, `exit/2`, `modedef/1`, `decl/1`, `decl/2`, `doc/2`, `comment/2`.
- **Implicit imports:**
  - *System library modules:*

    `assertions_props`.
  - *Internal (engine) modules:*

    `term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`.
  - *Packages:*

    `prelude`, `initial`, `condcomp`, `assertions/assertions_basic`.

52.4 Documentation on new declarations

pred/1: DECLARATION

`pred` assertions are the most general type of assertion, and they are used to provide information on the set of admissible calls to a predicate, the set of successes, global properties, and documentation. The body of a `pred` assertion (its only argument) contains properties or comments in different fields following the formats specified by `assrt_body/1`.

There can be more than one of these assertions per predicate, in which case each one represents a possible " mode" of use (usage) of the predicate. The exact scope of the usage is defined by the properties given for calls in the body of each assertion (which should thus distinguish the different usages intended). Predicates are typically specified using a *set* of `pred` assertions, so that together they cover all ways in which the predicate is intended be used (all usages). Each `pred` assertion is translated internally to a `calls` assertion covering all the calling modes and a `success` assertion covering the successes for those calls.

For example, the following assertions would describe all intended modes (and the only modes) of use of a predicate `length/2` (see `lists`):

```
:- pred length(L,N) : list * var => list * integer
    # "Computes the length of L.".
```

```
:- pred length(L,N) : var * integer => list * integer
    # "Outputs L of length N.".
:- pred length(L,N) : list * integer => list * integer
    # "Checks that L is of length N.".
```

Usage: :- `pred(AssertionBody)`.

– *The following properties should hold at call time:*

`AssertionBody` is an assertion body. (`assrt_body/1`)

pred/2: DECLARATION

A `pred` assertion (see `pred/1`) can be preceded (as most other assertions) by an assertion status (`assrt_status/1`). If no assertion status is present (i.e., in `pred/1` assertions) the status is assumed to be `check`.

For example, the following assertion:

```
:- pred length(L,N) : list * var => list * integer.
```

is equivalent to:

```
:- check pred length(L,N) : list * var => list * integer.
```

Usage: :- `pred(AssertionStatus,AssertionBody)`.

– *The following properties should hold at call time:*

`AssertionStatus` is an acceptable status for an assertion. (`assrt_status/1`)

`AssertionBody` is an assertion body. (`assrt_body/1`)

calls/1: DECLARATION

`calls` assertions are similar to `pred/1` assertions but the only provide information about the calls to a predicate. The set of calls assertions for a predicate describe *all* possible calls to the predicate.

For example, the following assertion describes all possible calls to predicate `is/2` (see `arithmetic`):

```
:- calls is(term,arithexpression).
```

Usage: :- `calls(AssertionBody)`.

– *The following properties should hold at call time:*

`AssertionBody` is a call assertion body. (`c_assrt_body/1`)

calls/2: DECLARATION

A `calls` assertion can be preceded (as most other assertions) by an assertion status (`assrt_status/1`). If no assertion status is present (i.e., in `calls/1` assertions) the status is assumed to be `check`.

Usage: :- `calls(AssertionStatus,AssertionBody)`.

– *The following properties should hold at call time:*

`AssertionStatus` is an acceptable status for an assertion. (`assrt_status/1`)

`AssertionBody` is a call assertion body. (`c_assrt_body/1`)

success/1: DECLARATION

`success` assertions specify properties of the answers of a predicate, similarly to the corresponding `success` field of a `pred` assertion. The assertion can be limited to apply to a particular way of calling the predicate if a `calls` field is present. However, unlike `pred` or `calls` assertions, the predicate is not forced to be called only that way.

For example, the following assertion specifies the answers of the `length/2` predicate *if* it is called as in the first mode of usage above (note that the previous pred assertion already conveys such information, however it also restricts the set of admissible `calls`, while the success assertion does not):

```
:- success length(L,N) : list * var => list * integer.
```

Usage: :- `success(AssertionBody)`.

– *The following properties should hold at call time:*

`AssertionBody` is a predicate assertion body. (`s_assrt_body/1`)

success/2: DECLARATION

A `success` assertion can be preceded (as most other assertions) by an assertion status (`assrt_status/1`). If no assertion status is present (i.e., in `success/1` assertions) the status is assumed to be `check`.

Usage: :- `success(AssertionStatus,AssertionBody)`.

– *The following properties should hold at call time:*

`AssertionStatus` is an acceptable status for an assertion. (`assrt_status/1`)

`AssertionBody` is a predicate assertion body. (`s_assrt_body/1`)

comp/1: DECLARATION

`comp` assertions specify global properties of the execution of a predicate, similarly to the corresponding `comp` field of a `pred` assertion. The assertion can be limited to apply to a particular way of calling the predicate if a `calls` field is present. However, unlike `pred` or `calls` assertions, the predicate is not forced to be called only that way.

For example, the following assertion specifies that the computation of `append/3` (see `lists`) will not fail *if* it is called as described (but does not force the predicate to be called only that way):

```
:- comp append(Xs,Ys,Zs) : var * var * var + not_fail.
```

Usage: :- `comp(AssertionBody)`.

– *The following properties should hold at call time:*

`AssertionBody` is a comp assertion body. (`g_assrt_body/1`)

comp/2: DECLARATION

A `comp` assertion can be preceded (as most other assertions) by an assertion status (`assrt_status/1`). If no assertion status is present (i.e., in `comp/1` assertions) the status is assumed to be `check`.

Usage: :- `comp(AssertionStatus,AssertionBody)`.

– *The following properties should hold at call time:*

`AssertionStatus` is an acceptable status for an assertion. (`assrt_status/1`)

`AssertionBody` is a comp assertion body. (`g_assrt_body/1`)

prop/1: DECLARATION

`prop` assertions are similar to a `pred/1` assertions but they flag that the predicate being documented is also a " property."

Properties are standard predicates, but which are *guaranteed to terminate for any possible instantiation state of their argument(s)*, do not perform side-effects which may interfere with the program behaviour, and do not further instantiate their arguments or add new constraints.

Provided the above holds, properties can thus be safely used as run-time checks. The program transformation used in `ciaopp` for run-time checking guarantees the third requirement. It also performs some basic checks on properties which in most cases are enough for the second requirement. However, it is the user's responsibility to guarantee termination of the properties defined. (See also Chapter 54 [Declaring regular types], page 351 for some considerations applicable to writing properties.)

The set of properties is thus a strict subset of the set of predicates. Note that properties, in addition to being used to describe characteristics of arguments in assertions, they can also be executed (called) as any other predicates.

Usage: :- `prop(AssertionBody)`.

– *The following properties should hold at call time:*

`AssertionBody` is an assertion body. (`assrt_body/1`)

prop/2: DECLARATION

This assertion is similar to a `prop/1` assertion but it is explicitely qualified. Non-qualified `prop/1` assertions are assumed the qualifier `check`.

Usage: :- `prop(AssertionStatus,AssertionBody)`.

– *The following properties should hold at call time:*

`AssertionStatus` is an acceptable status for an assertion. (`assrt_status/1`)

`AssertionBody` is an assertion body. (`assrt_body/1`)

test/1: DECLARATION

This assertion is similar to a success assertion but it specifies a concrete test case to be run in order verify (partially) that the predicate is working as expected. For example, the following test will verify that the length predicate works well for the particular list given:

```
:- test length(L,N) : ( L = [1,2,5,2] ) => ( N = 4 ).
```

Usage: :- `test(AssertionBody)`.

– *The following properties should hold at call time:*

`AssertionBody` is a predicate assertion body. (`s_assrt_body/1`)

test/2: DECLARATION

This assertion is similar to a `test/1` assertion but it is explicitely qualified with an assertion status. Non-qualified `test/1` assertions are assumed to have `check` status. In this context, check means that the test should be executed when the developer runs the test battery.

Usage: :- `test(AssertionStatus,AssertionBody)`.

– *The following properties should hold at call time:*

`AssertionStatus` is an acceptable status for an assertion. (`assrt_status/1`)

`AssertionBody` is a predicate assertion body. (`s_assrt_body/1`)

texec/1: DECLARATION

This assertion is similar to a `calls/1` assertion but it is used to provide input data and execution commands for run-time testing.

Usage: :- `texec(AssertionBody)`.

– *The following properties should hold at call time:*

`AssertionBody` is a call assertion body. (`c_assrt_body/1`)

texec/2: DECLARATION

This assertion is similar to a `texec/1` assertion but it is explicitely qualified with an assertion status. Non-qualified `texec/1` assertions are assumed to have `check` status.

Usage: :- `texec(AssertionStatus,AssertionBody)`.

– *The following properties should hold at call time:*

`AssertionStatus` is an acceptable status for an assertion. (`assrt_status/1`)

`AssertionBody` is a call assertion body. (`c_assrt_body/1`)

entry/1: DECLARATION

`entry` assertions provide information about the *external* calls to a predicate. They are identical syntactically to a `calls/1` assertion. However, they describe only the external calls, i.e., the calls to the exported predicates of a module from outside the module, or calls to the predicates in a non-modular file from other files (or the user).

These assertions are *trusted* by the compiler, i.e., they are similar to writing a `trust calls` assertion (except for referring only to the external calls). As a result, if they are erroneous they can introduce bugs in programs. Thus, `entry` assertions should be written with care.

An important use of these assertions is in providing information to the compiler which it may not be able to infer from the program. The main use is in providing information on the ways in which exported predicates of a module will be called from outside the module. This will greatly improve the precision of the analyzer, which otherwise has to assume that the arguments that exported predicates receive are any arbitrary term.

The distinction between external and internal calls is not always relevant and in those cases the use of `trust calls` assertions is preferred. Because of this, `entry` assertions may be deprecated in the future, since the distinction between external and internal calls can also be achieved by means of a bridge predicate.

Usage: :- `entry(AssertionBody)`.

– *The following properties should hold at call time:*

`AssertionBody` is a call assertion body. (`c_assrt_body/1`)

exit/1: DECLARATION

This type of assertion provides information about the answers that an (exported) predicate provides for *external* calls. It is identical syntactically to a `success/1` assertion. However, it describes only external answers, i.e., answers to the exported predicates of a module from outside the module, or answers to the predicates in a non-modular file from other files (or the user). The described answers may be conditioned to a particular way of calling the predicate. E.g.:

```
:- exit length(L,N) : list * var => list * integer.
```

These assertions are *trusted* by the compiler, i.e., they are similar to writing a `trust success` assertion (except for referring only to the external calls). As a result, if they are erroneous they can introduce bugs in programs. Thus, `exit` assertions should be written with care.

The distinction between external and internal calls is not always relevant and in those cases the use of `trust success` assertions is preferred. Because of this, `entry` assertions may be deprecated in the future, since the distinction between external and internal calls can also be achieved by means of a bridge predicate.

Usage: :- `exit(AssertionBody)`.

– *The following properties should hold at call time:*

`AssertionBody` is a predicate assertion body. (`s_assrt_body/1`)

exit/2: DECLARATION

exit assertion This assertion is similar to an `exit/1` assertion but it is explicitely qualified with an assertion status. Non-qualified `exit/1` assertions are assumed the qualifier `check`.

Usage: :- `exit(AssertionStatus,AssertionBody)`.

– *The following properties should hold at call time:*

`AssertionStatus` is an acceptable status for an assertion. (`assrt_status/1`)

`AssertionBody` is a predicate assertion body. (`s_assrt_body/1`)

modedef/1: DECLARATION

This assertion is used to define modes. A mode defines in a compact way a set of call and success properties. Once defined, modes can be applied to predicate arguments in assertions. The meaning of this application is that the call and success properties defined by the mode hold for the argument to which the mode is applied. Thus, a mode is conceptually a "property macro."

The syntax of mode definitions is similar to that of `pred` declarations. For example, the following set of assertions:

```
:- modedef +A : nonvar(A) # "A is bound upon predicate entry.".

:- pred p(+A,B) : integer(A) =>  ground(B).
```

is equivalent to:

```
:- pred p(A,B) : (nonvar(A),integer(A)) =>  ground(B)
   # "A is bound upon predicate entry.".
```

Usage: :- `modedef(AssertionBody)`.

– *The following properties should hold at call time:*

`AssertionBody` is an assertion body. (`assrt_body/1`)

decl/1: DECLARATION

This assertion is similar to a `pred/1` assertion but it is used to describe declarations instead of predicates.

Usage: :- `decl(AssertionBody)`.

– *The following properties should hold at call time:*

`AssertionBody` is an assertion body. (`assrt_body/1`)

decl/2: DECLARATION

This assertion is similar to a `decl/1` assertion but it also has a status. Non-qualified `decl/1` assertions are assumed to have status `check`.

Usage: :- `decl(AssertionStatus,AssertionBody)`.

– *The following properties should hold at call time:*

`AssertionStatus` is an acceptable status for an assertion. (`assrt_status/1`)

`AssertionBody` is an assertion body. (`assrt_body/1`)

doc/2: DECLARATION

Usage: :- `doc(Pred,Comment)`.

Documentation . This assertion provides a text `Comment` for a given predicate `Pred`, as well as other directives for the documenter.

– *The following properties should hold at call time:*

`Pred` is a head pattern. (`head_pattern/1`)

`Comment` is a text comment with admissible documentation commands. The usual formatting commands that are applicable in comment strings are defined by `stringcommand/1`. See the `lpdoc` manual for documentation on comments. (`docstring/1`)

comment/2: DECLARATION

Usage: :- `comment(Pred,Comment)`.

An alias for `doc/2` (deprecated, for compatibility with older versions).

– *The following properties should hold at call time:*

`Pred` is a head pattern. (`head_pattern/1`)

`Comment` is a text comment with admissible documentation commands. The usual formatting commands that are applicable in comment strings are defined by `stringcommand/1`. See the `lpdoc` manual for documentation on comments. (`docstring/1`)

– *The following properties should hold globally:*

DEPRECATED. (`deprecated/1`)

52.5 Documentation on exports

check/1: PREDICATE

Usage: `check(PropertyConjunction)`

This assertion provides information on a clause program point (position in the body of a clause). Calls to a `check/1` assertion can appear in the body of a clause in any place where a literal can normally appear. The property defined by `PropertyConjunction` should hold in all the run-time stores corresponding to that program point. See also Chapter 64 [Run-time checking of assertions], page 407.

– *The following properties should hold at call time:*

`PropertyConjunction` is either a term or a *conjunction* of terms. The main functor and arity of each of those terms corresponds to the definition of a property. The first argument of each such term is a variable which appears as a head argument. (`property_conjunction/1`)

trust/1: PREDICATE

Usage: `trust(PropertyConjunction)`

This assertion also provides information on a clause program point. It is identical syntactically to a `check/1` assertion. However, the properties stated are not taken as something to be checked but are instead *trusted* by the compiler. While the compiler may in some cases detect an inconsistency between a `trust/1` assertion and the program, in all other cases the information given in the assertion will be taken to be true. As a result, if these assertions are erroneous they can introduce bugs in programs. Thus, `trust/1` assertions should be written with care.

An important use of these assertions is in providing information to the compiler which it may not be able to infer from the program (either because the information is not present or because the analyzer being used is not precise enough). In particular, providing information on external predicates which may not be accessible at the time of compiling the module can greatly improve the precision of the analyzer. This can be easily done with trust assertion.

– *The following properties should hold at call time:*

`PropertyConjunction` is either a term or a *conjunction* of terms. The main functor and arity of each of those terms corresponds to the definition of a property. The first argument of each such term is a variable which appears as a head argument. (`property_conjunction/1`)

true/1: PREDICATE

Usage: `true(PropertyConjunction)`

This assertion is identical syntactically to a `check/1` assertion. However, the properties stated have been proved to hold by the analyzer. Thus, these assertions often represent the analyzer output.

– *The following properties should hold at call time:*

`PropertyConjunction` is either a term or a *conjunction* of terms. The main functor and arity of each of those terms corresponds to the definition of a property. The first argument of each such term is a variable which appears as a head argument. (`property_conjunction/1`)

false/1: PREDICATE

Usage: `false(PropertyConjunction)`

This assertion is identical syntactically to a `check/1` assertion. However, the properties stated have been proved not to hold by the analyzer. Thus, these assertions often represent the analyzer output.

– *The following properties should hold at call time:*

`PropertyConjunction` is either a term or a *conjunction* of terms. The main functor and arity of each of those terms corresponds to the definition of a property. The first argument of each such term is a variable which appears as a head argument. (`property_conjunction/1`)

53 Types and properties related to assertions

Author(s): Manuel Hermenegildo.

This module is part of the `assertions` library. It provides the formal definition of the syntax of several forms of assertions and describes their meaning. It does so by defining types and properties related to the assertions themselves. The text describes, for example, the overall fields which are admissible in the bodies of assertions, where properties can be used inside these bodies, how to combine properties for a given predicate argument (e.g., conjunctions) , etc. and provides some examples.

53.1 Usage and interface

- **Library usage:**
  `:- use_module(library(assertions/assertions_props)).`
- **Exports:**
  - *Properties:*
    `head_pattern/1`, `nabody/1`, `docstring/1`.
  - *Regular Types:*
    `assrt_body/1`, `complex_arg_property/1`, `property_conjunction/1`, `property_starterm/1`, `complex_goal_property/1`, `dictionary/1`, `c_assrt_body/1`, `s_assrt_body/1`, `g_assrt_body/1`, `assrt_status/1`, `assrt_type/1`, `predfunctor/1`, `propfunctor/1`.

53.2 Documentation on exports

assrt_body/1: REGTYPE

This predicate defines the different types of syntax admissible in the bodies of `pred/1`, `decl/1`, etc. assertions. Such a body is of the form:

```
Pr [:: DP] [: CP] [=> AP] [+ GP] [# CO]
```

where (fields between [...] are optional):

- `Pr` is a head pattern (`head_pattern/1`) which describes the predicate or property and possibly gives some implicit call/answer information.
- `DP` is a (possibly empty) complex argument property (`complex_arg_property/1`) which expresses properties which are compatible with the predicate, i.e., instantiations made by the predicate are *compatible* with the properties in the sense that applying the property at any point would not make it fail.
- `CP` is a (possibly empty) complex argument property (`complex_arg_property/1`) which applies to the *calls* to the predicate.
- `AP` is a (possibly empty) complex argument property (`complex_arg_property/1`) which applies to the *answers* to the predicate (if the predicate succeeds). These only apply if the (possibly empty) properties given for calls in the assertion hold.
- `GP` is a (possibly empty) complex goal property (`complex_goal_property/1`) which applies to the *whole execution* of a call to the predicate. These only apply if the (possibly empty) properties given for calls in the assertion hold.

- `CO` is a comment string (`docstring/1`). This comment only applies if the (possibly empty) properties given for calls in the assertion hold. The usual formatting commands that are applicable in comment strings can be used (see `stringcommand/1`).

  See the `lpdoc` manual for documentation on assertion comments.

Usage: `assrt_body(X)`

`X` is an assertion body.

head_pattern/1: PROPERTY

A head pattern can be a predicate name (functor/arity) (`predname/1`) or a term. Thus, both `p/3` and `p(A,B,C)` are valid head patterns. In the case in which the head pattern is a term, each argument of such a term can be:

- A variable. This is useful in order to be able to refer to the corresponding argument positions by name within properties and in comments. Thus, `p(Input,Parameter,Output)` is a valid head pattern.
- A variable, as above, but preceded by a " mode." This mode determines in a compact way certain call or answer properties. For example, the head pattern `p(Input,+Parameter,Output)` is valid, as long as `+/1` is declared as a mode.

  Some useful mode definitions can be found in the `basicmodes` and `isomodes` libraries. Users can define modes using the `modedef/1` declaration.
- Any term. In this case this term determines the instantiation state of the corresponding argument position of the predicate calls to which the assertion applies.
- A ground term preceded by a " mode." The ground term determines a property of the corresponding argument. The mode determines if it applies to the calls and/or the successes. The actual property referred to is that given by the term but with one more argument added at the beginning, which is a new variable which, in a rewriting of the head pattern, appears at the argument position occupied by the term. For example, the head pattern `p(Input,+list(int),Output)` is valid for mode `+/1` defined in `library(isomodes)`, and equivalent in this case to having the head pattern `p(Input,A,Output)` and stating that the property `list(int,A)` holds for the calls of the predicate.
- Any term preceded by a " mode." In this case, only one variable is admitted, it has to be the first argument of the mode, and it represents the argument position. I.e., it plays the role of the new variable mentioned above. Thus, no rewriting of the head pattern is performed in this case. For example, the head pattern `p(Input,+(Parameter,list(int)),Output)` is valid for mode `+/2` defined in `library(isomodes)`, and equivalent in this case to having the head pattern `p(Input,Parameter,Output)` and stating that the property `list(int,Parameter)` holds for the calls of the predicate.

Usage: `head_pattern(Pr)`

`Pr` is a head pattern.

complex_arg_property/1: REGTYPE

`complex_arg_property(Props)`

`Props` is a (possibly empty) complex argument property. Such properties can appear in two formats, which are defined by `property_conjunction/1` and `property_starterm/1` respectively. The two formats can be mixed provided they are not in the same field of an assertion. I.e., the following is a valid assertion:

```
:- pred foo(X,Y) : nonvar * var => (ground(X),ground(Y)).
```

Usage: `complex_arg_property(Props)`

`Props` is a (possibly empty) complex argument property

property_conjunction/1: REGTYPE

This type defines the first, unabridged format in which properties can be expressed in the bodies of assertions. It is essentially a conjunction of properties which refer to variables. The following is an example of a complex property in this format:

- `(integer(X),list(integer,Y))`: `X` has the property `integer/1` and `Y` has the property `list/2`, with second argument `integer`.

Usage: `property_conjunction(Props)`

`Props` is either a term or a *conjunction* of terms. The main functor and arity of each of those terms corresponds to the definition of a property. The first argument of each such term is a variable which appears as a head argument.

property_starterm/1: REGTYPE

This type defines a second, compact format in which properties can be expressed in the bodies of assertions. A `property_starterm/1` is a term whose main functor is `*/2` and, when it appears in an assertion, the number of terms joined by `*/2` is exactly the arity of the predicate it refers to. A similar series of properties as in `property_conjunction/1` appears, but the arity of each property is one less: the argument position to which they refer (first argument) is left out and determined by the position of the property in the `property_starterm/1`. The idea is that each element of the `*/2` term corresponds to a head argument position. Several properties can be assigned to each argument position by grouping them in curly brackets. The following is an example of a complex property in this format:

- `integer * list(integer)`: the first argument of the procedure (or function, or ...) has the property `integer/1` and the second one has the property `list/2`, with second argument `integer`.
- `{integer,var} * list(integer)`: the first argument of the procedure (or function, or ...) has the properties `integer/1` and `var/1` and the second one has the property `list/2`, with second argument `integer`.

Usage: `property_starterm(Props)`

`Props` is either a term or several terms separated by `*/2`. The main functor of each of those terms corresponds to that of the definition of a property, and the arity should be one less than in the definition of such property. All arguments of each such term are ground.

complex_goal_property/1: REGTYPE

`complex_goal_property(Props)`

`Props` is a (possibly empty) complex goal property. Such properties can be either a term or a *conjunction* of terms. The main functor and arity of each of those terms corresponds to the definition of a property. Such properties apply to all executions of all goals of the predicate which comply with the assertion in which the `Props` appear.

The arguments of the terms in `Props` are implicitely augmented with a first argument which corresponds to a goal of the predicate of the assertion in which the `Props` appear. For example, the assertion

```
:- comp var(A) + not_further_inst(A).
```

has property `not_further_inst/1` as goal property, and establishes that in all executions of `var(A)` it should hold that `not_further_inst(var(A),A)`.

Usage: `complex_goal_property(Props)`

`Props` is either a term or a *conjunction* of terms. The main functor and arity of each of those terms corresponds to the definition of a property. A first implicit argument in such terms identifies goals to which the properties apply.

nabody/1: PROPERTY

Usage: `nabody(ABody)`

`ABody` is a normalized assertion body.

dictionary/1: REGTYPE

Usage: `dictionary(D)`

`D` is a dictionary of variable names.

c_assrt_body/1: REGTYPE

This predicate defines the different types of syntax admissible in the bodies of `call/1`, `entry/1`, etc. assertions. The following are admissible:

```
Pr : CP [# CO]
```

where (fields between [...] are optional):

- `CP` is a (possibly empty) complex argument property (`complex_arg_property/1`) which applies to the *calls* to the predicate.
- `CO` is a comment string (`docstring/1`). This comment only applies if the (possibly empty) properties given for calls in the assertion hold. The usual formatting commands that are applicable in comment strings can be used (see `stringcommand/1`).

The format of the different parts of the assertion body are given by `n_assrt_body/5` and its auxiliary types.

Usage: `c_assrt_body(X)`

`X` is a call assertion body.

s_assrt_body/1: REGTYPE

This predicate defines the different types of syntax admissible in the bodies of `pred/1`, `func/1`, etc. assertions. The following are admissible:

```
Pr : CP => AP # CO
Pr : CP => AP
Pr => AP # CO
Pr => AP
```

where:

- `Pr` is a head pattern (`head_pattern/1`) which describes the predicate or property and possibly gives some implicit call/answer information.
- `CP` is a (possibly empty) complex argument property (`complex_arg_property/1`) which applies to the *calls* to the predicate.
- `AP` is a (possibly empty) complex argument property (`complex_arg_property/1`) which applies to the *answers* to the predicate (if the predicate succeeds). These only apply if the (possibly empty) properties given for calls in the assertion hold.
- `CO` is a comment string (`docstring/1`). This comment only applies if the (possibly empty) properties given for calls in the assertion hold. The usual formatting commands that are applicable in comment strings can be used (see `stringcommand/1`).

The format of the different parts of the assertion body are given by `n_assrt_body/5` and its auxiliary types.

Usage: `s_assrt_body(X)`

`X` is a predicate assertion body.

g_assrt_body/1: REGTYPE

This predicate defines the different types of syntax admissible in the bodies of `comp/1` assertions. The following are admissible:

```
Pr : CP + GP # CO
Pr : CP + GP
Pr + GP # CO
Pr + GP
```

where:

- `Pr` is a head pattern (`head_pattern/1`) which describes the predicate or property and possibly gives some implicit call/answer information.
- `CP` is a (possibly empty) complex argument property (`complex_arg_property/1`) which applies to the *calls* to the predicate.
- `GP` contains (possibly empty) complex goal property (`complex_goal_property/1`) which applies to the *whole execution* of a call to the predicate. These only apply if the (possibly empty) properties given for calls in the assertion hold.
- `CO` is a comment string (`docstring/1`). This comment only applies if the (possibly empty) properties given for calls in the assertion hold. The usual formatting commands that are applicable in comment strings can be used (see `stringcommand/1`).

The format of the different parts of the assertion body are given by `n_assrt_body/5` and its auxiliary types.

Usage: `g_assrt_body(X)`

`X` is a comp assertion body.

assrt_status/1: REGTYPE

The types of assertion status. They have the same meaning as the program-point assertions, and are as follows:

```
assrt_status(true).
assrt_status(false).
assrt_status(check).
assrt_status(checked).
```

```
assrt_status(trust).
```

Usage: `assrt_status(X)`

`X` is an acceptable status for an assertion.

assrt_type/1: REGTYPE

The admissible kinds of assertions:

```
assrt_type(pred).
assrt_type(prop).
assrt_type(decl).
assrt_type(func).
assrt_type(calls).
assrt_type(success).
assrt_type(comp).
assrt_type(entry).
assrt_type(exit).
assrt_type(test).
assrt_type(texec).
assrt_type(modedef).
```

Usage: `assrt_type(X)`

`X` is an admissible kind of assertion.

predfunctor/1: REGTYPE

Usage: `predfunctor(X)`

`X` is a type of assertion which defines a predicate.

propfunctor/1: REGTYPE

Usage: `propfunctor(X)`

`X` is a type of assertion which defines a *property*.

docstring/1: PROPERTY

Usage: `docstring(String)`

`String` is a text comment with admissible documentation commands. The usual formatting commands that are applicable in comment strings are defined by `stringcommand/1`. See the `lpdoc` manual for documentation on comments.

53.3 Documentation on imports

This module has the following direct dependencies:

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `regtypes`.

54 Declaring regular types

Author(s): Manuel Hermenegildo, Pedro López, Francisco Bueno.

This library package adds declarations and new operator definitions which provide simple syntactic sugar to write regular type definitions in source code. Regular types are just properties which have the additional characteristic of being regular types (`basic_props:regtype/1`), defined below.

For example, this library package allows writing:

```
:- regtype tree(X) # "X is a tree.".
```

instead of the more cumbersome:

```
:- prop tree(X) + regtype # "X is a tree.".
```

Regular types can be used as properties to describe predicates and play an essential role in program debugging (see the Ciao Prolog preprocessor (`ciaopp`) manual).

In this chapter we explain some general considerations worth taking into account when writing properties in general, not just regular types.

54.1 Defining properties

Given the classes of assertions in the Ciao assertion language, there are two fundamental classes of properties. Properties used in assertions which refer to execution states (i.e., `calls/1`, `success/1`, and the like) are called *properties of execution states*. Properties used in assertions related to computations (i.e., `comp/1`) are called *properties of computations*. Different considerations apply when writing a property of the former or of the latter kind.

Consider a definition of the predicate `string_concat/3` which concatenates two character strings (represented as lists of ASCII codes):

```
string_concat([],L,L).
string_concat([X|Xs],L,[X|NL]):- string_concat(Xs,L,NL).
```

Assume that we would like to state in an assertion that each argument "is a list of integers." However, we must decide which one of the following two possibilities we mean exactly: "the argument is *instantiated* to a list of integers" (let us call this property `instantiated_to_intlist/1`), or "if any part of the argument is instantiated, this instantiation must be compatible with the argument being a list of integers" (we will call this property `compatible_with_intlist/1`). For example, `instantiated_to_intlist/1` should be true for the terms `[]` and `[1,2]`, but should not for `X`, `[a,2]`, and `[X,2]`. In turn, `compatible_with_intlist/1` should be true for `[]`, `X`, `[1,2]`, and `[X,2]`, but should not be for `[X|1]`, `[a,2]`, and `1`. We refer to properties such as `instantiated_to_intlist/1` above as *instantiation properties* and to those such as `compatible_with_intlist/1` as *compatibility properties* (corresponding to the traditional notions of "instantiation types" and "compatibility types").

It turns out that both of these notions are quite useful in practice. In the example above, we probably would like to use `compatible_with_intlist/1` to state that on success of `string_concat/3` all three argument must be compatible with lists of integers in an assertion like:

```
:- success string_concat(A,B,C) => ( compatible_with_intlist(A),
                                      compatible_with_intlist(B),
                                      compatible_with_intlist(C) ).
```

With this assertion, no error will be flagged for a call to `string_concat/3` such as `string_concat([20],L,R)`, which on success produces the resulting atom `string_concat([20],L,[20|L])`, but a call `string_concat([],a,R)` would indeed flag an error.

On the other hand, and assuming that we are running on a Prolog system, we would probably like to use `instantiated_to_intlist/1` for `sumlist/2` as follows:

```
:- calls sumlist(L,N) : instantiated_to_intlist(L).

sumlist([],0).
sumlist([X|R],S) :- sumlist(R,PS), S is PS+X.
```

to describe the type of calls for which the program has been designed, i.e., those in which the first argument of `sumlist/2` is indeed a list of integers.

The property `instantiated_to_intlist/1` might be written as in the following (Prolog) definition:

```
:- prop instantiated_to_intlist/1.

instantiated_to_intlist(X) :-
       nonvar(X), instantiated_to_intlist_aux(X).

instantiated_to_intlist_aux([]).
instantiated_to_intlist_aux([X|T]) :-
       integer(X), instantiated_to_intlist(T).
```

(Recall that the Prolog builtin `integer/1` itself implements an instantiation check, failing if called with a variable as the argument.)

The property `compatible_with_intlist/1` might in turn be written as follows (also in Prolog):

```
:- prop compatible_with_intlist/1.

compatible_with_intlist(X) :- var(X).
compatible_with_intlist(X) :-
       nonvar(X), compatible_with_intlist_aux(X).

compatible_with_intlist_aux([]).
compatible_with_intlist_aux([X|T]) :-
       int_compat(X), compatible_with_intlist(T).

int_compat(X) :- var(X).
int_compat(X) :- nonvar(X), integer(X).
```

Note that these predicates meet the criteria for being properties and thus the `prop/1` declaration is correct.

Ensuring that a property meets the criteria for "not affecting the computation" can sometimes make its coding somewhat tedious. In some ways, one would like to be able to write simply:

```
intlist([]).
intlist([X|R]) :- int(X), intlist(R).
```

(Incidentally, note that the above definition, provided that it suits the requirements for being a property and that `int/1` is a regular type, meets the criteria for being a regular type. Thus, it could be declared `:- regtype intlist/1`.)

But note that (independently of the definition of `int/1`) the definition above is not the correct instantiation check, since it would succeed for a call such as `intlist(X)`. In fact, it is not strictly correct as a compatibility property either, because, while it would fail or succeed as expected, it would perform instantiations (e.g., if called with `intlist(X)` it would bind `X` to `[]`). In practice, it is convenient to provide some run-time support to aid in this task.

The run-time support of the Ciao system (see Chapter 64 [Run-time checking of assertions], page 407) ensures that the execution of properties is performed in such a way that properties written as above can be used directly as instantiation checks. Thus, writing:

```
:- calls sumlist(L,N) : intlist(L).
```

has the desired effect. Also, the same properties can often be used as compatibility checks by writing them in the assertions as `compat(Property)` (`basic_props:compat/1`). Thus, writing:

```
:- success string_concat(A,B,C) => ( compat(intlist(A)),
                                     compat(intlist(B)),
                                     compat(intlist(C)) ).
```

also has the desired effect.

As a general rule, the properties that can be used directly for checking for compatibility should be *downwards closed*, i.e., once they hold they will keep on holding in every state accessible in forwards execution. There are certain predicates which are inherently *instantiation* checks and should not be used as *compatibility* properties nor appear in the definition of a property that is to be used with `compat`. Examples of such predicates (for Prolog) are `==`, `ground`, `nonvar`, `integer`, `atom`, `>`, etc. as they require a certain instantiation degree of their arguments in order to succeed.

In contrast with properties of execution states, *properties of computations* refer to the entire execution of the call(s) that the assertion relates to. One such property is, for example, `not_fails/1` (note that although it has been used as in `:- comp append(Xs,Ys,Zs) + not_fails`, it is in fact read as `not_fails(append(Xs,Ys,Zs))`; see `assertions_props:complex_goal_property/1`). For this property, which should be interpreted as "execution of the predicate either succeeds at least once or loops," we can use the following predicate `not_fails/1` for run-time checking:

```
not_fails(Goal):-
      if( call(Goal),
          true,            %% then
          warning(Goal) ). %% else
```

where the `warning/1` (library) predicate simply prints a warning message.

In this simple case, implementation of the predicate is not very difficult using the (non-standard) `if/3` builtin predicate present in many Prolog systems.

However, it is not so easy to code predicates which check other properties of the computation and we may in general need to program a meta-interpreter for this purpose.

54.2 Usage and interface

- **Library usage:**
  `:- use_package(regtypes).`
  or
  `:- module(...,...,[regtypes]).`
- **New operators defined:**
  `regtype/1` [1150,fx], `regtype/2` [1150,xfx].
- **New declarations defined:**
  `regtype/1`, `regtype/2`.
- **Implicit imports:**
  - *System library modules:*
    `assertions_props`.
  - *Internal (engine) modules:*
    `term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`.
  - *Packages:*
    `prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`.

54.3 Documentation on new declarations

regtype/1: DECLARATION

This assertion is similar to a prop assertion but it flags that the property being documented is also a " regular type." Regular types are properties whose definitions are *regular programs* (see below). This allows for example checking whether it is in the class of types supported by the regular type checking and inference modules.

A regular program is defined by a set of clauses, each of the form:

```
p(v_1, ..., v_n, x)  :- body_1, ..., body_k.
```

where:

1. `x` is a term whose variables (which are called *term variables*) are unique, i.e., it is not allowed to introduce equality constraints between the variables of `x`.

   For example, `p(f(X, Y)) :- ...` is valid, but `p(f(X, X)) :- ...` is not.
2. in all clauses defining `p/n+1` the terms `x` do not unify except maybe for one single clause in which `x` is a variable.
3. `n` >= 0 and `p/n` is a *parametric type functor* (whereas the predicate defined by the clauses is `p/n+1`).
4. `v_1`, ..., `v_n` are unique variables, which are called *parametric variables*.
5. Each `body_i` is of the form:
   1. `t(z)` where `z` is one of the *term variables* and `t` is a *regular type expression*;
   2. `q(t_1, ..., t_m, y)` where `m` >= 0, `q/m` is a *parametric type functor*, not in the set of functors `=/2`, `^/2`, `./3`.

      `t_1, ..., t_m` are *regular type expressions*, and `y` is a *term variable*.
6. Each term variable occurs at most once in the clause's body (and should be as the last argument of a literal).

A *regular type expression* is either a parametric variable or a parametric type functor applied to some of the parametric variables.

A parametric type functor is a regular type, defined by a regular program, or a basic type. Basic types are defined in Chapter 55 [Basic data types and properties], page 357.

The set of regular types is thus a well defined subset of the set of properties. Note that types can be used to describe characteristics of arguments in assertions and they can also be executed (called) as any other predicates.

Usage: :- `regtype(AssertionBody)`.

– *The following properties should hold at call time:*

`AssertionBody` is an assertion body. (`assrt_body/1`)

regtype/2: DECLARATION

This assertion is similar to a `regtype/1` assertion but it is explicitely qualified. Non-qualified `regtype/1` assertions are assumed the qualifier `check`. Note that checking regular type definitions should be done with the `ciaopp` preprocessor.

Usage: :- `regtype(AssertionStatus,AssertionBody)`.

– *The following properties should hold at call time:*

`AssertionStatus` is an acceptable status for an assertion. (`assrt_status/1`)

`AssertionBody` is an assertion body. (`assrt_body/1`)

55 Basic data types and properties

Author(s): Daniel Cabeza, Manuel Hermenegildo.

This library contains the set of basic properties used by the builtin predicates, and which constitute the basic data types and properties of the language. They are intented to be used as properties in assertions (for both runtime and compile time checking).

Note that most of those properties can be used directly from goals as type testing builtins, and they should be correct when terms are sufficiently instantiated. Calling with uninstantiated terms have undefined behaviour (failure or non termination, depending on the type). Please use the run-time checking facilities (`inst/2` and `compat/2`) to ensure well-defined behaviour. For low-level instantiation checks we encourage the use `term_typing` builtins.

55.1 Usage and interface

- **Library usage:**
  This module is automatically imported by the `assertions` package. It can be imported explicitly with the `:- use_module(engine(basic_props))` directive.
- **Exports:**
  - *Predicates:*
    `check/1`, `trust/1`, `true/1`, `false/1`.
  - *Properties:*
    `callable/1`, `member/2`, `compat/2`, `inst/2`, `iso/1`, `deprecated/1`, `srcloc/4`, `example/1`, `not_further_inst/2`, `sideff/2`, `regtype/1`, `native/1`, `native/2`, `rtcheck/1`, `rtcheck/2`, `no_rtcheck/1`, `eval/1`, `equiv/2`, `bind_ins/1`, `error_free/1`, `memo/1`, `filter/2`, `pe_type/1`.
  - *Regular Types:*
    `term/1`, `int/1`, `nnegint/1`, `flt/1`, `num/1`, `atm/1`, `struct/1`, `gnd/1`, `gndstr/1`, `constant/1`, `cgoal/1`, `internal_module_id/1`, `operator_specifier/1`, `list/1`, `list/2`, `nlist/2`, `sequence/2`, `sequence_or_list/2`, `character_code/1`, `string/1`, `bytelist/1`, `predname/1`, `atm_or_atm_list/1`, `flag_values/1`.

55.2 Documentation on exports

term/1: REGTYPE

The most general type (includes all possible terms).

Usage: `term(X)`

`X` is any term.

- *The following properties hold globally:*
  This predicate is understood natively by CiaoPP. (`native/1`)

Other properties:

`term(X)`

- *The following properties hold globally:*
  `term(X)` is side-effect `free`. (`sideff/2`)

`term(X)`

– *The following properties hold globally:*
`term(X)` is evaluable at compile-time. (`eval/1`)

`term(X)`
– *The following properties hold globally:*
`term(X)` is equivalent to `true`. (`equiv/2`)

int/1: REGTYPE

The type of integers. The range of integers is `[-2^2147483616, 2^2147483616)`. Thus for all practical purposes, the range of integers can be considered infinite.

Usage: `int(T)`

`T` is an integer.

– *The following properties hold globally:*
This predicate is understood natively by CiaoPP. (`native/1`)

Other properties:

`int(T)`
– *The following properties hold globally:*
`int(T)` is side-effect `free`. (`sideff/2`)

`int(T)`
– *If the following properties hold at call time:*
`T` is currently a term which is not a free variable. (`nonvar/1`)
then the following properties hold globally:
`int(T)` is evaluable at compile-time. (`eval/1`)
All calls of the form `int(T)` are deterministic. (`is_det/1`)

`int(T)`
– *The following properties hold upon exit:*
`T` is an integer. (`int/1`)
– *The following properties hold globally:*
Indicates the type of test that a predicate performs. Required by the nonfailure analyisis. (`test_type/2`)

nnegint/1: REGTYPE

The type of non-negative integers, i.e., natural numbers.

Usage: `nnegint(T)`

`T` is a non-negative integer.

– *The following properties hold globally:*
This predicate is understood natively by CiaoPP. (`native/1`)

Other properties:

`nnegint(T)`
– *The following properties hold globally:*
`nnegint(T)` is side-effect `free`. (`sideff/2`)

`nnegint(T)`

– *If the following properties hold at call time:*

`T` is currently a term which is not a free variable. (`nonvar/1`)

then the following properties hold globally:

`nnegint(T)` is evaluable at compile-time. (`eval/1`)

`nnegint(T)`

– *The following properties hold upon exit:*

`T` is a non-negative integer. (`nnegint/1`)

– *The following properties hold globally:*

Indicates the type of test that a predicate performs. Required by the nonfailure analyisis. (`test_type/2`)

flt/1: REGTYPE

The type of floating-point numbers. The range of floats is the one provided by the C `double` type, typically `[4.9e-324, 1.8e+308]` (plus or minus). There are also three special values: Infinity, either positive or negative, represented as `1.0e1000` and `-1.0e1000`; and Not-a-number, which arises as the result of indeterminate operations, represented as `0.Nan`

Usage: `flt(T)`

`T` is a float.

– *The following properties hold globally:*

This predicate is understood natively by CiaoPP. (`native/1`)

Other properties:

`flt(T)`

– *The following properties hold globally:*

`flt(T)` is side-effect `free`. (`sideff/2`)

`flt(T)`

– *If the following properties hold at call time:*

`T` is currently a term which is not a free variable. (`nonvar/1`)

then the following properties hold globally:

`flt(T)` is evaluable at compile-time. (`eval/1`)

All calls of the form `flt(T)` are deterministic. (`is_det/1`)

`flt(T)`

– *The following properties hold upon exit:*

`T` is a float. (`flt/1`)

– *The following properties hold globally:*

Indicates the type of test that a predicate performs. Required by the nonfailure analyisis. (`test_type/2`)

num/1: REGTYPE

The type of numbers, that is, integer or floating-point.

Usage: `num(T)`

`T` is a number.

– *The following properties hold globally:*
This predicate is understood natively by CiaoPP. (native/1)

Other properties:
num(T)
– *The following properties hold globally:*
num(T) is side-effect free. (sideff/2)
num(T) is binding insensitive. (bind_ins/1)

num(T)
– *If the following properties hold at call time:*
T is currently a term which is not a free variable. (nonvar/1)
then the following properties hold globally:
num(T) is evaluable at compile-time. (eval/1)
All calls of the form num(T) are deterministic. (is_det/1)

num(T)
– *The following properties hold upon exit:*
T is a number. (num/1)
– *The following properties hold globally:*
Indicates the type of test that a predicate performs. Required by the nonfailure analyisis. (test_type/2)

atm/1: REGTYPE
The type of atoms, or non-numeric constants. The size of atoms is unbound.
Usage: atm(T)
T is an atom.
– *The following properties hold globally:*
This predicate is understood natively by CiaoPP. (native/1)

Other properties:
atm(T)
– *The following properties hold globally:*
atm(T) is side-effect free. (sideff/2)

atm(T)
– *If the following properties hold at call time:*
T is currently a term which is not a free variable. (nonvar/1)
then the following properties hold globally:
atm(T) is evaluable at compile-time. (eval/1)
All calls of the form atm(T) are deterministic. (is_det/1)

atm(T)
– *The following properties hold upon exit:*
T is an atom. (atm/1)
– *The following properties hold globally:*
Indicates the type of test that a predicate performs. Required by the nonfailure analyisis. (test_type/2)

struct/1: REGTYPE

The type of compound terms, or terms with non-zeroary functors. By now there is a limit of 255 arguments.

Usage: `struct(T)`

`T` is a compound term.

– *The following properties hold globally:*

This predicate is understood natively by CiaoPP. (`native/1`)

Other properties:

`struct(T)`

– *The following properties hold globally:*

`struct(T)` is side-effect `free`. (`sideff/2`)

`struct(T)`

– *If the following properties hold at call time:*

`T` is currently a term which is not a free variable. (`nonvar/1`)

then the following properties hold globally:

`struct(T)` is evaluable at compile-time. (`eval/1`)

`struct(T)`

– *The following properties hold upon exit:*

`T` is a compound term. (`struct/1`)

gnd/1: REGTYPE

The type of all terms without variables.

Usage: `gnd(T)`

`T` is ground.

– *The following properties hold globally:*

This predicate is understood natively by CiaoPP. (`native/1`)

Other properties:

`gnd(T)`

– *The following properties hold globally:*

`gnd(T)` is side-effect `free`. (`sideff/2`)

`gnd(T)`

– *If the following properties hold at call time:*

`T` is currently ground (it contains no variables). (`ground/1`)

then the following properties hold globally:

`gnd(T)` is evaluable at compile-time. (`eval/1`)

All calls of the form `gnd(T)` are deterministic. (`is_det/1`)

`gnd(T)`

– *The following properties hold upon exit:*

`T` is ground. (`gnd/1`)

– *The following properties hold globally:*

Indicates the type of test that a predicate performs. Required by the nonfailure analyisis. (`test_type/2`)

gndstr/1: REGTYPE

Usage: `gndstr(T)`

`T` is a ground compound term.

– *The following properties hold globally:*
This predicate is understood natively by CiaoPP. (`native/1`)

Other properties:

`gndstr(T)`

– *The following properties hold globally:*
`gndstr(T)` is side-effect `free`. (`sideff/2`)

`gndstr(T)`

– *If the following properties hold at call time:*
`T` is currently ground (it contains no variables). (`ground/1`)
then the following properties hold globally:
`gndstr(T)` is evaluable at compile-time. (`eval/1`)
All calls of the form `gndstr(T)` are deterministic. (`is_det/1`)

`gndstr(T)`

– *The following properties hold upon exit:*
`T` is a ground compound term. (`gndstr/1`)

constant/1: REGTYPE

Usage: `constant(T)`

`T` is an atomic term (an atom or a number).

Other properties:

`constant(T)`

– *The following properties hold globally:*
`constant(T)` is side-effect `free`. (`sideff/2`)

`constant(T)`

– *If the following properties hold at call time:*
`T` is currently a term which is not a free variable. (`nonvar/1`)
then the following properties hold globally:
`constant(T)` is evaluable at compile-time. (`eval/1`)
All calls of the form `constant(T)` are deterministic. (`is_det/1`)

`constant(T)`

– *The following properties hold upon exit:*
`T` is an atomic term (an atom or a number). (`constant/1`)

cgoal/1: REGTYPE

Usage: `cgoal(T)`

`T` is a term which represents a goal, i.e., an atom or a structure.

Other properties:

`cgoal(T)`

– *The following properties hold globally:*
`cgoal(T)` is side-effect `free`. (`sideff/2`)

`cgoal(T)`
– *If the following properties hold at call time:*
`T` is currently a term which is not a free variable. (`nonvar/1`)
then the following properties hold globally:
`cgoal(T)` is evaluable at compile-time. (`eval/1`)
All calls of the form `cgoal(T)` are deterministic. (`is_det/1`)

`cgoal(T)`
– *The following properties hold upon exit:*
`T` is currently a term which is not a free variable. (`nonvar/1`)

callable/1: PROPERTY

Usage: `callable(T)`

`T` is instantiated with an atom or a structure (also known as callable).

Other properties:

`callable(T)`
– *The following properties hold globally:*
`callable(T)` is side-effect `free`. (`sideff/2`)

`callable(T)`
– *If the following properties hold at call time:*
`T` is currently a term which is not a free variable. (`nonvar/1`)
then the following properties hold globally:
`callable(T)` is evaluable at compile-time. (`eval/1`)
All calls of the form `callable(T)` are deterministic. (`is_det/1`)

`callable(T)`
– *The following properties hold upon exit:*
`T` is currently a term which is not a free variable. (`nonvar/1`)

internal_module_id/1: REGTYPE

For a user file it is a term user/1 with an argument different for each user file, for other modules is just the name of the module (as an atom).

Usage: `internal_module_id(M)`

`M` is an internal module identifier

operator_specifier/1: REGTYPE

The type and associativity of an operator is described by the following mnemonic atoms:

`xfx` Infix, non-associative: it is a requirement that both of the two subexpressions which are the arguments of the operator must be of *lower* precedence than the operator itself.

`xfy` Infix, right-associative: only the first (left-hand) subexpression must be of lower precedence; the right-hand subexpression can be of the *same* precedence as the main operator.

`yfx` Infix, left-associative: same as above, but the other way around.

`fx` Prefix, non-associative: the subexpression must be of *lower* precedence than the operator.

`fy` Prefix, associative: the subexpression can be of the *same* precedence as the operator.

`xf` Postfix, non-associative: the subexpression must be of *lower* precedence than the operator.

`yf` Postfix, associative: the subexpression can be of the *same* precedence as the operator.

Usage: `operator_specifier(X)`

`X` specifies the type and associativity of an operator.

Other properties:

`operator_specifier(X)`

– *The following properties hold globally:*

`operator_specifier(X)` is side-effect `free`. (`sideff/2`)

`operator_specifier(X)`

– *If the following properties hold at call time:*

`X` is currently a term which is not a free variable. (`nonvar/1`)

then the following properties hold globally:

`operator_specifier(X)` is evaluable at compile-time. (`eval/1`)

All calls of the form `operator_specifier(X)` are deterministic. (`is_det/1`)

Goal `operator_specifier(X)` produces `7` solutions. (`relations/2`)

`operator_specifier(T)`

– *The following properties hold upon exit:*

`T` specifies the type and associativity of an operator. (`operator_specifier/1`)

list/1: REGTYPE

A list is formed with successive applications of the functor `'.'/2`, and its end is the atom `[]`. Defined as

```
list([]).
list([_1|L]) :-
    list(L).
```

Usage: `list(L)`

`L` is a list.

Other properties:

`list(L)`

– *The following properties hold globally:*

`list(L)` is side-effect `free`. (`sideff/2`)

`list(L)`

– *If the following properties hold at call time:*
`L` is currently ground (it contains no variables). (`ground/1`)
then the following properties hold globally:
`list(L)` is evaluable at compile-time. (`eval/1`)
All calls of the form `list(L)` are deterministic. (`is_det/1`)

`list(T)`
– *The following properties hold upon exit:*
`T` is a list. (`list/1`)

list/2: REGTYPE

`list(T,L)`

`L` is a list, and for all its elements, `T` holds.

Usage: `list(T,L)`

`L` is a list of `T`s.

Meta-predicate with arguments: `list(pred(1),?)`.

Other properties:

`list(T,L)`
– *The following properties hold globally:*
`list(T,L)` is side-effect `free`. (`sideff/2`)

`list(T,L)`
– *If the following properties hold at call time:*
`T` is currently ground (it contains no variables). (`ground/1`)
`L` is currently ground (it contains no variables). (`ground/1`)
then the following properties hold globally:
`list(T,L)` is evaluable at compile-time. (`eval/1`)

`list(T,X)`
– *The following properties hold upon exit:*
`X` is a list. (`list/1`)

nlist/2: REGTYPE

Usage: `nlist(T,L)`

`L` is `T` or a nested list of `T`s. Note that if `T` is term, this type is equivalent to term, this fact explains why we do not have an `nlist/1` type.

Meta-predicate with arguments: `nlist(pred(1),?)`.

Other properties:

`nlist(T,L)`
– *The following properties hold globally:*
`nlist(T,L)` is side-effect `free`. (`sideff/2`)

`nlist(T,L)`

– *If the following properties hold at call time:*
`T` is currently ground (it contains no variables). (`ground/1`)
`L` is currently ground (it contains no variables). (`ground/1`)
then the following properties hold globally:
`nlist(T,L)` is evaluable at compile-time. (`eval/1`)

`nlist(T,X)`
– *The following properties hold upon exit:*
`X` is any term. (`term/1`)

member/2: PROPERTY

Usage: `member(X,L)`

`X` is an element of `L`.

Other properties:

`member(X,L)`
– *The following properties hold globally:*
`member(X,L)` is side-effect `free`. (`sideff/2`)
`member(X,L)` is binding insensitive. (`bind_ins/1`)

`member(X,L)`
– *If the following properties hold at call time:*
`L` is a list. (`list/1`)
then the following properties hold globally:
`member(X,L)` is evaluable at compile-time. (`eval/1`)

`member(_X,L)`
– *The following properties hold upon exit:*
`L` is a list. (`list/1`)

`member(X,L)`
– *If the following properties hold at call time:*
`L` is currently ground (it contains no variables). (`ground/1`)
then the following properties hold upon exit:
`X` is currently ground (it contains no variables). (`ground/1`)

sequence/2: REGTYPE

A sequence is formed with zero, one, or more occurrences of the operator `','/2`. For example, `a, b, c` is a sequence of three atoms, `a` is a sequence of one atom.

Usage: `sequence(T,S)`

`S` is a sequence of `T`s.

Meta-predicate with arguments: `sequence(pred(1),?)`.

Other properties:

`sequence(T,S)`
– *The following properties hold globally:*
`sequence(T,S)` is side-effect `free`. (`sideff/2`)

`sequence(T,S)`

– *If the following properties hold at call time:*
`T` is currently ground (it contains no variables). (`ground/1`)
`S` is currently ground (it contains no variables). (`ground/1`)
then the following properties hold globally:
`sequence(T,S)` is evaluable at compile-time. (`eval/1`)

`sequence(T,E)`

– *The following properties hold upon exit:*
`T` is currently ground (it contains no variables). (`ground/1`)
`E` is currently a term which is not a free variable. (`nonvar/1`)

sequence_or_list/2: REGTYPE

Usage: `sequence_or_list(T,S)`

`S` is a sequence or list of `T`s.

Meta-predicate with arguments: `sequence_or_list(pred(1),?)`.

Other properties:

`sequence_or_list(T,S)`

– *The following properties hold globally:*
`sequence_or_list(T,S)` is side-effect `free`. (`sideff/2`)

`sequence_or_list(T,S)`

– *If the following properties hold at call time:*
`T` is currently ground (it contains no variables). (`ground/1`)
`S` is currently ground (it contains no variables). (`ground/1`)
then the following properties hold globally:
`sequence_or_list(T,S)` is evaluable at compile-time. (`eval/1`)

`sequence_or_list(T,E)`

– *The following properties hold upon exit:*
`T` is currently ground (it contains no variables). (`ground/1`)
`E` is currently a term which is not a free variable. (`nonvar/1`)

character_code/1: REGTYPE

Usage: `character_code(T)`

`T` is an integer which is a character code.

Other properties:

`character_code(T)`

– *The following properties hold globally:*
`character_code(T)` is side-effect `free`. (`sideff/2`)

`character_code(T)`

– *If the following properties hold at call time:*
`T` is currently a term which is not a free variable. (`nonvar/1`)
then the following properties hold globally:
`character_code(T)` is evaluable at compile-time. (`eval/1`)

`character_code(I)`

– *The following properties hold upon exit:*
`I` is an integer which is a character code. (`character_code/1`)

string/1: REGTYPE

A string is a list of character codes. The usual syntax for strings `"string"` is allowed, which is equivalent to `[0's,0't,0'r,0'i,0'n,0'g]` or `[115,116,114,105,110,103]`. There is also a special Ciao syntax when the list is not complete: `"st"||R` is equivalent to `[0's,0't|R]`.

Usage: `string(T)`

`T` is a string (a list of character codes).

Other properties:

`string(T)`

– *The following properties hold globally:*
`string(T)` is side-effect `free`. (`sideff/2`)

`string(T)`

– *If the following properties hold at call time:*
`T` is currently ground (it contains no variables). (`ground/1`)
then the following properties hold globally:
`string(T)` is evaluable at compile-time. (`eval/1`)

`string(T)`

– *The following properties hold upon exit:*
`T` is a string (a list of character codes). (`string/1`)

bytelist/1: REGTYPE

Usage: `bytelist(T)`

`T` is list of bytes.

Other properties:

`bytelist(T)`

– *The following properties hold globally:*
`bytelist(T)` is side-effect `free`. (`sideff/2`)

`bytelist(T)`

– *If the following properties hold at call time:*
`T` is currently ground (it contains no variables). (`ground/1`)
then the following properties hold globally:
`bytelist(T)` is evaluable at compile-time. (`eval/1`)

`bytelist(T)`

– *The following properties hold upon exit:*
`T` is list of bytes. (`bytelist/1`)

predname/1: REGTYPE

`predname(P)`

`P` is a Name/Arity structure denoting a predicate name:

```
predname(P/A) :-
    atm(P),
    nnegint(A).
```

Usage: `predname(P)`

`P` is a predicate name.

Other properties:

`predname(P)`

– *The following properties hold globally:*

`predname(P)` is side-effect `free`. (`sideff/2`)

`predname(P)`

– *If the following properties hold at call time:*

`P` is currently ground (it contains no variables). (`ground/1`)

then the following properties hold globally:

`predname(P)` is evaluable at compile-time. (`eval/1`)

`predname(P)`

– *The following properties hold upon exit:*

`P` is a predicate name. (`predname/1`)

atm_or_atm_list/1: REGTYPE

Usage: `atm_or_atm_list(T)`

`T` is an atom or a list of atoms.

Other properties:

`atm_or_atm_list(T)`

– *The following properties hold globally:*

`atm_or_atm_list(T)` is side-effect `free`. (`sideff/2`)

`atm_or_atm_list(T)`

– *If the following properties hold at call time:*

`T` is currently ground (it contains no variables). (`ground/1`)

then the following properties hold globally:

`atm_or_atm_list(T)` is evaluable at compile-time. (`eval/1`)

`atm_or_atm_list(T)`

– *The following properties hold upon exit:*

`T` is an atom or a list of atoms. (`atm_or_atm_list/1`)

compat/2: PROPERTY

This property captures the notion of type or property compatibility. The instantiation or constraint state of the term is compatible with the given property, in the sense that assuming that imposing that property on the term does not render the store inconsistent.

For example, terms `X` (i.e., a free variable), `[Y|Z]`, and `[Y,Z]` are all compatible with the regular type `list/1`, whereas the terms `f(a)` and `[1|2]` are not.

Usage: `compat(Term,Prop)`

`Term` is *compatible* with `Prop`.

Meta-predicate with arguments: `compat(?,pred(1))`.

Other properties:

`compat(Term,Prop)`

– *If the following properties hold at call time:*
`Term` is currently ground (it contains no variables). (`ground/1`)
`Prop` is currently ground (it contains no variables). (`ground/1`)
then the following properties hold globally:
`compat(Term,Prop)` is evaluable at compile-time. (`eval/1`)

inst/2: PROPERTY

Usage: `inst(Term,Prop)`

`Term` is instantiated enough to satisfy `Prop`.

Meta-predicate with arguments: `inst(?,pred(1))`.

Other properties:

`inst(Term,Prop)`

– *The following properties hold globally:*
`inst(Term,Prop)` is side-effect `free`. (`sideff/2`)

`inst(Term,Prop)`

– *If the following properties hold at call time:*
`Term` is currently ground (it contains no variables). (`ground/1`)
`Prop` is currently ground (it contains no variables). (`ground/1`)
then the following properties hold globally:
`inst(Term,Prop)` is evaluable at compile-time. (`eval/1`)

iso/1: PROPERTY

Specifies that the predicate and usage marked with this global property complies with the ISO-Prolog standard.

Usage: `iso(G)`

Complies with the ISO-Prolog standard.

Meta-predicate with arguments: `iso(goal)`.

Other properties:

`iso(G)`

– *The following properties hold globally:*
`iso(G)` is side-effect `free`. (`sideff/2`)

deprecated/1: PROPERTY

Specifies that the predicate marked with this global property has been deprecated, i.e., its use is not recommended any more since it will be deleted at a future date. Typically this is done because its functionality has been superseded by another predicate.

Usage: `deprecated(G)`

DEPRECATED.

Meta-predicate with arguments: `deprecated(goal)`.

Other properties:

`deprecated(G)`

– *The following properties hold globally:*

`deprecated(G)` is side-effect `free`. (`sideff/2`)

srcloc/4: PROPERTY

This annotation (pseudo-property) is used to mark that the element (normally assertion) in which it appears was originally between lines `LB-LE` of source file `Src`.

Usage: `srcloc(Goal,Src,LB,LE)`

– *The following properties should hold globally:*

`srcloc(Goal,Src,LB,LE)` is side-effect `free`. (`sideff/2`)

Meta-predicate with arguments: `srcloc(?,?,?,?)`.

example/1: PROPERTY

This pseudo-property can be used as a qualifier for test assertions. Specifies that the test assertion in which it appears is actually an example and should be included as such in the manual by the auto-documeter.

Usage: `example(G)`

EXAMPLE.

Meta-predicate with arguments: `example(goal)`.

Other properties:

`example(G)`

– *The following properties hold globally:*

`example(G)` is side-effect `free`. (`sideff/2`)

not_further_inst/2: PROPERTY

Usage: `not_further_inst(G,V)`

`V` is not further instantiated.

Meta-predicate with arguments: `not_further_inst(goal,?)`.

Other properties:

`not_further_inst(G,V)`

– *The following properties hold globally:*

`not_further_inst(G,V)` is side-effect `free`. (`sideff/2`)

`not_further_inst(G,V)` is not checked during run-time checking. (`no_rtcheck/1`)

sideff/2: PROPERTY

`sideff(G,X)`

Declares that `G` is side-effect free (if its execution has no observable result other than its success, its failure, or its abortion), soft (if its execution may have other observable results which, however, do not affect subsequent execution, e.g., input/output), or hard (e.g., assert/retract).

Usage: `sideff(G,X)`

`G` is side-effect `X`.

– *If the following properties should hold at call time:*

`G` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)

`X` is an element of `[free,soft,hard]`. (`member/2`)

Meta-predicate with arguments: `sideff(goal,?)`.

Other properties:

`sideff(G,X)`

– *The following properties hold globally:*

This predicate is understood natively by CiaoPP. (`native/1`)

`sideff(G,X)` is side-effect `free`. (`sideff/2`)

`sideff(G,X)` is not checked during run-time checking. (`no_rtcheck/1`)

regtype/1: PROPERTY

Usage: `regtype(G)`

Defines a regular type.

Meta-predicate with arguments: `regtype(goal)`.

Other properties:

`regtype(G)`

– *The following properties hold globally:*

`regtype(G)` is side-effect `free`. (`sideff/2`)

native/1: PROPERTY

Usage: `native(Pred)`

This predicate is understood natively by CiaoPP.

Meta-predicate with arguments: `native(goal)`.

Other properties:

`native(P)`

– *The following properties hold globally:*

`native(P)` is side-effect `free`. (`sideff/2`)

native/2: PROPERTY

Usage: `native(Pred,Key)`

This predicate is understood natively by CiaoPP as `Key`.

Meta-predicate with arguments: `native(goal,?)`.

Other properties:

`native(P,K)`

– *The following properties hold globally:*

`native(P,K)` is side-effect `free`. (`sideff/2`)

rtcheck/1: PROPERTY

Usage: `rtcheck(G)`

Equivalent to rtcheck(G, complete).

– *If the following properties should hold at call time:*

`G` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)

Meta-predicate with arguments: `rtcheck(goal)`.

Other properties:

`rtcheck(G)`

– *The following properties hold globally:*

`rtcheck(G)` is side-effect `free`. (`sideff/2`)

rtcheck/2: PROPERTY

Usage: `rtcheck(G,Status)`

The runtime check of this property is `Status`.

– *If the following properties should hold at call time:*

`G` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)

`Status` is the status of the runtime-check implementation for a given property. Valid values are:

- complete: The implementation of the run-time check for this property is complete. i.e., an error is reported always if the property is violated. Default.
- incomplete: The current run-time check is incomplete, i.e., it is possible that no error is reported even if the property is violated.
- unimplemented: No run-time checker has been implemented (yet) for the property.
- unknown: It has not been determined yet whether the current implementation of the run-time checker is complete or not.
- impossible: The property cannot be checked at run time (for theoretical or practical reasons).

(`rtc_status/1`)

Meta-predicate with arguments: `rtcheck(goal,?)`.

Other properties:

`rtcheck(G,Status)`

– *The following properties hold globally:*

`rtcheck(G,Status)` is side-effect `free`. (`sideff/2`)

no_rtcheck/1: PROPERTY

This comp pseudo-property is used to declare that the assertion in which it appears should not be checked at run-time. Equivalent to `rtcheck(G, S)` with `S` unimplemented, impossible, etc.

Usage: `no_rtcheck(G)`

`G` is not checked during run-time checking.

– *If the following properties should hold at call time:*

`G` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)

Meta-predicate with arguments: `no_rtcheck(goal)`.

Other properties:

`no_rtcheck(G)`

– *The following properties hold globally:*

`no_rtcheck(G)` is side-effect `free`. (`sideff/2`)

eval/1: PROPERTY

Usage: `eval(Goal)`

`Goal` is evaluable at compile-time.

Meta-predicate with arguments: `eval(goal)`.

equiv/2: PROPERTY

Usage: `equiv(Goal1,Goal2)`

`Goal1` is equivalent to `Goal2`.

Meta-predicate with arguments: `equiv(goal,goal)`.

bind_ins/1: PROPERTY

Usage: `bind_ins(Goal)`

`Goal` is binding insensitive.

Meta-predicate with arguments: `bind_ins(goal)`.

error_free/1: PROPERTY

Usage: `error_free(Goal)`

`Goal` is error free.

Meta-predicate with arguments: `error_free(goal)`.

memo/1: PROPERTY

Usage: `memo(Goal)`

`Goal` should be memoized (not unfolded).

Meta-predicate with arguments: `memo(goal)`.

filter/2: PROPERTY

Usage: `filter(Vars,Goal)`

`Vars` should be filtered during global control).

flag_values/1: REGTYPE

Usage: `flag_values(X)`

Define the valid flag values

pe_type/1: PROPERTY

Usage: `pe_type(Goal)`

`Goal` will be filtered in partial evaluation time according to the PE types defined in the assertion.

Meta-predicate with arguments: `pe_type(goal)`.

check/1: PREDICATE

No further documentation available for this predicate.

trust/1: PREDICATE

No further documentation available for this predicate.

true/1: PREDICATE

No further documentation available for this predicate.

false/1: PREDICATE

No further documentation available for this predicate.

55.3 Documentation on imports

This module has the following direct dependencies:

– *System library modules:*

`native_props`, `terms_check`.

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `hiord_rt`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `nortchecks`, `nativeprops`.

56 Properties which are native to analyzers

Author(s): Francisco Bueno, Manuel Hermenegildo, Pedro López, Edison Mera, Amadeo Casas, Jose F. Morales.

This library contains a set of properties which are natively understood by the different program analyzers of `ciaopp`. They are used by `ciaopp` on output and they can also be used as properties in assertions.

Some of the properties can also be used as runtime-checks. See `native_props_rtc` for the runtime-check implementation of such properties.

57 Properties related to sharing/aliasing, groundness

These properties are part of the `native_props` library.

57.1 Usage and interface

- **Library usage:**
  `:- use_module(library(assertions/native_props))`
  or also as a package `:- use_package(nativeprops)`.
  Note the slightly different names of the library and the package.
- **Exports:**
  - *Properties:*
    `mshare/1`, `mshare/2`, `indep/2`, `indep/1`, `covered/2`, `linear/1`, `ivar/1`, `nonground/1`, `clique/1`, `clique_1/1`.

57.2 Documentation on exports

mshare/1: PROPERTY

`mshare(X)`

`X` contains all *sharing sets* [JL88, MH89b] which specify the possible variable occurrences in the terms to which the variables involved in the clause may be bound. Sharing sets are a compact way of representing groundness of variables and dependencies between variables. This representation is however generally difficult to read for humans. For this reason, this information is often translated to `ground/1`, `indep/1` and `indep/2` properties, which are easier to read.

Usage: `mshare(X)`

The sharing pattern for the variables in the clause is `X`.

- *The following properties should hold globally:*
  This predicate is understood natively by CiaoPP as `sharing(X)`. (`native/2`)
  `mshare(X)` is not checked during run-time checking. (`no_rtcheck/1`)

mshare/2: PROPERTY

Usage: `mshare(Xs,Xss)`

The sharing pattern for the variables `Xs` is `Xss`.

- *The following properties should hold globally:*
  This predicate is understood natively by CiaoPP as `sharing(Xs,Xss)`. (`native/2`)
  `mshare(Xs,Xss)` is not checked during run-time checking. (`no_rtcheck/1`)

indep/2: PROPERTY

Usage: `indep(X,Y)`

`X` and `Y` do not have variables in common.

- *The following properties should hold globally:*
  This predicate is understood natively by CiaoPP as `indep([[X,Y]])`. (`native/2`)

indep/1: PROPERTY

Usage: `indep(X)`

The variables in the the pairs in `X` are pairwise independent.

– *The following properties should hold globally:*

This predicate is understood natively by CiaoPP as `indep(X)`. (`native/2`)

covered/2: PROPERTY

`covered(X,Y)`

All variables occuring in `X` occur also in `Y`. Used by the non-strict independence-based annotators.

Usage: `covered(X,Y)`

`X` is covered by `Y`.

– *The following properties should hold globally:*

This predicate is understood natively by CiaoPP. (`native/1`)

linear/1: PROPERTY

`linear(X)`

`X` is bound to a term which is linear, i.e., if it contains any variables, such variables appear only once in the term. For example, `[1,2,3]` and `f(A,B)` are linear terms, while `f(A,A)` is not.

Usage: `linear(X)`

`X` is instantiated to a linear term.

– *The following properties should hold globally:*

This predicate is understood natively by CiaoPP. (`native/1`)

ivar/1: PROPERTY

`ivar(X)`

`X` is a free variable independent of the rest of the variables appearing in the head of the predicate.

For a predicate `p(X0, ..., Xn)`, `ivar(X0)` conceptually expands to `(var(X0), indep([[X0,X1], ..., [X0,Xn]]))`.

Usage: `ivar(X)`

`X` is a free independent variable.

nonground/1: PROPERTY

Usage: `nonground(X)`

`X` is not ground.

– *The following properties should hold globally:*

This predicate is understood natively by CiaoPP as `not_ground(X)`. (`native/2`)

clique/1: PROPERTY

`clique(X)`

`X` is a set of variables of interest, much the same as a sharing group but `X` represents all the sharing groups in the powerset of those variables. Similar to a sharing group, a clique is often translated to `ground/1`, `indep/1`, and `indep/2` properties.

Usage: `clique(X)`

The clique sharing pattern is `X`.

– *The following properties should hold globally:*

This predicate is understood natively by CiaoPP as `clique(X)`. (`native/2`)

`clique(X)` is not checked during run-time checking. (`no_rtcheck/1`)

clique_1/1: PROPERTY

`clique_1(X)`

`X` is a set of variables of interest, much the same as a sharing group but `X` represents all the sharing groups in the powerset of those variables but disregarding the singletons. Similar to a sharing group, a clique_1 is often translated to `ground/1`, `indep/1`, and `indep/2` properties.

Usage: `clique_1(X)`

The 1-clique sharing pattern is `X`.

– *The following properties should hold globally:*

This predicate is understood natively by CiaoPP as `clique_1(X)`. (`native/2`)

`clique_1(X)` is not checked during run-time checking. (`no_rtcheck/1`)

57.3 Documentation on imports

This module has the following direct dependencies:

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `regtypes`.

58 Properties related to determinacy, failure, choice-points

These properties are part of the `native_props` library.

58.1 Usage and interface

- **Library usage:**
  `:- use_module(library(assertions/native_props))`
  or also as a package `:- use_package(nativeprops)`.
  Note the slightly different names of the library and the package.
- **Exports:**
  - *Properties:*
    `det/1`, `fails/1`, `semidet/1`, `multi/1`, `nondet/1`, `mut_exclusive/1`, `not_mut_exclusive/1`, `possibly_not_mut_exclusive/1`, `covered/1`, `not_covered/1`, `possibly_not_covered/1`, `no_choicepoints/1`, `leaves_choicepoints/1`, `is_det/1`, `non_det/1`, `possibly_nondet/1`, `not_fails/1`, `possibly_fails/1`.

58.2 Documentation on exports

det/1: PROPERTY

`det(X)`

Calls of the form `X` are deterministic, i.e., produce exactly one solution (or do not terminate).

Note that it can still leave choice points after its execution, but when backtracking into these, it can only fail or go into an infinite loop.

These properties are inferred and checked natively by CiaoPP using the domains and techniques of [LGBH05, LGBH10, DLGH97, BLGH04].

Usage: `det(X)`

Calls of the form `X` are deterministic.

Meta-predicate with arguments: `det(goal)`.

fails/1: PROPERTY

`fails(X)`

Calls of the form `X` fail.

Usage: `fails(X)`

Calls of the form `X` fail.

- *The following properties should hold globally:*
  This predicate is understood natively by CiaoPP. (`native/1`)

Meta-predicate with arguments: `fails(goal)`.

semidet/1: PROPERTY

`semidet(X)`

Calls of the form `X` are semi-deterministic, i.e., produce at most one solution (or do not terminate).

Note that it can still leave choice points after its execution, but when backtracking into these, it can only fail or go into an infinite loop.

These properties are inferred and checked natively by CiaoPP using the domains and techniques of [LGBH05, LGBH10, DLGH97, BLGH04].

Usage: `semidet(X)`

Calls of the form `X` are semi-deterministic.

Meta-predicate with arguments: `semidet(goal)`.

multi/1: PROPERTY

`multi(X)`

Calls of the form `X` are multi-deterministic, i.e., they produce one or more solutions and do not fail.

Usage: `multi(X)`

Calls of the form `X` are multi-deterministic.

Meta-predicate with arguments: `multi(goal)`.

nondet/1: PROPERTY

`nondet(X)`

Nothing is ensured about failure and determinacy of calls to `X`. This is the default when no information is given for a predicate, so this property does not need to be stated explicitly.

Usage: `nondet(X)`

Calls of the form `X` are non-deterministic.

– *The following properties should hold globally:*

`nondet(X)` is not checked during run-time checking. (`no_rtcheck/1`)

Meta-predicate with arguments: `nondet(goal)`.

mut_exclusive/1: PROPERTY

`mut_exclusive(X)`

For any call of the form `X` there is at most one clause whose test (guard) succeeds, i.e., clause tests are pairwise exclusive. Note that determinacy is the transitive closure (to all called predicates) of this property. This property is inferred and checked natively by CiaoPP using the domains and techniques of [LGBH05, LGBH10].

Usage: `mut_exclusive(X)`

For any call of the form `X` at most one clause test succeeds.

– *The following properties should hold globally:*

The runtime check of this property is `unimplemented`. (`rtcheck/2`)

Meta-predicate with arguments: `mut_exclusive(goal)`.

not_mut_exclusive/1: PROPERTY

`not_mut_exclusive(X)`

For calls of the form `X` more than one clause test may succeed. I.e., clause tests are not disjoint for some call.

Usage: `not_mut_exclusive(X)`

For some calls of the form `X` more than one clause test may succeed.

– *The following properties should hold globally:*

The runtime check of this property is `unimplemented`. (`rtcheck/2`)

Meta-predicate with arguments: `not_mut_exclusive(goal)`.

possibly_not_mut_exclusive/1: PROPERTY

`possibly_not_mut_exclusive(X)`

Mutual exclusion of the clause tests for calls of the form `X` cannot be ensured. This is the default when no information is given for a predicate, so this property does not need to be stated explicitly.

Usage: `possibly_not_mut_exclusive(X)`

Mutual exclusion is not ensured for calls of the form `X`.

– *The following properties should hold globally:*

`possibly_not_mut_exclusive(X)` is not checked during run-time checking. (`no_rtcheck/1`)

Meta-predicate with arguments: `possibly_not_mut_exclusive(goal)`.

covered/1: PROPERTY

`covered(X)`

For any call of the form `X` there is at least one clause whose test (guard) succeeds (i.e., all the calls of the form `X` are covered). Note that nonfailure is the transitive closure (to all called predicates) of this property. [DLGH97, BLGH04].

Usage: `covered(X)`

All the calls of the form `X` are covered.

– *The following properties should hold globally:*

The runtime check of this property is `unimplemented`. (`rtcheck/2`)

Meta-predicate with arguments: `covered(goal)`.

not_covered/1: PROPERTY

`not_covered(X)`

There is some call of the form `X` for which there is no clause whose test succeeds [DLGH97].

Usage: `not_covered(X)`

Not all of the calls of the form `X` are covered.

– *The following properties should hold globally:*

The runtime check of this property is `unimplemented`. (`rtcheck/2`)

Meta-predicate with arguments: `not_covered(goal)`.

possibly_not_covered/1: PROPERTY

`possibly_not_covered(X)`

Covering is not ensured for any call of the form `X`. In other words, nothing can be ensured about covering of such calls.

Usage: `possibly_not_covered(X)`

Covering is not ensured for calls of the form `X`.

– *The following properties should hold globally:*

`possibly_not_covered(X)` is not checked during run-time checking. (`no_rtcheck/1`)

Meta-predicate with arguments: `possibly_not_covered(goal)`.

no_choicepoints/1: PROPERTY

Usage: `no_choicepoints(X)`

A call to `X` does not leave new choicepoints.

Meta-predicate with arguments: `no_choicepoints(goal)`.

leaves_choicepoints/1: PROPERTY

Usage: `leaves_choicepoints(X)`

A call to `X` leaves new choicepoints.

Meta-predicate with arguments: `leaves_choicepoints(goal)`.

is_det/1: PROPERTY

`is_det(X)`

All calls of the form `X` are deterministic, i.e., produce at most one solution (or do not terminate). In other words, if `X` succeeds, it can only succeed once. It can still leave choice points after its execution, but when backtracking into these, it can only fail or go into an infinite loop. This property is inferred and checked natively by CiaoPP using the domains and techniques of [LGBH05, LGBH10].

Usage: `is_det(X)`

All calls of the form `X` are deterministic.

Meta-predicate with arguments: `is_det(goal)`.

non_det/1: PROPERTY

`non_det(X)`

All calls of the form `X` are non-deterministic, i.e., they always produce more than one solution.

Usage: `non_det(X)`

All calls of the form `X` are non-deterministic.

Meta-predicate with arguments: `non_det(goal)`.

possibly_nondet/1: PROPERTY

`possibly_nondet(X)`

Non-determinism is not ensured for calls of the form `X`. In other words, nothing can be ensured about determinacy of such calls. This is the default when no information is given for a predicate, so this property does not need to be stated explicitly.

Usage: `possibly_nondet(X)`

Non-determinism is not ensured for calls of the form `X`.

– *The following properties should hold globally:*

`possibly_nondet(X)` is not checked during run-time checking. (`no_rtcheck/1`)

Meta-predicate with arguments: `possibly_nondet(goal)`.

not_fails/1: PROPERTY

`not_fails(X)`

Calls of the form `X` produce at least one solution (succeed), or do not terminate. This property is inferred and checked natively by CiaoPP using the domains and techniques of [DLGH97, BLGH04].

Usage: `not_fails(X)`

All the calls of the form `X` do not fail.

– *The following properties should hold globally:*

This predicate is understood natively by CiaoPP. (`native/1`)

Meta-predicate with arguments: `not_fails(goal)`.

possibly_fails/1: PROPERTY

`possibly_fails(X)`

Non-failure is not ensured for any call of the form `X`. In other words, nothing can be ensured about non-failure nor termination of such calls.

Usage: `possibly_fails(X)`

Non-failure is not ensured for calls of the form `X`.

– *The following properties should hold globally:*

`possibly_fails(X)` is not checked during run-time checking. (`no_rtcheck/1`)

Meta-predicate with arguments: `possibly_fails(goal)`.

58.3 Documentation on imports

This module has the following direct dependencies:

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `regtypes`.

59 Properties related to cardinality and exact solutions

These properties are part of the `native_props` library.

59.1 Usage and interface

- **Library usage:**
  `:- use_module(library(assertions/native_props))`
  or also as a package `:- use_package(nativeprops)`.
  Note the slightly different names of the library and the package.
- **Exports:**
  - *Properties:*
    `cardinality/3`, `num_solutions/2`, `relations/2`, `finite_solutions/1`, `solutions/2`.

59.2 Documentation on exports

cardinality/3: PROPERTY

Usage: `cardinality(Goal,Lower,Upper)`

`Goal` has a number of solutions between `Lower` and `Upper`.

- *The following properties should hold globally:*
  `cardinality(Goal,Lower,Upper)` is not checked during run-time checking. (`no_rtcheck/1`)

Meta-predicate with arguments: `cardinality(goal,?,?)`.

num_solutions/2: PROPERTY

Usage 1: `num_solutions(X,N)`

Calls of the form `X` have `N` solutions, i.e., `N` is the cardinality of the solution set of `X`.

- *If the following properties should hold at call time:*
  `X` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)
  `N` is an integer. (`int/1`)

Usage 2: `num_solutions(Goal,Check)`

For a call to `Goal`, `Check(X)` succeeds, where `X` is the number of solutions.

- *If the following properties should hold at call time:*
  `Goal` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)
  `Check` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)

relations/2: PROPERTY

`relations(X,N)`

Calls of the form `X` produce `N` solutions, i.e., `N` is the cardinality of the solution set of `X`.

Usage: `relations(X,N)`

Goal `X` produces `N` solutions.

– *If the following properties should hold at call time:*
`X` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)
`N` is an integer. (`int/1`)
then the following properties should hold globally:
The runtime check of this property is `unimplemented`. (`rtcheck/2`)

Meta-predicate with arguments: `relations(goal,?)`.

finite_solutions/1: PROPERTY

`finite_solutions(X)`

Calls of the form `X` produce a finite number of solutions [DLGH97].

Usage: `finite_solutions(X)`

All the calls of the form `X` have a finite number of solutions.

– *The following properties should hold globally:*
`finite_solutions(X)` is not checked during run-time checking. (`no_rtcheck/1`)

Meta-predicate with arguments: `finite_solutions(goal)`.

solutions/2: PROPERTY

Usage: `solutions(Goal,Sols)`

Goal `Goal` produces the solutions listed in `Sols`.

– *If the following properties should hold at call time:*
`Goal` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)
`Sols` is a list. (`list/1`)

59.3 Documentation on imports

This module has the following direct dependencies:

– *Internal (engine) modules:*
`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`.

– *Packages:*
`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `regtypes`.

60 Properties related to exceptions and signals

These properties are part of the `native_props` library.

60.1 Usage and interface

- **Library usage:**
  `:- use_module(library(assertions/native_props))`
  or also as a package `:- use_package(nativeprops)`.
  Note the slightly different names of the library and the package.
- **Exports:**
  - *Properties:*
    `exception/1`, `exception/2`, `possible_exceptions/2`, `no_exception/1`, `no_exception/2`, `signal/1`, `signal/2`, `possible_signals/2`, `no_signal/1`, `no_signal/2`.

60.2 Documentation on exports

exception/1: PROPERTY

Usage: `exception(Goal)`

Calls of the form `Goal` will throw an (unspecified) exception.

Meta-predicate with arguments: `exception(goal)`.

exception/2: PROPERTY

Usage: `exception(Goal,E)`

Calls to `Goal` will throw an exception that unifies with `E`.

Meta-predicate with arguments: `exception(goal,?)`.

possible_exceptions/2: PROPERTY

Usage: `possible_exceptions(Goal,Es)`

Calls of the form `Goal` may throw exceptions, but only the ones that unify with the terms listed in `Es`.

- *If the following properties should hold at call time:*
  `Es` is a list. (`list/1`)
  then the following properties should hold globally:
  The runtime check of this property is `unimplemented`. (`rtcheck/2`)

Meta-predicate with arguments: `possible_exceptions(goal,?)`.

no_exception/1: PROPERTY

Usage: `no_exception(Goal)`

Calls of the form `Goal` do not throw any exception.

Meta-predicate with arguments: `no_exception(goal)`.

no_exception/2: PROPERTY

Usage: `no_exception(Goal,E)`

Calls of the form `Goal` do not throw any exception that unifies with `E`.

Meta-predicate with arguments: `no_exception(goal,?)`.

signal/1: PROPERTY

Usage: `signal(Goal)`

Calls to `Goal` will send an (unspecified) signal.

Meta-predicate with arguments: `signal(goal)`.

signal/2: PROPERTY

Usage: `signal(Goal,E)`

Calls to `Goal` will send a signal that unifies with `E`.

Meta-predicate with arguments: `signal(goal,?)`.

possible_signals/2: PROPERTY

Usage: `possible_signals(Goal,Es)`

Calls of the form `Goal` may generate signals, but only the ones that unify with the terms listed in `Es`.

– *The following properties should hold globally:*
  The runtime check of this property is `unimplemented`. (`rtcheck/2`)

Meta-predicate with arguments: `possible_signals(goal,?)`.

no_signal/1: PROPERTY

Usage: `no_signal(Goal)`

Calls of the form `Goal` do not send any signal.

Meta-predicate with arguments: `no_signal(goal)`.

no_signal/2: PROPERTY

Usage: `no_signal(Goal,E)`

Calls of the form `Goal` do not send any signals that unify with `E`.

Meta-predicate with arguments: `no_signal(goal,?)`.

60.3 Documentation on imports

This module has the following direct dependencies:

– *Internal (engine) modules:*
`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`.

– *Packages:*
`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `regtypes`.

61 Properties related to side effects

These properties are part of the `native_props` library.

61.1 Usage and interface

- **Library usage:**
  `:- use_module(library(assertions/native_props))`
  or also as a package `:- use_package(nativeprops)`.
  Note the slightly different names of the library and the package.
- **Exports:**
  - *Properties:*
    `sideff_pure/1`, `sideff_soft/1`, `sideff_hard/1`.

61.2 Documentation on exports

sideff_pure/1: PROPERTY

Usage: `sideff_pure(X)`

`X` is pure, i.e., has no side-effects.

- *The following properties should hold globally:*
  `sideff_pure(X)` is not checked during run-time checking. (`no_rtcheck/1`)

Meta-predicate with arguments: `sideff_pure(goal)`.

sideff_soft/1: PROPERTY

Usage: `sideff_soft(X)`

`X` has *soft side-effects*, i.e., those not affecting program execution (e.g., input/output).

- *The following properties should hold globally:*
  `sideff_soft(X)` is not checked during run-time checking. (`no_rtcheck/1`)

Meta-predicate with arguments: `sideff_soft(goal)`.

sideff_hard/1: PROPERTY

Usage: `sideff_hard(X)`

`X` has *hard side-effects*, i.e., those that might affect program execution (e.g., assert/retract).

- *The following properties should hold globally:*
  `sideff_hard(X)` is not checked during run-time checking. (`no_rtcheck/1`)

Meta-predicate with arguments: `sideff_hard(goal)`.

61.3 Documentation on imports

This module has the following direct dependencies:

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `regtypes`.

62 Properties related to polyhedral constraints

These properties are part of the `native_props` library.

62.1 Usage and interface

- **Library usage:**
  `:- use_module(library(assertions/native_props))`
  or also as a package `:- use_package(nativeprops)`.
  Note the slightly different names of the library and the package.
- **Exports:**
  - *Properties:*
    `constraint/1`.

62.2 Documentation on exports

constraint/1: PROPERTY

`constraint(C)`

`C` contains a list of linear (in)equalities that relate variables and `int` values. For example, `[A < B + 4]` is a constraint while `[A < BC + 4]` or `[A = 3.4, B >= C]` are not. Used by polyhedra-based analyses.

Usage: `constraint(C)`

`C` is a list of linear equations.

- *The following properties should hold globally:*
  This predicate is understood natively by CiaoPP. (`native/1`)

62.3 Documentation on imports

This module has the following direct dependencies:

- *Internal (engine) modules:*
  `term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`.
- *Packages:*
  `prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `regtypes`.

63 Properties related to data sizes, cost, termination

These properties are part of the `native_props` library.

63.1 Usage and interface

- **Library usage:**
  `:- use_module(library(assertions/native_props))`
  or also as a package `:- use_package(nativeprops)`.
  Note the slightly different names of the library and the package.
- **Exports:**
  - *Properties:*
    `resource_id/1`, `size/2`, `size/3`, `size/4`, `size_lb/2`, `size_ub/2`, `size_o/2`, `size_metric/3`, `size_metric/4`, `steps_lb/2`, `steps_ub/2`, `steps/2`, `steps_o/2`, `rsize/2`, `costb/4`, `cost/4`, `terminates/1`.
  - *Regular Types:*
    `approx/1`, `cost_expression/1`, `agg_expression/1`, `numeric_constant/1`, `size_term/1`, `indexvar/1`, `number_lattice/1`, `measure_t/1`.

63.2 Documentation on exports

approx/1: REGTYPE

The types of approximations (bounding) supported by the size and cost analyses (see also `resources_basic.pl`).

- `ub`: for upper bounds.
- `lb`: for lower bounds.
- `exact`: for an exact expression.
- `o`: for the big-O.

Usage: `approx(X)`

`X` represents an approximation.

resource_id/1: PROPERTY

A resource is a numerical property that varies (is used) throughout the execution of a piece of code. Resources can be predefined (i.e., in a library) or user-defined. Examples are computational (resolution) steps, time spent, energy consumed, memory usage, bytes sent over a wire, procedure calls, database operations, files left open, monetary units spent, disk space used, etc. See also `resources_decl`.

Usage: `resource_id(X)`

`X` is the name/identifier of a resource, either an atom or a compound term.

cost_expression/1: REGTYPE

A cost expression is a symbolic function representing the cost of executing a piece of code in terms of the sizes of its input arguments and possibly other parameters. It is a term built from elements of the lattice of real numbers (see `number_lattice`), numerical constants (see `numeric_constant/1`), size metrics (see `size_metric`) and the following functors:

- `- /1`: sign reversal.
- `+ /1`: identity.
- `-- /1`: decrement by one.
- `++ /1`: increment by one.
- `+ /2`: addition.
- `- /2`: subtraction.
- `* /2`: multiplication.
- `/ /2`: division.
- `** /2`: exponentiation.
- `exp/2`: exponentiation (DEPRECATED use `** /2`).
- `log/2`: logarithm given the base.
- `log10/1`: 10-base logarithm.
- `log2/1`: 2-base logarithm.
- `exp/1`: exponential (e to the power of).
- `log/1`: natural logarithm (base e).
- `sqrt/1`: square root.
- `fact/1`: factorial.
- `max/2`: maximum.
- `min/2`: minimum.
- `sum(Index,LowerBound,UpperBound,Exp)`: summation of all `Exp`s obtained by instantiating index variable `Index` from `LowerBound` to `UpperBound`.
- `prod(Index,LowerBound,UpperBound,Exp)`: product of all `Exp`s obtained by instantiating index variable `Index` from `LowerBound` to `UpperBound`.

Usage: `cost_expression(X)`

`X` is a cost expression.

agg_expression/1: REGTYPE

An aggregation expression is an expression appearing in an aggregation function (`sum/4`, `prod/4`). An aggregation expression can be a regular cost expression (see `cost_expression/1`) or it may include index variables as well (see `indexvar/1`).

Usage: `agg_expression(X)`

`X` is an aggregation expression.

numeric_constant/1: REGTYPE

A numeric constant is a fixed, well-defined real number.

Currently supported constants:

- `e`: Euler's number.

Usage: `numeric_constant(X)`

`X` represents a numeric constant.

size_term/1: REGTYPE

A size term is a term in a cost expression (see `cost_expression/1`) representing the size of a term in a given metric (see `measure_t/1`).

Usage: `size_term(X)`

`X` represents the size of a term.

indexvar/1: REGTYPE

A variable used as an index in an aggregation expression.

Usage: `indexvar(X)`

`X` is an index variable.

number_lattice/1: REGTYPE

A lattice containing real numbers, `inf` and `bot`.

Usage: `number_lattice(X)`

`X` is a number, `inf` or `bot`.

size/2: PROPERTY

`size(X,Y)`

The exact size (for any approximation) of term `X` is given by expression `Y`, which may depend on the size of other terms. `size(X,Y)` is equivalent to `size(exact,X,Y)`.

Usage: `size(X,Y)`

`Y` is the size of argument `X`, for any approximation.

– *If the following properties should hold at call time:*

`X` is any term. (`term/1`)

`Y` is a cost expression. (`cost_expression/1`)

then the following properties should hold globally:

`size(X,Y)` is not checked during run-time checking. (`no_rtcheck/1`)

size/3: PROPERTY

`size(A,X,Y)`

The size of term `X` for the approximation `A` is given by expression `Y`, which may depend on the size of other terms.

Usage: `size(A,X,Y)`

`Y` is the size of argument `X`, for the approximation `A`.

– *If the following properties should hold at call time:*

`A` represents an approximation. (`approx/1`)

`X` is any term. (`term/1`)

`Y` is a cost expression. (`cost_expression/1`)

then the following properties should hold globally:

`size(A,X,Y)` is not checked during run-time checking. (`no_rtcheck/1`)

size/4: PROPERTY

`size(A,M,X,Y)`

The size of term `X`, measured in metric `M`, for the approximation `A` is given by expression `Y`, which may depend on the size of other terms.

Usage: `size(A,M,X,Y)`

`Y` is the size of argument `X` measured in `M`, for the approximation `A`.

– *If the following properties should hold at call time:*

`A` represents an approximation. (`approx/1`)

`M` is a term size metric. (`measure_t/1`)

`X` is any term. (`term/1`)

`Y` is a cost expression. (`cost_expression/1`)

then the following properties should hold globally:

`size(A,M,X,Y)` is not checked during run-time checking. (`no_rtcheck/1`)

size_lb/2: PROPERTY

`size_lb(X,Y)`

The minimum size of the terms to which the argument `X` is bound is given by the expression `Y`. Various measures can be used to determine the size of an argument, e.g., list-length, term-size, term-depth, integer-value, etc. [DL93, LGHD96]. See `measure_t/1`.

Usage: `size_lb(X,Y)`

`Y` is a lower bound on the size of argument `X`.

– *If the following properties should hold at call time:*

`X` is any term. (`term/1`)

`Y` is a cost expression. (`cost_expression/1`)

then the following properties should hold globally:

`size_lb(X,Y)` is not checked during run-time checking. (`no_rtcheck/1`)

size_ub/2: PROPERTY

`size_ub(X,Y)`

The maximum size of the terms to which the argument `X` is bound is given by the expression `Y`. Various measures can be used to determine the size of an argument, e.g., list-length, term-size, term-depth, integer-value, etc. [DL93, LGHD96]. See `measure_t/1`.

Usage: `size_ub(X,Y)`

`Y` is a upper bound on the size of argument `X`.

– *If the following properties should hold at call time:*

`X` is any term. (`term/1`)

`Y` is a cost expression. (`cost_expression/1`)

then the following properties should hold globally:

`size_ub(X,Y)` is not checked during run-time checking. (`no_rtcheck/1`)

size_o/2: PROPERTY

Usage: `size_o(X,Y)`

The size of argument `X` is in the order of expression `Y`.

– *If the following properties should hold at call time:*

`X` is any term. (`term/1`)

`Y` is a cost expression. (`cost_expression/1`)

then the following properties should hold globally:

`size_o(X,Y)` is not checked during run-time checking. (`no_rtcheck/1`)

size_metric/3: PROPERTY

Usage: `size_metric(Head,Var,Metric)`

`Metric` is the measure used to determine the size of the terms that `Var` is bound to, for any type of approximation.

– *If the following properties should hold at call time:*

`Head` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)

`Var` is any term. (`term/1`)

`Metric` is a term size metric. (`measure_t/1`)

then the following properties should hold globally:

`size_metric(Head,Var,Metric)` is not checked during run-time checking. (`no_rtcheck/1`)

Meta-predicate with arguments: `size_metric(goal,?,?)`.

size_metric/4: PROPERTY

Usage: `size_metric(Head,Approx,Var,Metric)`

`Metric` is the measure used to determine the size of the terms that variable `Var` bound to, for the approximation `Approx`.

– *If the following properties should hold at call time:*

`Head` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)

`Approx` represents an approximation. (`approx/1`)

`Var` is any term. (`term/1`)

`Metric` is a term size metric. (`measure_t/1`)

then the following properties should hold globally:

`size_metric(Head,Approx,Var,Metric)` is not checked during run-time checking. (`no_rtcheck/1`)

Meta-predicate with arguments: `size_metric(goal,?,?,?)`.

measure_t/1: REGTYPE

The types of term size measures currently supported in size and cost analysis (see also in `resources_basic.pl`).

- `int`: The size of the term (which is an integer) is the integer value itself.
- `length`: The size of the term (which is a list) is its length.
- `size`: The size is the overall of the term (number of subterms).

- `depth([_|_])`: The size of the term is its depth.
- `void`: Used to indicate that the size of this argument should be ignored.

Usage: `measure_t(X)`

`X` is a term size metric.

steps_lb/2: PROPERTY

`steps_lb(X,Y)`

The minimum computation (in resolution steps) spent by any call of the form `X` is given by the expression `Y` [DLGHL97, LGHD96]

Usage: `steps_lb(X,Y)`

`Y` is a lower bound on the cost of any call of the form `X`.

– *If the following properties should hold at call time:*
`X` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)
`Y` is a cost expression. (`cost_expression/1`)
then the following properties should hold globally:
`steps_lb(X,Y)` is not checked during run-time checking. (`no_rtcheck/1`)

Meta-predicate with arguments: `steps_lb(goal,?)`.

steps_ub/2: PROPERTY

`steps_ub(X,Y)`

The maximum computation (in resolution steps) spent by any call of the form `X` is given by the expression `Y` [DL93, LGHD96].

Usage: `steps_ub(X,Y)`

`Y` is a upper bound on the cost of any call of the form `X`.

– *If the following properties should hold at call time:*
`X` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)
`Y` is a cost expression. (`cost_expression/1`)
then the following properties should hold globally:
`steps_ub(X,Y)` is not checked during run-time checking. (`no_rtcheck/1`)

Meta-predicate with arguments: `steps_ub(goal,?)`.

steps/2: PROPERTY

`steps(X,Y)`

The computation (in resolution steps) spent by any call of the form `X` is given by the expression `Y`

Usage: `steps(X,Y)`

`Y` is the cost (number of resolution steps) of any call of the form `X`.

– *If the following properties should hold at call time:*
`X` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)
`Y` is a cost expression. (`cost_expression/1`)
then the following properties should hold globally:
`steps(X,Y)` is not checked during run-time checking. (`no_rtcheck/1`)

Meta-predicate with arguments: `steps(goal,?)`.

steps_o/2: PROPERTY

`steps_o(X,Y)`

The big O expression of the computation (in resolution steps) spent by any call of the form `X` is given by the expression `Y`

Usage: `steps_o(X,Y)`

`Y` is the complexity order of the cost of any call of the form `X`.

– *If the following properties should hold at call time:*

`X` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)

`Y` is a cost expression. (`cost_expression/1`)

then the following properties should hold globally:

`steps_o(X,Y)` is not checked during run-time checking. (`no_rtcheck/1`)

Meta-predicate with arguments: `steps_o(goal,?)`.

rsize/2: PROPERTY

Usage: `rsize(Var,SizeDescr)`

`Var` has its size defined by `SizeDescr`.

– *The following properties should hold globally:*

`rsize(Var,SizeDescr)` is not checked during run-time checking. (`no_rtcheck/1`)

costb/4: PROPERTY

`costb(Goal,Resource,Lower,Upper)`

`Lower` (res. `Upper`) is a (safe) lower (res. upper) bound on the cost of the computation of `Goal` in terms of `Resource` units.

Usage: `costb(Goal,Resource,Lower,Upper)`

`Lower` (resp. `Upper`) is a (safe) lower (resp. upper) bound on the cost of the computation of `Goal` expressed in terms of `Resource` units.

– *If the following properties should hold at call time:*

`Goal` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)

`Resource` is the name/identifier of a resource, either an atom or a compound term. (`resource_id/1`)

`Lower` is a cost expression. (`cost_expression/1`)

`Upper` is a cost expression. (`cost_expression/1`)

then the following properties should hold globally:

`costb(Goal,Resource,Lower,Upper)` is not checked during run-time checking. (`no_rtcheck/1`)

Meta-predicate with arguments: `costb(goal,?,?,?)`.

cost/4: PROPERTY

`cost(Goal,Approx,Resource,Expr)`

`Expr` is a (safe) upper or lower bounds, depending on the value of `Approx` (see `approx/1`), of the cost of computation of the goal `Goal` in terms of `Resource` units.

Usage: `cost(Goal,Approx,Resource,Expr)`

`Expr` is a safe upper or lower bounds (depending on `Approx`) of the cost of computing `Goal` in terms of `Resource` units.

– *If the following properties should hold at call time:*

`Goal` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)

`Approx` represents an approximation. (`approx/1`)

`Resource` is the name/identifier of a resource, either an atom or a compound term. (`resource_id/1`)

`Expr` is a cost expression. (`cost_expression/1`)

then the following properties should hold globally:

`cost(Goal,Approx,Resource,Expr)` is not checked during run-time checking. (`no_rtcheck/1`)

Meta-predicate with arguments: `cost(goal,?,?,?)`.

terminates/1: PROPERTY

`terminates(X)`

Calls of the form `X` always terminate.

Usage: `terminates(X)`

All calls of the form `X` terminate.

– *If the following properties should hold at call time:*

`X` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)

then the following properties should hold globally:

`terminates(X)` is not checked during run-time checking. (`no_rtcheck/1`)

Meta-predicate with arguments: `terminates(goal)`.

63.3 Documentation on imports

This module has the following direct dependencies:

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `regtypes`.

64 Run-time checking of assertions

Author(s): Edison Mera, Nataliia Stulova.

Stability: [**beta**] Most of the functionality is there but it is still missing some testing and/or verification.

This package provides a complete implementation of run-time checks of predicate assertions. The program is instrumented to check such assertions at run time, and in case a property does not hold, the error is reported. Note that there is also an older package called rtchecks, by David Trallero. The advantage of this one is that it can be used independently of CiaoPP and also has updated functionality.

There are two main applications of run-time checks:

- To improve debugging of certain predicates, specifying some expected behavior that is checked at run-time with the assertions.
- To avoid manual implementation of run-time checks that should be done in some predicates, leaving the code clean and understandable.

64.1 Run-time checks configuration with flags

The run-time checks can be configured using prolog flags. Below we itemize the valid prolog flags with its values and a brief explanation of the meaning:

- `rtchecks_level`
  - `exports`: Only use rtchecks for external calls of the exported predicates.
  - `inner` : Use also rtchecks for internal calls. Default.
- `rtchecks_trust`
  - `no` : Disable rtchecks for trust assertions.
  - `yes` : Enable rtchecks for trust assertions. Default.
- `rtchecks_entry`
  - `no` : Disable rtchecks for entry assertions.
  - `yes` : Enable rtchecks for entry assertions. Default.
- `rtchecks_exit`
  - `no` : Disable rtchecks for exit assertions.
  - `yes` : Enable rtchecks for exit assertions. Default.
- `rtchecks_test`
  - `no` : Disable rtchecks for test assertions. Default.
  - `yes` : Enable rtchecks for test assertions. Used for debugging purposes, but is better to use the unittest library.
- `rtchecks_asrloc` Controls the usage of locators for the assertions in the error messages. The locator says the file and lines that contains the assertion that had failed. Valid values are:
  - `no` : Disabled.
  - `yes` : Enabled. Default.
- `rtchecks_predloc` Controls the usage of locators for the predicate that caused the run-time check error. The locator says the first clause of the predicate that the violated assertion refers to.
  - `no` : Disabled.
  - `yes` : Enabled, Default.
- `rtchecks_callloc`

  - `no` : Do not show the stack of predicates that caused the failure
  - `predicate`: Show the stack of predicates that caused the failure. Instrument it in the predicate. Default.
  - `literal` : Show the stack of predicates that caused the failure. Instrument it in the literal. This mode provides more information, because reports also the literal in the body of the predicate.
- `rtchecks_namefmt`
  - `long` : Show the name of predicates, properties and the values of the variables. Default.
  - `short` : Only show the name of the predicate in a reduced format.

64.2 Custom implementation for property checks

Note: this is a new feature and under active development. The documentation may be partial/obsolete.

The run-time check instrumentation can use custom property checks implementations. This is useful when defining native properties (without a clause-based definition supported by the default instrumentation) or when the generic run-time checks are not efficient enough. The custom implementation can be used specifically in run-time checks, while keeping a declarative version (which might be easier to read or is better understood by some static analyzer).

To provide the custom property implementation for run-time checking it is recommended to edit two files (suppose the original property is defined in a module `foo.pl`):

- the `foo_rtc.pl` module that contains the custom property implementation and is placed in the same folder as `foo.pl`. Make sure the custom property implementation is exported from both modules.
- `$CIAOROOT/core/lib/rtchecks/rtchecks_rt_propimpl.pl`, a database file that stores the links between different property implementations in the format of declarations '`:-rtc_impl(ModOr:PropOr/ArityOr, ModRt:PropRt/ArityRt).`' where `ModOr` and `ModRt` are names of the two modules that contain the original and the custom property definitions, `PropOr` and `PropRt` are the two different property implementations with respective arities `ArityOr` and `ArityRt`.

After these edits the `rtchecks` library needs to be rebuilt.

For an example of a system library that uses this feature see the `assertions/native_props` library.

64.3 Usage and interface

- **Library usage:**
  :- module(...,...,[...,rtchecks]).
- **Implicit imports:**
  - *Internal (engine) modules:*
    `term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`.
  - *Packages:*
    `prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`.

64.4 Other information

Note: the `assertions` package must always be included together with the `rtchecks` package (see `core/lib/compiler/global_module_options.pl` for details).

65 Applying assertions during fixpoint

Author(s): Isabel Garcia-Contreras.

This module contains the logic of what assertions need to be applied depending on the analysis step.

This module reads the values of the following flags:

- `fixp_stick_to_success`: whether to use the value of the success assertions instead of what was inferred for the fixpoint (not working for eterms).

  For a module:

  ```
  :- module(_,[p/1],[assertions]).

  :- pred p(X) => atm(X).
  p(X) :- X = a.
  ```

  If `fixp_stick_to_success` is set to `on`, the analysis result will be:

  ```
  :- module(_,[p/1],[assertions]).

  :- true pred p(X) => atm(X).
  p(X) :- X = a.
  ```

  Because the value of the assertion is used as it is. If it is set to `off`, it will use the assertion only when it allows to gain precision (useless in this case).

  ```
  :- module(_,[p/1],[assertions,regtypes]).

  :- true pred p(X) => rta(X).
  p(X) :- X = a.

  :- regtype rta/1.
  rta(a).
  ```

- `fixp_stick_to_calls`: **not implemented yet**, whether to use the value of the calls assertion instead of what was inferred by the fixpoint. This is harder than the success case since the heads of the analysis information may not be normalized.

  For example in the following module:

  ```
  :- module(_,[main/0,p/1],[assertions]).

  main :-
      p(a).

  :- pred p(X) : atm(X).
  p(X).
  ```

  Since the plai does not normalize heads it is imposible to generalize `p(a)` to `p(X) : atm(X)`, the variables that the abstract substitution approximates must be in the head. However `p(X) : rta(X)` can be generalized only by changing the abstract substitution because the variable is already in the head.

  The fixpoint would have to be modified so that applying assertions can change the goals

- `use_check_as_trust`: To activate the runtime semantics of the check assertions, i.e., use them as trust in the fixpoint.

Program point assertions are not processed here.

65.1 Usage and interface

- **Library usage:**
  `:- use_module(ciaopp(plai/apply_assertions)).`
- **Exports:**
  - *Predicates:*
    `call_asr/5`, `success_asr/6`, `cleanup_applied_assertions/1`, `apply_assrt_call_to_success/8`, `apply_assrt_exit/7`, `apply_assrt_no_source/6`, `get_call_assertions_asub/5`, `get_succ_assertion_asubs/7`, `add_success_asr/6`, `abs_normalize/8`, `get_applicable_status/3`.

65.2 Documentation on exports

call_asr/5: PREDICATE

No further documentation available for this predicate. The predicate is of type *data*.

success_asr/6: PREDICATE

No further documentation available for this predicate. The predicate is of type *data*.

cleanup_applied_assertions/1: PREDICATE

Cleans the cached assertions

apply_assrt_call_to_success/8: PREDICATE

Usage: `apply_assrt_call_to_success(AbsInt,Sg,Sv,Proj0,HvFv_u,Call,NewProj,NewCall)`

`NewProj` and `NewCall` are the result of applying the assertions that correspond to the `call_to_success` analysis point.

Currently, the implementation has only one option which is applying `true` and `trust` call assertions, and `true` success assertions (that are applicable to `Sg`:`Proj`).

- *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable.	(`nonvar/1`)
`Sg` is currently a term which is not a free variable.	(`nonvar/1`)
`Sv` is currently a term which is not a free variable.	(`nonvar/1`)
`Proj0` is currently a term which is not a free variable.	(`nonvar/1`)
`HvFv_u` is currently a term which is not a free variable.	(`nonvar/1`)
`Call` is currently a term which is not a free variable.	(`nonvar/1`)
`NewProj` is a free variable.	(`var/1`)
`NewCall` is a free variable.	(`var/1`)
`AbsInt` is an atom.	(`atm/1`)
`Sv` is a list.	(`list/1`)
`HvFv_u` is a list.	(`list/1`)

– *The following properties should hold globally:*
All the calls of the form `apply_assrt_call_to_success(AbsInt,Sg,Sv,Proj0,HvFv_u,Call,NewProj,NewCall)` do not fail. (`not_fails/1`)

apply_assrt_exit/7: PREDICATE

Usage: `apply_assrt_exit(AbsInt,Sg,Sv,Proj0,LPrime,NLPrime,Applied)`

– *The following properties should hold at call time:*
`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)
`Sg` is currently a term which is not a free variable. (`nonvar/1`)
`Sv` is currently a term which is not a free variable. (`nonvar/1`)
`Proj0` is currently a term which is not a free variable. (`nonvar/1`)
`LPrime` is currently a term which is not a free variable. (`nonvar/1`)
`NLPrime` is a free variable. (`var/1`)
`AbsInt` is an atom. (`atm/1`)
`Sv` is a list. (`list/1`)
`LPrime` is a list. (`list/1`)

– *The following properties should hold upon exit:*
`NLPrime` is a list. (`list/1`)

– *The following properties should hold globally:*
All the calls of the form `apply_assrt_exit(AbsInt,Sg,Sv,Proj0,LPrime,NLPrime,Applied)` do not fail. (`not_fails/1`)
All calls of the form `apply_assrt_exit(AbsInt,Sg,Sv,Proj0,LPrime,NLPrime,Applied)` are deterministic. (`is_det/1`)

apply_assrt_no_source/6: PREDICATE

Usage: `apply_assrt_no_source(SgKey,AbsInt,Sg,Sv,Proj,Prime)`

Succeeds if there are applicable assertions to `Sg:Proj` understood by domain `AbsInt` and `Prime` is the answer pattern.

– *The following properties should hold at call time:*
`SgKey` is currently a term which is not a free variable. (`nonvar/1`)
`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)
`Sg` is currently a term which is not a free variable. (`nonvar/1`)
`Sv` is currently a term which is not a free variable. (`nonvar/1`)
`Proj` is currently a term which is not a free variable. (`nonvar/1`)
`Prime` is a free variable. (`var/1`)
`SgKey` is an atom. (`atm/1`)
`AbsInt` is an atom. (`atm/1`)
`Sv` is a list. (`list/1`)

– *The following properties should hold upon exit:*
`Prime` is currently a term which is not a free variable. (`nonvar/1`)

get_call_assertions_asub/5: PREDICATE

Usage: `get_call_assertions_asub(Head,SgKey,Sts,AbsInt,AsrProj)`

– *The following properties should hold at call time:*

`Head` is currently a term which is not a free variable. (`nonvar/1`)

`AsrProj` is a free variable. (`var/1`)

`Sts` is a list. (`list/1`)

`SgKey` is an atom. (`atm/1`)

`AbsInt` is an atom. (`atm/1`)

– *The following properties should hold upon exit:*

`AsrProj` is currently a term which is not a free variable. (`nonvar/1`)

get_succ_assertion_asubs/7: PREDICATE

Usage: `get_succ_assertion_asubs(SgKey,Head,Hv,Sts,AbsInt,Proj,Prime)`

This predicate succeeds if there are assertions that are applicable to `Head:Proj` (normalized). If no `Sts` is specified all trusted status are returned

– *The following properties should hold at call time:*

`SgKey` is currently a term which is not a free variable. (`nonvar/1`)

`Head` is currently a term which is not a free variable. (`nonvar/1`)

`Hv` is currently a term which is not a free variable. (`nonvar/1`)

`Sts` is currently a term which is not a free variable. (`nonvar/1`)

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`Proj` is currently a term which is not a free variable. (`nonvar/1`)

`Prime` is a free variable. (`var/1`)

`SgKey` is an atom. (`atm/1`)

`Hv` is a list. (`list/1`)

`Sts` is a list. (`list/1`)

`AbsInt` is an atom. (`atm/1`)

– *The following properties should hold upon exit:*

`Prime` is currently a term which is not a free variable. (`nonvar/1`)

add_success_asr/6: PREDICATE

Usage: `add_success_asr(SgKey,Head,Sts,AbsInt,AsrProj,AsrPrime)`

Joins an abstract success pattern from an assertion with a previous value for the call pattern `Head:AsrProj`.

– *The following properties should hold at call time:*

`SgKey` is currently a term which is not a free variable. (`nonvar/1`)

`Head` is currently a term which is not a free variable. (`nonvar/1`)

`Sts` is currently a term which is not a free variable. (`nonvar/1`)

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`AsrProj` is currently a term which is not a free variable. (`nonvar/1`)

`AsrPrime` is currently a term which is not a free variable. (`nonvar/1`)

`SgKey` is an atom. (`atm/1`)

`Sts` is a list. (`list/1`)

`AbsInt` is an atom. (`atm/1`)

– *The following properties should hold globally:*
All the calls of the form `add_success_asr(SgKey,Head,Sts,AbsInt,AsrProj,AsrPrime)` do not fail. (`not_fails/1`)

abs_normalize/8: PREDICATE

Usage: `abs_normalize(AbsInt,Sg,Sv,ASub0,Head,Hv,ASub,ExtraInfo)`

– *The following properties should hold at call time:*
`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)
`Sg` is currently a term which is not a free variable. (`nonvar/1`)
`Sv` is currently a term which is not a free variable. (`nonvar/1`)
`ASub0` is currently a term which is not a free variable. (`nonvar/1`)
`ASub` is a free variable. (`var/1`)
`ExtraInfo` is a free variable. (`var/1`)
`AbsInt` is an atom. (`atm/1`)
`Sv` is a list. (`list/1`)

– *The following properties should hold upon exit:*
`ASub` is currently a term which is not a free variable. (`nonvar/1`)

– *The following properties should hold globally:*
All the calls of the form `abs_normalize(AbsInt,Sg,Sv,ASub0,Head,Hv,ASub,ExtraInfo)` do not fail. (`not_fails/1`)

get_applicable_status/3: PREDICATE

No further documentation available for this predicate.

65.3 Documentation on imports

This module has the following direct dependencies:

– *Application modules:*
`preprocess_flags`, `frontend_driver`, `fixpo_ops`, `apply_assertions_old`, `domains`, `plai_errors`.

– *System library modules:*
`datafacts_rt`, `native_props`, `terms_vars`, `aggregates`, `lists`, `assrt_lib`, `program_keys`, `p_unit`, `p_unit_db`.

– *Internal (engine) modules:*
`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`.

– *Packages:*
`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `isomodes`, `datafacts`, `nativeprops`, `.(notrace)`.

66 PART III - Extending CiaoPP

Author(s): The Ciao Development Team.

67 Adding a new analysis domain to CiaoPP

Author(s): The Ciao Development Team.

One of the most relevant features of the CiaoPP system is that it allows the addition of new analysis domains to the abstract interpretation-based framework in an easy way.

The next Chapter (Chapter 68 [Plug-in points for abstract domains], page 421) describes the module `domains.pl`, the general interface used by the analyzer for accessing the operations of the different domains implemented in the system. The developer of a new domain must edit this module, adding the necessary clauses to link the general interface with the specific operations of the new domain.

The procedure of adding a new domain is illustrated in Chapter 16 [Simple groundness abstract domain], page 103 by means of a simple abstract domain for groundness information inference. It includes a list of the predicates that need to be implemented by the developer in order to add the abstract domain to CiaoPP.

68 Plug-in points for abstract domains

Author(s): Maria Garcia de la Banda, Francisco Bueno, Jose F. Morales (aidomain package).

This module contains the predicates for selecting the abstract operations that correspond to an analysis domain. The selection depends on the name of the domain given as first argument to all predicates. Whenever a new domain is added to the system, a new clause for each predicate exported here will be needed to call the corresponding domain operation in the domain module. Some local operations used but not exported by this module would have to be defined, too. See the following chapter for an example domain module.

Adding an analysis domain to PLAI requires only changes in this module. However, in order for other CiaoPP operations to work, you may need to change other modules. See, for example, module `infer_dom`.

In this chapter, arguments referred to as `Sv`, `Hv`, `Fv`, `Qv`, `Vars` are lists of program variables and are supposed to always be sorted. Abstract substitutions are referred to as `ASub`, and are also supposed sorted (except where indicated), although this depends on the domain.

68.1 Variable naming convention for CiaoPP domains

Both in the PLAI fixpoints and domains, for simplicity, we use the following variable name meanings:

- `AbsInt` : identifier of the abstract interpreter being used.
- `Sg` : Subgoal being analysed.
- `SgKey` : Subgoal key (represented by functor/arity).
- `Head` : Head of the clause being analysed.
- `Sv` : Subgoal variables.
- `Hv` : Head variables.
- `Fv` : Free variables in the body of the clause being considered.
- `Vars` : Any possible set of variables.
- `Call` : Abstract call substitution.
- `Proj` : `Call` projected onto `Sv`.
- `Entry` : Abstract entry substitution (i.e. the abstract subtitution obtained after the abstract unification of `Sg` and `Head` projected onto `Hv + Fv`).
- `Exit` : Abstract exit substitution (i.e. the abstract subtitution obtained after the analysis of the clause being considered projected onto `Hv`).
- `Prime` : Abstract prime substitution (i.e. the abstract subtitution obtained after the analysis of the clause being considered projected onto `Sv`).
- `Succ` : Abstract success substitution (i.e. the abstract subtitution obtained after the analysis of the clause being considered extended to the variables of the clause in which Sg appears).
- `ASub` : Any possible abstract substitution.
- `R_flag` : Flag which represents the recursive characteristics of a predicate. It will be “nr” in case the predicate be non recursive. Otherwise it will be r (recursive).
- `List` : (can be represented as `OldList`,`List`,`AddList`,`IdList`,`NewList`) current the list of nodes which a given node depends on.
- `_s` : The suffix `_s` means that the term to which the variable is bound to has been sorted. By default they are always sorted thus `_s` is added only when it appears neccessary to say it explicitely.
- `_uns` : The suffix `_uns` means that the term to which the variable is bound is not sorted.
- `ExtraInfo`: Info computed during the `call_to_entry` that can be reused during the `exit_to_prime` step.

68.2 Usage and interface

- **Library usage:**
  `:- use_module(ciaopp(plai/domains)).`
- **Exports:**
  - *Predicates:*
    `init_abstract_domain/2`, `amgu/5`, `augment_asub/4`, `augment_two_asub/4`, `call_to_entry/10`, `exit_to_prime/8`, `project/5`, `project/6`, `needs/2`, `widencall/4`, `dual_widencall/4`, `widen/4`, `dual_widen/4`, `normalize_asub/3`, `compute_lub/3`, `compute_glb/3`, `identical_proj/5`, `identical_proj_1/7`, `identical_abstract/3`, `abs_sort/3`, `extend/6`, `less_or_equal_proj/5`, `less_or_equal/3`, `glb/4`, `eliminate_equivalent/3`, `abs_subset/3`, `call_to_success_fact/10`, `special_builtin/6`, `body_succ_builtin/9`, `success_builtin/7`, `obtain_info/5`, `info_to_asub/7`, `full_info_to_asub/5`, `asub_to_info/5`, `asub_to_native/6`, `concrete/4`, `unknown_call/5`, `unknown_entry/4`, `empty_entry/4`, `part_conc/5`, `multi_part_conc/4`, `collect_types_in_abs/4`, `rename_types_in_abs/4`, `dom_statistics/2`, `abstract_instance/5`, `contains_parameters/2`, `absub_eliminate_equivalent/3`, `absub_fixpoint_covered/3`, `body_builtin/9`, `undef_call_to_success_builtin/2`.
  - *Multifiles:*
    `aidomain/1`, `aidom.init_abstract_domain/2`, `aidom.amgu/5`, `aidom.augment_asub/4`, `aidom.augment_two_asub/4`, `aidom.call_to_entry/10`, `aidom.exit_to_prime/8`, `aidom.project/6`, `aidom.widencall/4`, `aidom.needs/2`, `aidom.widen/4`, `aidom.compute_lub/3`, `aidom.compute_clauses_lub/4`, `aidom.compute_clauses_glb/4`, `aidom.fixpoint_covered/3`, `aidom.fixpoint_covered_gfp/3`, `aidom.identical_abstract/3`, `aidom.abs_sort/3`, `aidom.extend/6`, `aidom.less_or_equal/3`, `aidom.glb/4`, `aidom.eliminate_equivalent/3`, `aidom.abs_subset/3`, `aidom.call_to_success_fact/10`, `aidom.special_builtin/6`, `aidom.combined_special_builtin0/3`, `aidom.body_succ_builtin/9`, `aidom.split_combined_domain/4`, `aidom.success_builtin/7`, `aidom.call_to_success_builtin/7`, `aidom.obtain_info/5`, `aidom.input_interface/5`, `aidom.input_user_interface/6`, `aidom.asub_to_native/6`, `aidom.concrete/4`, `aidom.unknown_call/5`, `aidom.unknown_entry/4`, `aidom.empty_entry/4`, `aidom.part_conc/5`, `aidom.multi_part_conc/4`, `aidom.collect_auxinfo_asub/4`, `aidom.rename_auxinfo_asub/4`, `aidom.dom_statistics/2`, `aidom.contains_parameters/2`.

68.3 Documentation on exports

init_abstract_domain/2: PREDICATE

`init_abstract_domain(AbsInt,PushedFlags)`

Initializes abstract domain `AbsInt`. Tells the list of modified (pushed) PP flags to pop afterwards.

amgu/5: PREDICATE

Usage: `amgu(AbsInt,Sg,Head,ASub,AMGU)`

Perform the abstract unification `AMGU` between `Sg` and `Head` given an initial abstract substitution `ASub` and abstract domain `AbsInt`.

– *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`Sg` is currently a term which is not a free variable. (`nonvar/1`)

`Head` is currently a term which is not a free variable. (`nonvar/1`)

`ASub` is currently a term which is not a free variable. (`nonvar/1`)

`AMGU` is a free variable. (`var/1`)

`AbsInt` is an atom. (`atm/1`)

– *The following properties should hold globally:*

All the calls of the form `amgu(AbsInt,Sg,Head,ASub,AMGU)` do not fail. (`not_fails/1`)

augment_asub/4: PREDICATE

`augment_asub(AbsInt,ASub,Vars,ASub0)`

Augment the abstract substitution `ASub` adding the variables `Vars` and then resulting the abstract substitution `ASub0`.

augment_two_asub/4: PREDICATE

`augment_two_asub(AbsInt,ASub0,ASub1,ASub)`

`ASub` is an abstract substitution resulting of augmenting two abstract substitutions: `ASub0` and `ASub1` whose domains are disjoint.

call_to_entry/10: PREDICATE

Usage:

`call_to_entry(AbsInt,Sv,Sg,Hv,Head,ClauseKey,Fv,Proj,Entry,ExtraInfo)`

Obtains the abstract substitution `Entry` which results from adding the abstraction of the unification `Sg` = `Head` to abstract substitution `Proj` (the call substitution for `Sg` projected on its variables `Sv`) and then projecting the resulting substitution onto `Hv` (the variables of `Head`) plus `Fv` (the free variables of the relevant clause). `ExtraInfo` is information which may be reused later in other abstract operations.

Assumtions: This predicate assumes that the variables in `Sv` and `Proj` are sorted (see sortedness for each domain).

.

– *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`Sv` is currently a term which is not a free variable. (`nonvar/1`)

`Sg` is currently a term which is not a free variable. (`nonvar/1`)

`Hv` is currently a term which is not a free variable. (`nonvar/1`)

`Head` is currently a term which is not a free variable. (`nonvar/1`)

`ClauseKey` is currently a term which is not a free variable. (`nonvar/1`)

`Fv` is currently a term which is not a free variable. (`nonvar/1`)

`Proj` is currently a term which is not a free variable. (`nonvar/1`)

`Entry` is a free variable. (`var/1`)

`ExtraInfo` is a free variable. (`var/1`)

`AbsInt` is an atom. (`atm/1`)

`Sv` is a list. (`list/1`)

`Hv` is a list. (`list/1`)

`Fv` is a list. (`list/1`)

– *The following properties should hold globally:*

All the calls of the form `call_to_entry(AbsInt,Sv,Sg,Hv,Head,ClauseKey,Fv,Proj,Entry,ExtraInfo)` do not fail. (`not_fails/1`)

All calls of the form `call_to_entry(AbsInt,Sv,Sg,Hv,Head,ClauseKey,Fv,Proj,Entry,ExtraInfo)` are deterministic. (`is_det/1`)

exit_to_prime/8: PREDICATE

Usage: `exit_to_prime(AbsInt,Sg,Hv,Head,Sv,Exit,ExtraInfo,Prime)`

Computes the abstract substitution `Prime` which results from adding the abstraction of the unification `Sg` = `Head` to abstract substitution `Exit` (the exit substitution for a clause `Head` projected over its variables `Hv`), projecting the resulting substitution onto `Sv`.

– *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`Sg` is currently a term which is not a free variable. (`nonvar/1`)

`Hv` is currently a term which is not a free variable. (`nonvar/1`)

`Head` is currently a term which is not a free variable. (`nonvar/1`)

`Sv` is currently a term which is not a free variable. (`nonvar/1`)

`Exit` is currently a term which is not a free variable. (`nonvar/1`)

`Prime` is a free variable. (`var/1`)

`AbsInt` is an atom. (`atm/1`)

`Hv` is a list of `var`s. (`list/2`)

`Sv` is a list of `var`s. (`list/2`)

– *The following properties should hold globally:*

All the calls of the form `exit_to_prime(AbsInt,Sg,Hv,Head,Sv,Exit,ExtraInfo,Prime)` do not fail. (`not_fails/1`)

project/5: PREDICATE

Usage: `project(AbsInt,Vars,HvFv_u,ASub,Proj)`

Projects the abstract substitution `ASub` onto the variables of list `Vars` resulting in the projected abstract substitution `Proj`.

– *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`Vars` is currently a term which is not a free variable. (`nonvar/1`)

`HvFv_u` is currently a term which is not a free variable. (`nonvar/1`)

`ASub` is currently a term which is not a free variable. (`nonvar/1`)

`Proj` is a free variable. (`var/1`)
`AbsInt` is an atom. (`atm/1`)
`Vars` is a list. (`list/1`)
`HvFv_u` is a list. (`list/1`)
`ASub` is any term. (`term/1`)
`Proj` is any term. (`term/1`)

– *The following properties should hold globally:*

All the calls of the form `project(AbsInt,Vars,HvFv_u,ASub,Proj)` do not fail. (`not_fails/1`)

All calls of the form `project(AbsInt,Vars,HvFv_u,ASub,Proj)` are deterministic. (`is_det/1`)

project/6: PREDICATE

Usage: `project(AbsInt,Sg,Vars,HvFv_u,ASub,Proj)`

Projects the abstract substitution `ASub` onto the variables of list `Vars` resulting in the projected abstract substitution `Proj`.

– *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)
`Sg` is currently a term which is not a free variable. (`nonvar/1`)
`Vars` is currently a term which is not a free variable. (`nonvar/1`)
`HvFv_u` is currently a term which is not a free variable. (`nonvar/1`)
`ASub` is currently a term which is not a free variable. (`nonvar/1`)
`Proj` is a free variable. (`var/1`)
`AbsInt` is an atom. (`atm/1`)
`Sg` is any term. (`term/1`)
`Vars` is a list. (`list/1`)
`HvFv_u` is a list. (`list/1`)
`ASub` is any term. (`term/1`)
`Proj` is any term. (`term/1`)

– *The following properties should hold globally:*

All the calls of the form `project(AbsInt,Sg,Vars,HvFv_u,ASub,Proj)` do not fail. (`not_fails/1`)

All calls of the form `project(AbsInt,Sg,Vars,HvFv_u,ASub,Proj)` are deterministic. (`is_det/1`)

needs/2: PREDICATE

Usage: `needs(AbsInt,Op)`

Succeeds if `AbsInt` needs operation `Op` for correctness/termination. It must only be used for checking, not enumerating. The supported operations are: `widen` (whether widening is necessary for termination), `clauses_lub` (whether the lub must be performed over the abstract substitution split by clase), `split_combined_domain` (whether the domain contains information of several domains and it needs to be split), and `aux_info` (whether the information in the abstract substitutions is not complete and an external solver may be needed, currently only used when outputing the analysis in a `.dump` file)

– *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`Op` is currently a term which is not a free variable. (`nonvar/1`)

– *The following properties should hold globally:*

All calls of the form `needs(AbsInt,Op)` are deterministic. (`is_det/1`)

widencall/4: PREDICATE

Usage: `widencall(AbsInt,ASub0,ASub1,ASub)`

`ASub` is the result of widening abstract substitution `ASub0` and `ASub1`, which are supposed to be consecutive call patterns in a fixpoint computation.

This predicate is allowed to fail and it fails if the domain does not define a widening on calls.

– *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`ASub0` is currently a term which is not a free variable. (`nonvar/1`)

`ASub1` is currently a term which is not a free variable. (`nonvar/1`)

`ASub` is a free variable. (`var/1`)

`AbsInt` is an atom. (`atm/1`)

dual_widencall/4: PREDICATE

`dual_widencall(AbsInt,ASub0,ASub1,ASub)`

`ASub` is the result of dual widening abstract substitution `ASub0` and `ASub1`, which are supposed to be consecutive call patterns in a fixpoint computation.

widen/4: PREDICATE

Usage: `widen(AbsInt,ASub0,ASub1,ASub)`

`ASub` is the result of widening abstract substitution `ASub0` and `ASub1`, which are supposed to be consecutive approximations to the same abstract value. I.e., `less_or_equal(AbsInt,ASub0,ASub1)` succeeds.

– *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`ASub0` is currently a term which is not a free variable. (`nonvar/1`)

`ASub1` is currently a term which is not a free variable. (`nonvar/1`)

`ASub` is a free variable. (`var/1`)

`AbsInt` is an atom. (`atm/1`)

– *The following properties should hold globally:*

All the calls of the form `widen(AbsInt,ASub0,ASub1,ASub)` do not fail. (`not_fails/1`)

dual_widen/4: PREDICATE

`dual_widen(AbsInt,ASub0,ASub1,ASub)`

`ASub` is the result of dual widening abstract substitution `ASub0` and `ASub1`, which are supposed to be consecutive approximations to the same abstract value.

normalize_asub/3: PREDICATE

`normalize_asub(AbsInt,ASub0,ASub1)`

`ASub1` is the result of normalizing abstract substitution `ASub0`. This is required in some domains, specially to perform the widening.

compute_lub/3: PREDICATE

Usage: `compute_lub(AbsInt,ListASub,LubASub)`

`LubASub` is the least upper bound of the abstract substitutions in list `ListASub`.

– *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`ListASub` is currently a term which is not a free variable. (`nonvar/1`)

`LubASub` is a free variable. (`var/1`)

`AbsInt` is an atom. (`atm/1`)

`ListASub` is a list. (`list/1`)

`LubASub` is any term. (`term/1`)

– *The following properties should hold globally:*

All the calls of the form `compute_lub(AbsInt,ListASub,LubASub)` do not fail. (`not_fails/1`)

All calls of the form `compute_lub(AbsInt,ListASub,LubASub)` are deterministic. (`is_det/1`)

compute_glb/3: PREDICATE

`compute_glb(AbsInt,ListASub,GlbASub)`

`GlbASub` is the greatest lower bound of the abstract substitutions in list `ListASub`.

identical_proj/5: PREDICATE

Usage: `identical_proj(AbsInt,Sg,Proj,Sg1,Proj1)`

Abstract patterns `Sg:Proj` and `Sg1:Proj1` are equivalent in domain `AbsInt`. Note that `Proj` is assumed to be already sorted.

> This predicate unifies `Sg` and `Sg1`.

– *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`Sg` is currently a term which is not a free variable. (`nonvar/1`)

`Proj` is currently a term which is not a free variable. (`nonvar/1`)

`Sg1` is currently a term which is not a free variable. (`nonvar/1`)

`Proj1` is currently a term which is not a free variable. (`nonvar/1`)

`AbsInt` is an atom. (`atm/1`)

identical_proj_1/7: PREDICATE

Usage: `identical_proj_1(AbsInt,Sg,Proj,Sg1,Proj1,Prime1,Prime2)`

Abstract patterns `Sg:Proj` and `Sg1:Proj1` are equivalent in domain `AbsInt`. Note that `Proj` is assumed to be already sorted. It is different from `identical_proj/5` because it can be true although `Sg` and `Sg1` are not variant

– *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`Sg` is currently a term which is not a free variable. (`nonvar/1`)

`Proj` is currently a term which is not a free variable. (`nonvar/1`)

`Sg1` is currently a term which is not a free variable. (`nonvar/1`)

`Proj1` is currently a term which is not a free variable. (`nonvar/1`)

`Prime1` is currently a term which is not a free variable. (`nonvar/1`)

`Prime2` is currently a term which is not a free variable. (`nonvar/1`)

identical_abstract/3: PREDICATE

Usage: `identical_abstract(AbsInt,ASub1,ASub2)`

Succeeds if, in the particular abstract domain, the two abstract substitutions `ASub1` and `ASub2` are defined on the same variables and are equivalent.

– *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`ASub1` is currently a term which is not a free variable. (`nonvar/1`)

`ASub2` is currently a term which is not a free variable. (`nonvar/1`)

`AbsInt` is an atom. (`atm/1`)

abs_sort/3: PREDICATE

Usage: `abs_sort(AbsInt,ASub_u,ASub)`

`ASub` is the result of sorting abstract substitution `ASub_u`.

– *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`ASub_u` is currently a term which is not a free variable. (`nonvar/1`)

`AbsInt` is an atom. (`atm/1`)

– *The following properties should hold globally:*

All the calls of the form `abs_sort(AbsInt,ASub_u,ASub)` do not fail. (`not_fails/1`)

All calls of the form `abs_sort(AbsInt,ASub_u,ASub)` are deterministic. (`is_det/1`)

extend/6: PREDICATE

Usage: `extend(AbsInt,Sg,Prime,Sv,Call,Succ)`

`Succ` is the extension the information given by `Prime` (success abstract substitution over the goal variables `Sv`) to the rest of the variables of the clause in which the goal occurs (those over which abstract substitution `Call` is defined on). I.e., it is like a conjunction of the information in `Prime` and `Call`, except that they are defined over different sets of variables, and that `Prime` is a successor substitution to `Call` in the execution of the program.

– *The following properties should hold at call time:*
`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)
`Sg` is currently a term which is not a free variable. (`nonvar/1`)
`Prime` is currently a term which is not a free variable. (`nonvar/1`)
`Sv` is currently a term which is not a free variable. (`nonvar/1`)
`Call` is currently a term which is not a free variable. (`nonvar/1`)
`Succ` is a free variable. (`var/1`)
`AbsInt` is an atom. (`atm/1`)
– *The following properties should hold globally:*
All the calls of the form `extend(AbsInt,Sg,Prime,Sv,Call,Succ)` do not fail. (`not_fails/1`)
All calls of the form `extend(AbsInt,Sg,Prime,Sv,Call,Succ)` are deterministic. (`is_det/1`)

less_or_equal_proj/5: PREDICATE

Usage: `less_or_equal_proj(AbsInt,Sg,Proj,Sg1,Proj1)`

Abstract pattern `Sg`:`Proj` is less general or equivalent to abstract pattern `Sg1`:`Proj1` in domain `AbsInt`.

– *The following properties should hold at call time:*
`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)
`Sg` is currently a term which is not a free variable. (`nonvar/1`)
`Proj` is currently a term which is not a free variable. (`nonvar/1`)
`Sg1` is currently a term which is not a free variable. (`nonvar/1`)
`Proj1` is currently a term which is not a free variable. (`nonvar/1`)
`AbsInt` is an atom. (`atm/1`)

less_or_equal/3: PREDICATE

Usage: `less_or_equal(AbsInt,ASub0,ASub1)`

Succeeds if `ASub1` is more general or equivalent to `ASub0`.

– *The following properties should hold at call time:*
`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)
`ASub0` is currently a term which is not a free variable. (`nonvar/1`)
`ASub1` is currently a term which is not a free variable. (`nonvar/1`)
`AbsInt` is an atom. (`atm/1`)

glb/4: PREDICATE

Usage: `glb(AbsInt,ASub0,ASub1,GlbASub)`

`GlbASub` is the greatest lower bound of abstract substitutions `ASub0` and `ASub1`.

– *The following properties should hold at call time:*
`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)
`ASub0` is currently a term which is not a free variable. (`nonvar/1`)
`ASub1` is currently a term which is not a free variable. (`nonvar/1`)
`GlbASub` is a free variable. (`var/1`)
`AbsInt` is an atom. (`atm/1`)

– *The following properties should hold globally:*

All the calls of the form `glb(AbsInt,ASub0,ASub1,GlbASub)` do not fail. (`not_fails/1`)

All calls of the form `glb(AbsInt,ASub0,ASub1,GlbASub)` are deterministic. (`is_det/1`)

eliminate_equivalent/3: PREDICATE

`eliminate_equivalent(AbsInt,TmpLSucc,LSucc)`

The list `LSucc` is reduced wrt the list `TmpLSucc` in that it does not contain abstract substitutions which are equivalent.

abs_subset/3: PREDICATE

`abs_subset(AbsInt,LASub1,LASub2)`

Succeeds if each abstract substitution in list `LASub1` is equivalent to some abstract substitution in list `LASub2`.

call_to_success_fact/10: PREDICATE

Usage: `call_to_success_fact(AbsInt,Sg,Hv,Head,K,Sv,Call,Proj,Prime,Succ)`

Specialized version of call_to_entry + entry_to_exit + exit_to_prime for a fact `Head`.

– *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`Sg` is currently a term which is not a free variable. (`nonvar/1`)

`Hv` is currently a term which is not a free variable. (`nonvar/1`)

`Head` is currently a term which is not a free variable. (`nonvar/1`)

`K` is currently a term which is not a free variable. (`nonvar/1`)

`Sv` is currently a term which is not a free variable. (`nonvar/1`)

`Call` is currently a term which is not a free variable. (`nonvar/1`)

`Proj` is currently a term which is not a free variable. (`nonvar/1`)

`Prime` is a free variable. (`var/1`)

`Succ` is a free variable. (`var/1`)

`AbsInt` is an atom. (`atm/1`)

– *The following properties should hold globally:*

All the calls of the form `call_to_success_fact(AbsInt,Sg,Hv,Head,K,Sv,Call,Proj,Prime,Succ)` do not fail. (`not_fails/1`)

special_builtin/6: PREDICATE

Usage: `special_builtin(AbsInt,SgKey,Sg,Subgoal,Type,Condvars)`

Predicate `Sg` is considered a "builtin" of type `Type` in domain `AbsInt`. Types are domain dependent. Domains may have two different ways to treat these predicates: see `body_succ_builtin/9`.

– *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`SgKey` is currently a term which is not a free variable. (`nonvar/1`)

`Type` is a free variable. (`var/1`)

`Condvars` is a free variable. (`var/1`)

`AbsInt` is an atom. (`atm/1`)

body_succ_builtin/9: PREDICATE

Usage: `body_succ_builtin(AbsInt,Type,Sg,Vs,Sv,Hv,Call,Proj,Succ)`

Specialized version of call_to_entry + entry_to_exit + exit_to_prime + extend for predicate `Sg` considered a "builtin" of type `Type` in domain `AbsInt`. Whether a predicate is "builtin" in a domain is determined by `special_builtin/5`. There are two different ways to treat these predicates, depending on `Type`: `success_builtin` handles more usual types of "builtins", `call_to_success_builtin` handles particular predicates. The later is called when `Type` is of the form `special(SgKey)`.

– *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`Type` is currently a term which is not a free variable. (`nonvar/1`)

`Sg` is currently a term which is not a free variable. (`nonvar/1`)

`Sv` is currently a term which is not a free variable. (`nonvar/1`)

`Hv` is currently a term which is not a free variable. (`nonvar/1`)

`Call` is currently a term which is not a free variable. (`nonvar/1`)

`Proj` is currently a term which is not a free variable. (`nonvar/1`)

`Succ` is a free variable. (`var/1`)

`AbsInt` is an atom. (`atm/1`)

– *The following properties should hold globally:*

All the calls of the form `body_succ_builtin(AbsInt,Type,Sg,Vs,Sv,Hv,Call,Proj,Succ)` do not fail. (`not_fails/1`)

success_builtin/7: PREDICATE

Usage: `success_builtin(AbsInt,Type,Sv,Condvars,HvFv_u,Call,Succ)`

`Succ` is the success substitution on domain `AbsInt` for a call `Call` to a goal of a "builtin" (domain dependent) type `Type` with variables `Sv`. `Condvars` can be used to transfer some information from `special_builtin/5`.

– *The following properties should hold at call time:*

`AbsInt` is an atom. (`atm/1`)

– *The following properties should hold globally:*

All the calls of the form `success_builtin(AbsInt,Type,Sv,Condvars,HvFv_u,Call,Succ)` do not fail. (`not_fails/1`)

obtain_info/5: PREDICATE

Usage: `obtain_info(AbsInt,Prop,Vars,ASub,Info)`

Obtains variables `Info` for which property `Prop` holds given abstract substitution `ASub` on variables `Vars` for domain `AbsInt`.

– *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable.	(`nonvar/1`)
`Prop` is currently a term which is not a free variable.	(`nonvar/1`)
`Vars` is currently a term which is not a free variable.	(`nonvar/1`)
`ASub` is currently a term which is not a free variable.	(`nonvar/1`)
`Info` is a free variable.	(`var/1`)
`AbsInt` is an atom.	(`atm/1`)

info_to_asub/7: PREDICATE

`info_to_asub(AbsInt,Kind,InputUser,Qv,ASub,Sg,MaybeCallASub)`

Obtains the abstract substitution `ASub` on variables `Qv` for domain `AbsInt` from the user supplied information `InputUser` refering to properties on `Qv`. It works by calling `input_interface/5` on each property of `InputUser` which is a native property, so that they are accumulated, and then calls `input_user_interface/6`.

full_info_to_asub/5: PREDICATE

`full_info_to_asub(AbsInt,InputUser,Qv,ASub,Sg)`

Same as `info_to_asub(AbsInt,InputUser,Qv,ASub)` except that it fails if some property in `InputUser` is not native or not relevant to the domain `AbsInt`.

asub_to_info/5: PREDICATE

`asub_to_info(AbsInt,ASub,Qv,OutputUser,CompProps)`

Transforms an abstract substitution `ASub` on variables `Qv` for a domain `AbsInt` to a list of state properties `OutputUser` and computation properties `CompProps`, such that properties are visible in the preprocessing unit. It fails if `ASub` represents bottom. It works by calling `asub_to_native/6`.

asub_to_native/6: PREDICATE

`asub_to_native(AbsInt,ASub,Qv,OutFlag,NativeStat,NativeComp)`

`NativeStat` and `NativeComp` are the list of native (state and computational, resp.) properties that are the concretization of abstract substitution `ASub` on variables `Qv` for domain `AbsInt`. These are later translated to the properties which are visible in the preprocessing unit.

concrete/4: PREDICATE

`concrete(AbsInt,Var,ASub,List)`

`List` are (all) the terms to which `Var` can be bound in the concretization of `ASub`, if they are a finite number of finite terms. Otherwise, the predicate fails.

unknown_call/5: PREDICATE

Usage: `unknown_call(AbsInt,Sg,Vars,Call,Succ)`

`Succ` is the result of adding to `Call` the "topmost" abstraction in domain `AbsInt` of the variables `Vars` involved in a literal `Sg` whose definition is not present in the preprocessing unit. I.e., it is like the conjunction of the information in `Call` with the top for a subset of its variables.

– *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`Sg` is currently a term which is not a free variable. (`nonvar/1`)

`Vars` is currently a term which is not a free variable. (`nonvar/1`)

`Call` is currently a term which is not a free variable. (`nonvar/1`)

`Succ` is a free variable. (`var/1`)

`AbsInt` is an atom. (`atm/1`)

`Sg` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)

`Vars` is a list. (`list/1`)

– *The following properties should hold globally:*

All the calls of the form `unknown_call(AbsInt,Sg,Vars,Call,Succ)` do not fail. (`not_fails/1`)

unknown_entry/4: PREDICATE

Usage: `unknown_entry(AbsInt,Sg,Vars,Entry)`

`Entry` is the "topmost" abstraction in domain `AbsInt` of variables `Vars` corresponding to literal `Sg`.

– *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`Sg` is currently a term which is not a free variable. (`nonvar/1`)

`Vars` is currently a term which is not a free variable. (`nonvar/1`)

`Entry` is a free variable. (`var/1`)

`AbsInt` is an atom. (`atm/1`)

`Vars` is a list. (`list/1`)

– *The following properties should hold globally:*

All the calls of the form `unknown_entry(AbsInt,Sg,Vars,Entry)` do not fail. (`not_fails/1`)

empty_entry/4: PREDICATE

Usage: `empty_entry(AbsInt,Sg,Vars,Entry)`

`Entry` is the "empty" abstraction in domain `AbsInt` of variables `Vars`. I.e., it is the abstraction of a substitution on `Vars` in which all variables are unbound: free and unaliased.

– *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`Sg` is currently a term which is not a free variable. (`nonvar/1`)

`Vars` is currently a term which is not a free variable. (`nonvar/1`)

`Entry` is a free variable. (`var/1`)

`AbsInt` is an atom. (`atm/1`)

`Sg` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)

`Vars` is a list. (`list/1`)

`Entry` is any term. (`term/1`)

– *The following properties should hold globally:*

All the calls of the form `empty_entry(AbsInt,Sg,Vars,Entry)` do not fail. (`not_fails/1`)

part_conc/5: PREDICATE

`part_conc(AbsInt,Sg,Subs,NSg,NSubs)`

This operation returns in `NSg` an instance of `Sg` in which the deterministic structure information available in `Subs` is materialized. The substitution `NSubs` refers to the variables in `NSg`.

multi_part_conc/4: PREDICATE

`multi_part_conc(AbsInt,Sg,Subs,List)`

Similar to part_conc but it gives instantiations of goals even in the case types are not deterministic, it generates a `List` of pairs of goals and substitutions. It stops unfolding types as soon as they are recursive.

collect_types_in_abs/4: PREDICATE

Usage: `collect_types_in_abs(ASub,AbsInt,Types,Tail)`

Collects the type symbols occurring in `ASub` of domain `AbsInt` in a difference list `Types-Tail`.

– *The following properties should hold at call time:*

`ASub` is currently a term which is not a free variable. (`nonvar/1`)

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

– *The following properties should hold globally:*

All calls of the form `collect_types_in_abs(ASub,AbsInt,Types,Tail)` are deterministic. (`is_det/1`)

All the calls of the form `collect_types_in_abs(ASub,AbsInt,Types,Tail)` do not fail. (`not_fails/1`)

rename_types_in_abs/4: PREDICATE

Usage: `rename_types_in_abs(ASub0,AbsInt,Dict,ASub1)`

Renames the type symbols occurring in `ASub0` of domain `AbsInt` for the corresponding symbols as in (avl-tree) `Dict` yielding `ASub1`.

– *The following properties should hold at call time:*

`ASub0` is currently a term which is not a free variable. (`nonvar/1`)

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`Dict` is currently a term which is not a free variable. (`nonvar/1`)

– *The following properties should hold globally:*
  All calls of the form `rename_types_in_abs(ASub0,AbsInt,Dict,ASub1)` are deterministic. (`is_det/1`)
  All the calls of the form `rename_types_in_abs(ASub0,AbsInt,Dict,ASub1)` do not fail. (`not_fails/1`)

dom_statistics/2: PREDICATE
`dom_statistics(AbsInt,Info)`
Obtains in list `Info` statistics about the results of the abstract interpreter `AbsInt`.

abstract_instance/5: PREDICATE
Usage: `abstract_instance(AbsInt,Sg1,Proj1,Sg2,Proj2)`
The pair <Sg1,Proj1> is an abstract instance of the pair <Sg2,Proj2>, i.e., the concretization of <Sg1,Proj1> is included in the concretization of <Sg2,Proj2>.

contains_parameters/2: PREDICATE
`contains_parameters(AbsInt,Subst)`
True if an abstract substitution `Subst` contains type parameters

absub_eliminate_equivalent/3: PREDICATE
No further documentation available for this predicate.

absub_fixpoint_covered/3: PREDICATE
No further documentation available for this predicate.

body_builtin/9: PREDICATE
No further documentation available for this predicate.

undef_call_to_success_builtin/2: PREDICATE
No further documentation available for this predicate.

68.4 Documentation on multifiles

aidomain/1: PREDICATE

`aidomain(AbsInt)`

Declares that `AbsInt` identifies an abstract domain. The predicate is *multifile*.

aidom.init_abstract_domain/2: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

aidom.amgu/5: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_asub/4: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

aidom.augment_two_asub/4: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_entry/10: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

aidom.exit_to_prime/8: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

aidom.project/6: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

aidom.widencall/4: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

aidom.needs/2: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

aidom.widen/4: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_lub/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_lub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.compute_clauses_glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.fixpoint_covered_gfp/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.identical_abstract/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_sort/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.extend/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.less_or_equal/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.glb/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.eliminate_equivalent/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.abs_subset/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_fact/10: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.special_builtin/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.combined_special_builtin0/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.body_succ_builtin/9: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.split_combined_domain/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.call_to_success_builtin/7: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.obtain_info/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_interface/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.input_user_interface/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.asub_to_native/6: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.concrete/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_call/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.unknown_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.empty_entry/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.part_conc/5: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.multi_part_conc/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.collect_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.rename_auxinfo_asub/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.dom_statistics/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidom.contains_parameters/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

68.5 Documentation on internals

call_to_success_builtin/7: PREDICATE
Usage: `call_to_success_builtin(AbsInt,Type,Sg,Sv,Call,Proj,Succ)`

`Succ` is the success substitution on domain `AbsInt` for a call `Call` to a goal `Sg` with variables `Sv` considered of a "builtin" (domain dependent) type `Type`. `Proj` is `Call` projected on `Sv`.

– *The following properties should hold globally:*
All the calls of the form `call_to_success_builtin(AbsInt,Type,Sg,Sv,Call,Proj,Succ)` do not fail. (`not_fails/1`)

input_interface/5: PREDICATE

`input_interface(AbsInt,Prop,Kind,Struc0,Struc1)`

`Prop` is a native property that is relevant to domain `AbsInt` (i.e., the domain knows how to fully –`+Kind`=perfect– or approximately –`-Kind`=approx– abstract it) and `Struct1` is a (domain defined) structure resulting of adding the (domain dependent) information conveyed by `Prop` to structure `Struct0`. This way, the properties relevant to a domain are being accumulated.

input_user_interface/6: PREDICATE

`input_user_interface(AbsInt,Struct,Qv,ASub,Sg,MaybeCallASub)`

`ASub` is the abstraction in `AbsInt` of the information collected in `Struct` (a domain defined structure) on variables `Qv`.

68.6 Documentation on imports

This module has the following direct dependencies:

– *Application modules:*

`fixpo_ops`, `low_level_props`, `preprocess_flags`, `pd`, `pdb`, `fr_top`, `frdef`, `lsign`, `lsigndiff`, `gr`, `def`, `sharing`, `sharefree`, `sharefree_non_var`, `shfret`, `shareson`, `shfrson`, `sondergaard`, `sharing_amgu`, `sharefree_amgu`, `shfrlin_amgu`, `sharing_clique`, `sharing_clique_1`, `sharefree_clique`, `sharing_clique_def`, `sharefree_clique_def`, `aeq`, `depthk`, `top_path_sharing`, `termsd`, `ptypes`, `eterms`, `etermsvar`, `svterms`, `deftypes`, `nonrel_intervals`, `nfdet`, `nfplai`, `detplai`.

– *System library modules:*

`native_props`, `p_unit`, `terms_check`, `terms_vars`, `native_props_rtc`, `sets`, `sort`, `lists`, `messages`.

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `regtypes`, `isomodes`, `nativeprops`, `ciaopp(ciaopp_options)`, `aidomain`.

69 PART IV - CiaoPP Internals

CiaoPP is provided as a module that can be either loaded in the shell or imported into a user program module. There are predicates that activate each option, a predicate to load the file to be processed, and predicates to perform the action of each task of CiaoPP.

This document describes the structure of the code of CiaoPP, its components (each performing a task), and their functionality, from the point of view of the implementor, not of the user.

69.1 How to use CiaoPP in your own preprocessor

If you implement a program for preprocessing Ciao programs, you can take advantage of the facilities provided by CiaoPP. The basic facilities are described in the following three chapters. In particular, the chapter on module `driver` explains how to integrate your tool and CiaoPP to make them work together.

One particularly useful feature of CiaoPP is that it provides for the correct reading of an input program to be preprocessed (this is more tricky than it seems, because of all of the language features that the program might be using). Once a program is read in by CiaoPP, your tool can process it as plain Prolog. The chapter on module `p_unit` explains how a program is (correctly) read in, and provides an interface so that you can retrieve information about that program.

Depending on the kind of preprocessing you want to do, you may want to use other parts of CiaoPP. If your program is doing program transformations, then the chapters on `program_keys` and `tr_syntax` might be helpful. If you want to use analysis information to help the transformations, then the chapter on `infer` is the one to read. If your program is a program analyzer based on abstract interpretation, then have a look at the chapters on `plai` and `domains`. Program analyses not based on abstract interpretation (and other possible tools) may be a bit harder to incorporate: you might need to develop first your skills with the CiaoPP code...

69.2 Other information

The work of CiaoPP is focused on one-module-at-a-time. The file being preprocessed at a given time is called the *current module* . If the file is of the user module, it is considered as a module which exports all its predicates.

The preprocessing unit is the code of the current module together with the set of assertions / properties which allows a correct and complete interpretation of the assertions present for the current module. Assertions and properties are usually cached in auxiliary files, which are called the .asr files.

69.3 Basic structure of the code

The code of CiaoPP is divided into *components*, each of which provides a particular functionality. The top-level organization of the main components is as follows:

Each component is addressed by a particular qualifier, which makes reference to modules independent of the particular library paths. These qualifiers are defined in file `paths.pl`. The qualifier for the top-level components is `ciaopp`.

The component `p_unit` is addressed by qualifier `program` and is in charge of processing the .asr files, gathering together the code for the preprocessing unit of the current module.

The component `tr_syntax` is addressed by qualifier `syntax` and implements simple source code syntactic transformations (like removing disjunctions and the like).

The component `infer` is addressed by qualifier `infer` and is in charge of serving all known semantic information on the current module, from any analysis and/or assertion.

The component `plai` is addressed by qualifier `plai` and implements abstract interpretation based analysis.

The component `infernf` is addressed by qualifier `infernf` and implements the non-failure analysis.

The component `infercost` is addressed by qualifier `infercost` and implements the cost analysis.

70 Frontend driver (monolithic)

This module provides the main entry points for loading source programs (in a suitable form for performing analysis and transformations) and print them back as source.

70.1 Adding new frontend

(to be written)

70.2 Usage and interface

- **Library usage:**
  `:- use_module(ciaopp(frontend_driver)).` This module is loaded by default in the CiaoPP toplevel and reexported from the `ciaopp` module.
- **Exports:**
  - *Predicates:*
    `supported_language/1`, `language_extension/2`, `language_output_extension/2`, `module/1`, `module/2`, `entry_assertion/3`, `assrt_used_as_entry/2`, `is_library/1`, `cleanup_history/0`, `push_history/1`, `pop_history/1`, `get_output_path/2`, `output/0`, `output/1`, `output/2`, `output_ext/1`, `output_by_ext/2`, `write_one_type/2`, `ensure_libcache_loaded/0`, `gen_and_load_libcache/0`.
  - *Multifiles:*
    `hook_compact_global_prop/2`, `hook_compact_calls_prop/2`, `hook_native_prop/2`, `hook_pp_info_clause/3`, `hook_pp_info_lit/4`, `hook_legal_regtype/1`, `hook_insert_regtype/2`, `hook_post_init_regtypes/0`, `hook_cleanup_lib_regtypes/0`, `hook_restore_lib_regtypes/1`, `hook_save_lib_regtypes/1`, `file_search_path/2`, `library_directory/1`.

70.3 Documentation on exports

supported_language/1: PREDICATE

`supported_language(L)`

Indicates that a translation is available from language `L` to Ciao Prolog language.

language_extension/2: PREDICATE

`language_extension(L,E)`

`E` is an extension (including the dot) for files that must be translated from language `L` to Ciao.

language_output_extension/2: PREDICATE

`language_output_extension(L,E)`

`E` is the extension of the file produced as output by the Ciao printer for language `L`.

module/1: PREDICATE

Usage 1: `module(FileName)`

Reads the code of `FileName` and its preprocessing unit, and sets it as the current module.

– *The following properties should hold at call time:*

`FileName` is currently a term which is not a free variable. (`nonvar/1`)

`FileName` is a source name. (`sourcename/1`)

Usage 2: `module(FileNameList)`

Reads the code of the list of file names `FileNameList` (and their preprocessing units), and sets them as the current modules.

– *The following properties should hold at call time:*

`FileNameList` is currently a term which is not a free variable. (`nonvar/1`)

`FileNameList` is a list of `atm`s. (`list/2`)

module/2: PREDICATE

Usage: `module(Ms,Info)`

Same as `module/1` but it also prints the time required to read the module and returns extra information (including the time) on its second argument.

– *The following properties should hold at call time:*

`Ms` is currently a term which is not a free variable. (`nonvar/1`)

`Info` is a free variable. (`var/1`)

entry_assertion/3: PREDICATE

Usage: `entry_assertion(Goal,Call,Name)`

There is an entry assertion for `Goal` with call pattern `Call`, uniquely identifiable by `Name`.

– *The following properties should hold upon exit:*

`Goal` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)

assrt_used_as_entry/2: PREDICATE

Usage: `assrt_used_as_entry(Sg,AssrtType)`

Assertion with head `Sg` and assertion type `AssrtType` is used as an analysis entry (depending on values of `entry_points_auto` and `entry_calls_scope`).

– *The following properties should hold at call time:*

`Sg` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)

`AssrtTYpe` is an atom. (`atm/1`)

is_library/1: PREDICATE

Usage: `is_library(Base)`

– *The following properties should hold at call time:*

`Base` is currently a term which is not a free variable. (`nonvar/1`)

cleanup_history/0: PREDICATE

Usage:

Cleanup history items.

push_history/1: PREDICATE

Usage: `push_history(X)`

Push history item `X`.

– *The following properties should hold at call time:*

`X` is currently instantiated to an atom. (`atom/1`)

pop_history/1: PREDICATE

Usage: `pop_history(X)`

Pop history item `X`.

– *The following properties should hold at call time:*

`X` is currently instantiated to an atom. (`atom/1`)

get_output_path/2: PREDICATE

Usage: `get_output_path(UseHistory,Path)`

Default output file name based. Encode analysis/transformation history if `UseHistory` is `yes`.

– *The following properties should hold upon exit:*

`UseHistory` is an atom. (`atm/1`)

`Path` is an atom. (`atm/1`)

output/0: PREDICATE

Usage:

Outputs the current module preprocessing state with the default output options. Equivalent to `output(File,[])`.

output/1: PREDICATE

Usage: `output(File)`

Outputs to `File` the current module preprocessing state with the default output options. If unbound, `File` is unified with a default name (encoding the preprocessing steps). Equivalent to `output(File,[])`.

output/2: PREDICATE

Usage: `output(File,Opts)`

Outputs the current module preprocessing state to a file `File`. If unbound, `File` is unified with a default name (encoding the preprocessing steps). The output format (which should be valid for the loaded program) is guessed from the file extension. `Opts` is a list of options for this predicate (see `output_option/1`)

– *The following properties should hold at call time:*

`Opts` is currently a term which is not a free variable. (`nonvar/1`)

output_ext/1: PREDICATE

Usage: `output_ext(Ext)`

Extension `Ext` is a supported output extension.

– *The following properties should hold at call time:*

`Ext` is an atom. (`atm/1`)

output_by_ext/2: PREDICATE

Usage: `output_by_ext(Ext,File)`

Produce output `File` for the given extension `Ext`.

– *The following properties should hold at call time:*

`Ext` is an atom. (`atm/1`)

`File` is a source name. (`sourcename/1`)

write_one_type/2: PREDICATE

No further documentation available for this predicate.

ensure_libcache_loaded/0: PREDICATE

Usage:

Ensure that the libcache is loaded (if `use_libcache` is enabled and the cache is generated) (see `p_unit:load_libcache/1`).

gen_and_load_libcache/0: PREDICATE

Usage:

Generate and load the libcache (see `p_unit:gen_libcache/1`).

get_data/2: (UNDOC_REEXPORT)

Imported from `p_dump` (see the corresponding documentation for details).

clean_ciaopp_db/1: (UNDOC_REEXPORT)

Imported from `p_dump` (see the corresponding documentation for details).

clean_all_ciaopp_db/0: (UNDOC_REEXPORT)

Imported from `p_dump` (see the corresponding documentation for details).

dump/2: (UNDOC_REEXPORT)

Imported from `p_dump` (see the corresponding documentation for details).

dump_dir/1: (UNDOC_REEXPORT)
Imported from `p_dump` (see the corresponding documentation for details).

add_to_db/1: (UNDOC_REEXPORT)
Imported from `p_dump` (see the corresponding documentation for details).

show_dump/1: (UNDOC_REEXPORT)
Imported from `p_dump` (see the corresponding documentation for details).

restore/2: (UNDOC_REEXPORT)
Imported from `p_dump` (see the corresponding documentation for details).

restore/1: (UNDOC_REEXPORT)
Imported from `p_dump` (see the corresponding documentation for details).

dump/1: (UNDOC_REEXPORT)
Imported from `p_dump` (see the corresponding documentation for details).

70.4 Documentation on multifiles

hook_compact_global_prop/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

hook_compact_calls_prop/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

hook_native_prop/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

hook_pp_info_clause/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

hook_pp_info_lit/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

hook_legal_regtype/1: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

hook_insert_regtype/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

hook_post_init_regtypes/0: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

hook_cleanup_lib_regtypes/0: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

hook_restore_lib_regtypes/1: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

hook_save_lib_regtypes/1: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

file_search_path/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.
The predicate is of type *dynamic*.

library_directory/1: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.
The predicate is of type *dynamic*.

70.5 Documentation on imports

This module has the following direct dependencies:

– *Application modules:*

`ciaopp_log`, `analysis_stats`, `preprocess_flags`, `incanal`, `analyze_driver`, `intermod_ops`, `transform_driver`, `raw_printer`, `p_dump`, `prepare_ai_output`, `infer_db`, `infer_dom`.

– *System library modules:*

`native_props`, `datafacts_rt`, `p_unit`, `p_printer`, `aggregates`, `unexpand`, `p_unit_db`, `assrt_lib`, `native`, `typeslib`, `system`, `pathnames`, `lists`, `pretty_print`, `messages`, `terms`, `format`, `sort`, `terms_vars`, `formulae`.

– *Internal (engine) modules:*

  `term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`, `internals`, `runtime_control`, `stream_basic`, `io_basic`.

– *Packages:*

  `prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `basicmodes`, `regtypes`, `nativeprops`, `hiord`, `datafacts`, `ciaopp(ciaopp_options)`, `compiler/p_unit/p_unit_argnames`, `argnames`.

71 Advanced output of preprocessor

Author(s): Isabel Garcia-Contreras.

Raw printer outputs the analysis results of ciaopp without preprocessing any information, as it is represented internally in CiaoPP

71.1 How to use it

```
?- set_pp_flag(output_lang, raw).

yes
% make analysis
?- module(foo).
{Loading current module from foo.pl
{loaded in 390.268 msec.}
}

yes
?- analyze(eterms).
{Analyzing foo.pl
{preprocessed for the plai fixpoint in 1.736 msec.}
{analyzed by plai using eterms with local-control off in 5.106 msec.}
}

?- output.
{written file .../foo_eterms_co.pl}

yes
?- % open file or C-c C-v in emacs
```

The output will be generated as a module importing package raw. The idea is to be able to load this analysis (containing the translations to avoid recomputation), but it not implemented yet.

71.2 Usage and interface

- **Library usage:**
  `:- use_module(ciaopp(raw_printer)).`
- **Exports:**
  - *Predicates:*
    `raw_output/1`, `show_trans_clauses/0`, `show_analysis/0`, `show_registry_info/0`, `show_global_answer_table/1`, `show_change_list/0`.

71.3 Documentation on exports

raw_output/1: PREDICATE

Usage: `raw_output(File)`

Shows the current state of the plai databases in file `File`, including:

- Transformed clauses.
- Inferred assertions (completes).
- Information at program point (memo_tables).
- State of the types library.

– *The following properties should hold at call time:*

`File` is an open stream. (`stream/1`)

show_trans_clauses/0: PREDICATE

Usage:

Shows the code transformed to be used by the fixpoints (given by `trans_clause/3`).

show_analysis/0: PREDICATE

Usage:

Shows all the information inferred by ciaopp.

show_registry_info/0: PREDICATE

Shows information about the modular analysis registries.

show_global_answer_table/1: PREDICATE

Usage: `show_global_answer_table(AbsInt)`

Shows de global answer table for modular analysis with domain `AbsInt`

show_change_list/0: PREDICATE

Shows the list of changes that need computation in the fixpoint dd.

71.4 Documentation on imports

This module has the following direct dependencies:

– *Application modules:*

`preprocess_flags`, `transform`, `plai_db`, `intermod_db`, `plai`, `fixpo_dd`.

– *System library modules:*

`datafacts_rt`, `write`, `format`, `lists`, `aggregates`, `assrt_write`, `assrt_lib`, `typeslib`, `program_keys`, `p_unit`, `p_unit_db`.

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`, `stream_basic`, `io_basic`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `isomodes`, `datafacts`.

72 Analyze driver (monolithic)

This module provides the main entry points for performing analysis and assertion checking. It requires loading the program before (e.g., with `frontend_driver`).

72.1 Adding new analyses

To include a new analysis, add a clause for `analyze/2` (and for `analysis/1`).

As an alternative, you can add clauses for the multifile predicates `analysis/4` and `analysis/1`, directly in your own sources.

See the file `examples/Extending/myanalyzer.pl` in the source directory for an example of this.

72.2 Usage and interface

- **Library usage:**
  `:- use_module(ciaopp(analyze_driver))`. This module is loaded by default in the CiaoPP toplevel and reexported from the `ciaopp` module.
- **Exports:**
  - *Predicates:*
    `assert_domain/1`, `last_domain_used/1`, `analyze/1`, `analyze/2`, `analyze1/2`, `acheck_summary/1`, `acheck_summary/2`, `get_assert_count/1`, `acheck/0`, `acheck/1`, `acheck/2`, `clean_analysis_info/0`, `clean_analysis_info0/0`, `cleanup_for_codegen/0`.
  - *Regular Types:*
    `ctcheck_sum/1`.
  - *Multifiles:*
    `lazy_analysis/1`, `analysis_module/2`, `loaded_analysis/1`, `analysis/4`, `analysis/1`, `aidomain/1`.

72.3 Documentation on exports

assert_domain/1: PREDICATE

No further documentation available for this predicate.

last_domain_used/1: PREDICATE

No further documentation available for this predicate.

analyze/1: PREDICATE

Usage: `analyze(Analysis)`

Analyzes the current module with `Analysis`. If the intermod flag is not off, this predicate may call `module/1`.

– *The following properties should hold at call time:*

`Analysis` is currently a term which is not a free variable. (`nonvar/1`)

`Analysis` is a valid analysis identifier. (`analysis/1`)

– *The following properties should hold globally:*

All the calls of the form `analyze(Analysis)` do not fail. (`not_fails/1`)

A call to `analyze(Analysis)` does not leave new choicepoints. (`no_choicepoints/1`)

analyze/2: PREDICATE

Usage: `analyze(Analysis,Info)`

Same as analyze(`Analysis`) but in `Info` returns statistics (time and memory).

– *The following properties should hold at call time:*

`Analysis` is currently a term which is not a free variable. (`nonvar/1`)

`Info` is a free variable. (`var/1`)

analyze1/2: PREDICATE

No further documentation available for this predicate.

ctcheck_sum/1: REGTYPE

A regular type, defined as follows:

```
ctcheck_sum(ok).
ctcheck_sum(warning).
ctcheck_sum(error).
```

acheck_summary/1: PREDICATE

Usage: `acheck_summary(S)`

Checks assertions w.r.t. analysis information. Upon success `S` is bound to: ok (the compile-time checking process has generated no error nor warning), warning (compile-time checking has not generated any error, but there has been at least one warning) or error (at least one error has been produced).

– *The following properties should hold at call time:*

`S` is a free variable. (`var/1`)

– *The following properties should hold upon exit:*

`ctcheck_sum(S)` (`ctcheck_sum/1`)

acheck_summary/2: PREDICATE

Usage: `acheck_summary(Info,S)`

Same as acheck_summary(`S`) but in `Info` returns assertion checking statistics.

– *The following properties should hold at call time:*

`Info` is a free variable. (`var/1`)

`S` is a free variable. (`var/1`)

get_assert_count/1: PREDICATE

No further documentation available for this predicate.

acheck/0: PREDICATE

Usage:

Checks assertions w.r.t. analysis information, obtains from `domain/1` which analyses were run.

acheck/1: PREDICATE

Usage: `acheck(AbsInt)`

Checks assertions using the analysis information of `AbsInt`. The analysis must be present in CiaoPP (via analysis or restore dump).

acheck/2: PREDICATE

Usage 1: `acheck(AbsInt,ModList)`

- *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable.	(`nonvar/1`)
`ModList` is currently a term which is not a free variable.	(`nonvar/1`)
`AbsInt` is a list of `atm`s.	(`list/2`)
`ModList` is a list of `atm`s.	(`list/2`)

Usage 2: `acheck(AbsInt,MaybeModList)`

If `MaybeModList` is the atom `all`, all modules in the current punit are considered. If it is a list of **module names**, only the assertions or predicates in those modules are checked.

- *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable.	(`nonvar/1`)
`MaybeModList` is currently a term which is not a free variable.	(`nonvar/1`)
`AbsInt` is a list of `atm`s.	(`list/2`)
`MaybeModList` is an atom.	(`atm/1`)

clean_analysis_info/0: PREDICATE

Usage:

Cleans all analysis info but keep the program as wether it would be just read.

clean_analysis_info0/0: PREDICATE

No further documentation available for this predicate.

cleanup_for_codegen/0: PREDICATE

No further documentation available for this predicate.

trace_fixp/1: PREDICATE

Usage 1: `trace_fixp(X)`

Mode for setting the current flag to a single value.

- *The following properties should hold at call time:*
  `trace_option(X)` (`trace_option/1`)
- *The following properties should hold globally:*
  `X` is not further instantiated. (`not_further_inst/2`)

Usage 2: `trace_fixp(X)`

Mode for setting the current flag to several values.

- *The following properties should hold at call time:*
  `X` is a list of `trace_option`s. (`list/2`)
- *The following properties should hold globally:*
  `X` is not further instantiated. (`not_further_inst/2`)

72.4 Documentation on multifiles

lazy_analysis/1: PREDICATE

Specifies an analysis that can be lazy loaded The predicate is *multifile*.

analysis_module/2: PREDICATE

Given an analysis, returns the module that contains the implementation (or entry point) of a lazy loadable analysis. Such module must implement the analysis/4 multifile clause. The predicate is *multifile*.

loaded_analysis/1: PREDICATE

Helps to determine if an analysis was already loaded. Must be defined in the same module specified by analysis_module/2. The predicate is *multifile*.

analysis/4: PREDICATE

Usage: `analysis(Analysis,Clauses,Dictionaries,Info)`

Performs `Analysis` on program `Clauses`.

- *The following properties should hold at call time:*
  `Analysis` is a valid analysis identifier. (`analysis/1`)

The predicate is *multifile*.

analysis/1: PROPERTY

Usage: `analysis(Analysis)`

`Analysis` is a valid analysis identifier.

The predicate is *multifile*.

aidomain/1: PREDICATE

See the chapter on `domains`. The predicate is *multifile*.

72.5 Documentation on imports

This module has the following direct dependencies:

- *Application modules:*

  `ciaopp_log`, `analysis_stats`, `preprocess_flags`, `infer_db`, `frontend_driver`, `trace_fixp`, `incanal`, `intermod`, `plai`, `vartypes`, `inferseff`, `infer_dom`, `ctchecks_pred`, `ctchecks_pp`, `ctchecks_common`, `preproc_errors`, `intermod_ops`.
- *System library modules:*

  `native_props`, `datafacts_rt`, `compiler`, `p_unit`, `p_unit_db`, `typeslib`, `counters`, `aggregates`.
- *Internal (engine) modules:*

  `term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`, `messages_basic`.
- *Packages:*

  `prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `basicmodes`, `regtypes`, `nativeprops`, `datafacts`, `ciaopp(ciaopp_options)`, `ciaopp(analysis_register)`.

73 Transform driver (monolithic)

This module provides the main entry points for for performing program transformations. It requires loading the program before (e.g., with `frontend_driver`).

73.1 Adding new transformation

To include a new program transformation, add a clause for `transform/2` (and for `transformation/1`).

As an alternative, you can add clauses for the multifile predicates `transformation/4` and `transformation/1`, directly in your own sources.

See the file `examples/Extending/myspecializer.pl` in the source directory for an example of this.

73.2 Usage and interface

- **Library usage:**
  `:- use_module(ciaopp(transform_driver)).` This module is loaded by default in the CiaoPP toplevel and reexported from the `ciaopp` module.
- **Exports:**
  - *Predicates:*
    `transform/1`, `transform/2`.
  - *Multifiles:*
    `transformation/4`, `transformation/1`.

73.3 Documentation on exports

transform/1: PREDICATE

Usage 1: `transform(Trans)`

Returns on backtracking all available program transformation identifiers.

- *The following properties should hold at call time:*
  `Trans` is a free variable. (`var/1`)
- *The following properties should hold upon exit:*
  `Trans` is a valid transformation identifier. (`transformation/1`)

Usage 2: `transform(Trans)`

Performs transformation `Trans` on the current module.

- *The following properties should hold at call time:*
  `Trans` is currently a term which is not a free variable. (`nonvar/1`)
  `Trans` is a valid transformation identifier. (`transformation/1`)

transform/2: PREDICATE

Usage: `transform(Trans,Info)`

Same as transform(`Trans`) but returns information that can be used to check the results of the transformation.

– *The following properties should hold at call time:*
`Trans` is currently a term which is not a free variable. (`nonvar/1`)
`Info` is a free variable. (`var/1`)

73.4 Documentation on multifiles

transformation/4: PREDICATE

Usage: `transformation(Transformation,Clauses,Dictionaries,Info)`

Performs `Transformation` on program `Clauses`.

– *The following properties should hold at call time:*
`Transformation` is a valid transformation identifier. (`transformation/1`)

The predicate is *multifile*.

transformation/1: PROPERTY

Usage: `transformation(Transformation)`

`Transformation` is a valid transformation identifier.

The predicate is *multifile*.

73.5 Documentation on imports

This module has the following direct dependencies:

– *Application modules:*
`preprocess_flags`, `ciaopp_log`, `frontend_driver`, `normalize_args`, `re_analysis`, `spec`, `spec_multiple`, `codegen`, `slicing`, `arg_filtering`, `unfold_non_rec`, `analyze_driver`.

– *System library modules:*
`native_props`, `datafacts_rt`, `p_unit_db`, `p_unit`.

– *Internal (engine) modules:*
`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`, `messages_basic`.

– *Packages:*
`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `basicmodes`, `regtypes`, `nativeprops`, `datafacts`, `ciaopp(ciaopp_options)`.

74 Modular driver

Author(s): The Ciao Development Team, Isabel Garcia-Contreras.

Stability: [**devel**] Currently the subject of active development and/or research. Functionality may be limited and API and/or functionality may change without warning or deprecation period. Not recommended yet for use in production.

This module provides intermodular analysis to CiaoPP (high-level).

Global compilation options of intermodular analysis are available in `intermod_options`. Edit this file to activate tracing or run-time checks.

74.1 Usage and interface

- **Library usage:**
  `:- use_module(ciaopp(plai/intermod)).`
- **Exports:**
  - *Predicates:*
    `cleanup_intermod/0`, `intermod_analyze/2`, `intermod_analyze/3`, `intermod_ctcheck/2`, `intermod_transform/3`, `intermod_simp_libs/2`, `intermod_simp_libs/3`, `inductive_ctcheck/2`, `inductive_ctcheck/4`, `inductive_ctcheck_summary/3`, `intermod_ctcheck_opt/2`, `intermod_ctcheck_opt/3`.
  - *Properties:*
    `valid_mod_analysis/1`.
  - *Multifiles:*
    `dump_flags_list/2`, `aidomain/1`, `transformation/1`, `library_directory/1`, `file_search_path/2`.

74.2 Documentation on exports

cleanup_intermod/0: PREDICATE

Usage:

Cleans up the internal database of the intermodular analysis global level.

valid_mod_analysis/1: PROPERTY

Usage 1: `valid_mod_analysis(Domain)`

Succeeds if `Domain` is a valid analysis domain for modular analysis

Usage 2: `valid_mod_analysis(DomainList)`

Succeeds if the domains in `DomainList` are valid analysis domains for modular analysis

intermod_analyze/2: PREDICATE

No further documentation available for this predicate.

intermod_analyze/3: PREDICATE

No further documentation available for this predicate.

intermod_ctcheck/2: PREDICATE

Usage: `intermod_ctcheck(AbsInts,Modules)`

Assuming that modular fixpoint already reached. Only supporting ctchecks of pred assertions (not program point)

– *The following properties should hold at call time:*

`AbsInts` is currently a term which is not a free variable. (`nonvar/1`)

`Modules` is currently a term which is not a free variable. (`nonvar/1`)

`AbsInts` is a list of `atm`s. (`list/2`)

`Modules` is a list of `atm`s. (`list/2`)

– *The following properties should hold globally:*

All the calls of the form `intermod_ctcheck(AbsInts,Modules)` do not fail. (`not_fails/1`)

intermod_transform/3: PREDICATE

Usage: `intermod_transform(AbsInt,Trans,TopLevel)`

Performs transformation `Trans` of the program unit which has `TopLevel` as top-level module, using `AbsInt` to get information about the program.

– *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`Trans` is currently a term which is not a free variable. (`nonvar/1`)

`TopLevel` is currently a term which is not a free variable. (`nonvar/1`)

intermod_simp_libs/2: PREDICATE

Usage: `intermod_simp_libs(TopLevel,Dir)`

Generates a copy of the program represented by `TopLevel` and the libraries used (except those in `engine`) in `Dir`, and removes dead-code from both user modules and libraries.

– *The following properties should hold at call time:*

`TopLevel` is currently a term which is not a free variable. (`nonvar/1`)

`Dir` is currently a term which is not a free variable. (`nonvar/1`)

intermod_simp_libs/3: PREDICATE

No further documentation available for this predicate.

inductive_ctcheck/2: PREDICATE

No further documentation available for this predicate.

inductive_ctcheck/4: PREDICATE
No further documentation available for this predicate.

inductive_ctcheck_summary/3: PREDICATE
No further documentation available for this predicate.

intermod_ctcheck_opt/2: PREDICATE
Usage: `intermod_ctcheck_opt(AbsInt,TopLevel)`
Performs CT assertion checking of the program unit which has `TopLevel` as a top-level module, using `AbsInt` to get information about the program (exploits order of the modules).
- *The following properties should hold at call time:*
  `AbsInt` is currently a term which is not a free variable. (`nonvar/1`)
  `TopLevel` is currently a term which is not a free variable. (`nonvar/1`)

intermod_ctcheck_opt/3: PREDICATE
No further documentation available for this predicate.

74.3 Documentation on multifiles

dump_flags_list/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

aidomain/1: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

transformation/1: PROPERTY
Usage: `transformation(Transformation)`
`Transformation` is a valid transformation identifier.
The predicate is *multifile*.

library_directory/1: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.
The predicate is of type *dynamic*.

file_search_path/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.
The predicate is of type *dynamic*.

74.4 Documentation on imports

This module has the following direct dependencies:

– *Application modules:*

`mem_usage`, `intermod_db`, `intermod_schedule`, `intermod_punit`, `intermod_entry`, `intermod_ops`, `frontend_driver`, `analyze_driver`, `re_analysis`, `plai`, `spec`, `codegen`, `plai_db`, `fixpo_ops`, `preprocess_flags`, `p_dump`, `ciaopp_log`, `raw_printer`, `ctchecks_pred`, `unfold_times`, `analysis_stats`.

– *System library modules:*

`native_props`, `datafacts_rt`, `dynamic_rt`, `p_unit`, `aux_filenames`, `p_unit_db`, `counters`, `system`, `process`, `system_extra`, `terms`, `c_itf`, `lists`, `llists`, `pathnames`, `aggregates`, `hiordlib`.

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`, `internals`, `stream_basic`, `runtime_control`, `messages_basic`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `basicmodes`, `nativeprops`, `fsyntax`, `dynamic`, `datafacts`, `spec(nomem_usage)`.

75 Database for intermodular analysis driver

This module contains the predicates used as data base (state) of intermodular analysis. This includes the program unit graph, i.e., the imported/exported modules graph; and the global analysis graph (registry), i.e., the intermodular equivalent of complete/7 in plai_db, that contains the relations of the predicates in the boundaries of the modules, i.e., how exported predicates call imported predicates.

75.1 Usage and interface

- **Library usage:**
  `:- use_module(ciaopp(plai/intermod_db)).`
- **Exports:**
  - *Predicates:*
    `add_main_module/1`, `main_module/2`, `punit_module/2`, `local_ana_module/2`, `registry/3`, `registry_header/2`, `module_depth/2`, `imported_module/2`, `caller_module/2`, `src_changed/1`, `add_src_changed/1`, `unset_src_changed/1`, `clean_program_structure/0`, `set_main_module/1`, `set_punit_modules/1`, `set_local_ana_modules/1`, `get_registry/4`, `add_registry/2`, `cleanup_registry/1`, `reg_version/1`, `registry_header_format/2`, `mod_typedb/2`, `add_mod_typedb/2`, `enum_mod_typedb/1`.

75.2 Documentation on exports

add_main_module/1: PREDICATE

No further documentation available for this predicate.

main_module/2: PREDICATE

Usage: `main_module(Base,Mod)`

Succeeds if `Base` is an entry module of the program unit to be analyzed.

The predicate is of type *data*.

punit_module/2: PREDICATE

Usage: `punit_module(Base,Mod)`

Succeeds if `Base` is a module of the program unit to be analyzed (if reachable).

The predicate is of type *data*.

local_ana_module/2: PREDICATE

Usage: `local_ana_module(Base,Mod)`

Succeeds if `File` is a module of the program unit that is being analyzed in this iteration of the intermodular analysis.

The predicate is of type *data*.

registry/3: PREDICATE

Usage: `registry(Key,Module,Registry)`

Data predicate to locally store information about the registry of one or several modules. `Module` is the name of the module for which `Registry` is an entry in the registry file. It corresponds to the *global answer table* as it is described in [PCH03], or other auxiliary information (e.g., types).

The predicate is of type *data*.

registry_header/2: PREDICATE

Usage: `registry_header(Module,HeaderTerm)`

`HeaderTerm` is a term read from the registry header of module `Module`. Data predicate to store the header terms of every registry file read. The list of registry header terms depends on the registry file version, and is stored in `registry_header_format/2`

The predicate is of type *data*.

module_depth/2: PREDICATE

No further documentation available for this predicate. The predicate is of type *data*.

imported_module/2: PREDICATE

Usage: `imported_module(Module,Base)`

Enumerates the modules imported by the current module

The predicate is of type *data*.

caller_module/2: PREDICATE

Usage: `caller_module(Module,BaseName)`

List of caller modules to be processed.

The predicate is of type *data*.

src_changed/1: PREDICATE

No further documentation available for this predicate. The predicate is of type *data*.

add_src_changed/1: PREDICATE

No further documentation available for this predicate.

unset_src_changed/1: PREDICATE

No further documentation available for this predicate.

clean_program_structure/0: PREDICATE

No further documentation available for this predicate.

set_main_module/1: PREDICATE

Usage: `set_main_module(File)`

- *The following properties should hold at call time:*

  `File` is currently a term which is not a free variable. (`nonvar/1`)

- *The following properties should hold globally:*

  All the calls of the form `set_main_module(File)` do not fail. (`not_fails/1`)

set_punit_modules/1: PREDICATE

Usage: `set_punit_modules(File)`

- *The following properties should hold at call time:*

  `File` is currently a term which is not a free variable. (`nonvar/1`)

  `File` is a list. (`list/1`)

- *The following properties should hold globally:*

  All the calls of the form `set_punit_modules(File)` do not fail. (`not_fails/1`)

set_local_ana_modules/1: PREDICATE

Usage: `set_local_ana_modules(Mods)`

- *The following properties should hold at call time:*

  `Mods` is a list. (`list/1`)

- *The following properties should hold globally:*

  All the calls of the form `set_local_ana_modules(Mods)` do not fail. (`not_fails/1`)

  All calls of the form `set_local_ana_modules(Mods)` are deterministic. (`is_det/1`)

get_registry/4: PREDICATE

No further documentation available for this predicate.

add_registry/2: PREDICATE

No further documentation available for this predicate.

cleanup_registry/1: PREDICATE

No further documentation available for this predicate.

reg_version/1: PREDICATE

Usage: `reg_version(Version)`

Contains a version number which identifies the registry files associated with this version of the assertion library. Should be changed every time changes are made which render registry files incompatible, since this forces recomputation of all such files.

– *The following properties should hold upon exit:*

`Version` is an atom. (`atm/1`)

registry_header_format/2: PREDICATE

Usage: `registry_header_format(Version,TermList)`

`TermList` is the list of terms which must appear in the header of version `Version` registry files, excluding the version number term itself.

– *The following properties should hold at call time:*

`Version` is an atom. (`atm/1`)

– *The following properties should hold upon exit:*

`TermList` is a list. (`list/1`)

mod_typedb/2: PREDICATE

Usage: `mod_typedb(Module,TypeDef)`

Data predicate to locally store information about the types used in the registry of one or several modules. `Module` is the name of the module for which the type definition `TypeDef` is referenced in the registry file. The original definition of `TypeDef` may not reside in `Module`, but in a related module.

– *The following properties should hold upon exit:*

`Module` is an atom. (`atm/1`)

`TypeDef` is any term. (`term/1`)

add_mod_typedb/2: PREDICATE

No further documentation available for this predicate.

enum_mod_typedb/1: PREDICATE

No further documentation available for this predicate.

75.3 Documentation on imports

This module has the following direct dependencies:

– *System library modules:*

`native_props`, `datafacts_rt`, `streams`, `aux_filenames`, `program_keys`.

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `isomodes`, `regtypes`, `nativeprops`, `datafacts`.

76 Intermodular analysis scheduler

This module implements different intermodular scheduling policies. This affects the order in which modular iteration is performed.

76.1 Usage and interface

- **Library usage:**
  `:- use_module(ciaopp(plai/intermod_schedule)).`
- **Exports:**
  - *Predicates:*
    `modules_analyzed/1`, `reset_queue/0`, `push/2`, `pop/2`, `naive_pending_modules/1`, `force_analysis/1`, `cleanup_intermod_scheduling/0`, `naive_module_order/1`, `iterations/1`, `module_processed/2`, `setup_scheduling/4`, `is_naive_scheduling/1`, `add_naive_pending_modules/1`.

76.2 Documentation on exports

modules_analyzed/1: PREDICATE

No further documentation available for this predicate. The predicate is of type *data*.

reset_queue/0: PREDICATE

Usage:

Empties the queue.

push/2: PREDICATE

Usage 1: `push(Element,Priority)`

Pushes a new element `Element` with priority `Priority` into the priority queue. If `Element` is already in the queue, it is not duplicated, but its priority is changed to the maximum prioriy of the already existing element and the priority of the new element.

- *The following properties should hold at call time:*

  `Element` is currently a term which is not a free variable. (`nonvar/1`)

  `Priority` is currently a term which is not a free variable. (`nonvar/1`)

  `Element` is an atom. (`atm/1`)

  `Priority` is an integer. (`int/1`)

Usage 2: `push(ElementList,Priority)`

Pushes a set of new elements `ElementList` with priority `Priority` into the priority queue. If any element of `ElementList` is already in the queue, it is not duplicated, but its priority is changed to the maximum prioriy of the already existing element and the priority of the new element.

– *The following properties should hold at call time:*

`ElementList` is currently a term which is not a free variable. (`nonvar/1`)

`Priority` is currently a term which is not a free variable. (`nonvar/1`)

`ElementList` is a list of `atm`s. (`list/2`)

`Priority` is currently instantiated to an integer. (`integer/1`)

pop/2: PREDICATE

Usage: `pop(Element,Priority)`

Pops the element `Element` with highest priority from the priority queue.

– *The following properties should hold at call time:*

`Element` is a free variable. (`var/1`)

`Priority` is a free variable. (`var/1`)

– *The following properties should hold upon exit:*

`Element` is an atom. (`atm/1`)

`Priority` is an integer. (`int/1`)

naive_pending_modules/1: PREDICATE

No further documentation available for this predicate. The predicate is of type *data*.

force_analysis/1: PREDICATE

No further documentation available for this predicate. The predicate is of type *data*.

cleanup_intermod_scheduling/0: PREDICATE

No further documentation available for this predicate.

naive_module_order/1: PREDICATE

No further documentation available for this predicate. The predicate is of type *data*.

iterations/1: PREDICATE

No further documentation available for this predicate. The predicate is of type *data*.

module_processed/2: PREDICATE

Usage: `module_processed(Module,AlreadyProcessed)`

Lists the modules in the program unit and whether they are already processed or not.

The predicate is of type *data*.

setup_scheduling/4: PREDICATE

Usage: `setup_scheduling(SchedPolicy,Domains,TopLevel,ModList)`

This predicate sets up some stuff in specific global scheduling policies. Implemented policies are as follows:

- `abs_depth_first` Starting from the modules which require analysis (those in `ModList`, it uses the depth in the intermodule dependency graph as priority, and analyzes the modules with higher priority first.
- `naive_top_down` Traverses the list of modules in the intermodule graph in top-down order, and analyzes the modules which have pending patterns. Initially, the modules with pending patterns are the ones in `ModList`. It stops when in a module traversal there is no module with pending patterns.
- `naive_bottom_up` The same as `naive_top_down`, but the list of modules is in reverse top-down order.
- `top_down_preanalysis` The same as `naive_top_down`, but initially all modules are scheduled for analysis. This scheduling policy is intended for using an entry policy different of `main_module` (for example, `all`).
- `bottom_up_preanalysis` The same as `top_down_preanalysis`, but a bottom-up traversal of the intermodule graph is made.

is_naive_scheduling/1: PREDICATE

No further documentation available for this predicate.

add_naive_pending_modules/1: PREDICATE

Usage:

– *The following properties should hold at call time:*

`Arg1` is a list. (`list/1`)

– *The following properties should hold globally:*

All the calls of the form `add_naive_pending_modules(Arg1)` do not fail. (`not_fails/1`)

76.3 Documentation on imports

This module has the following direct dependencies:

– *Application modules:*

`intermod_db`, `intermod_punit`.

– *System library modules:*

`native_props`, `datafacts_rt`, `lists`, `sets`.

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `isomodes`, `nativeprops`, `datafacts`.

77 Program structure for intermodular analysis

This module contains the functionality to compute the intermodular graph of a program, i.e., the dependencies of its modules.

The predicate `compute_intermodule_graph/1` calls the Ciao compiler to obtain which modules are in the intermodular punit, which is controlled by the flag `punit_boundary`. This is done by:

- `process_changed_module/1`: Is executed if the module changed (w.r.t. the `.itf` file.
- `check_stop_one_module/1`: Decides whether the compiler needs to keep processing the modules imported by the current module.
- `redo_unchanged_module/1`: Is executed if there were no changes since the last time the module was **compiled**, if always fails because it is asking whether to process the file **again**.

77.1 Usage and interface

- **Library usage:**
  `:- use_module(ciaopp(plai/intermod_punit)).`
- **Exports:**
  - *Predicates:*
    `compute_punit_modules/3`, `get_punit_modules/1`, `get_punit_included_files/1`, `get_all_module_cycles/2`, `module_is_processable/1`, `ensure_registry_file/3`, `read_registry_file/3`, `write_registry_file/3`, `open_mode/3`, `change_open_mode/2`, `save_registry_info/3`, `save_registry_info/2`, `compute_imported_modules/0`, `get_imported_module_base/2`, `get_modules_analyzed/1`, `set_modules_analyzed/1`.

77.2 Documentation on exports

compute_punit_modules/3: PREDICATE

Usage: `compute_punit_modules(TopLevel,ModList,Error)`

`ModList` is the list of modules to analyze. This list is formed by the modules which have their .reg file outdated, or if the module is not completely analyzed (some of the entries in the .reg file are marked or invalid). For those modules which have no .reg file, the *parents* of the module are included in the list (as there are no call patterns for those modules without .reg file).

The structure of the elements in the list is a term (`Mod`,`Depth`,`Force`), where `Mod` stands for the module name, `Depth` is the maximum depth without cycles in the intermodular graph, and `Force` marks those modules which must be completely reanalyzed (only useful for the parents of the modules with no reg file).

- *The following properties should hold at call time:*
  `TopLevel` is currently a term which is not a free variable. (`nonvar/1`)
- *The following properties should hold upon exit:*
  `ModList` is currently a term which is not a free variable. (`nonvar/1`)
  `Error` is currently a term which is not a free variable. (`nonvar/1`)

– *The following properties should hold globally:*

All the calls of the form `compute_punit_modules(TopLevel,ModList,Error)` do not fail. (`not_fails/1`)

All calls of the form `compute_punit_modules(TopLevel,ModList,Error)` are deterministic. (`is_det/1`)

get_punit_modules/1: PREDICATE

Usage: `get_punit_modules(ModList)`

Obtains `ModList`, the list of modules in the program unit that is currently loaded. This list is formed by the modules which appear in the top-down modular graph traversal with registries set to read_write mode (and including library modules if punit_boundary flag is set to 'on'. `compute_punit_modules/2` needs to be called before.

– *The following properties should hold upon exit:*

`ModList` is currently a term which is not a free variable. (`nonvar/1`)

`ModList` is a list. (`list/1`)

– *The following properties should hold globally:*

All the calls of the form `get_punit_modules(ModList)` do not fail. (`not_fails/1`)

All calls of the form `get_punit_modules(ModList)` are deterministic. (`is_det/1`)

get_punit_included_files/1: PREDICATE

Usage: `get_punit_included_files(IncludeList)`

Returns the list of included files in the program unit. This list includes not only files explicitly included with `:- include` declarations, but also packages used. `compute_punit_modules/2` needs to be called before.

– *The following properties should hold upon exit:*

`IncludeList` is currently a term which is not a free variable. (`nonvar/1`)

`IncludeList` is a list of `filename`s. (`list/2`)

– *The following properties should hold globally:*

All the calls of the form `get_punit_included_files(IncludeList)` do not fail. (`not_fails/1`)

All calls of the form `get_punit_included_files(IncludeList)` are deterministic. (`is_det/1`)

get_all_module_cycles/2: PREDICATE

Usage: `get_all_module_cycles(TopLevelFile,CycleList)`

Obtains `CycleList`, the list of cycles in the program unit whose top-level module is `TopLevelFile`. A cycle is a ciclic dependency in the module dependency graph. Every element of `CycleList` is a list of the modules which belong to each cycle. Modules not belonging to any cycle are represented as one-element lists. `CycleList` is sorted as a post-order traversal of the inter-cycle dependency graph.

The modules included in `CycleList` are those which appear in the top-down modular graph traversal with registries set to read_write mode (and including library modules if punit_boundary flag is set to 'on'.)

– *The following properties should hold at call time:*

`TopLevelFile` is currently a term which is not a free variable. (`nonvar/1`)

– *The following properties should hold upon exit:*

`CycleList` is currently a term which is not a free variable. (`nonvar/1`)

`CycleList` is a list. (`list/1`)

– *The following properties should hold globally:*

All the calls of the form `get_all_module_cycles(TopLevelFile,CycleList)` do not fail. (`not_fails/1`)

All calls of the form `get_all_module_cycles(TopLevelFile,CycleList)` are deterministic. (`is_det/1`)

module_is_processable/1: PREDICATE

Usage: `module_is_processable(Base)`

Succeeds if module in `Base` can be processed by intermodular preprocessing tools. This predicate may have to load the registry file of that module, in order to check that the module has read-write mode.

– *The following properties should hold at call time:*

`Base` is currently a term which is not a free variable. (`nonvar/1`)

ensure_registry_file/3: PREDICATE

No further documentation available for this predicate.

read_registry_file/3: PREDICATE

Usage: `read_registry_file(Module,Base,Verb)`

Reads the registry file of `Module` and loads it into `registry/2`, erasing any previous registry information for that module. `Base` must be the absolute file name, but excluding file extension.

– *The following properties should hold at call time:*

`Module` is currently a term which is not a free variable. (`nonvar/1`)

`Base` is currently a term which is not a free variable. (`nonvar/1`)

`Verb` is currently a term which is not a free variable. (`nonvar/1`)

`Module` is an atom. (`atm/1`)

`Base` is an atom. (`atm/1`)

`Verb` is an atom. (`atm/1`)

– *The following properties should hold globally:*

All the calls of the form `read_registry_file(Module,Base,Verb)` do not fail. (`not_fails/1`)

All calls of the form `read_registry_file(Module,Base,Verb)` are deterministic. (`is_det/1`)

write_registry_file/3: PREDICATE

Usage: `write_registry_file(Base,Module,Verb)`

Writes to disk the registry information stored in memory for module `Module` which has as base file name `Base`.

- *The following properties should hold at call time:*

  `Base` is an atom. (`atm/1`)

  `Module` is an atom. (`atm/1`)

  `Verb` is an atom. (`atm/1`)

- *The following properties should hold globally:*

  All the calls of the form `write_registry_file(Base,Module,Verb)` do not fail. (`not_fails/1`)

  All calls of the form `write_registry_file(Base,Module,Verb)` are deterministic. (`is_det/1`)

open_mode/3: PREDICATE

Usage: `open_mode(Base,Type,OpenMode)`

Module with basename `Base` is of type `Type` and it is opened with mode `OpenMode`. `Type` can be `user` or `library`. `OpenMode` is used to indicate if an imported module's registry can be updated. It can take the values `read_write` or `read_only`.

change_open_mode/2: PREDICATE

Usage: `change_open_mode(Base,OpenMode)`

`OpenMode` is the new open mode of the module with basename `Base`. `OpenMode` can take the values `read_write` and `read_only`.

- *The following properties should hold at call time:*

  `Base` is currently a term which is not a free variable. (`nonvar/1`)

  `OpenMode` is currently a term which is not a free variable. (`nonvar/1`)

save_registry_info/3: PREDICATE

Usage: `save_registry_info(Verb,CurrBase,Info)`

Writes on disk the registry information of the modules related to the current module (`CurrBase`) which have been modified. This information is updated by `gen_registry_info/3`. Even if this predicate is used, `save_registry_info/2` must be used after performing intermodular preprocessing.

- *The following properties should hold at call time:*

  `Verb` is currently a term which is not a free variable. (`nonvar/1`)

  `CurrBase` is currently a term which is not a free variable. (`nonvar/1`)

  `Verb` is an atom. (`atm/1`)

  `CurrBase` is an atom. (`atm/1`)

  `Info` is any term. (`term/1`)

- *The following properties should hold globally:*

  All the calls of the form `save_registry_info(Verb,CurrBase,Info)` do not fail. (`not_fails/1`)

  All calls of the form `save_registry_info(Verb,CurrBase,Info)` are deterministic. (`is_det/1`)

save_registry_info/2: PREDICATE

Usage: `save_registry_info(Verb,Info)`

Writes on disk the registry information of the modules loaded into Ciaopp or related to modules loaded into Ciaopp. This information is updated by `gen_registry_info/3`. This predicate must be called after performing intermodular preprocessing (analysis, specialization...), even if `save_registry_info/3` has been used.

– *The following properties should hold at call time:*

`Verb` is currently a term which is not a free variable. (`nonvar/1`)

`Verb` is an atom. (`atm/1`)

`Info` is any term. (`term/1`)

– *The following properties should hold globally:*

All the calls of the form `save_registry_info(Verb,Info)` do not fail. (`not_fails/1`)

All calls of the form `save_registry_info(Verb,Info)` are deterministic. (`is_det/1`)

compute_imported_modules/0: PREDICATE

Usage:

Gets the list of imported modules from the current module. This list is obtained from the itf information of the current module, and is stored in `imported_module/1`.

– *The following properties should hold globally:*

All the calls of the form `compute_imported_modules` do not fail. (`not_fails/1`)

All calls of the form `compute_imported_modules` are deterministic. (`is_det/1`)

get_imported_module_base/2: PREDICATE

No further documentation available for this predicate.

get_modules_analyzed/1: PREDICATE

Usage: `get_modules_analyzed(ModList)`

Returns the list of modules analyzed the last time a modular analysis was executed.

– *The following properties should hold upon exit:*

`ModList` is a list. (`list/1`)

set_modules_analyzed/1: PREDICATE

Usage: `set_modules_analyzed(ModList)`

Sets the list of modules which have been analyzed.

– *The following properties should hold at call time:*

`ModList` is a list. (`list/1`)

77.3 Documentation on imports

This module has the following direct dependencies:

– *Application modules:*

`preprocess_flags`, `ciaopp_log`, `analysis_stats`, `intermod_db`, `tarjan`, `frontend_driver`, `intermod_ops`.

– *System library modules:*

`native_props`, `datafacts_rt`, `p_unit_db`, `p_asr`, `aux_filenames`, `c_itf_props`, `aggregates`, `ctrlcclean`, `errhandle`, `streams`, `write`, `read`, `pathnames`, `system`, `fastrw`, `hiordlib`, `bundle_paths`, `c_itf`.

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`, `stream_basic`, `io_basic`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `modes`, `nativeprops`, `datafacts`.

78 Intermodular entry policy

This module provides the entry policy algorithms for modular analysis. The entry policy is determined by the `entry_policy` preprocessing flag.

78.1 Usage and interface

- **Library usage:**
  `:- use_module(ciaopp(plai/intermod_entry)).`
- **Exports:**
  - *Predicates:*
    `check_curr_entry_id/1`, `curr_entry_id/1`, `get_entry_info/3`, `intermod_entry_point/7`, `add_entries_to_registry/1`.

78.2 Documentation on exports

check_curr_entry_id/1: PREDICATE

Usage: `check_curr_entry_id(Id)`

Checks that `Id` was an entry of the last fixpoint analysis.

- *The following properties should hold at call time:*
  `Id` is currently a term which is not a free variable. (`nonvar/1`)

curr_entry_id/1: PREDICATE

Usage: `curr_entry_id(Id)`

Enumerates the `Id`s of the entries of the last fixpoint analysis.

get_entry_info/3: PREDICATE

Usage: `get_entry_info(AbsInt,Sg,Proj)`

Provides on backtracking entry abstract substitutions for the current module in the global level of intermodular analysis. In the case of manual scheduling, this predicate should be called for every module in the program unit. In the case of automatic scheduling, this predicate should only be called with top-level(U).

- *The following properties should hold at call time:*
  `AbsInt` is currently a term which is not a free variable. (`nonvar/1`)
  `Sg` is a free variable. (`var/1`)
  `Proj` is a free variable. (`var/1`)

intermod_entry_point/7: PREDICATE

Usage:

User-specified entry points for intermodular analysis. I.e., according to the policy defined

add_entries_to_registry/1: PREDICATE

Usage: `add_entries_to_registry(AbsInt)`

– *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`AbsInt` is an atom. (`atm/1`)

– *The following properties should hold globally:*

All the calls of the form `add_entries_to_registry(AbsInt)` do not fail. (`not_fails/1`)

78.3 Documentation on imports

This module has the following direct dependencies:

– *Application modules:*

`intermod_ops`, `preprocess_flags`, `domains`, `transform`, `apply_assertions`, `intermod_db`.

– *System library modules:*

`native_props`, `datafacts_rt`, `lists`, `terms_vars`, `counters`, `vndict`, `p_unit`, `program_keys`, `p_unit_db`, `assrt_lib`.

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `isomodes`, `nativeprops`, `datafacts`.

79 Intermodular success policy

This module implements the policies to compute (possibly) temporary success patterns when modular analysis is performed.

79.1 Usage and interface

- **Library usage:**
  `:- use_module(ciaopp(plai/intermod_success)).`
- **Exports:**
  - *Predicates:*
    `get_success_info/7`, `apply_success_policy/9`.

79.2 Documentation on exports

get_success_info/7: PREDICATE

Usage: `get_success_info(Call,SgKey,Sg,Sv,AbsInt,Prime,PatternsApplied)`

Given a call pattern for an imported predicate defined by `Call` call and `Sg` abstract substitution, `Prime` is the success substitution resulting from the application of the success policy for imported predicates. `PatternsApplied` is instatiated to `no` if there are no applicable patterns. The predicate is allowed to fail if no patterns are found.

- *The following properties should hold at call time:*

`Call` is currently a term which is not a free variable.	(`nonvar/1`)
`SgKey` is currently a term which is not a free variable.	(`nonvar/1`)
`Sg` is currently a term which is not a free variable.	(`nonvar/1`)
`Sv` is currently a term which is not a free variable.	(`nonvar/1`)
`AbsInt` is currently a term which is not a free variable.	(`nonvar/1`)
`Prime` is a free variable.	(`var/1`)
`PatternsApplied` is a free variable.	(`var/1`)

apply_success_policy/9: PREDICATE

Usage: `apply_success_policy(SuccPolicy,AbsInt,SgKey,Sg,Sv,Proj,Patterns,Prime,PatternsApplied)`

Applies the success policy given as first argument to the list of triples (SgProj,Proj,Succ) `Patterns` w.r.t. `Proj`. If there are no applicable patterns in `Patterns`, it returns either `'$bottom'` or the topmost substitution, depending on the type of the success policy (either it is underapproximating or overapproximating, respectively.) `PatternsApplied` is instatiated to `no` if there are no applicable patterns.

- *The following properties should hold at call time:*

`SuccPolicy` is currently a term which is not a free variable.	(`nonvar/1`)
`AbsInt` is currently a term which is not a free variable.	(`nonvar/1`)
`SgKey` is currently a term which is not a free variable.	(`nonvar/1`)
`Sg` is currently a term which is not a free variable.	(`nonvar/1`)

`Sv` is currently a term which is not a free variable.	(`nonvar/1`)
`Proj` is currently a term which is not a free variable.	(`nonvar/1`)
`Patterns` is currently a term which is not a free variable.	(`nonvar/1`)
`Prime` is a free variable.	(`var/1`)
`PatternsApplied` is a free variable.	(`var/1`)

79.3 Documentation on imports

This module has the following direct dependencies:

– *Application modules:*

`intermod_ops`, `preprocess_flags`, `domains`, `fixpo_ops`, `intermod_db`, `intermod_punit`.

– *System library modules:*

`datafacts_rt`, `terms_vars`, `aggregates`, `terms_check`, `lists`, `p_unit_db`, `program_keys`.

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `isomodes`, `datafacts`.

80 Preprocessing Flags

80.1 Usage and interface

- **Library usage:**
  `:- use_module(ciaopp(preprocess_flags)).`
- **Exports:**
  - *Predicates:*
    `push_pp_flag/2`, `pop_pp_flag/1`, `current_pp_flag/2`, `set_pp_flag/2`, `pp_flag/2`, `valid_flag_values/2`, `dump_flags/1`, `save_config/1`, `restore_config/1`, `remove_config/1`, `show_config/1`, `show_configs/0`, `sublist2/2`, `typeanalysis/1`.
  - *Properties:*
    `valid_flag_value/2`.
  - *Regular Types:*
    `pp_flag/1`, `flag_value/1`.
  - *Multifiles:*
    `$is_persistent/2`, `persistent_dir/2`, `persistent_dir/4`, `dump_flags_list/2`.

80.2 Documentation on exports

push_pp_flag/2: PREDICATE

Usage: `push_pp_flag(Flag,Value)`

Sets `Value` for preprocessor flag `Flag`, storing the current value to restore it with `pop_pp_flag/1`.

- *The following properties should hold at call time:*
  `Flag` is a valid preprocessor flag. (`pp_flag/1`)
  `Value` is a valid value for preprocessor flag `Flag`. (`valid_flag_value/2`)

pop_pp_flag/1: PREDICATE

Usage: `pop_pp_flag(Flag)`

Restores the value of the preprocessor flag `Flag` previous to the last non-canceled `push_pp_flag/2` on it.

- *The following properties should hold at call time:*
  `Flag` is a valid preprocessor flag. (`pp_flag/1`)

current_pp_flag/2: PREDICATE

Usage: `current_pp_flag(Name,Value)`

Preprocess flag `Name` has the value `Value`.

- *The following properties should hold at call time:*
  `Name` is a valid preprocessor flag. (`pp_flag/1`)
- *The following properties should hold upon exit:*
  `Value` is a valid value for preprocessor flag `Name`. (`valid_flag_value/2`)

set_pp_flag/2: PREDICATE

Usage: `set_pp_flag(Name,Value)`

Sets `Value` for preprocessor flag `Name`.

– *The following properties should hold at call time:*

`Name` is a valid preprocessor flag. (`pp_flag/1`)

`Value` is a valid value for preprocessor flag `Name`. (`valid_flag_value/2`)

pp_flag/2: PREDICATE

Usage: `pp_flag(Name,Help)`

`Name` is a valid preprocess flag.`Help` is a description of what `Name` does.

pp_flag/1: REGTYPE

The list of valid flags and their values is as follows:

(This list is outdated – see source code for a complete description)

- for the output:
  - `analysis_info` (`off, on`) Whether to output the results of analysis.
  - `point_info` (`off,on`) Whether to output analysis information for program points within clauses.
  - `collapse_ai_vers` (`off, on`) to output all the versions of call/success patterns inferred by analysis or just one version (summing-up all of them).
  - `type_output` (`defined, all`) to output the types inferred for predicates in terms only of types defined by the user or including types inferred anew.
  - `simplify_checks` (`on, off`) to output simplified check assertions after verification or not.
- for analysis:
  - `fixpoint` (`plai, dd, di, check_di, check_di2, check_di3, check_di4`) The kind of fixpoint computation used.
  - `multi_success` (`off, on`) Whether to allow success multivariance.
  - `widen` (`off, on`) Whether to perform widening.
  - `intermod` (`off, on, auto`) The policy for inter-modular analysis.
  - `success_policy` (`best, first, all, top, botfirst, botbest, botall, bottom`) The policy for obtaining success information for imported predicates during inter-modular analysis.
  - `entry_policy` (`all, top_level, force, force_assrt`) The policy for obtaining entry call patterns for exported predicates during inter-modular analysis.
  - `process_libraries` (`on, off, no_engine`) Whether to perform the analysis of Ciao system libraries when a modular user program is analyzed.
  - `initial_guess` (`botfirst, botbest, botall, bottom`) The policy for obtaining initial guess when computing the analysis of a predicate from the current module.
  - `use_check_assrt` (`off, on`) Whether to use check assertions for imported predicates as if they were trust assertions.

- `depth` (a non-negative integer) The maximum depth of abstractions in analyses based on term depth.
- `type_eval` (`on, off`) Whether to attempt concrete evaluation of types being inferred.
- `type_precision` (`defined, all`) to use during type analysis only types defined by the user or also types inferred anew.
- `entry_points_auto` (`none, calls, all`) What kind of assertions to use as entry points: `entry/1` will always be used, `calls/1` and `calls/2` will be used if the flag is **not** set to `none`; and `success/1`, `success/2`, `comp/1` and `comp/2` will be used if the flag is set to `all`.
- `entry_calls_scope` (`exported, all`) What non-`entry` assertions to use as entry points. If the flag takes the value `exported`, only assertions from exported predicates will be used; if it takes the value `all`, exported and non-exported assertions will be used.

- for partial evaluation:
  - `global_control` (`off, id, inst, hom_emb`) The abstraction function to use to control the creation of new patterns to analyze as a result of unfolding.
  - `comp_rule` (`leftmost, safe_jb, bind_ins_jb, no_sideff_jb, jump_builtin, eval_builtin, local_emb`) The computation rule for the selection of atoms in a goal.
  - `local_control` (`off, orig, inst, det, det_la, depth, first_sol, first_sol_d, all_sol, hom_emb, hom_emb_anc, hom_emb_as, df_hom_emb_as, df_tree_hom_emb, df_hom_emb`) The unfolding rule to use during partial evaluation.
  - `unf_depth` (a non-negative integer) The depth limit for unfolding.
  - `rem_use_cls` (`off, pre, post, both`) Whether to remove useless clauses.
  - `abs_spec_defs` (`off, rem, exec, all`) Whether to exploit abstract substitutions while obtaining specialized definitions on unfolding.
  - `filter_nums` (`off, on`) Whether to filter away numbers in partial evaluation.
  - `exec_unif` (`off, on`) Whether to execute unifications during specialization time or not.
  - `pres_inf_fail` (`off, on`) Whether infinite failure should be preserved in the specialized program.
  - `part_concrete` (`off, mono, multi`) The kind of partial concretization to be performed.
- for parallelization and granularity control:
  - `granularity_threshold` (a non-negative integer) The threshold on computational cost at which parallel execution pays off.

Usage: `pp_flag(Flag)`

`Flag` is a valid preprocessor flag.

flag_value/1: REGTYPE

Usage: `flag_value(V)`

`V` is a value for a flag.

valid_flag_value/2: PROPERTY

Usage: `valid_flag_value(Name,Value)`

`Value` is a valid value for preprocessor flag `Name`.

– *If the following properties should hold at call time:*

`Name` is a valid preprocessor flag. (`pp_flag/1`)

`Value` is a value for a flag. (`flag_value/1`)

valid_flag_values/2: PREDICATE

Usage: `valid_flag_values(Name,Value_Checker)`

`Value_Checker` is a goal that checks that a value given as first argument of this term is a valid value for `Name`.

– *Call and exit should be compatible with:*

`Name` is a valid preprocessor flag. (`pp_flag/1`)

`Value_Checker` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)

dump_flags/1: PREDICATE

Usage: `dump_flags(Name)`

`Name` represent the list of flags to be dumped. To associate a name (key) with a list, use `dump_flags_list`.

– *The following properties should hold at call time:*

`Name` is an atom. (`atm/1`)

save_config/1: PREDICATE

Usage: `save_config(Name)`

Save the current flags configuration under the `Name` key.

– *The following properties should hold at call time:*

`Name` is an atom. (`atm/1`)

restore_config/1: PREDICATE

Usage: `restore_config(Name)`

Restores the set of flags saved previously under the name of `Name`.

– *The following properties should hold at call time:*

`Name` is an atom. (`atm/1`)

remove_config/1: PREDICATE

Usage: `remove_config(Name)`

Remove the configuration stored with the `Name` key.

– *The following properties should hold at call time:*

`Name` is an atom. (`atm/1`)

show_config/1: PREDICATE

Usage: `show_config(C)`

Show specific configuration values pointed by `C` key.

– *The following properties should hold at call time:*

`C` is an atom. (`atm/1`)

show_configs/0: PREDICATE

Usage:

Show all stored configs.

sublist2/2: PREDICATE

No further documentation available for this predicate.

typeanalysis/1: PREDICATE

No further documentation available for this predicate.

80.3 Documentation on multifiles

$is_persistent/2: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

The predicate is of type *data*.

persistent_dir/2: PREDICATE

Usage 1: `persistent_dir(Key,Dir)`

– *The following properties hold upon exit:*

`Key` is an atom. (`atm/1`)

`Dir` is an atom. (`atm/1`)

Usage 2: `persistent_dir(Key,Dir)`

– *The following properties should hold at call time:*

`Key` is an atom. (`atm/1`)

`Dir` is a free variable. (`var/1`)

Usage 3: `persistent_dir(Key,Dir)`

– *The following properties should hold at call time:*

`Key` is an atom. (`atm/1`)

`Dir` is an atom. (`atm/1`)

The predicate is *multifile*.

The predicate is of type *data*.

persistent_dir/4: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

The predicate is of type *data*.

dump_flags_list/2: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

80.4 Documentation on imports

This module has the following direct dependencies:

- *Application modules:*

  `frontend_driver`.
- *System library modules:*

  `datafacts_rt`, `persdb_rt`, `pathnames`, `system`, `lists`, `aggregates`, `write`, `menu_generator`.
- *Internal (engine) modules:*

  `term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`, `messages_basic`, `io_basic`.
- *Packages:*

  `prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `nortchecks`, `regtypes`, `isomodes`, `persdb`, `datafacts`, `persdb/persdb_decl`, `ciaopp(ciaopp_options)`.

81 Debugging PLAI analyses

Author(s): Isabel Garcia-Contreras.

This module is intended for debugging fixpoints and abstract domains. The debugging modes are sorted by difficulty and knowledge required by the programmer.

General comments. To discard errors related with not cleaning properly internal databases it is better not to debug in the ciao/ciaopp toplevel, but rather use the ciaopp command line if possible.

81.1 Debug raw analysis result

Output the analysis result without postprocessing. This is using internal clause representation of ciaopp and internal representation of the abstract domain. For this, simply set the flag `output_lang` to `raw`.

For every **reachable** program point there is one or more `true` annotations, one for every inferred call pattern. In the body, annotations with the same number correspond to the execution of the abstract call with that number. A raw assertion will appear with the same id for such abstract call and success.

Note that this option is specially useful when developing a new abstract domain. If the predicates `asub_to_info/5`, `asub_to_native/6`, etc are not defined, no useful information appears in the usual.

81.2 Inspect analysis graphs

Dump the analysis graph in some <file>:

```
ciaopp ?- use_module(ciaopp(p_dump)).
ciaopp ?- dump(<file>).
```

Use the command `ciaopp-dump` to inspect:

```
$ ciaopp-dump show <file>
     # Print info of the dump <file>.
$ ciaopp-dump fmt <file>
     # Outputs the analysis result in dot format.
$ dot -Tpdf <file>.dot -o <file>.pdf
     # Generates a graph in pdf of the dot analysis format.
```

81.3 Trace fixpoint operations

Output steps to reach fixpoint. It is useful to combine this option with the raw output, as it shows the steps to generate the graphs using the same numbers for ids.

In file `src/plai/fixpoint_options.pl`, uncomment `:- use_package(.(notrace)).`, and recompile:

```
$ ciao build --bin ciaopp
```

A clean may be necessary, due to some undetected changes in incremental compilation of programs with included files.

```
$ ciao clean ciaopp
```

Then set flag `trace_fixp` to `trace` in the `ciaopp` toplevel or activate it in the command line:

```
$ ciaopp -A <file> -ftrace_fixp=trace
```

Additionally, if the flag `timestamp_trace` is set to `on` (can only be set in the `ciaopp` toplevel) a timestamp is printed when tracing. This can help finding perfomance issues.

81.4 Activate run-time checks

Go to any module, add `:- use_package(rtchecks).` and recompile by

```
$ ciao build --bin ciaopp
```

Modules recommended:

- Generic domain interface `src/plai/domains.pl`.
- Any specific domain. of `src/domains/*` (check that it has assertions!).
- Fixpoints: `src/plai/fixpoint_options.pl`.
- Generic fixpoint operations: `src/plai/fixpo_ops.pl`.
- Modular analysis: `src/plai/intermod_options.pl`.
- Incremental analysis: `src/plai/incanal/incanal_options.pl`.
- Assertions during fixpoint: `src/plai/apply_assertions.pl`/`src/plai/apply_assertions_old.pl`.

In `domains.pl` the assertions were written by looking only at some domains, not all of them. It could happen that they are too restrictive. If you find that an assertion does not hold in run-time, please open an issue.

81.5 Debug fixpoint step by step

For this, it is recommended to deactivate run-time checks, as the debugger shows also the code for RT checking.

Write `:- use_package(trace).` in `src/plai/fixpoint_options.pl` and recompile:

```
$ ciao build --bin ciaopp
```

In an emacs shell buffer do `M-x ciao-inferior-mode`. Then execute the ciaopp command to debug

```
$ ciaopp -A <file>
```

81.6 Access PLAI databases directly

```
ciaopp ?- use_module(ciaopp(plai/plai_db)).
ciaopp ?- complete(SgKey,AbsInt,Sg,Proj,Prime,Id,Parents).
ciaopp ?- memo_table(LitKey,AbsInt,Id,Child,Vars_u,Call).
```

82 Incremental analysis (high level)

Author(s): Isabel Garcia-Contreras.

Stability: [**devel**] Currently the subject of active development and/or research. Functionality may be limited and API and/or functionality may change without warning or deprecation period. Not recommended yet for use in production.

This module implements a high level interface of incremental analysis (see `incanal_driver` for the low level interface).

Global compilation options of incremental analysis are available in `incanal_options`. Edit this file to activate tracing or run-time checks.

Incremental analysis only works with fixpoint dd, one abstract domain and multivariance on success off. The assertions of the predicates of this module reflect this.

82.1 Usage

Important: For using incremental analysis some ciaopp flags have to be set:

```
?- set_pp_flag(fixpoint, dd),
   set_pp_flag(incremental, on),
   set_pp_flag(del_strategy, top_down). %% select strategy for incremental deletion
```

1. (Re)Load a list of modules to be analyzed with `incremental_module/1` (or `incremental_module/2` to get statistics). It can be done several times before reanalyzing.
2. (Re)Analyze the code with `incremental_analyze/1` (or `incremental_analyze/2` to get statistics). Internally, the changes will be automatically incrementally applied.

   This predicate depends on the ciaopp flag `del_strategy` for incremental deletion.

Note: If a module is not present in the reloading list, it is assumed that it has been removed from analysis so all modules must be in the input list although they may have not changed.

Tip (under construction!!): If you want to quickly display the information inferred by the analyzer between analyses you can:

```
?- use_module(ciaopp(raw_printer)).
?- show_analysis.
```

82.2 Example

Example of incremental analysis for file `foo.pl`

```
:- module(foo, [p/1], []).

p(1).
p(3).
```

Incremental analysis from Ciao toplevel:

```
?- use_module(ciaopp(plai/incanal)), use_module(ciaopp(preprocess_flags)).

yes
```

```
?- % incremental flags
   set_pp_flag(fixpoint, dd),
   set_pp_flag(incremental, on).

yes
?- incremental_module(foo, T).

T = [time(317.96,[])] ?

yes
?- incremental_analyze(eterms, T).

T = [proc_diff(0.244),add(2.281),delete(0.001)] ?

yes
% reload changes:
?- incremental_module(foo, T).

T = [time(299.822,[])] ?

yes
?- incremental_analyze(eterms, T).
{Incrementally analyzed with dd for eterms }

T = [proc_diff(0.314),add(2.148),delete(2.797)] ?

yes
```

82.3 Side effects

As a result of the incremental analysis, auxiliary files are generated for each analyzed module:

- When loaded a module: `File.itf`.
- When analyzed a module: `File.dump`.

They are used to detect if changes were made in a module. To reset the incremental analysis these files have to be removed.

WARNING: There might be problems with clause locators because Ids generated when transforming the code can be modified.

82.4 Usage and interface

- **Library usage:**
  `:- use_module(ciaopp(plai/incanal)).`
- **Exports:**
  - *Predicates:*
    `incremental_module/1`, `incremental_module/2`, `incremental_analyze/1`, `incremental_analyze/2`, `reset_incremental_analysis_info/0`, `config_incremental_load/1`, `all_assertions_pred/4`.

82.5 Documentation on exports

incremental_module/1: PREDICATE

Usage: `incremental_module(Files)`

Loads and transforms the code of `Files` to the ciaopp code database, computing the differences with the code previously present

- *The following properties should hold at call time:*
  `Files` is a list. (`list/1`)
- *The following properties should hold globally:*
  All the calls of the form `incremental_module(Files)` do not fail. (`not_fails/1`)

incremental_module/2: PREDICATE

Usage: `incremental_module(Files,Stats)`

Same as `incremental_module/1` but returns runtime statistics in `Stats`.

- *The following properties should hold at call time:*
  `Files` is a list. (`list/1`)
- *The following properties should hold upon exit:*
  `Stats` is a list. (`list/1`)
- *The following properties should hold globally:*
  All the calls of the form `incremental_module(Files,Stats)` do not fail. (`not_fails/1`)

incremental_analyze/1: PREDICATE

Usage: `incremental_analyze(AbsInt)`

Applies `Diff` to the current analysis by performing all deletions according to the deletion strategy set the ciaopp flag (`top_down` or `bottom_up`), reanalyzing and adding all clauses and assertions after.

- *The following properties should hold at call time:*
  `AbsInt` is an atom. (`atm/1`)

incremental_analyze/2: PREDICATE

Usage: `incremental_analyze(AbsInt,Stats)`

Same as `incremental_analyze/1` but returns runtime statistics in `Stats`. Statistics are divided in:

- `proc_diff`: Time needed to apply the differences to the incremental database.
- `add`: Time needed for performing the addition of clauses.
- `delete`: Time needed for performing the deletion of clauses according to the selected deletion strategy.

– *The following properties should hold at call time:*

`AbsInt` is an atom. (`atm/1`)

– *The following properties should hold upon exit:*

`Stats` is a list. (`list/1`)

– *The following properties should hold globally:*

All the calls of the form `incremental_analyze(AbsInt,Stats)` do not fail. (`not_fails/1`)

reset_incremental_analysis_info/0: PREDICATE

Usage:

Resets incremental and regular ciaopp internal data structures.

config_incremental_load/1: PREDICATE

Usage: `config_incremental_load(X)`

– *The following properties should hold at call time:*

`load_config(X)` (`load_config/1`)

all_assertions_pred/4: PREDICATE

No further documentation available for this predicate.

82.6 Documentation on imports

This module has the following direct dependencies:

– *Application modules:*

`frontend_driver`, `analyze_driver`, `preprocess_flags`, `fixpo_dd`, `incanal_driver`, `incanal_db`, `incanal_persistent_db`, `tarjan_inc`, `apply_assertions_inc`, `ciaopp_log`, `analysis_stats`.

– *System library modules:*

`datafacts_rt`, `native_props`, `lists`, `aggregates`, `diff`, `pathnames`, `p_unit_db`, `program_keys`.

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `regtypes`, `modes`, `datafacts`, `nativeprops`, `ciaopp(plai/notrace)`.

83 Incremental analysis (low level)

Author(s): Isabel Garcia-Contreras (ported from ciaopp-0.8).

This module contains the basic operations for adding or removing clauses to ciaopp (currently working for fixpoint dd) and perform an incremental reanalysis.

The posible actions are:

- Initialize ciaopp for incremental analysis (see `init_empty_inc_analysis`), for clauses to be added/removed from, they should be implemented in a file passed to this predicate.
- Add clauses to analysis (see `td_add_clauses/2`). Adds clauses and performs top down reanalysis.
- Remove clauses from analysis, following a top down strategy (see `td_delete_clauses/2`). Removes clauses and performs top down reanalysis.
- Remove clauses from analysis, following a bottom up strategy (see `bu_delete_clauses/2`). Removes clauses and reanalyzes according to the strategy defined.

83.1 Usage and interface

- **Library usage:**
  `:- use_module(ciaopp(plai/incanal/incanal_driver)).`
- **Exports:**
  - *Predicates:*
    `init_empty_inc_analysis/0`, `init_file_inc_analysis/3`, `td_add_clauses/2`, `td_delete_clauses/2`, `bu_delete_clauses/2`, `td_rec_delete_complete/3`, `module_has_entries/1`, `remove_useless_completes/1`, `run_inc_fixpoint/1`, `incrementally_update_analysis/2`, `process_external_complete_change/6`.

83.2 Documentation on exports

init_empty_inc_analysis/0: PREDICATE

Initializes ciaopp for incremental analysis. **Removes all previous analysis info**.

init_file_inc_analysis/3: PREDICATE

Usage: `init_file_inc_analysis(Files,Cls,Ds)`

Initializes incremental analysis with a file.

- *The following properties should hold at call time:*
  `Files` is a list. (`list/1`)

td_add_clauses/2: PREDICATE

Usage: `td_add_clauses(ClKeys,AbsInt)`

Adds a list of already processed clauses, expressed with their clause id (`ClKeys`) to the code database and updates the analysis of abstract domain `AbsInt` with them.

– *The following properties should hold at call time:*

`ClKeys` is a list. (`list/1`)

`AbsInt` is an atom. (`atm/1`)

– *The following properties should hold globally:*

All the calls of the form `td_add_clauses(ClKeys,AbsInt)` do not fail. (`not_fails/1`)

All calls of the form `td_add_clauses(ClKeys,AbsInt)` are deterministic. (`is_det/1`)

td_delete_clauses/2: PREDICATE

Usage: `td_delete_clauses(ClKeys,AbsInt)`

Removes clauses with ids of list `ClKeys` for abstract domain `AbsInt` from analysis using top-down deletion strategy and performs a reanalysis.

– *The following properties should hold at call time:*

`ClKeys` is a list. (`list/1`)

`AbsInt` is an atom. (`atm/1`)

– *The following properties should hold globally:*

All the calls of the form `td_delete_clauses(ClKeys,AbsInt)` do not fail. (`not_fails/1`)

All calls of the form `td_delete_clauses(ClKeys,AbsInt)` are deterministic. (`is_det/1`)

bu_delete_clauses/2: PREDICATE

Usage: `bu_delete_clauses(ClKeys,AbsInt)`

Removes clauses `Cls` for abstract domain `AbsInt` from analysis using the bottom up deletion strategy and performs a reanalysis.

– *The following properties should hold at call time:*

`ClKeys` is a list. (`list/1`)

`AbsInt` is an atom. (`atm/1`)

– *The following properties should hold globally:*

All the calls of the form `bu_delete_clauses(ClKeys,AbsInt)` do not fail. (`not_fails/1`)

All calls of the form `bu_delete_clauses(ClKeys,AbsInt)` are deterministic. (`is_det/1`)

td_rec_delete_complete/3: PREDICATE

Usage: `td_rec_delete_complete(Id,Key,AbsInt)`

This predicate removes the complete with `Id` in domain `AbsInt` and all its dependent information

– *The following properties should hold at call time:*

`Id` is currently a term which is not a free variable. (`nonvar/1`)

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`plai_db_id(Id)` (`plai_db_id/1`)

`AbsInt` is an atom. (`atm/1`)

– *The following properties should hold globally:*

All the calls of the form `td_rec_delete_complete(Id,Key,AbsInt)` do not fail. (`not_fails/1`)

module_has_entries/1: PREDICATE

No further documentation available for this predicate.

remove_useless_completes/1: PREDICATE

No further documentation available for this predicate.

run_inc_fixpoint/1: PREDICATE

Usage: `run_inc_fixpoint(AbsInt)`

This predicate runs fixpoint for abstract domain `AbsInt`. It should to be run after adding information from registry files in intermodular analysis.

– *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

– *The following properties should hold globally:*

All the calls of the form `run_inc_fixpoint(AbsInt)` do not fail. (`not_fails/1`)

All calls of the form `run_inc_fixpoint(AbsInt)` are deterministic. (`is_det/1`)

incrementally_update_analysis/2: PREDICATE

Usage: `incrementally_update_analysis(Mod,AbsInt)`

`Mod` is the module that will be reanalyzed after updating its external completes. To be called in modular analysis, no following analysis needed. This is a top-down strategy update

– *The following properties should hold at call time:*

`Mod` is currently a term which is not a free variable. (`nonvar/1`)

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

– *The following properties should hold globally:*

All the calls of the form `incrementally_update_analysis(Mod,AbsInt)` do not fail. (`not_fails/1`)

All calls of the form `incrementally_update_analysis(Mod,AbsInt)` are deterministic. (`is_det/1`)

process_external_complete_change/6: PREDICATE

Usage: `process_external_complete_change(AbsInt,NewPrime,SgKey,Sg,Id,Proj)`

This predicate updates analysis information given a complete that has changed externally. Typically this is used for updating completes that are outdated as a consequence of modular analysis (the analysis of a module was improved). The complete that has change has key `SgKey` and id `Id`. The new answer for the complete is `NewPrime` and refers to domain `AbsInt`.

Changes in answers are updated as follows:

- If the new answer is more general than the previous one, the update is as simple as replacing the answer in the complete and adding an event.
- If the new answer is more specific or incompatible, the information that depends on it has to be deleted and recomputed. We are removing the information with a top-down deletion strategy, although a bottom-up deletion strategy could more efficient. The fixpoint has to be runned after this deletion.

– *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`NewPrime` is currently a term which is not a free variable. (`nonvar/1`)

`SgKey` is currently a term which is not a free variable. (`nonvar/1`)

`Sg` is currently a term which is not a free variable. (`nonvar/1`)

`Id` is currently a term which is not a free variable. (`nonvar/1`)

`Proj` is currently a term which is not a free variable. (`nonvar/1`)

`AbsInt` is an atom. (`atm/1`)

`NewPrime` is a list. (`list/1`)

`SgKey` is an atom. (`atm/1`)

`plai_db_id(Id)` (`plai_db_id/1`)

– *The following properties should hold globally:*

All the calls of the form `process_external_complete_change(AbsInt,NewPrime,SgKey,Sg,Id,Proj)` do not fail. (`not_fails/1`)

83.3 Documentation on imports

This module has the following direct dependencies:

– *Application modules:*

`fixpo_dd`, `fixpo_ops`, `transform`, `domains`, `tarjan`, `plai_db`, `plai`, `intermod_entry`, `intermod_ops`, `frontend_driver`, `analyze_driver`, `preprocess_flags`, `analysis_stats`, `ciaopp_log`, `p_dump`, `tarjan_inc`, `plai_db_comparator`, `incanal_deletion`, `incanal_db`, `raw_printer`.

– *System library modules:*

`datafacts_rt`, `native_props`, `aggregates`, `lists`, `terms_vars`, `sort`, `p_unit`, `program_keys`, `p_unit_db`.

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`, `runtime_control`, `messages_basic`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `isomodes`, `datafacts`, `nativeprops`, `ciaopp(plai/notrace)`.

84 Update plai_db after clause deletion (incremental analysis)

Author(s): Isabel Garcia-Contreras (ported from ciaopp-0.8).

This module contains predicates for removing completes and related memo_table data from analysis necessary for recomputing correctly analysis after removing clauses or modifying the answers of the analysis.

84.1 Usage and interface

- **Library usage:**
  `:- use_module(ciaopp(plai/incanal/incanal_deletion)).`
- **Exports:**
  - *Predicates:*
    `remove_clauses_and_related_info_collect_preds/4`, `bottom_up_delete_completes_preds/4`, `bottom_up_delete_complete/5`, `external_calls/4`.

84.2 Documentation on exports

remove_clauses_and_related_info_collect_preds/4: PREDICATE

Usage:
`remove_clauses_and_related_info_collect_preds(ClKeys,AbsInt,Preds,Keys)`

`Cls` is a set of clauses which has have been eliminated from the program. Thus, they must be deleted from the database of clauses used by the analyzer. In addition to the clause, we delete all the memo_tables and memo_lubs for the clauses. In `Preds` and `Keys` we collect the name,arity and keys of predicates for which clauses have been deleted. This will later be used for updating the SCCs.

- *The following properties should hold at call time:*
  `ClKeys` is currently a term which is not a free variable. (`nonvar/1`)
  `AbsInt` is currently a term which is not a free variable. (`nonvar/1`)
  `Preds` is a free variable. (`var/1`)
  `Keys` is a free variable. (`var/1`)
- *The following properties should hold globally:*
  All the calls of the form `remove_clauses_and_related_info_collect_preds(ClKeys,AbsInt,Preds,Keys)` do not fail. (`not_fails/1`)
  All calls of the form `remove_clauses_and_related_info_collect_preds(ClKeys,AbsInt,Preds,Keys)` are deterministic. (`is_det/1`)

bottom_up_delete_completes_preds/4: PREDICATE

Usage: `bottom_up_delete_completes_preds(Keys,SCCs,AbsInt,ExtCompletes)`

`Keys` is the list of keys of predicates for which clauses have been deleted. The completes for such predicates may no longer be accurate enough. Thus we collect the external calls in `ExtCompletes` and erase the corresponding completes from the analysis database.

– *The following properties should hold at call time:*

`Keys` is currently a term which is not a free variable. (`nonvar/1`)

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`ExtCompletes` is a free variable. (`var/1`)

– *The following properties should hold globally:*

All the calls of the form `bottom_up_delete_completes_preds(Keys,SCCs,AbsInt,ExtCompletes)` do not fail. (`not_fails/1`)

bottom_up_delete_complete/5: PREDICATE

Usage: `bottom_up_delete_complete(SgKey,Id,SCC,AbsInt,ExtCompletes)`

– *The following properties should hold at call time:*

`SgKey` is currently a term which is not a free variable. (`nonvar/1`)

`Id` is currently a term which is not a free variable. (`nonvar/1`)

`SCC` is currently a term which is not a free variable. (`nonvar/1`)

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`ExtCompletes` is a free variable. (`var/1`)

– *The following properties should hold globally:*

All the calls of the form `bottom_up_delete_complete(SgKey,Id,SCC,AbsInt,ExtCompletes)` do not fail. (`not_fails/1`)

external_calls/4: PREDICATE

No further documentation available for this predicate.

84.3 Documentation on imports

This module has the following direct dependencies:

– *Application modules:*

`tarjan`, `domains`, `plai_db`, `transform`, `plai_db_comparator`.

– *System library modules:*

`native_props`, `datafacts_rt`, `program_keys`, `sort`, `aggregates`, `lists`.

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `isomodes`, `nativeprops`, `datafacts`, `ciaopp(plai/notrace)`.

85 Database for incremental analysis

Predicates for mantaining the structures needed for incremental analysis

85.1 Usage and interface

- **Library usage:**
  `:- use_module(ciaopp(plai/incanal/incanal_db)).`
- **Exports:**
  - *Predicates:*
    `init_clkeys/0`, `clean_incremental_db/0`, `change_id_clause/2`, `insert_after_clkey/2`, `save_clause_db/0`, `restore_clause_db/0`, `remove_clauses_pred/2`, `add_all_clauses/1`, `add_new_preds/1`, `get_current_clauses/1`, `get_current_assertions/1`, `add_assertion_source_db/1`, `del_assertion_source_db/1`, `add_changed_registry/4`, `get_changed_registry/4`, `clean_incanal_mod_data/0`, `update_inc_clkey/1`, `all_different_mods/0`, `set_loaded_mods/1`, `loaded_mods/1`, `set_analyzed_mods/1`, `analyzed_mods/1`, `fixpoint_id_/2`, `store_current_fixpoint_id/1`, `restore_fixpoint_id/1`.

85.2 Documentation on exports

init_clkeys/0: PREDICATE

This predicate annotates which is the last clause identifier that was assinged by module program_key. This is needed to give new ids to the clauses that are added to the analysis.

clean_incremental_db/0: PREDICATE

Remove databases for incremental analysis.

change_id_clause/2: PREDICATE

Usage: `change_id_clause(Cl,NCl)`

Changes the Ids through `Cl` so that there is no conflict with other clauses already present in the analysis.

insert_after_clkey/2: PREDICATE

Usage: `insert_after_clkey(Id,Cl)`

- *The following properties should hold at call time:*
  `Id` is an atom. (`atm/1`)

save_clause_db/0: PREDICATE

Stores locally the current source database of ciaopp.

restore_clause_db/0: PREDICATE

Restores from a local copy the source database of ciaopp.

remove_clauses_pred/2: PREDICATE

Usage: `remove_clauses_pred(Pred,Cls)`

Removes from the database all clauses for predicate `Pred` of the form `F/A` and returns them in `Cls`.

add_all_clauses/1: PREDICATE

Usage: `add_all_clauses(Cls)`

Asserts the list of clauses `Cls` to the temporal database.

- *The following properties should hold at call time:*

  `Cls` is a list. (`list/1`)

add_new_preds/1: PREDICATE

Usage: `add_new_preds(Preds)`

This predicates adds predicates which were not defined before.

This predicate is needed for the initialization of the counters for Ids.

- *The following properties should hold at call time:*

  `Preds` is currently a term which is not a free variable. (`nonvar/1`)

get_current_clauses/1: PREDICATE

Usage: `get_current_clauses(Cls)`

Returns all clauses currently present in the source database.

- *The following properties should hold at call time:*

  `Cls` is a free variable. (`var/1`)

- *The following properties should hold upon exit:*

  `Cls` is a list. (`list/1`)

get_current_assertions/1: PREDICATE

Usage: `get_current_assertions(Assrts)`

Returns all assertions currently present in the source database.

- *The following properties should hold at call time:*

  `Assrts` is a free variable. (`var/1`)

- *The following properties should hold upon exit:*

  `Assrts` is a list. (`list/1`)

add_assertion_source_db/1: PREDICATE

No further documentation available for this predicate.

del_assertion_source_db/1: PREDICATE

No further documentation available for this predicate.

add_changed_registry/4: PREDICATE

Usage: `add_changed_registry(SgKey,ImMod,Module,Reg)`

This predicate annotates changes that occurs on the registry of predicate `SgKey` exported in `Module`.

– *The following properties should hold at call time:*

`SgKey` is an atom. (`atm/1`)

`Module` is an atom. (`atm/1`)

get_changed_registry/4: PREDICATE

Usage: `get_changed_registry(Key,CMod,Mod,Reg)`

The data of answer of predicate `Key` exported by module `Mod` has changed to `Reg`.

– *Call and exit should be compatible with:*

`Key` is an atom. (`atm/1`)

`CMod` is an atom. (`atm/1`)

`Mod` is an atom. (`atm/1`)

`Reg` is any term. (`term/1`)

clean_incanal_mod_data/0: PREDICATE

Cleans structures needed for incremental modular analysis.

update_inc_clkey/1: PREDICATE

Usage: `update_inc_clkey(NClKey)`

Updates the value of the last id assigned by the program_keys module.

– *The following properties should hold at call time:*

`NClKey` is an atom. (`atm/1`)

all_different_mods/0: PREDICATE

Flag that determines if the set of modules to be loaded with `incremental_module/2` is disjoint with the set of the previously loaded The predicate is of type *data*.

set_loaded_mods/1: PREDICATE

Usage: `set_loaded_mods(M)`

Sets the context (as a list of loaded modules) of the incremental analysis.

– *The following properties should hold at call time:*

`M` is a list. (`list/1`)

loaded_mods/1: PREDICATE

Usage: `loaded_mods(Ms)`

Returns the list of currently loaded modules.

– *The following properties should hold upon exit:*

`Ms` is a list. (`list/1`)

set_analyzed_mods/1: PREDICATE

Usage: `set_analyzed_mods(M)`

Sets the context (as a list of loaded modules) of the incremental analysis.

– *The following properties should hold at call time:*

`M` is a list. (`list/1`)

analyzed_mods/1: PREDICATE

Usage: `analyzed_mods(Ms)`

Returns the list of currently loaded modules.

– *The following properties should hold upon exit:*

`Ms` is a list. (`list/1`)

fixpoint_id_/2: PREDICATE

No further documentation available for this predicate. The predicate is of type *data*.

store_current_fixpoint_id/1: PREDICATE

No further documentation available for this predicate.

restore_fixpoint_id/1: PREDICATE

No further documentation available for this predicate.

85.3 Documentation on imports

This module has the following direct dependencies:

– *Application modules:*

`domains`, `fixpo_ops`, `preprocess_flags`.

– *System library modules:*

`datafacts_rt`, `aggregates`, `lists`, `hiordlib`, `pathnames`, `p_unit_db`, `program_keys`.

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `isomodes`, `datafacts`.

86 Persistent database for incremental analysis

This module handles the maintenance of the persistent database needed for resuming a stopped incremental analysis.

86.1 Usage and interface

- **Library usage:**
  `:- use_module(ciaopp(plai/incanal/incanal_persistent_db)).`
- **Exports:**
  - *Predicates:*
    `set_loaded_module/1`, `reset_persistent_db/0`, `load_persistent_if_needed/2`, `top_level_of_files/2`, `has_dump/2`, `set_inc_persistent/1`, `save_persistent_analysis/0`, `clean_persistent_analysis/0`.
  - *Regular Types:*
    `inc_persistent_status/1`.

86.2 Documentation on exports

set_loaded_module/1: PREDICATE

No further documentation available for this predicate.

reset_persistent_db/0: PREDICATE

Removes previous persistent data of an incremental analysis.

load_persistent_if_needed/2: PREDICATE

Usage: `load_persistent_if_needed(Top,Fs)`

Restores the persistent analysis of tiles in list `Fs` if it existed and the flag `inc_persistent` is on.

- *The following properties should hold at call time:*
  `Top` is an atom. (`atm/1`)
  `Fs` is a list. (`list/1`)

top_level_of_files/2: PREDICATE

No further documentation available for this predicate.

has_dump/2: PREDICATE

No further documentation available for this predicate.

set_inc_persistent/1: PREDICATE

Usage: `set_inc_persistent(St)`

This flags controls the storage of persistent information after the analysis.

– *The following properties should hold at call time:*

`St` Defines whether the analysis should be stored persistently. (`inc_persistent_status/1`)

inc_persistent_status/1: REGTYPE

`inc_persistent_status(X)`

`X` can be:

- `on`: Analysis information will be stored in the same location as the analyzed code (as dump files). This is usefull when analysis scheduling involves loading and unloading modules. To perform an analysis from scratch, these files have to be manually removed.
- `off`: No information is stored.

Usage: `inc_persistent_status(St)`

`St` Defines whether the analysis should be stored persistently.

save_persistent_analysis/0: PREDICATE

Usage:

Makes incremental analysis persistent by saving it to disk.

clean_persistent_analysis/0: PREDICATE

Usage:

Removes the persistent incremental analysis from disk.

86.3 Documentation on imports

This module has the following direct dependencies:

– *Application modules:*

`p_dump`, `analysis_stats`, `preprocess_flags`, `ciaopp_log`.

– *System library modules:*

`datafacts_rt`, `system`, `system_extra`, `pathnames`.

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `regtypes`, `datafacts`.

87 Incremental computation of tarjan algorithm

Author(s): Isabel Garcia-Contreras (ported from ciaopp-0.8).

This module contains predicates for computing incrementally the strongly connected components of programs using the tarjan algorithm.

87.1 Usage and interface

- **Library usage:**
  `:- use_module(ciaopp(plai/incanal/tarjan_inc)).`
- **Exports:**
  - *Predicates:*
    `inc_add_source_clauses/3`, `rearrange_tarjan_after_deletion/1`, `tarjan_data/1`, `predicates/1`, `rec/1`, `vertexes/1`, `rec_preds/1`.

87.2 Documentation on exports

inc_add_source_clauses/3: PREDICATE

Usage: `inc_add_source_clauses(Cls,Ds,AbsInt)`

Adds incrementally clauses of list `Cls` with their respective dictionaries in `Ds` for abstract domain `AbsInt` to the source code database, and updates the recursivity of the clauses that may have changed .

- *The following properties should hold at call time:*

  `Cls` is a list. (`list/1`)

  `Ds` is a list. (`list/1`)

  `AbsInt` is an atom. (`atm/1`)

rearrange_tarjan_after_deletion/1: PREDICATE

Usage: `rearrange_tarjan_after_deletion(Preds)`

`Preds` is the list of predicates for which clauses have been deleted. This predicate updates the SCCs after deleting a set of clauses.

- *The following properties should hold at call time:*

  `Preds` is currently a term which is not a free variable. (`nonvar/1`)

tarjan_data/1: PREDICATE

Computed recursive classes of the tarjan algorithm. The predicate is of type *data*.

predicates/1: PREDICATE

`predicates(Ps)`

`Ps` is a list of the predicates of the program. The predicate is of type *data*.

rec/1: PREDICATE

`rec(P/A)`

Succeeds if `P/A` is a recursive predicate of the program. The predicate is of type *data*.

vertexes/1: PREDICATE

The vertexes of the graph for performing the tarjan algorithm. The predicate is of type *data*.

rec_preds/1: PREDICATE

Usage: `rec_preds(Ps)`

`Ps` is the list of recursive predicates of the loaded program.

– *The following properties should hold upon exit:*

`Ps` is a list. (`list/1`)

87.3 Documentation on imports

This module has the following direct dependencies:

– *Application modules:*

`tarjan`, `transform`, `plai_db`, `plai`, `analysis_stats`.

– *System library modules:*

`datafacts_rt`, `lists`, `sets`, `aggregates`, `sort`, `idlists`, `program_keys`, `p_unit_db`.

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `isomodes`, `datafacts`.

88 Diff algorithm

Author(s): Isabel Garcia-Contreras, Jose F. Morales.

This module implements Eugene Myers' Greedy Difference Algorithm described in 'An O(ND) Difference Algorithm and Its Variations' [Mye86].

The implementation is parametric in the comparison predicate. This predicate has to succeed if two elements are considered equal.

88.1 Complexity

This 'greedy' algorithm that computes the number differences has complexity O((N+M)D) in both time and space. With M and N the lenghts of the input lists and D the number of changes.

88.2 Pseudocode

This pseudocode is copied from the original article, where:

- `a` and `b` are the input lists of lengths `N` and `M`,
- `k = x - y` and is used to label diagonals,
- `V[k]` contains the row index of the endpoint of a furthest reaching path in diagonal k.

```
Constant MAX [0,M+N]

Var V: Array [-MAX.. MAX] of Integer

V[1] = 0

For D = 0 to MAX Do
   For k = -D to D in steps of 2 Do
      If k = -D or (k = D and V[k-1] < V[k+1] Then
    x = V[k+1]
      Else
    x = V[k-1] + 1
    y = x - k
      While (x < N, y < M and a(x+1) = b(y+1) Do
    (x,y) = (x+1,y+1)
      V[k] = x
      If (x >= N and y >= M) Then
        Length of an SES is D
        Stop

Length of an SES is greater than MAX
```

88.3 Example

```
?- diff([a,a,b,c], [b,c,d], '=', Diff).

Diff = [del(0,a),del(0,a),ins(2,d)] ?

yes
?-
```

88.4 Patch

The patch operation applies a list of changes expressed as `diff_item/1` to obtain a new list. Note that given two lists L1, L2, if their Diff is applied to L1, it will be obtained L2:

```
?- L1 = [a,a,b,c], L2 = [b,c,d],
   diff(L1, L2, '=', Diff),
   patch(L1, Diff, L2).


Diff = [del(0,a),del(0,a),ins(2,d)],
L1 = [a,a,b,c],
L2 = [b,c,d] ?
yes
?-
```

88.5 Usage and interface

- **Library usage:**
  `:- use_module(library(diff)).`
- **Exports:**
  - *Predicates:*
    `diff/4`, `patch/3`.
  - *Regular Types:*
    `diff_item/1`.

88.6 Documentation on exports

diff/4: PREDICATE

Usage: `diff(Ls1,Ls2,Compare,Diff)`

`Diff` are the changes needed to transform `Ls1` into `Ls2`.

- *The following properties should hold at call time:*
  `Ls1` is a list. (`list/1`)
  `Ls2` is a list. (`list/1`)
- *The following properties should hold upon exit:*
  `Diff` is a list of `diff_items`. (`list/2`)

Meta-predicate with arguments: `diff(?,?,pred(2),?)`.

patch/3: PREDICATE

Usage: `patch(Ls,Diff,LNew)`

Apply a list of changes (`Diff`) onto a `Ls`.

- *The following properties should hold at call time:*
  `Ls` is a list. (`list/1`)
  `diff_item` is a list of `Diffs`. (`list/2`)

– *The following properties should hold upon exit:*
`LNew` is a list. (`list/1`)

diff_item/1: REGTYPE

`diff_item(X)`

`X` is an insertion denoted with `ins(Pos, Elem)` meaning that `Elem` has to be inserted in position `Pos`, or `del(Pos, Elem)` meaning that `Elem` has to be removed from position `Pos`. It is defined as:

```
diff_item(ins(P,_1)) :-
    nnegint(P).
diff_item(del(P,_1)) :-
    nnegint(P).
```

Usage: `diff_item(X)`

`X` is a single edition in a sequence (insertion or deletion)

88.7 Documentation on imports

This module has the following direct dependencies:

– *System library modules:*
`lists`.

– *Internal (engine) modules:*
`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`.

– *Packages:*
`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `hiord`, `regtypes`.

89 fixpo_dd (library)

Stability: [**devel**] Currently the subject of active development and/or research. Functionality may be limited and API and/or functionality may change without warning or deprecation period. Not recommended yet for use in production.

89.1 Usage and interface

- **Library usage:**
  `:- use_module(ciaopp(plai/fixpo_dd)).`
- **Exports:**
  - *Predicates:*
    `query/8`, `init_fixpoint/0`, `cleanup_fixpoint/1`, `entry_to_exit/7`, `$change_list/3`, `proj_to_prime_nr/9`, `proj_to_prime_r/8`, `proj_to_prime/9`, `compute/9`, `td_mark_parents_change_list/2`, `add_change/5`, `mark_parents_change_list_scc/3`, `add_change_scc/6`, `fixpoint_compute_change/9`.

89.2 Documentation on exports

query/8: PREDICATE

Usage: `query(AbsInt,QKey,Query,Qv,RFlag,N,Call,Succ)`

The success pattern of `Query` with `Call` is `Succ` in the analysis domain `AbsInt`. The predicate called is identified by `QKey`, and `RFlag` says if it is recursive or not. The goal `Query` has variables `Qv`, and the call pattern is uniquely identified by `N`.

- *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable.	(`nonvar/1`)
`QKey` is currently a term which is not a free variable.	(`nonvar/1`)
`Query` is currently a term which is not a free variable.	(`nonvar/1`)
`Qv` is currently a term which is not a free variable.	(`nonvar/1`)
`RFlag` is currently a term which is not a free variable.	(`nonvar/1`)
`Call` is currently a term which is not a free variable.	(`nonvar/1`)
`Succ` is a free variable.	(`var/1`)
`AbsInt` is an atom.	(`atm/1`)
`QKey` is an atom.	(`atm/1`)
`Query` is any term.	(`term/1`)
`Qv` is a list.	(`list/1`)
`RFlag` is an atom.	(`atm/1`)
`N` is any term.	(`term/1`)
`Call` is any term.	(`term/1`)
`Succ` is any term.	(`term/1`)

- *The following properties should hold globally:*
  All the calls of the form `query(AbsInt,QKey,Query,Qv,RFlag,N,Call,Succ)` do not fail. (`not_fails/1`)

init_fixpoint/0: PREDICATE

Usage:

Cleans up the database of analysis of temporary information.

cleanup_fixpoint/1: PREDICATE

Usage: `cleanup_fixpoint(AbsInt)`

Cleanups the database of analysis, of both temporary as well as permanent information regarding abstract domain `AbsInt`.

- *The following properties should hold globally:*

  All the calls of the form `cleanup_fixpoint(AbsInt)` do not fail. (`not_fails/1`)

entry_to_exit/7: PREDICATE

Usage: `entry_to_exit(Body,Key,Call,Exit,Vars_u,AbsInt,NewN)`

Traverses the body of a clause (first argument) obtaining the Exit for a given Entry (represented by Call, since it is both the Entry of the clause and the Call for the first subgoal).

- *The following properties should hold at call time:*

  `Body` is currently a term which is not a free variable. (`nonvar/1`)

  `Key` is currently a term which is not a free variable. (`nonvar/1`)

  `Call` is currently a term which is not a free variable. (`nonvar/1`)

  `Exit` is a free variable. (`var/1`)

  `Vars_u` is currently a term which is not a free variable. (`nonvar/1`)

  `AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

  `NewN` is currently a term which is not a free variable. (`nonvar/1`)

  `Key` is an atom. (`atm/1`)

  `Vars_u` is a list. (`list/1`)

  `AbsInt` is an atom. (`atm/1`)

- *The following properties should hold globally:*

  All the calls of the form `entry_to_exit(Body,Key,Call,Exit,Vars_u,AbsInt,NewN)` do not fail. (`not_fails/1`)

$change_list/3: PREDICATE

No further documentation available for this predicate. The predicate is of type *data*.

proj_to_prime_nr/9: PREDICATE

Usage: `proj_to_prime_nr(SgKey,Sg,Sv,Call,Proj,AbsInt,Clid,ListPrime,Id)`

This predicate obtains the list of Prime corresponding to each non recursive clause of Sg for a given Call. It first reads those non recursive clauses by means of a bagof and then proccess each one with a loop. If there is no non recursive clause, the answer will be `['$bottom']`.

> `Clid` may be 0 also (see `fixpo_ops:inexistent/1`.

– *The following properties should hold at call time:*

`SgKey` is currently a term which is not a free variable. (`nonvar/1`)

`Sg` is currently a term which is not a free variable. (`nonvar/1`)

`Sv` is currently a term which is not a free variable. (`nonvar/1`)

`Call` is currently a term which is not a free variable. (`nonvar/1`)

`Proj` is currently a term which is not a free variable. (`nonvar/1`)

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`Clid` is currently a term which is not a free variable. (`nonvar/1`)

`ListPrime` is a free variable. (`var/1`)

`Id` is currently a term which is not a free variable. (`nonvar/1`)

`SgKey` is an atom. (`atm/1`)

`Sv` is a list of `var`s. (`list/2`)

`AbsInt` is an atom. (`atm/1`)

`plai_db_id(Id)` (`plai_db_id/1`)

– *The following properties should hold upon exit:*

`ListPrime` is a list. (`list/1`)

– *The following properties should hold globally:*

All the calls of the form `proj_to_prime_nr(SgKey,Sg,Sv,Call,Proj,AbsInt,Clid,ListPrime,Id)` do not fail. (`not_fails/1`)

All calls of the form `proj_to_prime_nr(SgKey,Sg,Sv,Call,Proj,AbsInt,Clid,ListPrime,Id)` are deterministic. (`is_det/1`)

proj_to_prime_r/8: PREDICATE

Usage:

– *The following properties should hold globally:*

All the calls of the form `proj_to_prime_r(Arg1,Arg2,Arg3,Arg4,Arg5,Arg6,Arg7,Arg8)` do not fail. (`not_fails/1`)

proj_to_prime/9: PREDICATE

Usage: `proj_to_prime(Clauses,SgKey,Sg,Sv,Call,Proj,AbsInt,Prime,Id)`

– *The following properties should hold at call time:*

`Clauses` is currently a term which is not a free variable. (`nonvar/1`)

`SgKey` is currently a term which is not a free variable. (`nonvar/1`)

`Sg` is currently a term which is not a free variable. (`nonvar/1`)

`Sv` is currently a term which is not a free variable. (`nonvar/1`)

`Call` is currently a term which is not a free variable. (`nonvar/1`)

`Proj` is currently a term which is not a free variable. (`nonvar/1`)

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`Id` is currently a term which is not a free variable. (`nonvar/1`)

`Clauses` is a list. (`list/1`)

`SgKey` is an atom. (`atm/1`)

`Sv` is a list of `var`s. (`list/2`)

`AbsInt` is an atom. (`atm/1`)

– *The following properties should hold globally:*

All the calls of the form `proj_to_prime(Clauses,SgKey,Sg,Sv,Call,Proj,AbsInt,Prime,Id)` do not fail. (`not_fails/1`)

All calls of the form `proj_to_prime(Clauses,SgKey,Sg,Sv,Call,Proj,AbsInt,Prime,Id)` are deterministic. (`is_det/1`)

compute/9: PREDICATE

Usage: `compute(Clauses,SgKey,Sg,Sv,Proj,AbsInt,TempPrime,Prime,Id)`

It analyzes each recursive clause clause.

– *The following properties should hold at call time:*

`Clauses` is currently a term which is not a free variable. (`nonvar/1`)

`SgKey` is currently a term which is not a free variable. (`nonvar/1`)

`Sg` is currently a term which is not a free variable. (`nonvar/1`)

`Sv` is currently a term which is not a free variable. (`nonvar/1`)

`Proj` is currently a term which is not a free variable. (`nonvar/1`)

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`TempPrime` is currently a term which is not a free variable. (`nonvar/1`)

`Prime` is a free variable. (`var/1`)

`Id` is currently a term which is not a free variable. (`nonvar/1`)

`SgKey` is an atom. (`atm/1`)

`Sv` is a list of `var`s. (`list/2`)

`AbsInt` is an atom. (`atm/1`)

`plai_db_id(Id)` (`plai_db_id/1`)

– *The following properties should hold upon exit:*

`Prime` is currently a term which is not a free variable. (`nonvar/1`)

– *The following properties should hold globally:*

All the calls of the form `compute(Clauses,SgKey,Sg,Sv,Proj,AbsInt,TempPrime,Prime,Id)` do not fail. (`not_fails/1`)

All calls of the form `compute(Clauses,SgKey,Sg,Sv,Proj,AbsInt,TempPrime,Prime,Id)` are deterministic. (`is_det/1`)

td_mark_parents_change_list/2: PREDICATE

Usage: `td_mark_parents_change_list(Parents,AbsInt)`

This complete has changed. So we add the change in the $change_list of all parents.

– *The following properties should hold at call time:*

`Parents` is currently a term which is not a free variable. (`nonvar/1`)

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`Parents` is a list. (`list/1`)

`AbsInt` is an atom. (`atm/1`)

– *The following properties should hold globally:*

All the calls of the form `td_mark_parents_change_list(Parents,AbsInt)` do not fail. (`not_fails/1`)

All calls of the form `td_mark_parents_change_list(Parents,AbsInt)` are deterministic. (`is_det/1`)

add_change/5: PREDICATE

Usage: `add_change(Id,Lit_Key,Literal,Parents,AbsInt)`

`Id`: Id of the complete of the predicate that changed `Lit_Key`: Key of the `Literal` of the complete that needs recomputing. `Literal`: `Literal` with the term `F/A/C/L`. `Parents`: Program points in which the literal is called (0 means an entry) `AbsInt`: Abstract Domain.

– *The following properties should hold at call time:*

`Id` is currently a term which is not a free variable. (`nonvar/1`)

`Literal` is currently a term which is not a free variable. (`nonvar/1`)

`Parents` is currently a term which is not a free variable. (`nonvar/1`)

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`plai_db_id(Id)` (`plai_db_id/1`)

`Lit_Key` is an atom. (`atm/1`)

– *The following properties should hold globally:*

All the calls of the form `add_change(Id,Lit_Key,Literal,Parents,AbsInt)` do not fail. (`not_fails/1`)

mark_parents_change_list_scc/3: PREDICATE

Usage: `mark_parents_change_list_scc(Parents,SCC,AbsInt)`

This complete has changed. So we add the change in the $change_list of all parents. If the parent is in the same SCC then we recursively mark its parents as well.

– *The following properties should hold at call time:*

`Parents` is currently a term which is not a free variable. (`nonvar/1`)

`SCC` is currently a term which is not a free variable. (`nonvar/1`)

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`Parents` is a list. (`list/1`)

`SCC` is a list. (`list/1`)

`AbsInt` is an atom. (`atm/1`)

– *The following properties should hold globally:*

All the calls of the form `mark_parents_change_list_scc(Parents,SCC,AbsInt)` do not fail. (`not_fails/1`)

All calls of the form `mark_parents_change_list_scc(Parents,SCC,AbsInt)` are deterministic. (`is_det/1`)

add_change_scc/6: PREDICATE

Usage: `add_change_scc(Id,Lit_Key,Literal,Parents,SCC,AbsInt)`

`Lit_Key` may be free when a clause is marked to analyze from the begining (see second clause of `compute_change`).

– *The following properties should hold at call time:*

`Id` is currently a term which is not a free variable. (`nonvar/1`)

`Literal` is currently a term which is not a free variable. (`nonvar/1`)

`Parents` is currently a term which is not a free variable. (`nonvar/1`)

`SCC` is currently a term which is not a free variable. (`nonvar/1`)

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`Id` is an integer. (`int/1`)

`Lit_Key` is an atom. (`atm/1`)

`Literal` is any term. (`term/1`)

`Parents` is a list. (`list/1`)

`SCC` is a list. (`list/1`)

`AbsInt` is an atom. (`atm/1`)

– *The following properties should hold globally:*

All the calls of the form `add_change_scc(Id,Lit_Key,Literal,Parents,SCC,AbsInt)` do not fail. (`not_fails/1`)

All calls of the form `add_change_scc(Id,Lit_Key,Literal,Parents,SCC,AbsInt)` are deterministic. (`is_det/1`)

fixpoint_compute_change/9: PREDICATE

Usage: `fixpoint_compute_change(Changes,SgKey,Sg,Sv,Proj,AbsInt,TempPrime,Prime,Id)`

It obtains the Prime for the recursive predicate Sg with Call (which has been assigned to node Id), and the list of nodes it depends on In doing this it performs an iteration over the recursive clauses of Sg by calling to compute_change/13 and then checks if the fixpoint has been reached by calling to fixpoint/13. Fixpoint is reached if either NewList is empty (it means that Id does not depend on any node) or if Flag is a variable (it means that the information has not been modified within the iteration) LEntryInf is the list of (Entry,ExtraInfo) couples for each Clause. It will be computed in the first iteration and used in subsequent ones

– *The following properties should hold at call time:*

`Changes` is currently a term which is not a free variable. (`nonvar/1`)

`SgKey` is currently a term which is not a free variable. (`nonvar/1`)

`Sg` is currently a term which is not a free variable. (`nonvar/1`)

`Sv` is currently a term which is not a free variable. (`nonvar/1`)

`Proj` is currently a term which is not a free variable. (`nonvar/1`)

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`TempPrime` is currently a term which is not a free variable. (`nonvar/1`)

`Prime` is a free variable. (`var/1`)

`Id` is currently a term which is not a free variable. (`nonvar/1`)

`SgKey` is an atom. (`atm/1`)

`Sv` is a list of `var`s. (`list/2`)

`AbsInt` is an atom. (`atm/1`)

`plai_db_id(Id)` (`plai_db_id/1`)

– *The following properties should hold upon exit:*

`Prime` is currently a term which is not a free variable. (`nonvar/1`)

– *The following properties should hold globally:*

All the calls of the form `fixpoint_compute_change(Changes,SgKey,Sg,Sv,Proj,AbsInt,TempPrime,Prime,Id)` do not fail. (`not_fails/1`)

All calls of the form `fixpoint_compute_change(Changes,SgKey,Sg,Sv,Proj,AbsInt,TempPrime,Prime,Id)` are deterministic. (`is_det/1`)

89.3 Documentation on imports

This module has the following direct dependencies:

– *Application modules:*

`preprocess_flags`, `fixpo_ops`, `domains`, `plai_db`, `transform`, `apply_assertions_old`, `apply_assertions`, `global_control`, `tarjan`, `plai_db_comparator`.

– *System library modules:*

`native_props`, `datafacts_rt`, `write`, `lists`, `aggregates`, `terms_vars`, `sort`, `sets`, `program_keys`, `messages`.

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`, `messages_basic`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `nativeprops`, `datafacts`, `isomodes`, `regtypes`, `ciaopp(ciaopp_options)`, `.(notrace)`, `spec(no_debug)`.

90 The Preprocessing Unit Component

This component is in charge of processing the .asr files, gathering together the code for the preprocessing unit of the current module. The preprocessing unit is the code of the current module together with the set of assertions/properties which allows a precise interpretation of the assertions present for the current module. It serves the rest of the precompiler current module clauses, assertions, (definitions of) properties related, and characteristics of the current module predicates (e.g.: initialization directives, whether a predicate is a meta-predicate, whether it is a "builtin", etc.).

91 The Preprocessing Unit

This component handles data structures for the code of the current module and for all information about it that may be necessary to precompile that module. Since CiaoPP works in a per-module fashion, when preprocessing one module the modules imported by it may not be accessible. However, information on imported predicates may be essential for some manipulations of the current module: e.g., for analyzing it with greater precision. For this reason, information about exported predicates of a module is stored in separate cache files. The cache files of modules imported by the current module are then loaded together with the file of the current module. All the information stored together with the current module is called the preprocessing unit of the current module.

Cache files are used to save assertions that refer to exported predicates, properties exported or properties that are used in assertions for exported predicates, and properties used in the definiton of other relevant properties. (The exact definition of what is cached and how the preprocessing unit is obtained from this caches is given in the chapter for `p_asr`). This facilitates the use within CiaoPP of all information that may be relevant about exported predicates that may be imported into other modules. This information from (user) assertions is extracted from the module code.

Other information that may be relevant is that inferred by CiaoPP on its own. The information from analysis that refers to exported predicates of a module is also cached in separate files, so that the preprocessing of other modules that import such predicates can use the information. Currently, separate files are used for user supplied assertions (the so called .asr file) and for information from analysis (the so called .abs file). Module `p_asr` is in charge of the .asr file and module `p_abs` is in charge of the .abs files.

More information concerning the current module that this component serves includes: initialization directives, entry assertions that may need analysis, whether a predicate is a meta-predicate or a dynamic predicate, whether it is a `"builtin"`, a property, or a native property, etc. In the sections below we explain what is understood by builtin predicate and native property. The complete functionality offered by this component is explained in the following chapters.

91.1 The preprocessing unit

In the following, related files refer to files defining modules from which the current module imports a predicate, whether via direct importation or via re-exportation by an imported module. The *preprocessing unit* consists of:

1. the code (and directives) of the current module,
2. the assertions of the current module,
3. the (imported) properties of related files which are used in the previous assertions,
4. the assertions of related files for predicates imported by the current module,
5. the properties of related files (or imported by them) which are used in the previous assertions,
6. the properties transitively used in the definitions of all the previous properties, whichever file they are defined.

Note that once the preprocessing unit of the current module is loaded, every assertion for a predicate of the current module or imported into the current module can be correctly and completely interpreted, since all the properties that may appear in such assertions (or transitively used in the definitions of such properties) are available. This is the main reason for including the preprocessing unit of the current module instead of simply loading the current module itself alone (and some assertions for imported predicates, probably).

91.2 Builtin predicates

A predicate is builtin if there is information about it built into one of the components of CiaoPP. This is the case, for example, for analyzers. Usually, these predicates are ISO predicates, whose semantics conform with the standard, and thererefore, can be implemented into CiaoPP once and for all. The names used to refer to these predicates are thus usually also the ISO names.

However, in a modular system like Ciao, such builtin predicates may be defined in a module, and can be used (imported) or not by the current module. Whether the predicate is visible or not to the current module is solved by looking at the module interface of the current module. The exact name of the predicate (at the source language level) can be known; for example, ISO `var/1` in CiaoPP is `term_typing:var/1`. This name could also be built into CiaoPP, but this would tight CiaoPP to the particular module structure of the library of a system (Ciao, in this case). Instead, there is a dynamic scheme that makes CiaoPP more flexible: To indicate that a given predicate in a given module corresponds to a builtin predicate, the following kind of assertions are used:

```
:- pred var(X) + native(var(X)).
```

This assertion in module `term_typing` tells CiaoPP that predicate `term_typing:var(X)` corresponds to the predicate builtin into CiaoPP as `var(X)`. Note that the name `var/1` should be used all throughtout CiaoPP to identify that very same predicate (the one in ISO by that name, in this case). This is mandatory.

Note also that with the above scheme, the only real predicate name that is built into CiaoPP is that for the property `native(Pred,Name)`, which currently is precisely `native(Pred,Name)` (which is currently defined in library module `engine(basic_props)`).

91.3 Native properties

A property in Ciao is a predicate. Certain properties are used within CiaoPP in a native way, which means that some component understands the property natively (for example, an analysis for groundness understands the property of being ground). These properties are called *native properties* .

The same problem above for builtin predicates occurs also for native properties, and the same solution has been given to the problem also in this case. To indicate that a given predicate corresponds to a property understood natively by CiaoPP the following kind of assertions are used:

```
:- prop var(X) + native(free(X)).
```

This is interpreted by CiaoPP so that predicate `term_typing:var(X)` corresponds to the native property identified in CiaoPP as `free(X)`. Note that the name `free/1` should be used all throughtout CiaoPP to identify that property. The names of native properties are defined in `native:native/1`.

The (default) predicates that are used as source language level counterparts of the native property names are gathered together in a Ciao library module that currently is `library(assertions/native_props)`.

There is an scheme for translating predicate property names to native property names upon input of the current module, and native property names back to predicate property names upon output that is described in the chapter about module `domains`.

91.4 Organization of the code

The organization of the code of this component is as follows:

Module `p_unit` is in charge of supporting all other CiaoPP components when they require information about the program. Module `p_asr` is in charge of processing the .asr files and gathering together the preprocessing unit for the current module. Module `assrt_norm` is used to normalize assertions. Module `p_abs` is in charge of reading .abs files and writing them. Module `assrt_db` maintains the database of assertions, module `clause_db` the database of clauses, and module `itf_db` the database of information related to the module interface of the current module.

Each of the modules is documented in the following chapters.

92 Preprocessing Unit Information Server

Author(s): The Ciao Development Team.

This module loads the preprocessing unit of a file to be preprocessed and serves all the information related to it to the rest of CiaoPP, including (but not limited to) the source code.

92.1 Usage and interface

- **Library usage:**
  `:- use_module(library(compiler/p_unit)).`
- **Exports:**
  - *Predicates:*
    `preprocessing_unit/3`, `program/2`, `filtered_program_clauses/3`, `replace_program/2`, `native_to_prop/2`, `prop_to_native/2`, `native_to_props_visible/2`, `dynamic_or_unknown_predicate/1`, `get_assertion/2`, `add_assertions/1`, `add_assertion/1`, `add_directive/1`, `erase_directive/1`, `type_of_directive/2`, `pr_key_clean/0`, `pr_key_add/1`, `pr_key_get/1`, `add_defined_pred/2`, `new_predicate/3`, `predicate_names/1`, `multifile_predicate_names/1`, `inject_output_package/1`, `add_output_package/1`, `get_output_package/1`, `add_output_operator/3`, `get_output_operator/3`, `add_comment/1`, `get_comment/1`, `cleanup_comment_db/0`, `cleanup_commented_assrt/0`, `get_commented_assertion/2`, `add_commented_assertions/1`, `add_commented_assertion/1`, `cleanup_punit/0`, `get_call_from_call_assrt/7`, `get_pred_mod_defined/2`, `assertion_set_status/3`, `assertion_set_head/3`, `assertion_set_calls/3`, `assertion_set_success/3`, `assertion_set_comp/3`, `cleanup_libcache/0`, `loaded_libcache/0`, `load_libcache/1`, `gen_libcache/1`.
  - *Multifiles:*
    `define_flag/3`, `hook_compact_global_prop/2`, `hook_compact_calls_prop/2`, `hook_native_prop/2`, `hook_pp_info_clause/3`, `hook_pp_info_lit/4`, `hook_legal_regtype/1`, `hook_insert_regtype/2`, `hook_post_init_regtypes/0`, `hook_cleanup_lib_regtypes/0`, `hook_restore_lib_regtypes/1`, `hook_save_lib_regtypes/1`.

92.2 Documentation on exports

preprocessing_unit/3: PREDICATE

Usage 1: `preprocessing_unit(Fs,Ms,E)`

Loads the preprocessing unit of `Fs` defining `Ms`.

- *The following properties should hold at call time:*
  `Fs` is a list of `filenames`. (`list/2`)
- *The following properties should hold upon exit:*
  `Ms` is a list of `moddescs`. (`list/2`)
  `E` is an atom indicating yes/no. (`switch/1`)

Usage 2: `preprocessing_unit(F,M,E)`

Loads the preprocessing unit of `F` defining `M`.

- *The following properties should hold at call time:*
  `F` is an atom describing the name of a file. (`filename/1`)

– *The following properties should hold upon exit:*
`M` is a module descriptor. (`moddesc/1`)
`E` is an atom indicating yes/no. (`switch/1`)

program/2: PREDICATE

Usage: `program(P,D)`

`P` are the clauses (no directives) of the current module and `D` their dictionaries.

– *The following properties should hold at call time:*
`P` is a free variable. (`var/1`)
`D` is a free variable. (`var/1`)
– *The following properties should hold upon exit:*
`P` is a list of `clause`s. (`list/2`)
`D` is a list of `varnamedict`s. (`list/2`)

filtered_program_clauses/3: PREDICATE

Usage: `filtered_program_clauses(Mods,P,D)`

`P` are the clauses of module `Mod` and `D` their dictionaries.

– *The following properties should hold at call time:*
`Mods` is currently a term which is not a free variable. (`nonvar/1`)
`P` is a free variable. (`var/1`)
`D` is a free variable. (`var/1`)
`Mods` is a list. (`list/1`)
– *The following properties should hold upon exit:*
`Mods` is a list. (`list/1`)
`P` is a list of `clause`s. (`list/2`)
`D` is a list of `varnamedict`s. (`list/2`)

replace_program/2: PREDICATE

Usage: `replace_program(P,D)`

The database holding the program is updated by first deleting its contents and then adding the clauses in `P` and dictionaries in `D`.

– *The following properties should hold at call time:*
`P` is a list of `clause`s. (`list/2`)
`D` is a dictionary of variable names. (`varnamedict/1`)

native_to_prop/2: PREDICATE

Usage: `native_to_prop(NProp,Prop)`

Obtain the user predicate (lit) `Prop` that corresponds to the native property (lit) `NProp`.

– *The following properties should hold at call time:*
`NProp` is currently a term which is not a free variable. (`nonvar/1`)
`Prop` is a free variable. (`var/1`)

prop_to_native/2: PREDICATE

Usage: `prop_to_native(Prop,NProp)`

Obtain the native property (lit) `NProp` that corresponds to the (lit) `Prop` user predicate.

– *The following properties should hold at call time:*

`Prop` is currently a term which is not a free variable. (`nonvar/1`)

`NProp` is a free variable. (`var/1`)

native_to_props_visible/2: PREDICATE

Usage: `native_to_props_visible(Props,Goals)`

Maps native `Props` into their corresponding `Goals` visible in the current module.

– *The following properties should hold upon exit:*

`Props` is a list of `cgoals`. (`list/2`)

`Goals` is a list of `cgoals`. (`list/2`)

dynamic_or_unknown_predicate/1: PREDICATE

Usage: `dynamic_or_unknown_predicate(Goal)`

`Goal` is an atom for a predicate such that all its clauses might not be available or may change in the program unit.

get_assertion/2: PREDICATE

No further documentation available for this predicate.

add_assertions/1: PREDICATE

Usage: `add_assertions(AssrtList)`

Add assertions list `AssrtList` to internal DB.

– *The following properties should hold at call time:*

`AssrtList` is a list. (`list/1`)

add_assertion/1: PREDICATE

Usage: `add_assertion(Assrt)`

Add assertion `Assrt` to internal DB.

add_directive/1: PREDICATE

Usage: `add_directive(C)`

The directive `C` is added to the program data base. This directive will be considered as read from the program, i.e., analizers, transformations and output will use/show it.

– *The following properties should hold at call time:*

`C` is any term. (`term/1`)

erase_directive/1: PREDICATE

Usage: `erase_directive(D)`

Erase directive `D` (previously added with `add_directive/1`

– *The following properties should hold at call time:*

`D` is any term. (`term/1`)

type_of_directive/2: PREDICATE

Usage: `type_of_directive(Type,Body)`

There is a directive of the form `:- Type Body` (of arity one).

pr_key_clean/0: PREDICATE

Usage:

Removes all information about predicate order.

– *The following properties should hold globally:*

Calls of the form `pr_key_clean` are deterministic. (`det/1`)

pr_key_add/1: PREDICATE

Usage: `pr_key_add(K)`

Add a predicate key (once)

– *The following properties should hold upon exit:*

`K` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)

– *The following properties should hold globally:*

Calls of the form `pr_key_add(K)` are deterministic. (`det/1`)

pr_key_get/1: PREDICATE

Usage: `pr_key_get(K)`

Current predicate keys

– *The following properties should hold upon exit:*

`K` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)

– *The following properties should hold globally:*

Calls of the form `pr_key_get(K)` are multi-deterministic. (`multi/1`)

add_defined_pred/2: PREDICATE

Usage: `add_defined_pred(ClKey,M)`

Add the necessary data in itf_db (and `pr_key/1`) to define the predicate `ClKey` in the module `M`.

– *The following properties should hold at call time:*

`ClKey` is any term. (`term/1`)

`M` is an atom. (`atm/1`)

– *The following properties should hold globally:*

Calls of the form `add_defined_pred(ClKey,M)` are deterministic. (`det/1`)

new_predicate/3: PREDICATE

Usage: `new_predicate(F,A,NewF)`

Checks wether there is a predicate `F/A` in the program and returns `NewF` so that there is no predicate `NewF/A` in the program.

– *The following properties should hold at call time:*

`F` is currently a term which is not a free variable. (`nonvar/1`)

`A` is currently a term which is not a free variable. (`nonvar/1`)

`NewF` is a free variable. (`var/1`)

– *The following properties should hold globally:*

Calls of the form `new_predicate(F,A,NewF)` are deterministic. (`det/1`)

predicate_names/1: PREDICATE

Usage:

Returns the specs of predicates defined in the current punit.

– *Call and exit should be compatible with:*

`Arg1` is a list. (`list/1`)

– *The following properties should hold at call time:*

`Arg1` is a free variable. (`var/1`)

multifile_predicate_names/1: PREDICATE

Usage:

Returns the specs of predicates defined in the current punit.

– *Call and exit should be compatible with:*

`Arg1` is a list. (`list/1`)

– *The following properties should hold at call time:*

`Arg1` is a free variable. (`var/1`)

inject_output_package/1: PREDICATE

Usage: `inject_output_package(A)`

Inject the package `A` in the current program database (including the output package list). The necesary information from these packages is loaded for correct treatment and unexpansion.

– *The following properties should hold at call time:*

`A` is an atom. (`atm/1`)

add_output_package/1: PREDICATE

Usage: `add_output_package(A)`

Add the package `A` to the output packages list

– *The following properties should hold at call time:*

`A` is an atom. (`atm/1`)

get_output_package/1: PREDICATE

Usage: `get_output_package(X)`

`X` is a package that will be included in the output (`module` directive).

add_output_operator/3: PREDICATE

Usage: `add_output_operator(Prec,Type,OP)`

Define an operator for output (same arguments as in `op/3`).

- *The following properties should hold at call time:*

  `Prec` is an integer. (`int/1`)

  `Type` is an atom. (`atm/1`)

  `OP` is an atom or a list of atoms. (`atm_or_atm_list/1`)

get_output_operator/3: PREDICATE

Usage: `get_output_operator(Pred,Type,OP)`

Enumerate output operators (same arguments as in `op/3`).

- *The following properties should hold upon exit:*

  `Pred` is an integer. (`int/1`)

  `Type` is an atom. (`atm/1`)

  `OP` is an atom or a list of atoms. (`atm_or_atm_list/1`)

add_comment/1: PREDICATE

Usage: `add_comment(Comment)`

Add comment to the comment db

- *The following properties should hold at call time:*

  `Comment` is a string (a list of character codes). (`string/1`)

get_comment/1: PREDICATE

Usage: `get_comment(Comment)`

Retrieves comments from the comment db

- *The following properties should hold upon exit:*

  `Comment` is a string (a list of character codes). (`string/1`)

cleanup_comment_db/0: PREDICATE

Usage:

Cleans up the comment db

cleanup_commented_assrt/0: PREDICATE

No further documentation available for this predicate.

get_commented_assertion/2: PREDICATE

No further documentation available for this predicate.

add_commented_assertions/1: PREDICATE

Usage: `add_commented_assertions(A)`

Add the assertions list `A` to the commented assertions DB.

– *The following properties should hold at call time:*

`A` is a list. (`list/1`)

add_commented_assertion/1: PREDICATE

Usage: `add_commented_assertion(A)`

Add assertion `A` to the commented assertions DB.

– *The following properties should hold at call time:*

`A` is any term. (`term/1`)

cleanup_punit/0: PREDICATE

Usage:

Clean up all facts that p_unit asserts.

get_call_from_call_assrt/7: PREDICATE

Usage: `get_call_from_call_assrt(Sg,M,Status,Call,Source,LB,LE)`

Returns in `Call`, upon backtracking call patterns from calls assertions related to `Sg`, in module `M`. Also takes care of disjunctions.

get_pred_mod_defined/2: PREDICATE

Usage: `get_pred_mod_defined(Sg,Mod)`

Returns the module where a predicate given by goal `Sg` is defined. If the `Sg` is multifile, the modules where it is defined are enumerated.

– *The following properties should hold at call time:*

`Sg` is currently a term which is not a free variable. (`nonvar/1`)

`Mod` is a free variable. (`var/1`)

– *The following properties should hold globally:*

Calls of the form `get_pred_mod_defined(Sg,Mod)` are non-deterministic. (`nondet/1`)

assertion_set_status/3: PREDICATE

No further documentation available for this predicate.

assertion_set_head/3: PREDICATE
No further documentation available for this predicate.

assertion_set_calls/3: PREDICATE
No further documentation available for this predicate.

assertion_set_success/3: PREDICATE
No further documentation available for this predicate.

assertion_set_comp/3: PREDICATE
No further documentation available for this predicate.

cleanup_libcache/0: PREDICATE
Usage:
Cleans up libcache.

loaded_libcache/0: PREDICATE
Usage:
Checks if the libcache is loaded

load_libcache/1: PREDICATE
Usage: `load_libcache(DataDir)`
Load the preprocessed library cache (specified in the `core/Manifest/core.libcache.pl` module.

gen_libcache/1: PREDICATE
Usage: `gen_libcache(DataDir)`
Generate the preprocessed library cache (specified in the `core/Manifest/core.libcache.pl` module. .

type_of_goal/2: (UNDOC_REEXPORT)
Imported from `p_unit_basic` (see the corresponding documentation for details).

92.3 Documentation on multifiles

define_flag/3: PREDICATE

Usage: `define_flag(Flag,FlagValues,Default)`

– *The following properties hold upon exit:*

`Flag` is an atom. (`atm/1`)

Define the valid flag values (`flag_values/1`)

The predicate is *multifile*.

hook_compact_global_prop/2: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

hook_compact_calls_prop/2: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

hook_native_prop/2: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

hook_pp_info_clause/3: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

hook_pp_info_lit/4: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

hook_legal_regtype/1: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

hook_insert_regtype/2: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

hook_post_init_regtypes/0: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

hook_cleanup_lib_regtypes/0: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

hook_restore_lib_regtypes/1: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

hook_save_lib_regtypes/1: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

92.4 Documentation on imports

This module has the following direct dependencies:

– *System library modules:*

`datafacts_rt`, `native_props`, `c_itf_props`, `messages`, `aggregates`, `c_itf`, `hiordlib`, `lists`, `vndict`, `terms_check`, `assrt_lib`, `p_unit_db`, `program_keys`, `native`, `p_unit_basic`, `p_asr`, `tr_syntax`, `unexpand`, `streams`, `pathnames`, `bundle_paths`, `datadir`.

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`, `internals`, `runtime_control`, `stream_basic`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `basicmodes`, `regtypes`, `datafacts`, `hiord`, `nativeprops`, `define_flag`, `compiler/p_unit/p_unit_argnames`, `argnames`.

93 native (library)

This module has the basic procedures for understanding predicates as builtins and properties as native properties.

93.1 Usage and interface

- **Library usage:**
  `:- use_module(library(compiler/p_unit/native)).`
- **Exports:**
  - *Predicates:*
    `builtin/2`, `native_prop_map/3`, `wam_builtin/2`.
  - *Regular Types:*
    `native_prop_term/1`.
  - *Multifiles:*
    `hook_compact_global_prop/2`, `hook_compact_calls_prop/2`, `hook_native_prop/2`, `hook_pp_info_clause/3`, `hook_pp_info_lit/4`, `hook_legal_regtype/1`, `hook_insert_regtype/2`, `hook_post_init_regtypes/0`, `hook_cleanup_lib_regtypes/0`, `hook_restore_lib_regtypes/1`, `hook_save_lib_regtypes/1`.

93.2 Documentation on exports

builtin/2: PREDICATE

checks that a user level (property) predicate is declared native and translates it into the internal representation for that native (builtin or property) predicate.

native_prop_map/3: PREDICATE

`native_prop_map(Prop,P,Vars)`

`Prop` is a property `P`(`Vars`) representing a mapping `map`(`Vars`,`P`)

native_prop_term/1: REGTYPE

Defined as

```
native_prop_term(Prop) :-
    native:native(Prop).
native_prop_term(regtype(Prop)) :-
    cgoal(Prop).
```

Usage: `native_prop_term(Prop)`

`Prop` identifies a native property.

wam_builtin/2: PREDICATE

No further documentation available for this predicate.

93.3 Documentation on multifiles

hook_compact_global_prop/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

hook_compact_calls_prop/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

hook_native_prop/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

hook_pp_info_clause/3: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

hook_pp_info_lit/4: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

hook_legal_regtype/1: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

hook_insert_regtype/2: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

hook_post_init_regtypes/0: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

hook_cleanup_lib_regtypes/0: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

hook_restore_lib_regtypes/1: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

hook_save_lib_regtypes/1: PREDICATE
No further documentation available for this predicate. The predicate is *multifile*.

93.4 Documentation on internals

native/1: REGTYPE

`native(Prop)`

`Prop` is (the internal representation of) a native property: one that CiaoPP knows natively how to manipulate.

```
native(covered(V,L)) :-
    var(V),
    list(var,L).
native(free(L)) :-
    vlist(L).
native(ground(L)) :-
    vlist(L).
native(indep(L)) :-
    list(list(var),L).
native(instance(V,T)) :-
    var(V),
    nonvar(T).
native(linear(L)) :-
    vlist(L).
native(not_free(L)) :-
    vlist(L).
native(not_ground(L)) :-
    vlist(L).
native(sharing(L)) :-
    list(list(var),L).
native(sharing(Xs,Xss)) :-
    list(var,Xs),
    list(list(var),Xss).
native(det).
native(semidet).
native(multi).
native(nondet).
native(covered).
native(fails).
native(is_det).
native(mut_exclusive).
native(non_det).
native(not_covered).
native(not_fails).
native(not_mut_exclusive).
native(sideff(X)) :-
    member(X,[pure,soft,hard]).
native(steps(C)) :-
    cost_expression(C).
native(steps_lb(C)) :-
    cost_expression(C).
native(steps_ub(C)) :-
    cost_expression(C).
native(steps_o(C)) :-
    cost_expression(C).
```

```
native(cost(C)) :-
    cost_expression(C).
native(terminates).
native(size(C)) :-
    cost_expression(C).
native(size(A,B)) :-
    var(A),
    cost_expression(B).
native(size_lb(C)) :-
    cost_expression(C).
native(size_ub(C)) :-
    cost_expression(C).
native(size_o(C)) :-
    cost_expression(C).
native(rsize(A,_B)) :-
    var(A).
native(cardinality(_N,_M)).
native(costb(_R,_N,_M)).
native(X) :-
    native(X,X).
```

vlist/1: REGTYPE

```
vlist(L) :-
    var(L).
vlist(L) :-
    list(var,L).
```

93.5 Documentation on imports

This module has the following direct dependencies:

– *System library modules:*

`native_props`, `lists`.

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`, `runtime_control`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `regtypes`, `hiord`, `nortchecks`, `nativeprops`.

94 program_keys (library)

This module handles the format of the structures used to represent the program. It is a list of clauses, where each clause is identified by a key, and the clause body is a conjunction of literals, where each literal is also identified by a key.

When creating a new clause for a predicate `H` in the program, the following goal will give you a clause in the correct format:

```
clause_key(H,ClId), rewrite_source_clause(clause(H,Body),ClId,Clause),
```

94.1 Usage and interface

- **Library usage:**
  `:- use_module(library(compiler/p_unit/program_keys)).`
- **Exports:**
  - *Predicates:*
    `cleanup_program_keys/0`, `clause_key/2`, `clauses_keys/2`, `clause_number/2`, `first_key/2`, `last_clause/1`, `make_atom/2`, `inverse_rewrite_source_program_cl/2`, `inverse_rewrite_source_body/2`, `rewrite_source_all_clauses/2`, `rewrite_source_clause/3`, `decode_litkey/5`, `decode_clkey/4`, `decode_entrykey/4`, `decode_predkey/3`, `is_clkey/1`, `is_litkey/1`, `is_entrykey/1`, `is_directive/3`, `is_clause/4`, `orig_clause_id/2`, `lit_ppkey/3`, `clid_of_atomid/2`, `counter/3`, `get_predkey/3`, `get_predkeys/2`, `predkey_from_sg/2`, `get_clkey/4`, `get_litkey/5`.
  - *Properties:*
    `clausebody/1`.
  - *Regular Types:*
    `clause/1`, `literal_ppkey/1`, `litkey/1`, `clkey/1`, `predkey/1`.

94.2 Documentation on exports

cleanup_program_keys/0: PREDICATE

Cleanups internal database.

clause_key/2: PREDICATE

Usage: `clause_key(H,ClId)`

`ClId` is the clause key that an additional clause of predicate `H` should have.

- *The following properties should hold at call time:*
  `H` is a clause head identifier. (`head/1`)
  `ClId` is a free variable. (`var/1`)
- *The following properties should hold upon exit:*
  `ClId` is an atom that uniquely identifies a program clause. (`clkey/1`)

clauses_keys/2: PREDICATE

Usage: `clauses_keys(H,ClIds)`

`ClIds` are the clause keys of all clauses already known for predicate `H`.

– *The following properties should hold at call time:*

`H` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)

`ClIds` is a free variable. (`var/1`)

– *The following properties should hold upon exit:*

`H` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)

`ClIds` is a list of `clkey`s. (`list/2`)

clause_number/2: PREDICATE

No further documentation available for this predicate.

first_key/2: PREDICATE

No further documentation available for this predicate.

last_clause/1: PREDICATE

Usage: `last_clause(ClId)`

`ClId` is the clause key of the last known clause of the predicate to which it corresponds.

– *The following properties should hold at call time:*

`ClId` is an atom that uniquely identifies a program clause. (`clkey/1`)

make_atom/2: PREDICATE

No further documentation available for this predicate.

inverse_rewrite_source_program_cl/2: PREDICATE

No further documentation available for this predicate.

inverse_rewrite_source_body/2: PREDICATE

No further documentation available for this predicate.

rewrite_source_all_clauses/2: PREDICATE

`rewrite_source_all_clauses(Clauses,NewClauses)`

`NewClauses` is the result of applying the format transformation to the list of clauses `Clauses`.

rewrite_source_clause/3: PREDICATE

Usage: `rewrite_source_clause(Clause0,ClId,Clause)`

`Clause` is an structure representing the clause `Clause0` identified by `ClId` (does nothing for directives).

– *The following properties should hold at call time:*

`clause(Clause0)`	(`clause/1`)
`ClId` is an atom that uniquely identifies a program clause.	(`clkey/1`)
`Clause` is a free variable.	(`var/1`)

– *The following properties should hold upon exit:*

`clause(Clause0)`	(`clause/1`)
`ClId` is an atom that uniquely identifies a program clause.	(`clkey/1`)
`clause(Clause)`	(`clause/1`)

decode_litkey/5: PREDICATE

Usage: `decode_litkey(AtId,F,A,C,G)`

`AtId` identifies the `G`th literal of the body of the `C`th clause of predicate `F/A`.

– *Call and exit should be compatible with:*

`AtId` is an atom that uniquely identifies a program point of a program clause body literal.	(`litkey/1`)
`F` is an atom.	(`atm/1`)
`A` is a number.	(`num/1`)
`C` is a number.	(`num/1`)
`G` is a number.	(`num/1`)

decode_clkey/4: PREDICATE

Usage: `decode_clkey(ClId,F,A,C)`

`ClId` identifies the `C`th clause of predicate `F/A`.

– *Call and exit should be compatible with:*

`ClId` is an atom that uniquely identifies a program clause.	(`clkey/1`)
`F` is an atom.	(`atm/1`)
`A` is a number.	(`num/1`)
`C` is a number.	(`num/1`)

decode_entrykey/4: PREDICATE

No further documentation available for this predicate.

decode_predkey/3: PREDICATE

Usage: `decode_predkey(PredId,F,A)`

`PredId` identifies the predicate `F/A`.

– *Call and exit should be compatible with:*

`PredId` is an atom that uniquely identifies a program predicate.	(`predkey/1`)
`F` is an atom.	(`atm/1`)
`A` is a number.	(`num/1`)

is_clkey/1: PREDICATE

Usage: `is_clkey(Id)`

Succeeds if `Id` is a valid clause identifier. The predicate name must not contain '/' characters.

– *Call and exit should be compatible with:*

`Id` is an atom. (`atm/1`)

is_litkey/1: PREDICATE

Usage: `is_litkey(Id)`

Succeeds if `Id` is a valid atom identifier. The predicate name must not contain '/' characters.

– *Call and exit should be compatible with:*

`Id` is an atom. (`atm/1`)

is_entrykey/1: PREDICATE

Usage: `is_entrykey(Id)`

Succeeds if `Id` is a valid *entry point* identifier (predkey for exported predicates, clkey for entry assertions)

– *Call and exit should be compatible with:*

`Id` is an atom. (`atm/1`)

is_directive/3: PREDICATE

No further documentation available for this predicate.

is_clause/4: PREDICATE

No further documentation available for this predicate.

orig_clause_id/2: PREDICATE

`orig_clause_id(ClId,Orig_ClId)`

`Orig_ClId` is the clause identifier resulting from replacing the name of a newly generated predicate with the name of its corresponding predicate in the original program.

lit_ppkey/3: PREDICATE

Usage:

– *Call and exit should be compatible with:*

`literal_ppkey(Arg1)` (`literal_ppkey/1`)

`Arg2` is a term which represents a goal, i.e., an atom or a structure. (`cgoal/1`)

`Arg3` is an atom that uniquely identifies a program point of a program clause body literal. (`litkey/1`)

clid_of_atomid/2: PREDICATE

Usage: `clid_of_atomid(AtomId,ClId)`

Returns in `ClId` the clause identifier corresponding to `AtomId` goal identifier.

- *Call and exit should be compatible with:*
  `AtomId` is an atom. (`atm/1`)
  `ClId` is an atom. (`atm/1`)
- *The following properties should hold at call time:*
  `AtomId` is currently a term which is not a free variable. (`nonvar/1`)
  `ClId` is a free variable. (`var/1`)

clause/1: REGTYPE

Defined as:

```
clause(clause(Head,Body):Clid) :-
    cgoal(Head),
    clausebody(Body),
    clkey(Clid).
clause(directive(Body):Clid) :-
    clausebody(Body),
    drid(Clid).
```

clausebody/1: PREDICATE

`clausebody(Body)`

`Body` is a conjunction of simple goals; if a goal is a meta-predicate, its meta-arguments are terms of the form `'$'(Term,Body,Type)`, where `Term` is the original goal term, `Type` the type of meta-term as in the meta_predicate directive, and, if `Type` corresponds to an executable form of meta-term, `Body` is the `clausebody` that corresponds to `Term`.

```
clausebody(L) :-
    literal_ppkey(L).
clausebody((L,B)) :-
    literal_ppkey(L),
    clausebody(B).
```

literal_ppkey/1: REGTYPE

A regular type, defined as follows:

```
literal_ppkey(Lit:PPKey) :-
    cgoal(Lit),
    litkey(PPKey).
literal_ppkey(builtin(B):noinfo) :-
    cgoal(B).
literal_ppkey(!).
```

litkey/1: REGTYPE

Usage: `litkey(Key)`

`Key` is an atom that uniquely identifies a program point of a program clause body literal.

clkey/1: REGTYPE

Usage: `clkey(Id)`

`Id` is an atom that uniquely identifies a program clause.

predkey/1: REGTYPE

Usage: `predkey(Id)`

`Id` is an atom that uniquely identifies a program predicate.

counter/3: PREDICATE

No further documentation available for this predicate. The predicate is of type *data*.

get_predkey/3: PREDICATE

Usage: `get_predkey(F,A,Key)`

`Key` is the key corresponding to predicate `F/A`

- *The following properties should hold at call time:*

  `F` is an atom. (`atm/1`)

  `A` is an atom. (`atm/1`)

  `Key` is a free variable. (`var/1`)

- *The following properties should hold upon exit:*

  `Key` is an atom that uniquely identifies a program predicate. (`predkey/1`)

get_predkeys/2: PREDICATE

Usage: `get_predkeys(Preds,Keys)`

`Keys` is the list of atoms obtained from `Preds`.

- *The following properties should hold at call time:*

  `Preds` is a list. (`list/1`)

- *The following properties should hold upon exit:*

  `Keys` is a list of `predkeys`. (`list/2`)

predkey_from_sg/2: PREDICATE

Usage: `predkey_from_sg(Sg,Key)`

`Key` is the key corresponding to functor `Sg`

- *The following properties should hold at call time:*

  `Sg` is any term. (`term/1`)

  `Key` is a free variable. (`var/1`)

- *The following properties should hold upon exit:*

  `Key` is an atom that uniquely identifies a program predicate. (`predkey/1`)

get_clkey/4: PREDICATE

Usage: `get_clkey(F,A,Cl,ClKey)`

`ClKey` is the key corresponding to clause `F/A/Cl`

- *The following properties should hold at call time:*

  `F` is an atom. (`atm/1`)

  `A` is an atom. (`atm/1`)

  `Cl` is an atom. (`atm/1`)

  `ClKey` is a free variable. (`var/1`)

- *The following properties should hold upon exit:*

  `ClKey` is an atom that uniquely identifies a program clause. (`clkey/1`)

get_litkey/5: PREDICATE

Usage: `get_litkey(F,A,Cl,Lit,ClKey)`

`ClKey` is the key corresponding to clause `F/A/Cl/Lit`

- *The following properties should hold at call time:*

  `F` is an atom. (`atm/1`)

  `A` is an atom. (`atm/1`)

  `Cl` is an atom. (`atm/1`)

  `Lit` is an atom. (`atm/1`)

  `ClKey` is a free variable. (`var/1`)

- *The following properties should hold upon exit:*

  `ClKey` is an atom that uniquely identifies a program point of a program clause body literal. (`litkey/1`)

94.3 Documentation on internals

body/1: PREDICATE

`body(Body)`

`Body` is a conjunction of simple goals:

```
body((G,B)) :-
    cgoal(G),
    body(B).
body(G) :-
    cgoal(G).
```

drid/1: REGTYPE

Usage: `drid(Id)`

`Id` is a number that uniquely identifies a program directive.

head/1: REGTYPE

Defined as

```
head(0).
head(1).
head(X) :-
    cgoal(X).
```

Usage: `head(Head)`

`Head` is a clause head identifier.

94.4 Documentation on imports

This module has the following direct dependencies:

– *System library modules:*

`datafacts_rt`, `lists`, `prednames`, `p_unit_basic`.

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`, `messages_basic`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `basicmodes`, `regtypes`, `datafacts`.

95 tr_syntax (library)

95.1 Usage and interface

- **Library usage:**
  `:- use_module(library(compiler/p_unit/tr_syntax)).`
- **Exports:**
  - *Predicates:*
    `cleanup_tr_syntax/0`, `traverse_clauses/4`.

95.2 Documentation on exports

cleanup_tr_syntax/0: PREDICATE

`cleanup_tr_syntax`

Cleanups internal database.

traverse_clauses/4: PREDICATE

Usage: `traverse_clauses(Cls,Ds,NewCls,NewDs)`

It traverses program clauses `Cls` suitably changing the format for the following step (analysis, annotation, etc). In general, it will have to remove disjunctions, if-then-elses, remote cuts, etc. In doing this, the old clauses will be transformed and new clauses (and thus new dictionaries) can be created.

- *The following properties should hold at call time:*

`Cls` is currently a term which is not a free variable.	(`nonvar/1`)
`Ds` is currently a term which is not a free variable.	(`nonvar/1`)
`NewCls` is a free variable.	(`var/1`)
`NewDs` is a free variable.	(`var/1`)

95.3 Documentation on imports

This module has the following direct dependencies:

- *System library modules:*
  `datafacts_rt`, `program_keys`, `native`, `p_unit`, `p_unit_db`, `lists`, `sets`, `terms_vars`, `vndict`.
- *Internal (engine) modules:*
  `term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`.
- *Packages:*
  `prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `basicmodes`, `datafacts`.

96 The Global Information Server

This component is in charge of serving the rest of the precompiler all known semantic information on the current module, either from any analysis or from the assertions.

The (basic) organization of the code is as follows:

Module `infer` is in charge of interfacing with the rest of CiaoPP. Module `modes` implements a mode analysis based on sharing information. Module `vartypes` implements a moded type analysis based on freeness and regular type information. Module `infer_db` is the centralized repository for all analysis information. Module `typeslib` implements a library for manipulation of regular types.

97 Analysis Information Server

This module provides the other parts of the compiler with the information they require on properties of the program, either inferred or from the assertions.

97.1 Usage and interface

- **Library usage:**
  `:- use_module(ciaopp(infer)).`
- **Exports:**
  - *Predicates:*
    `get_info/5`, `get_absint/4`, `type2measure/3`, `type_holds/3`, `type_fails/3`, `get_memo_lub/5`, `get_completes_lub/6`, `get_completes/4`, `kind_of_info/7`.

97.2 Documentation on exports

get_info/5: PREDICATE

No further documentation available for this predicate.

get_absint/4: PREDICATE

No further documentation available for this predicate.

type2measure/3: PREDICATE

No further documentation available for this predicate.

type_holds/3: PREDICATE

No further documentation available for this predicate.

type_fails/3: PREDICATE

No further documentation available for this predicate.

get_memo_lub/5: PREDICATE

Usage: `get_memo_lub(Key,Vars,AbsInt,Lub,ASub)`

Obtains program point info inferred by domain `AbsInt` at point `Key`.

- *The following properties should hold at call time:*

`Key` is ground.	(`gnd/1`)
`Vars` is any term.	(`term/1`)
`AbsInt` is an atom.	(`atm/1`)
`Lub` is a free variable.	(`var/1`)
`ASub` is a free variable.	(`var/1`)

– *The following properties should hold upon exit:*

`Key` is ground.	(`gnd/1`)
`Vars` is a list of `var`s.	(`list/2`)
`AbsInt` is ground.	(`gnd/1`)
`Lub` is currently a term which is not a free variable.	(`nonvar/1`)
`ASub` is currently a term which is not a free variable.	(`nonvar/1`)

get_completes_lub/6: PREDICATE

No further documentation available for this predicate.

get_completes/4: PREDICATE

No further documentation available for this predicate.

kind_of_info/7: PREDICATE

No further documentation available for this predicate.

97.3 Documentation on imports

This module has the following direct dependencies:

– *Application modules:*

`infer_db`, `infer_dom`, `inferseff`, `vartypes`, `domains`, `plai_db`, `pool`, `preprocess_flags`, `nfdet_common`.

– *System library modules:*

`datafacts_rt`, `typeslib`, `p_unit`, `program_keys`, `aggregates`, `lists`, `sort`, `terms_check`, `terms_vars`.

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `datafacts`, `ciaopp(ciaopp_options)`.

98 The Abstract Interpretation Component -PLAI

This component is in charge of analysing the program with techniques based on abstract interpretation. See Chapter 7 [Available abstract domains], page 31 for the available abstract domains.

99 PLAI- Abstract Interpretation-based Analysis

Abstract interpretation based analysis in PLAI is implemented in a parametric fashion: there are four available fixpoint computation algorithms for the analysis which can be used with several abstract domains.

The (basic) organization of the code is as follows:

Module `plai` is in charge of interfacing with the rest of CiaoPP. Modules `tarjan`, `normalize`, and `transform` support the preprocessing needed for analysis: identify strongly connected components, normalize the program (if required), and assert it in a format suitable for analysis, respectively. Module `plai_db` stores the final results of analysis. Module `trust` handles the assertions used during analysis and module `domains` interfaces to the domain-dependent operations.

Module `fixpo_plai` implements the classical top-down fixpoint algorithm of PLAI. In the figure, it represents several other fixpoint algorithms available, namely: `fixpo_del` for delay analysis, and `fixpo_dd` and `fixpo_di` for incremental analysis. Module `re_analysis` supports the recovery of analysis information after transformation of the source program.

Modules `trace_fixp` and `view_fixp` implement tracing of the analysis procedure, including a graphic visualization of the and-or graph being constructed during analysis.

100 Program Analysis (PLAI)

Stability: [**devel**] Currently the subject of active development and/or research. Functionality may be limited and API and/or functionality may change without warning or deprecation period. Not recommended yet for use in production.

100.1 Usage and interface

- **Library usage:**

  `:- use_module(ciaopp(plai)).`
- **Exports:**
  - *Predicates:*

    `plai/5`, `cleanup_plai/1`, `mod_plai/5`, `is_checker/1`, `analyze/7`, `init_fixpoint/1`, `entry_point/5`, `generate_trans_clauses/4`, `transform_clauses_/5`, `topdown_analysis/3`, `mod_topdown_analysis/3`.

100.2 Documentation on exports

plai/5: PREDICATE

`plai(Cls,Ds,Fixp,AbsInt,Info)`

Performs the analysis of the clauses in `Cls` (dictionaries of variables in `Ds`) with fixpoint algorithm `Fixp` and analysis domain `AbsInt`. The analysis results are left in a permanent database (see `plai_db`). `Info` is a list of properties and informations. One possible value is `[time(Total,[(subtask1,T1),...,(subtaskN,TN)])]`.

cleanup_plai/1: PREDICATE

`cleanup_plai(AbsInt)`

Cleanups the database of analysis of all permanent information regarding abstract domain `AbsInt`.

mod_plai/5: PREDICATE

`mod_plai(Cls,Ds,Fixp,AbsInt,Time)`

Performs the analysis of the clauses in `Cls` (dictionaries of variables in `Ds`) with fixpoint algorithm `Fixp` and analysis domain `AbsInt`. The analysis results are left in a permanent database (see `plai_db`).

The analysis uses the entry information provided by the entry policy selected in entry_policy preprocessing flag.

is_checker/1: PREDICATE

No further documentation available for this predicate.

analyze/7: PREDICATE
No further documentation available for this predicate.

init_fixpoint/1: PREDICATE
No further documentation available for this predicate.

entry_point/5: PREDICATE
No further documentation available for this predicate.

generate_trans_clauses/4: PREDICATE
No further documentation available for this predicate.

transform_clauses_/5: PREDICATE
No further documentation available for this predicate.

topdown_analysis/3: PREDICATE
No further documentation available for this predicate.

mod_topdown_analysis/3: PREDICATE
No further documentation available for this predicate.

100.3 Documentation on imports

This module has the following direct dependencies:

– *Application modules:*

`analysis_stats`, `ciaopp_log`, `sp_clauses`, `unfold_times`, `frontend_driver`, `intermod_entry`, `preprocess_flags`, `mem_usage`, `domains`, `normalize_args`, `plai_errors`, `fixpo_plai`, `fixpo_dd`, `fixpo_di`, `fixpo_check_di`, `fixpo_check_di2`, `fixpo_check_di3`, `fixpo_check_di4`, `fixpo_check_di5`, `fixpo_plai_gfp`, `fixpo_check_reduced_di`, `fixpo_bu`, `tarjan`, `transform`, `fixpo_ops`, `trace_fixp`.

– *System library modules:*

`aggregates`, `counters`, `lists`, `terms_vars`, `vndict`, `port_reify`, `messages`, `p_unit`, `program_keys`, `p_unit_db`.

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`.

101 fixpo_plai (library)

Author(s): Kalyan Muthukumar, Maria Garcia de la Banda, Francisco Bueno.

Stability: [**alpha**] A good part of the functionality is there but has not been the subject of significant testing and/or verification.

This module implements the top-down fixpoint algorithm of PLAI, both in its mono-variant and multi-variant on successes versions. It is always multi-variant on calls. The algorithm is parametric on the particular analysis domain.

101.1 Usage and interface

- **Library usage:**
  `:- use_module(ciaopp(plai/fixpo_plai)).`
- **Exports:**
  - *Predicates:*
    `query/8`, `init_fixpoint/0`, `cleanup_fixpoint/1`, `entry_to_exit/9`, `approx/6`, `fixpoint/6`, `$depend_list/3`.

101.2 Documentation on exports

query/8: PREDICATE

Usage: `query(AbsInt,QKey,Query,Qv,RFlag,N,Call,Succ)`

The success pattern of `Query` with `Call` is `Succ` in the analysis domain `AbsInt`. The predicate called is identified by `QKey`, and `RFlag` says if it is recursive or not. The goal `Query` has variables `Qv`, and the call pattern is uniquely identified by `N`.

- *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable.	(`nonvar/1`)
`QKey` is currently a term which is not a free variable.	(`nonvar/1`)
`Query` is currently a term which is not a free variable.	(`nonvar/1`)
`Qv` is currently a term which is not a free variable.	(`nonvar/1`)
`RFlag` is currently a term which is not a free variable.	(`nonvar/1`)
`Call` is currently a term which is not a free variable.	(`nonvar/1`)
`Succ` is a free variable.	(`var/1`)

init_fixpoint/0: PREDICATE

Usage:

Cleanups the database of analysis of temporary information.

cleanup_fixpoint/1: PREDICATE

Usage: `cleanup_fixpoint(AbsInt)`

Cleans up the database of analysis, of both temporary as well as permanent information regarding abstract domain `AbsInt`.

entry_to_exit/9: PREDICATE
No further documentation available for this predicate.

approx/6: PREDICATE
No further documentation available for this predicate. The predicate is of type *data*.

fixpoint/6: PREDICATE
No further documentation available for this predicate. The predicate is of type *data*.

$depend_list/3: PREDICATE
No further documentation available for this predicate. The predicate is of type *data*.

101.3 Documentation on imports

This module has the following direct dependencies:

- *Application modules:*
  `preprocess_flags`, `fixpo_ops`, `domains`, `plai_db`, `psets`, `transform`, `apply_assertions_old`.
- *System library modules:*
  `native_props`, `datafacts_rt`, `aggregates`, `lists`, `terms_vars`, `sets`, `sort`, `messages`.
- *Internal (engine) modules:*
  `term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`.
- *Packages:*
  `prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `basicmodes`, `nativeprops`, `datafacts`, `ciaopp(ciaopp_options)`, `.(notrace)`, `spec(no_debug)`.

102 Available type domains and widenings

102.1 Available widenings

All widenings are briefly described in the eterms domain paper [VB02]

Widening	Implemented	Domain	Typeslib	Using 'names'	Tested	Working
Type Jungle	yes	evalterms	yes	yes (why?)	no	not connected to p
Shortening	yes	termsd	yes	no	barely	apparently
Topological Clash	yes	ptypes	yes	no	barely	no
Structural	yes	eterms	yes	yes	yes	yes (slow)
Depth	no					
Functor	no					

Restricted shortening is also implemented according to comments in termsd.

102.2 Other type domains

Domain	widening needed?	Typeslib	Using 'names'	Tested	Working
svterms	yes (structural)	yes	yes (structural)	barely	apparently (slow)
deftypes	no	yes	no	barely	apparently
depthk	no	no	no	barely	?

102.3 Some experiments

Some very simple experiments FixFail means that analyzing with plai the message "Something has failed" appeared.

Benchmarks are located in `ciaopp/tests/benchs/widening/` list_of_lists and sorted were used because they are used as examples in the eterms paper. `minimal_lists` and `minimal_functors` were designed to capture the complexity problem that currently eterms has.

Widening	list_of_lists	sorted	minimal_lists	minimal_functors
Shortening	2.532	30.195	26.668	9.28
Topological Clash	FixFail	FixFail	FixFail	FixFail
Structural	2.388	2.855	23161.302	9.822
svterms	3.183	3.443	37948.465	8.553
deftypes	1.647	2.348	2.603	8.803
depthk	8.527	5.725	4.879	7.11

For structural widening, e.g. using domain eterms or svterms, analyzing `minimal_lists` creates 1500 types.

103 plai_db (library)

103.1 Usage and interface

- **Library usage:**
  `:- use_module(ciaopp(plai/plai_db)).`
- **Exports:**
  - *Predicates:*
    `complete/7`, `lub_complete/6`, `memo_call/5`, `memo_table/6`, `memo_lub/5`, `pragma/5`, `complete_parent/2`, `cleanup_plai_db/1`, `invalid_call/6`, `raw_success/6`, `get_parent_key/4`, `get_complete/8`, `get_memo_table/7`, `get_raw_success/7`, `add_parent_complete/5`, `del_parent_complete/6`, `patch_parents/6`, `merge_parents/3`, `del_parent/4`, `update_complete_id/4`, `delete_complete/3`, `remove_extra_info_complete/3`, `delete_plai_db_one_clause/4`, `complete_key_from_id/3`, `erase_previous_memo_tables_and_parents/4`, `erase_last_memo_table/3`, `erase_previous_memo_lubs/2`, `erase_previous_parents_info/5`, `init_rev_idx/1`, `clean_rev_idx/1`, `complete_id_key/3`, `memo_table_id_key/3`, `add_invalid_call/6`, `store_raw_success/6`, `get_raw_success/6`.
  - *Regular Types:*
    `plai_db_id/1`.

103.2 Documentation on exports

complete/7: PREDICATE

`complete(SgKey,AbsInt,Sg,Proj,Prime,Id,Parents)`

The predicate `SgKey` has a variant success pattern `(Sg,Proj,Prime)` on the domain `AbsInt`. The and-or graph node is `Id`, and is called from the program points in list `Parents`.

Usage: `complete(SgKey,AbsInt,Sg,Proj,Prime,Id,Parents)`

- *The following properties should hold upon exit:*

`SgKey` is an atom that uniquely identifies a program predicate.	(`predkey/1`)
`AbsInt` is an atom.	(`atm/1`)
`Sg` is any term.	(`term/1`)
`Proj` is any term.	(`term/1`)
`Prime` is a list of `terms`.	(`list/2`)
`Id` is an integer.	(`int/1`)
`parents_complete(Parents)`	(`parents_complete/1`)

The predicate is of type *data*.

lub_complete/6: PREDICATE

`lub_complete(SgKey,AbsInt,Lub,Sg,Proj,Prime)`

The predicate `SgKey` has in all variants success pattern `(Sg,Proj,Prime)` on the domain `AbsInt`. If `Lub` is yes, `Proj` and `Prime` are substitutions, if `Lub` is no, they are lists of substitutions. The predicate is of type *data*.

memo_call/5: PREDICATE

No further documentation available for this predicate. The predicate is of type *data*.

memo_table/6: PREDICATE

`memo_table(LitKey,AbsInt,Id,Child,Vars_u,Call)`

Before calling the goal at program point `PointKey`, there is a variant in which `Call` on the domain `AbsInt` holds upon the program clause variables `Vars_u`. These variables need be sorted conveniently so that `Call` makes sense. The and-or graph node that causes this is `Id` and the call originated to the goal at this program point generates and-or graph node `Child`.

Usage: `memo_table(LitKey,AbsInt,Id,Child,Vars_u,Call)`

– *The following properties should hold upon exit:*

`LitKey` is an atom that uniquely identifies a program point of a program clause body literal. (`litkey/1`)

`AbsInt` is an atom. (`atm/1`)

`Id` is an integer. (`int/1`)

`Child` is an integer. (`int/1`)

`Vars_u` is any term. (`term/1`)

`Call` is a list of `terms`. (`list/2`)

The predicate is of type *data*.

memo_lub/5: PREDICATE

`memo_lub(PointKey,AbsInt,Lub,Vars_u,Call)`

Before calling the goal at program point `PointKey`, in all variants `Call` on the domain `AbsInt` holds upon the program clause variables `Vars_u`. If `Lub` is yes, `Call` is a substitution, if If `Lub` is no, `Call` is a list of substitutions. The predicate is of type *data*.

pragma/5: PREDICATE

No further documentation available for this predicate. The predicate is of type *data*.

complete_parent/2: PREDICATE

`complete_parent(Id,Parents)`

Used to keep the trace of the parents in the and-or graph for the dd/di fixpoints. The parents are used to choose previous aproximations to apply the widening operators on calls The and-or graph node is `Id`, and `Parents` is a list of couples of graph node and program points. The predicate is of type *data*.

cleanup_plai_db/1: PREDICATE

`cleanup_plai_db(AbsInt)`

Erases all data in this module for the analysis domain `AbsInt`.

invalid_call/6: PREDICATE

No further documentation available for this predicate. The predicate is of type *data*.

raw_success/6: PREDICATE

No further documentation available for this predicate. The predicate is of type *data*.

get_parent_key/4: PREDICATE

Usage: `get_parent_key(LitKey,Id,AbsInt,CKey)`

`CKey` is the key that corresponds to `Id`, it may not correspong to the decoding LitKey because of how meta_calls are indexed in the fixpoints

– *The following properties should hold upon exit:*

`LitKey` is an atom that uniquely identifies a program point of a program clause body literal. (`litkey/1`)

`Id` is an integer. (`int/1`)

`AbsInt` is an atom. (`atm/1`)

`CKey` is an atom that uniquely identifies a program predicate. (`predkey/1`)

get_complete/8: PREDICATE

Usage: `get_complete(SgKey,AbsInt,Sg,Proj,Prime,Id,Ps,Ref)`

– *The following properties should hold at call time:*

`Id` is currently a term which is not a free variable. (`nonvar/1`)

`SgKey` is an atom that uniquely identifies a program predicate. (`predkey/1`)

`AbsInt` is an atom. (`atm/1`)

`plai_db_id(Id)` (`plai_db_id/1`)

– *The following properties should hold globally:*

All calls of the form `get_complete(SgKey,AbsInt,Sg,Proj,Prime,Id,Ps,Ref)` are deterministic. (`is_det/1`)

get_memo_table/7: PREDICATE

Usage: `get_memo_table(LitKey,AbsInt,Id,Child,Vars,Call,Ref)`

– *The following properties should hold at call time:*

`LitKey` is currently a term which is not a free variable. (`nonvar/1`)

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`Id` is currently a term which is not a free variable. (`nonvar/1`)

`LitKey` is an atom that uniquely identifies a program point of a program clause body literal. (`litkey/1`)

`AbsInt` is an atom. (`atm/1`)

`plai_db_id(Id)` (`plai_db_id/1`)

get_raw_success/7: PREDICATE

Usage: `get_raw_success(ClKey,AbsInt,Id,Sg,Proj,Prime,Ref)`

– *The following properties should hold at call time:*

`ClKey` is currently a term which is not a free variable. (`nonvar/1`)

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`Id` is currently a term which is not a free variable. (`nonvar/1`)

`ClKey` is an atom that uniquely identifies a program point of a program clause body literal. (`litkey/1`)

`AbsInt` is an atom. (`atm/1`)

`plai_db_id(Id)` (`plai_db_id/1`)

– *The following properties should hold upon exit:*

`Sg` is currently a term which is not a free variable. (`nonvar/1`)

`Proj` is currently a term which is not a free variable. (`nonvar/1`)

`Prime` is currently a term which is not a free variable. (`nonvar/1`)

`Ref` is currently a term which is not a free variable. (`nonvar/1`)

add_parent_complete/5: PREDICATE

Usage: `add_parent_complete(SgKey,AbsInt,Id,PId,LitKey)`

– *The following properties should hold at call time:*

`SgKey` is currently a term which is not a free variable. (`nonvar/1`)

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`Id` is currently a term which is not a free variable. (`nonvar/1`)

`PId` is currently a term which is not a free variable. (`nonvar/1`)

`LitKey` is currently a term which is not a free variable. (`nonvar/1`)

del_parent_complete/6: PREDICATE

Usage: `del_parent_complete(SgKey,AbsInt,Id,PId,LitKey,NPs)`

– *The following properties should hold at call time:*

`SgKey` is currently a term which is not a free variable. (`nonvar/1`)

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`Id` is currently a term which is not a free variable. (`nonvar/1`)

`PId` is currently a term which is not a free variable. (`nonvar/1`)

`LitKey` is currently a term which is not a free variable. (`nonvar/1`)

`NPs` is a free variable. (`var/1`)

patch_parents/6: PREDICATE

Usage: `patch_parents(Ref,Memo,Key,Id,NewFs,Fs)`

– *The following properties should hold at call time:*

`Ref` is currently a term which is not a free variable. (`nonvar/1`)

`Memo` is currently a term which is not a free variable. (`nonvar/1`)

`Key` is currently a term which is not a free variable. (`nonvar/1`)

`Id` is currently a term which is not a free variable. (`nonvar/1`)

`Fs` is currently a term which is not a free variable. (`nonvar/1`)

`Fs` is a list. (`list/1`)

– *The following properties should hold globally:*
All the calls of the form `patch_parents(Ref,Memo,Key,Id,NewFs,Fs)` do not fail. (`not_fails/1`)

Meta-predicate with arguments: `patch_parents(?,fact,?,?,?,?)`.

merge_parents/3: PREDICATE
No further documentation available for this predicate.

del_parent/4: PREDICATE
No further documentation available for this predicate.

update_complete_id/4: PREDICATE
No further documentation available for this predicate.

delete_complete/3: PREDICATE
Usage: `delete_complete(SgKey,AbsInt,Id)`
Deletes the information of the complete with `Id`. This predicate does not delete recursively following its parents.

– *The following properties should hold at call time:*

`SgKey` is currently a term which is not a free variable.	(`nonvar/1`)
`AbsInt` is currently a term which is not a free variable.	(`nonvar/1`)
`Id` is currently a term which is not a free variable.	(`nonvar/1`)
`SgKey` is an atom.	(`atm/1`)
`AbsInt` is an atom.	(`atm/1`)
`plai_db_id(Id)`	(`plai_db_id/1`)

remove_extra_info_complete/3: PREDICATE
No further documentation available for this predicate.

delete_plai_db_one_clause/4: PREDICATE
Usage: `delete_plai_db_one_clause(PredKey,ClKey,Id,AbsInt)`
Removes from plai_db the information relative to the clause `ClKey` of complete `Id` for the domain `AbsInt`

– *The following properties should hold at call time:*

`PredKey` is currently a term which is not a free variable.	(`nonvar/1`)
`ClKey` is currently a term which is not a free variable.	(`nonvar/1`)
`Id` is currently a term which is not a free variable.	(`nonvar/1`)
`AbsInt` is currently a term which is not a free variable.	(`nonvar/1`)
`PredKey` is an atom.	(`atm/1`)
`ClKey` is an atom.	(`atm/1`)
`plai_db_id(Id)`	(`plai_db_id/1`)
`AbsInt` is an atom.	(`atm/1`)

complete_key_from_id/3: PREDICATE

No further documentation available for this predicate.

erase_previous_memo_tables_and_parents/4: PREDICATE

Usage: `erase_previous_memo_tables_and_parents(Body,AbsInt,ClKey,Id)`

We use `Body` to erase all the memo_tables and all the pointers in the dependency graph that are not longer valid

– *The following properties should hold at call time:*

`Body` is currently a term which is not a free variable. (`nonvar/1`)

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`ClKey` is currently a term which is not a free variable. (`nonvar/1`)

`Id` is currently a term which is not a free variable. (`nonvar/1`)

erase_last_memo_table/3: PREDICATE

Usage: `erase_last_memo_table(AbsInt,ClKey,Id)`

– *The following properties should hold at call time:*

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`ClKey` is currently a term which is not a free variable. (`nonvar/1`)

`Id` is currently a term which is not a free variable. (`nonvar/1`)

– *The following properties should hold globally:*

All the calls of the form `erase_last_memo_table(AbsInt,ClKey,Id)` do not fail. (`not_fails/1`)

erase_previous_memo_lubs/2: PREDICATE

Usage: `erase_previous_memo_lubs(Body,ClKey)`

This predicate traverses `Body` and removes the existing memo_lubs. When `Body` is finished, we also remove the memo-lub for the end of the clause using `ClKey`.

– *The following properties should hold at call time:*

`Body` is currently a term which is not a free variable. (`nonvar/1`)

`ClKey` is currently a term which is not a free variable. (`nonvar/1`)

erase_previous_parents_info/5: PREDICATE

Usage: `erase_previous_parents_info(Id,Goal,AbsInt,Key,NewN)`

`Id` is the node identifier of the complete that has this `Goal` in its list of parents. If Id is no then nothing needs to be done (it is a builtin)

– *The following properties should hold at call time:*

`Id` is currently a term which is not a free variable. (`nonvar/1`)

`Goal` is currently a term which is not a free variable. (`nonvar/1`)

`AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

`Key` is currently a term which is not a free variable. (`nonvar/1`)

`NewN` is currently a term which is not a free variable. (`nonvar/1`)

init_rev_idx/1: PREDICATE

No further documentation available for this predicate.

clean_rev_idx/1: PREDICATE

No further documentation available for this predicate.

complete_id_key/3: PREDICATE

No further documentation available for this predicate.

memo_table_id_key/3: PREDICATE

No further documentation available for this predicate.

add_invalid_call/6: PREDICATE

Usage: `add_invalid_call(SgKey,AbsInt,LitKey,Id,Sg,Proj)`

- *The following properties should hold at call time:*

  `SgKey` is currently a term which is not a free variable. (`nonvar/1`)

  `AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

  `LitKey` is currently a term which is not a free variable. (`nonvar/1`)

  `Id` is currently a term which is not a free variable. (`nonvar/1`)

  `Sg` is currently a term which is not a free variable. (`nonvar/1`)

  `Proj` is currently a term which is not a free variable. (`nonvar/1`)

store_raw_success/6: PREDICATE

Usage: `store_raw_success(ClKey,AbsInt,Id,Sg,Proj,LPrime)`

- *The following properties should hold at call time:*

  `ClKey` is currently a term which is not a free variable. (`nonvar/1`)

  `AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

  `Id` is currently a term which is not a free variable. (`nonvar/1`)

  `Sg` is currently a term which is not a free variable. (`nonvar/1`)

  `Proj` is currently a term which is not a free variable. (`nonvar/1`)

  `LPrime` is currently a term which is not a free variable. (`nonvar/1`)

get_raw_success/6: PREDICATE

Usage: `get_raw_success(ClKey,AbsInt,Id,Sg,Proj,LPrime)`

- *The following properties should hold at call time:*

  `ClKey` is currently a term which is not a free variable. (`nonvar/1`)

  `AbsInt` is currently a term which is not a free variable. (`nonvar/1`)

  `Id` is currently a term which is not a free variable. (`nonvar/1`)

- *The following properties should hold upon exit:*

  `LPrime` is a list. (`list/1`)

plai_db_id/1: REGTYPE

A regular type, defined as follows:

```
plai_db_id(no).
plai_db_id(X) :-
    int(X).
```

103.3 Documentation on imports

This module has the following direct dependencies:

– *Application modules:*

`transform`.

– *System library modules:*

`datafacts_rt`, `native_props`, `program_keys`.

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `datafacts`, `regtypes`, `isomodes`, `nativeprops`.

104 Improving Analysis Using Trust Assertions

This section describes the use of trust assertions for improving (abstract interpretation based) top-down analyses. Trust assertions are (user given) assertions that do hold of the program. Therefore, analysis can take advantage of them to improve the information inferred.

A trust assertion for a given predicate will be denoted `C ⇒S`, where `C` is a call pattern and `S` a success pattern. Trust assertions for a given predicate are considered closed, that is, the set of call patterns covers all possible calls to the predicate.[1]

In the following, `L ⇒L'` will denote the abstract pattern inferred for a given predicate call by the analysis which is going to be improved with trust assertions. In the absence of the predicate, the success pattern cannot be inferred: however, it can be approximated a priori by the downwards closed information in the call pattern. Thus, if this is the case, `L' = L*`, where `L*` denotes the downwards closure restriction of `L` (i. e., the restriction of `L` to only its downwards closed information).

104.1 Complementation of Trust Assertions

Programmers are lazy writing trust assertions. This is not to blame them: it is just a matter of fact. They try to write as less as possible, and therefore make certain (justified) assumptions when writing assertions. Because of this, trust assertions need to be complemented in order to have as much information as possible available to the analysis.

One thing that programmers usually do is to write things like:

`ground(X) ⇒var(Y)`

where it is obvious that `ground(X)` does also hold on success. In order to deal with this case, trust assertions of the form `C ⇒S` are replaced by `C ⇒S'`, where:

`S' = C* meet S`

Another usual assumption in writing assertions is to say things once and for all. For example, programmers will probable write:

`true ⇒ground(X)`

`var(X) ⇒var(Y)`

where it is obvious that `ground(X)` does also hold on success in the second case. In order to deal with this case, trust assertions of the form `C⇒S'` are replaced by `C⇒S''` where:

`S'' = S' meet (meet S'_i)`

being `C_i⇒S'_i` a trust assertion such that `C_i >= C`.

Now we are in a position to take full advantage of all the information given in trust assertions.

104.2 Using Trust Assertions

Given abstract pattern `L⇒L'`, the success pattern can be improved by using the available trust assertions. The resulting success pattern is denoted `L_trust`. For better precision the most concrete applicable trust assertion should be used. Consider the set:

`St = {S''_i | C_i >= L and not exists j =/= i . C_j =< C_i }`

then:

`L_trust = L' meet (union St)`

However, `St` might be empty. In this case, no trust assertion is guaranteed to hold. But the call pattern inferred might be an over-approximation of the call patterns of some trust assertions.

[1] Reconsider this: It is not true for trust assertions inferred during inter-modular analysis. It may not be convenient, either, when having true/trust and check assertions intermixed.

And one of them must hold (since the trust assertions are supposed to be closed). Thus, in this case `St` is defined as:

```
St = {S''_i | C_i =< L and not exists j =/= i . C_j >= C_i | }
```

Nonetheless, it might also be the case that this set is empty. Then, since the trust assertions are supposed to be closed, this is an error: the inferred call pattern does not cover the possible calls.

But, in order to guarantee this error, all trust assertions should be applicable to the analysis domain (all call patterns should be fully abstractable in that domain). If this is not the case, a default success pattern can be used by defining:[2]

```
St = {S''_i | exists i}
```

[2] In contrast to the above, here `St` must include all trust assertions, whether or not applicable to the domain. This implies that the second `St` above might be incorrect!

105 Debugging the fixpoint operations

This component is in charge of tracing the fixpoint operations to ease debugging.

Make sure that the fixpoint that you want to trace is not importing package notrace (If this is the case, nothing will be shown).

The fixpoint can be traced in several forms: graphical (with daVinci graph viewer) or ascii, using `trace_fixp/1`.

105.1 Example of visualization

Note that daVinci executable has to be accesible in the path for Ciao.

```
?- trace_fixp(view).     % This will open a uDraw(Graph) window

?- module(PathToModule). % load the module to analyze (located in PathToModule)

?- analyze(AbsInt).      % Analyze for abstract domain AbsInt
% The process will appear in the uDraw(Graph) window.

?- trace_fixp(no).       % Stop the tracing
```

The implementation may not support all features of CiaoPP.

E.g. in the actions: `?- analyze(AbsInt), analyze(AbsInt).` the second analysis will fail (only if the tracing is on).

105.2 uDraw(Graph) extended features

A menu is generated in uDraw(Graph) (Edit) that allows to execute the analysis in a syncronous and asynchronous way (see Edit->Mode) to swich options.

If the synchronous option is on, once the analysis has started, the visualization (and the fixpoint) will do one operation each step. The next step will be performed only if command Edit->'One step ahead' is executed.

106 Fixpoint tracer

Stability: [**devel**] Currently the subject of active development and/or research. Functionality may be limited and API and/or functionality may change without warning or deprecation period. Not recommended yet for use in production.

This module traces the operations of fixpoints by explicitely calling `fixpoint_trace/7` during computation.

To deactivate tracing (it can slowdown the analysis), package `ciaopp(plai/notrace)` has to be imported in the used fixpoint.

106.1 Usage and interface

- **Library usage:**
  `:- use_module(ciaopp(plai/trace_fixp)).`
- **Exports:**
  - *Predicates:*
    `fixpoint_trace/7`, `trace_fixp/1`, `memotable_trace/3`, `show_spypoint_op_count/0`, `show_updated_memotable/3`, `trace_init/0`, `trace_end/0`, `trace_reset/0`.
  - *Regular Types:*
    `trace_option/1`.

106.2 Documentation on exports

fixpoint_trace/7: PREDICATE

No further documentation available for this predicate.

trace_fixp/1: PREDICATE

`trace_fixp(X)`

Toggle a trace of the fixpoint computation during analysis. The (X=op_count) option counts steps of fixpoint operations, show certain relevant spy points during analysis (X=trace), and/or display the analysis graph which is being constructed (X=view). The information added up can be seen at end of analysis with `show_fixpoint_op_count.`

Usage 1: `trace_fixp(X)`

Mode for setting the current flag to a single value.

- *The following properties should hold at call time:*
  `trace_option(X)` (`trace_option/1`)
- *The following properties should hold globally:*
  `X` is not further instantiated. (`not_further_inst/2`)

Usage 2: `trace_fixp(X)`

Mode for setting the current flag to several values.

– *The following properties should hold at call time:*
`X` is a list of `trace_options`. (`list/2`)
– *The following properties should hold globally:*
`X` is not further instantiated. (`not_further_inst/2`)

memotable_trace/3: PREDICATE
No further documentation available for this predicate.

show_spypoint_op_count/0: PREDICATE
No further documentation available for this predicate.

show_updated_memotable/3: PREDICATE
No further documentation available for this predicate.

trace_init/0: PREDICATE
No further documentation available for this predicate.

trace_end/0: PREDICATE
No further documentation available for this predicate.

trace_reset/0: PREDICATE
No further documentation available for this predicate.

trace_option/1: REGTYPE
A regular type, defined as follows:

```
trace_option(no).
trace_option(op_count).
trace_option(trace).
trace_option(view).
```

106.3 Documentation on imports

This module has the following direct dependencies:

– *Application modules:*

`analysis_stats`, `view_fixp`, `preprocess_flags`, `fixpo_plai`, `plai_db`.

– *System library modules:*

`datafacts_rt`, `aggregates`, `format`, `write`, `p_unit_db`, `pathnames`, `terms`, `terms_vars`.

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `messages_basic`, `stream_basic`, `io_basic`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `regtypes`, `datafacts`.

107 view_fixp (library)

107.1 Usage and interface

- **Library usage:**
  `:- use_module(ciaopp(plai/view_fixp)).`
- **Exports:**
  - *Predicates:*
    `start_view/0`, `end_view/0`, `clean_fixpoint_graph/0`, `view_fixpoint/7`.

107.2 Documentation on exports

start_view/0: PREDICATE
No further documentation available for this predicate.

end_view/0: PREDICATE
No further documentation available for this predicate.

clean_fixpoint_graph/0: PREDICATE
No further documentation available for this predicate.

view_fixpoint/7: PREDICATE
No further documentation available for this predicate.

107.3 Documentation on imports

This module has the following direct dependencies:

- *System library modules:*
  `datafacts_rt`.
- *Internal (engine) modules:*
  `term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`.
- *Packages:*
  `prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `datafacts`, `ciaopp(ciaopp_options)`.

108 Batch analysis client

Author(s): Isabel Garcia-Contreras.

Stability: [**devel**] Currently the subject of active development and/or research. Functionality may be limited and API and/or functionality may change without warning or deprecation period. Not recommended yet for use in production.

This module contains predicates for managing the batch analysis of sets of modules.

Note: this code is not performing multi-modular analysis. Some of its components can be generalized for other processes (compilation, program transformation) and be integrated into the build system, compiler, analyzer, etc.

108.1 Analysis options

- **no_incremental** : By default, analysis is made only for modules in Paths which were not analyzed before. With this option, analysis will be runned from scratch.
- **timeout(**`T`**)** : `T` is the time limit for the analysis of each module independently.
- **analysis(**`ListAbsInt`**)** : `ListAbsInt` is a list of abstract domains available in ciaopp.
- **workers(**`N`**)** : `N` is the number of threads use to perform the analysis of independent modules. Currently only 1 worker is supported.

Example:

```
? - use_module(ciaopp_batch(ciaopp_batch)).
? - analysis_start(['~/ciao-devel/core/lib/'], [timeout(40), analysis([eterms, gr])])
```

Fast load through caching of assertions from libraries is available in `ciaopp_worker`.
To **create** and **manually update** this cache run command: `update_lib_cache`

Configuring ciaopp flags is not available yet.

108.2 Description of the implementation

108.2.1 Prolog files:

- 'ciaopp_batch.pl': driver for the per-module CiaoPP analysis
- 'ciaopp_master.pl': performs control of ciaopp_workers, i.e., launchs them and kills them.
- 'ciaopp_worker.pl': does the actual analysis.
- 'ciaopp_batch_aux.pl': file for auxiliary predicates.
- 'statistics_collecter.pl': collects statistics of the analyzed files (time and memory).

108.2.2 Other directories:

- 'Attic/': placeholder for not used files that may be useful at some point

108.3 Data files

The status of the analysis is stored in the 'data/' directory:

- 'data/task_status.pl': status of the modules (analyzed, errors, etc)
- 'last_analyzed_file.pl': last analyzed predicate
- 'analysis.log': date and time when each module started being analyzed

108.4 Usage and interface

- **Library usage:**
  `:- use_module(ciaopp_batch(ciaopp_batch)).`
- **Exports:**
  - *Predicates:*
    `analysis_start/2`.

108.5 Documentation on exports

analysis_start/2: PREDICATE

Usage: `analysis_start(Paths,Opts)`

Analyzes modules in some `Paths` and dumps their analysis information to disk, given some `Opts`.

- *The following properties should hold at call time:*

  `Paths` is a list. (`list/1`)

  `Opts` is a list. (`list/1`)

update_tasks_analysis_status/0: (UNDOC_REEXPORT)

Imported from `db_analysis` (see the corresponding documentation for details).

update_tasks_analysis_status/0: (UNDOC_REEXPORT)

Imported from `db_analysis` (see the corresponding documentation for details).

108.6 Documentation on internals

analysis_opt/1: PROPERTY

Usage: `analysis_opt(Opt)`

Option of ciaopp batch (not ciaopp flags)

108.7 Documentation on imports

This module has the following direct dependencies:

– *Application modules:*

`db_analysis`.

– *System library modules:*

`datafacts_rt`, `process`, `lists`, `system`, `config_common`.

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`, `io_basic`, `stream_basic`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `isomodes`, `regtypes`, `datafacts`.

109 ciaopp_master (application)

This programs analyzes modules read in the form of terms from the standard input.

This program should not be used directly, it should be used through `ciaopp_batch`.

Workflow: This program uses workers to launch ciaopp analysis. It controls the analysis time of each worker with a timeout.

110 Worker for CiaoPP batch processing

Author(s): Isabel Garcia-Contreras.

This module implements an execution mode for CiaoPP as a worker for `ciaopp-batch` (using `ciaopp_batch(db_analysis)` for communication).

Note that this tool has to be used with an external timeout because the analysis of some modules could require too much memory or time to be performed. It must be used with ⟨undefined⟩ [Analysis management predicates], page ⟨undefined⟩.

110.1 Generated data

- Analysis information: For each module abstract analysis information is stored in a `.dump` file generated in the same location. This information and can be restored later.
- Run-time statistics: Statistics of time and memory used are stored in as a term in a `.err` file in the same location as the original module. This file contains also the output of the analyzer.
- Status of the analysis: For each module, information of load and analysis success is stored in `data/task_status.pl`.

  This allows also the script to be incremental, i.e., it does not repeat ciaopp analysis for a module if it has already been done.

  If the the user wants the tool to redo an analysis for all files, `task_status.pl` has to be removed before starting.
- `last_analyzed_file.pl`: This file contains the file that is being analyzed.

110.2 Usage and interface

- **Library usage:**
  `:- use_module(ciaopp_batch(ciaopp_worker)).`
- **Exports:**
  - *Predicates:*
    `start_worker/1`, `logged_once_port_reify/4`.

110.3 Documentation on exports

start_worker/1: PREDICATE

No further documentation available for this predicate.

logged_once_port_reify/4: PREDICATE

Usage: `logged_once_port_reify(Goal,Port,OutString,ErrString)`

Executes `Goal`, `Port` is the state when the predicate finishes (true, fail). Its stdout and stderr are stored in `OutString` and `ErrString` respectively.

- *The following properties should hold upon exit:*
  `OutString` is a string (a list of character codes). (`string/1`)
  `ErrString` is a string (a list of character codes). (`string/1`)

Meta-predicate with arguments: `logged_once_port_reify(goal,?,?,?)`.

110.4 Documentation on internals

task_status/1: REGTYPE

Usage: `task_status(Status)`

Type of analysis status.

110.5 Documentation on imports

This module has the following direct dependencies:

– *Application modules:*

`frontend_driver`, `analyze_driver`, `preprocess_flags`, `p_dump`, `ciaopp_batch_aux`, `tasks_db`, `db_analysis`.

– *System library modules:*

`datafacts_rt`, `lists`, `system`, `system_extra`, `port_reify`, `io_alias_redirection`, `stream_utils`, `read`.

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`, `stream_basic`, `io_basic`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `modes`, `regtypes`, `datafacts`.

111 Auxiliary predicates

Auxiliary predicates for ciaopp batch

111.1 Usage and interface

- **Library usage:**
  `:- use_module(ciaopp_batch(ciaopp_batch_aux)).`
- **Exports:**
  - *Predicates:*
    `dump_file/4`, `string_contained/2`, `get_mod_name_from_file/2`, `newer/2`, `make_dir_nofail/1`.

111.2 Documentation on exports

dump_file/4: PREDICATE

Usage: `dump_file(FilePath,Module,AbsInt,DumpFile)`

Given a `FilePath` and `Module` name, generates its associated `DumpFile`

- *The following properties should hold at call time:*
  `FilePath` is an atom. (`atm/1`)
  `Module` is an atom. (`atm/1`)
  `AbsInt` is an atom. (`atm/1`)
  `DumpFile` is a free variable. (`var/1`)

string_contained/2: PREDICATE

Usage: `string_contained(L1,L2)`

`L1` is a sublist of `L2`.

- *The following properties should hold at call time:*
  `L1` is a string (a list of character codes). (`string/1`)
  `L2` is a string (a list of character codes). (`string/1`)

get_mod_name_from_file/2: PREDICATE

Usage: `get_mod_name_from_file(FilePath,ModName)`

`ModName` is the name of the module located in `FilePath`.

newer/2: PREDICATE

Usage: `newer(FileA,FileB)`

`FileA` was modified later than `FileB`.

- *The following properties should hold at call time:*
  `FileA` is currently instantiated to an atom. (`atom/1`)
  `FileB` is currently instantiated to an atom. (`atom/1`)

make_dir_nofail/1: PREDICATE

Usage: `make_dir_nofail(X)`

Creates `X` if it does not exist already

– *The following properties should hold at call time:*

`X` is an atom. (`atm/1`)

111.3 Documentation on imports

This module has the following direct dependencies:

– *System library modules:*

`pathnames`, `system`, `lists`.

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`.

112 Database for ciaopp_batch process

Author(s): Isabel Garcia-Contreras.

This module manages the analysis database for ciaopp_batch.

112.1 Usage and interface

- **Library usage:**
  `:- use_module(ciaopp_batch(db_analysis)).`
- **Exports:**
  - *Predicates:*
    `add_task_status/5`, `task_status/5`, `update_task_status/0`, `last_file_log/2`, `init_analysis_db/0`, `init_tmp_db/1`, `clean_db/0`, `clean_tmp_db/0`, `set_current_task/2`, `current_task_proc/2`, `set_last_error/3`, `update_tasks_analysis_status/0`, `report_mod_info/3`, `db_data_dir/1`.
  - *Multifiles:*
    `$is_persistent/2`, `persistent_dir/2`, `persistent_dir/4`.

112.2 Documentation on exports

add_task_status/5: PREDICATE

Usage: `add_task_status(ModName,ModPath,Action,Flags,Status)`

Adds ciaopp action status for `ModName` located in `ModPath`

- *The following properties should hold at call time:*

`ModName` is an atom. (`atm/1`)
`ModPath` is an atom. (`atm/1`)
`Action` is an atom. (`atm/1`)
`Flags` is any term. (`term/1`)
`Status` is an atom. (`atm/1`)

task_status/5: PREDICATE

Usage: `task_status(ModName,ModPath,Action,Flags,Status)`

`Status` is the information of how `ModName` located in `ModPath` was analyzed

- *Call and exit should be compatible with:*

`ModName` is an atom. (`atm/1`)
`ModPath` is an atom. (`atm/1`)
`Action` is an atom. (`atm/1`)
`Flags` is any term. (`term/1`)
`Status` is an atom. (`atm/1`)

update_task_status/0: PREDICATE

Usage:

Updates the data with the last analysis information

last_file_log/2: PREDICATE

Usage: `last_file_log(ID,F)`

`F` is the associated file log to `ID`

- *The following properties should hold at call time:*

  `ID` is an atom. (`atm/1`)

- *The following properties should hold upon exit:*

  `F` is an atom. (`atm/1`)

init_analysis_db/0: PREDICATE

Usage:

Initializes analysis database

init_tmp_db/1: PREDICATE

Usage: `init_tmp_db(ID)`

Initializes a temporal DB for `ID`.

- *The following properties should hold at call time:*

  `ID` is an atom. (`atm/1`)

clean_db/0: PREDICATE

Usage:

Clears all analysis data.

clean_tmp_db/0: PREDICATE

Usage:

Removes all temporal databases.

set_current_task/2: PREDICATE

Usage: `set_current_task(ID,Task)`

Writes in a file that `Module` is currently being analyzed.

current_task_proc/2: PREDICATE

Usage: `current_task_proc(ID,Task)`

`Module` is the module being analyzed by `batch_analyze` currenlty

- *The following properties should hold at call time:*

  `Task` is a free variable. (`var/1`)

set_last_error/3: PREDICATE

Usage: `set_last_error(ModName,FilePath,AbsInt)`

Appends to the error file of `FilePath` that the analysis for domain `AbsInt` of the last module (`Module`) had a timeout.

update_tasks_analysis_status/0: PREDICATE

Usage:

Updates the task_status db to remove modules which are not updated, i.e., their `.dump` file is older than their `.pl` file.

For modules which could not be analyze, no information is updated

report_mod_info/3: PREDICATE

Usage: `report_mod_info(FilePath,ModName,LDiag)`

Stores in a file with extension `.err Info` about `ModName`

db_data_dir/1: PREDICATE

Usage: `db_data_dir(F)`

`F` is the location of data in this bundle

112.3 Documentation on multifiles

$is_persistent/2: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

The predicate is of type *data*.

persistent_dir/2: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

The predicate is of type *data*.

persistent_dir/4: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

The predicate is of type *data*.

112.4 Documentation on imports

This module has the following direct dependencies:

– *Application modules:*

`ciaopp_batch_aux`.

– *System library modules:*

`datafacts_rt`, `persdb_rt`, `system`, `terms_io`, `system_extra`, `read`, `pathnames`, `write`, `bundle_paths`, `datadir`, `format`.

– *Internal (engine) modules:*

`term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`, `hiord_rt`, `stream_basic`.

– *Packages:*

`prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `isomodes`, `persdb`, `datafacts`, `persdb/persdb_decl`.

113 tasks_db (library)

This handles the data base of modules to be analyzed. Currently it is implemented with persistent predicates

113.1 Usage and interface

- **Library usage:**
  `:- use_module(ciaopp_batch(tasks_db)).`
- **Exports:**
  - *Predicates:*
    `add_task/1`, `add_tasks/1`, `pop_task/4`, `analysis_task/4`, `clean_db/0`, `init_tasks_db/0`.
  - *Multifiles:*
    `$is_persistent/2`, `persistent_dir/2`, `persistent_dir/4`.

113.2 Documentation on exports

add_task/1: PREDICATE

Usage: `add_task(Mod)`

Add a task to analyze with abtract domain `AbsInt` and CiaoPP configuration `Flags`

add_tasks/1: PREDICATE

Usage: `add_tasks(Tasks)`

The same as `add_task/3` but for a list of tasks (for efficiency)

- *The following properties should hold at call time:*
  `Tasks` is a list. (`list/1`)

pop_task/4: PREDICATE

Usage: `pop_task(File,Mod,AbsInt,Flags)`

Remove a task to analyze

analysis_task/4: PREDICATE

Usage: `analysis_task(File,Mod,AbsInt,Flags)`

Checks a task to analyze, this predicate does not modify the DB

clean_db/0: PREDICATE

Usage 1:

Empties the database.

Usage 2:

Initializes the database.

init_tasks_db/0: PREDICATE

No further documentation available for this predicate.

113.3 Documentation on multifiles

$is_persistent/2: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

The predicate is of type *data*.

persistent_dir/2: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

The predicate is of type *data*.

persistent_dir/4: PREDICATE

No further documentation available for this predicate. The predicate is *multifile*.

The predicate is of type *data*.

113.4 Documentation on imports

This module has the following direct dependencies:

- *Application modules:*

  `db_analysis`.
- *System library modules:*

  `datafacts_rt`, `persdb_rt`, `format`, `bundle_paths`.
- *Internal (engine) modules:*

  `term_basic`, `arithmetic`, `atomic_basic`, `basiccontrol`, `exceptions`, `term_compare`, `term_typing`, `debugger_support`, `basic_props`.
- *Packages:*

  `prelude`, `initial`, `condcomp`, `assertions`, `assertions/assertions_basic`, `persdb`, `datafacts`, `persdb/persdb_decl`.

References

[**APG06**] E. Albert, G. Puebla, and J. Gallagher.
Non-Leftmost Unfolding in Partial Evaluation of Logic Programs with Impure Predicates.
In *15th International Symposium on Logic-based Program Synthesis and Transformation (LOPSTR'05)*, number 3901 in LNCS, pages 115–132. Springer-Verlag, April 2006.

[**BCC04**] F. Bueno, D. Cabeza, M. Carro, M. V. Hermenegildo, P. López-García, and G. Puebla-(Eds.).
The Ciao System. Reference Manual (v1.10).
The Ciao System Documentation Series–TR CLIP3/97.1.10(04), School of Computer Science, Technical University of Madrid (UPM), Facultad de Informática, 28660 Boadilla del Monte, Madrid, Spain, August 2004.
System and on-line version of the manual available at `http://ciao-lang.org`.

[**BCHP96**] F. Bueno, D. Cabeza, M. V. Hermenegildo, and G. Puebla.
Global Analysis of Standard Prolog Programs.
In *European Symposium on Programming*, number 1058 in LNCS, pages 108–124, Sweden, April 1996. Springer-Verlag.

[**BGH94**] F. Bueno, M. García de la Banda, and M. V. Hermenegildo.
The PLAI Abstract Interpretation System.
Technical Report CLIP2/94.0, Computer Science Dept., Technical U. of Madrid (UPM), Facultad Informatica UPM, 28660-Boadilla del Monte, Madrid-Spain, February 1994.

[**BLGH04**] F. Bueno, P. López-García, and M. V. Hermenegildo.
Multivariant Non-Failure Analysis via Standard Abstract Interpretation.
In *7th International Symposium on Functional and Logic Programming (FLOPS 2004)*, number 2998 in LNCS, pages 100–116, Heidelberg, Germany, April 2004. Springer-Verlag.

[**CH94**] D. Cabeza and M. Hermenegildo.
Extracting Non-strict Independent And-parallelism Using Sharing and Freeness Information.
In *1994 International Static Analysis Symposium*, number 864 in LNCS, pages 297–313, Namur, Belgium, September 1994. Springer-Verlag.

[**CMB93**] M. Codish, A. Mulkers, M. Bruynooghe, M. García de la Banda, and M. Hermenegildo.
Improving Abstract Interpretations by Combining Domains.
In *Proc. ACM SIGPLAN Symposium on Partial Evaluation and Semantics Based Program Manipulation*, pages 194–206. ACM, June 1993.

[**COS96**] The COSYTEC Team.
CHIP System Documentation, April 1996.

[**DEDC96**] P. Deransart, A. Ed-Dbali, and L. Cervoni.
Prolog: The Standard.
Springer-Verlag, 1996.

[**DL93**] S. K. Debray and N. W. Lin.
Cost Analysis of Logic Programs.
ACM Transactions on Programming Languages and Systems, 15(5):826–875, November 1993.

[**DLGH97**] S.K. Debray, P. López-García, and M. V. Hermenegildo.
Non-Failure Analysis for Logic Programs.
In *1997 International Conference on Logic Programming*, pages 48–62, Cambridge, MA, June 1997. MIT Press, Cambridge, MA.

[**DLGHL97**] S. K. Debray, P. López-García, M. V. Hermenegildo, and N.-W. Lin.
Lower Bound Cost Estimation for Logic Programs.
In *1997 International Logic Programming Symposium*, pages 291–305. MIT Press, Cambridge, MA, October 1997.

[**Dum94**] Veroniek Dumortier.
Freeness and Related Analyses of Constraint Logic Programs Using Abstract Interpretation.
PhD thesis, K.U.Leuven, Dept. of Computer Science, October 1994.

[**DZ92**] P.W. Dart and J. Zobel.
A Regular Type Language for Logic Programs.
In *Types in Logic Programming*, pages 157–187. MIT Press, 1992.

[**GdW94**] J.P. Gallagher and D.A. de Waal.
Fast and Precise Regular Approximations of Logic Programs.
In Pascal Van Hentenryck, editor, *Proc. of the 11th International Conference on Logic Programming (ICLP'94)*, pages 599–613. MIT Press, 1994.

[**GHM00**] M. García de la Banda, M. V. Hermenegildo, and K. Marriott.
Independence in CLP Languages.
ACM Transactions on Programming Languages and Systems, 22(2):269–339, March 2000.

[**HBC12**] M. V. Hermenegildo, F. Bueno, M. Carro, P. López, E. Mera, J.F. Morales, and G. Puebla.
An Overview of Ciao and its Design Philosophy.
Theory and Practice of Logic Programming, 12(1–2):219–252, January 2012.
http://arxiv.org/abs/1102.5497.

[**Her99**] M. V. Hermenegildo.
A Documentation Generator for Logic Programming Systems.
Technical Report CLIP10/99.0, Facultad de Informática, UPM, September 1999.

[**HPB99**] M. V. Hermenegildo, G. Puebla, and F. Bueno.
Using Global Analysis, Partial Specifications, and an Extensible Assertion Language for Program Validation and Debugging.
In K. R. Apt, V. Marek, M. Truszczynski, and D. S. Warren, editors, *The Logic Programming Paradigm: a 25–Year Perspective*, pages 161–192. Springer-Verlag, July 1999.

[**HPBLG05**] M. V. Hermenegildo, G. Puebla, F. Bueno, and P. Lopez-Garcia.
Integrated Program Debugging, Verification, and Optimization Using Abstract Interpretation (and The Ciao System Preprocessor).
Science of Computer Programming, 58(1–2):115–140, October 2005.

[**HPMS00**] M. V. Hermenegildo, G. Puebla, K. Marriott, and P. Stuckey.
Incremental Analysis of Constraint Logic Programs.
ACM Transactions on Programming Languages and Systems, 22(2):187–223, March 2000.

[**HR95**] M. Hermenegildo and F. Rossi.
Strict and Non-Strict Independent And-Parallelism in Logic Programs: Correctness,

Efficiency, and Compile-Time Conditions.
Journal of Logic Programming, 22(1):1–45, 1995.

[**JB92**] G. Janssens and M. Bruynooghe.
Deriving Descriptions of Possible Values of Program Variables by means of Abstract Interpretation.
Journal of Logic Programming, 13(2 and 3):205–258, July 1992.

[**JL88**] D. Jacobs and A. Langen.
Compilation of Logic Programs for Restricted And-Parallelism.
In *European Symposium on Programming*, pages 284–297, 1988.

[**Knu84**] D. Knuth.
Literate programming.
Computer Journal, 27:97–111, 1984.

[**Leu98**] M. Leuschel.
On the Power of Homeomorphic Embedding for Online Termination.
In Giorgio Levi, editor, *Proceedings of SAS'98*, volume 1503 of *LNCS*, pages 230–245, Pisa, Italy, September 1998. Springer-Verlag.

[**LGBH05**] P. López-García, F. Bueno, and M. V. Hermenegildo.
Determinacy Analysis for Logic Programs Using Mode and Type Information.
In *Proceedings of the 14th International Symposium on Logic-based Program Synthesis and Transformation (LOPSTR'04)*, number 3573 in LNCS, pages 19–35. Springer-Verlag, August 2005.

[**LGBH10**] P. López-García, F. Bueno, and M. V. Hermenegildo.
Automatic Inference of Determinacy and Mutual Exclusion for Logic Programs Using Mode and Type Information.
New Generation Computing, 28(2):117–206, 2010.

[**LGHD96**] P. López-García, M. V. Hermenegildo, and S. K. Debray.
A Methodology for Granularity Based Control of Parallelism in Logic Programs.
Journal of Symbolic Computation, Special Issue on Parallel Symbolic Computation, 21(4–6):715–734, 1996.

[**MBdlBH99**] K. Muthukumar, F. Bueno, M. García de la Banda, and M. Hermenegildo.
Automatic Compile-time Parallelization of Logic Programs for Restricted, Goal-level, Independent And-parallelism.
Journal of Logic Programming, 38(2):165–218, February 1999.

[**MH89a**] K. Muthukumar and M. Hermenegildo.
Determination of Variable Dependence Information at Compile-Time Through Abstract Interpretation.
Technical Report ACA-ST-232-89, Microelectronics and Computer Technology Corporation (MCC), Austin, TX 78759, March 1989.

[**MH89b**] K. Muthukumar and M. Hermenegildo.
Determination of Variable Dependence Information at Compile-Time Through Abstract Interpretation.
In *1989 North American Conference on Logic Programming*, pages 166–189. MIT Press, October 1989.

[**MH91**] K. Muthukumar and M. Hermenegildo.
Combined Determination of Sharing and Freeness of Program Variables Through Abstract Interpretation.
In *International Conference on Logic Programming (ICLP 1991)*, pages 49–63. MIT Press, June 1991.

[**MH92**] K. Muthukumar and M. Hermenegildo.
Compile-time Derivation of Variable Dependency Using Abstract Interpretation.
Journal of Logic Programming, 13(2/3):315–347, July 1992.

[**MS94**] K. Marriott and P. Stuckey.
Approximating Interaction Between Linear Arithmetic Constraints.
In *1994 International Symposium on Logic Programming*, pages 571–585. MIT Press, 1994.

[**Mye86**] Eugene W Myers.
An O(ND) difference algorithm and its variations.
Algorithmica, 1(1-4):251–266, 1986.

[**PAH04**] G. Puebla, E. Albert, and M. V. Hermenegildo.
Abstract Interpretation with Specialized Definitions.
Technical Report CLIP12/2004.0, Technical University of Madrid, School of Computer Science, UPM, September 2004.

[**PBH00**] G. Puebla, F. Bueno, and M. V. Hermenegildo.
An Assertion Language for Constraint Logic Programs.
In P. Deransart, M. V. Hermenegildo, and J. Maluszynski, editors, *Analysis and Visualization Tools for Constraint Programming*, number 1870 in LNCS, pages 23–61. Springer-Verlag, September 2000.

[**PCH03**] G. Puebla, J. Correas, and M. V. Hermenegildo.
The design of a generic framework for context-sensitive analysis of modular programs.
Technical Report CLIP7/2003.0, Technical University of Madrid, School of Computer Science, UPM, November 2003.

[**PH96**] G. Puebla and M. V. Hermenegildo.
Optimized Algorithms for the Incremental Analysis of Logic Programs.
In *International Static Analysis Symposium (SAS 1996)*, number 1145 in Lecture Notes in Computer Science, pages 270–284. Springer-Verlag, September 1996.

[**PRO**] The PROLOG IV Team.
PROLOG IV Manual.

[**SG94**] H. Saglam and J. Gallagher.
Approximating Logic Programs Using Types and Regular Descriptions.
Technical Report CSTR-94-19, Department of Computer Science, University of Bristol, Bristol BS8 1TR, 1994.

[**Son86**] H. Søndergaard.
An Application of Abstract Interpretation of Logic Programs: Occur Check Reduction.
In *European Symposium on Programming, LNCS 123*, pages 327–338. Springer-Verlag, 1986.

[**VB02**] C. Vaucheret and F. Bueno.
More Precise yet Efficient Type Inference for Logic Programs.
In *9th International Static Analysis Symposium (SAS'02)*, volume 2477 of *Lecture Notes in Computer Science*, pages 102–116. Springer-Verlag, September 2002.

[**VHCL95**] P. Van Hentenryck, A. Cortesi, and B. Le Charlier.
Type analysis of prolog using type graphs.
Journal of Logic Programming, 22(3):179–209, 1995.

Library/Module Index

A

adding_new_domain 419
aeq 33
analyze_driver 453
apply_assertions 411
assertions 335
assertions_props 345
auto_interface 11

B

basic_props 357

C

ciaopp 17
ciaopp_batch 583
ciaopp_batch_aux 591
ciaopp_worker 589

D

db_analysis 593
Debug_plai 489
debugging_in_ciaopp 325
def 39
deftypes 47
depthk 53
detplai 125
diff 509
domains 421

E

eterms 59
etermsvar 75

F

fixpo_dd 513
fixpo_plai 561
fr_top 95
frdef 87
frontend_driver 443

G

gr 103

I

incanal 491
incanal_db 501
incanal_deletion 499
incanal_driver 495
incanal_persistent_db 505
infer 553
intermod 461
intermod_db 465
intermod_entry 479
intermod_punit 473
intermod_schedule 469
intermod_success 481

L

lsign 109
lsigndiff 117

N

native 537
native_props_cardinality 389
native_props_cost 399
native_props_exceptions 391
native_props_nfdet 383
native_props_polyhedral 397
native_props_shfrg 379
native_props_sideff 395
nfplai 133
nonrel_intervals 143

P

p_unit 527
pd 157
pdb 163
plai 559
plai_db 565
Plai0 557
polyhedra 169
preprocess_flags 483
program_keys 541
ptypes 175
Punit0 523

R

raw_printer 451
regtypes 351
rtchecks 407

S

sharefree 181
sharefree_amgu 191
sharefree_clique 197
sharefree_clique_def 203
sharefree_non_var 209
shareson 215
sharing 221
sharing_amgu 229
sharing_clique 235
sharing_clique_1 243
sharing_clique_def 249
shfret 255
shfrlin_amgu 263
shfrson 269
sondergaard 275
svterms 283

T

tarjan_inc 507
tasks_db 597
termsd 291
top_path_sharing 305
tr_syntax 549
trace_fixp 577
transform_driver 459
Trust 573

V

view_fixp 581

Predicate Index

$

$change_list/3 514
$depend_list/3 562
$is_persistent/2 ..... 487, 595, 598

A

abs_eval_arith/3 69
abs_eval_arithcomp/4 69
abs_normalize/8 415
abs_sort/2 ..... 40, 182, 198, 222, 236, 275
abs_sort/3 428
abs_subset/3 430
abstract_instance/5 435
absub_eliminate_equivalent/3 435
absub_fixpoint_covered/3 435
acheck/0 ..... 23, 455
acheck/1 455
acheck/2 455
acheck_summary/1 454
acheck_summary/2 454
add_all_clauses/1 502
add_assertion/1 529
add_assertion_source_db/1 502
add_assertions/1 529
add_change/5 517
add_change_scc/6 518
add_changed_registry/4 503
add_comment/1 532
add_commented_assertion/1 533
add_commented_assertions/1 533
add_defined_pred/2 530
add_directive/1 529
add_entries_to_registry/1 480
add_environment_vars/3 186
add_invalid_call/6 571
add_main_module/1 465
add_mod_typedb/2 468
add_naive_pending_modules/1 471
add_new_preds/1 502
add_output_operator/3 532
add_output_package/1 531
add_parent_complete/5 568
add_registry/2 467
add_src_changed/1 466
add_success_asr/6 414
add_task/1 597
add_task_status/5 593
add_tasks/1 597
again/0 13
aidom.abs_sort/3 ..... 34, 42, 48, 54, 72, 83, 90, 98, 104, 113, 120, 129, 138, 144, 158, 164, 171, 176, 187, 194, 200, 204, 210, 216, 225, 231, 240, 244, 250, 259, 264, 270, 279, 287, 302, 307, 437
aidom.abs_subset/3 ... 35, 43, 49, 55, 72, 84, 91, 99, 105, 113, 121, 130, 139, 145, 159, 165, 171, 177, 188, 194, 200, 205, 211, 217, 225, 231, 240, 245, 251, 259, 265, 271, 279, 288, 302, 307, 437
aidom.amgu/5 ..... 33, 41, 47, 53, 70, 82, 89, 97, 103, 111, 119, 128, 137, 143, 157, 163, 170, 175, 186, 192, 199, 203, 209, 215, 224, 230, 239, 243, 249, 257, 263, 269, 277, 286, 301, 305, 436
aidom.asub_to_native/6 .. 36, 44, 50, 56, 73, 85, 92, 100, 106, 114, 122, 131, 140, 146, 160, 166, 172, 178, 189, 195, 201, 206, 212, 218, 226, 232, 241, 246, 252, 260, 266, 272, 280, 289, 303, 308, 438
aidom.augment_asub/4 .... 33, 41, 47, 53, 70, 82, 89, 97, 103, 112, 119, 128, 137, 143, 157, 163, 170, 175, 186, 192, 199, 203, 209, 215, 224, 230, 239, 243, 249, 257, 263, 269, 278, 286, 301, 306, 436
aidom.augment_two_asub/4 ... 33, 41, 47, 53, 70, 82, 89, 97, 103, 112, 119, 128, 137, 143, 157, 163, 170, 175, 186, 192, 199, 203, 209, 215, 224, 230, 239, 243, 249, 257, 263, 269, 278, 286, 301, 306, 436
aidom.body_succ_builtin/9 .. 35, 43, 49, 55, 72, 84, 91, 99, 105, 114, 121, 130, 139, 145, 159, 165, 172, 177, 188, 194, 201, 205, 211, 217, 226, 232, 241, 245, 251, 259, 265, 271, 280, 288, 303, 307, 438
aidom.call_to_entry/10 .. 33, 41, 47, 53, 71, 82, 89, 97, 103, 112, 119, 128, 137, 143, 157, 163, 170, 175, 186, 193, 199, 203, 209, 215, 224, 230, 239, 243, 249, 258, 263, 269, 278, 286, 301, 306, 436
aidom.call_to_success_builtin/7 .. 35, 43, 49, 55, 73, 84, 91, 99, 105, 114, 121, 130, 139, 145, 159, 165, 172, 177, 188, 195, 201, 205, 211, 217, 226, 232, 241, 245, 251, 260, 265, 271, 280, 288, 303, 308, 438
aidom.call_to_success_fact/10 .... 35, 43, 49, 55, 72, 84, 91, 99, 105, 113, 121, 130, 139, 145, 159, 165, 172, 177, 188, 194, 201, 205, 211, 217, 226, 232, 241, 245, 251, 259, 265, 271, 279, 288, 303, 307, 438
aidom.collect_auxinfo_asub/4 .. 36, 44, 50, 56, 74, 85, 92, 100, 106, 115, 122, 131, 140, 146, 160, 166, 173, 178, 189, 196, 202, 206, 212, 218, 227, 233, 242, 246, 252, 261, 266, 272, 281, 289, 304, 309, 439
aidom.combined_special_builtin0/3.... 35, 43, 49, 55, 72, 84, 91, 99, 105, 113, 121, 130, 139, 145, 159, 165, 172, 177, 188, 194, 201, 205, 211, 217,

226, 232, 241, 245, 251, 259, 265, 271, 279, 288, 303, 307, 438

aidom.compute_clauses_glb/4 ... 34, 42, 48, 54, 71, 83, 90, 98, 104, 112, 120, 129, 138, 144, 158, 164, 171, 176, 187, 193, 200, 204, 210, 216, 225, 231, 240, 244, 250, 258, 264, 270, 278, 287, 302, 306, 437

aidom.compute_clauses_lub/4 ... 34, 42, 48, 54, 71, 83, 90, 98, 104, 112, 120, 129, 138, 144, 158, 164, 171, 176, 187, 193, 200, 204, 210, 216, 225, 231, 240, 244, 250, 258, 264, 270, 278, 287, 302, 306, 437

aidom.compute_lub/3 .. 34, 42, 48, 54, 71, 83, 90, 98, 104, 112, 120, 129, 138, 144, 158, 164, 170, 176, 187, 193, 199, 204, 210, 216, 224, 230, 239, 244, 250, 258, 264, 270, 278, 287, 301, 306, 437

aidom.concrete/4 .... 36, 44, 50, 56, 73, 85, 92, 100, 106, 114, 122, 131, 140, 146, 160, 166, 172, 178, 189, 195, 201, 206, 212, 218, 226, 232, 241, 246, 252, 260, 266, 272, 280, 289, 303, 308, 438

aidom.contains_parameters/2 ... 36, 44, 50, 56, 74, 85, 92, 101, 107, 115, 122, 132, 140, 147, 160, 166, 173, 178, 189, 196, 202, 206, 212, 218, 227, 233, 242, 246, 252, 261, 266, 272, 281, 289, 304, 309, 439

aidom.dom_statistics/2 .. 36, 44, 50, 56, 74, 85, 92, 101, 107, 115, 122, 132, 140, 147, 160, 166, 173, 178, 189, 196, 202, 206, 212, 218, 227, 233, 242, 246, 252, 261, 266, 272, 281, 289, 304, 309, 439

aidom.eliminate_equivalent/3 .. 35, 43, 49, 55, 72, 84, 91, 99, 105, 113, 121, 130, 139, 145, 159, 165, 171, 177, 188, 194, 200, 205, 211, 217, 225, 231, 240, 245, 251, 259, 265, 271, 279, 288, 302, 307, 437

aidom.empty_entry/4 ..... 36, 44, 50, 56, 73, 85, 92, 100, 106, 114, 122, 131, 140, 146, 160, 166, 173, 178, 189, 195, 202, 206, 212, 218, 227, 233, 242, 246, 252, 260, 266, 272, 280, 289, 304, 308, 439

aidom.exit_to_prime/8 ... 33, 41, 47, 53, 71, 82, 89, 97, 104, 112, 119, 128, 137, 143, 157, 163, 170, 175, 186, 193, 199, 203, 209, 215, 224, 230, 239, 243, 249, 258, 263, 269, 278, 286, 301, 306, 436

aidom.extend/6 ... 34, 42, 48, 54, 72, 83, 90, 99, 105, 113, 120, 130, 138, 145, 158, 164, 171, 176, 187, 194, 200, 204, 210, 216, 225, 231, 240, 244, 250, 259, 264, 270, 279, 287, 302, 307, 437

aidom.fixpoint_covered/3 ... 34, 42, 48, 54, 71, 83, 90, 98, 104, 113, 120, 129, 138, 144, 158, 164, 171, 176, 187, 193, 200, 204, 210, 216, 225, 231, 240, 244, 250, 258, 264, 270, 279, 287, 302, 306, 437

aidom.fixpoint_covered_gfp/3 .. 34, 42, 48, 54, 71, 83, 90, 98, 104, 113, 120, 129, 138, 144, 158, 164, 171, 176, 187, 193, 200, 204, 210, 216, 225, 231, 240, 244, 250, 258, 264, 270, 279, 287, 302, 307, 437

aidom.glb/4 .. 34, 42, 49, 54, 72, 84, 91, 99, 105, 113, 120, 130, 139, 145, 159, 165, 171, 177, 188, 194, 200, 205, 211, 216, 225, 231, 240, 245, 251, 259, 265, 270, 279, 287, 302, 307, 437

aidom.identical_abstract/3 .... 34, 42, 48, 54, 72, 83, 90, 98, 104, 113, 120, 129, 138, 144, 158, 164, 171, 176, 187, 194, 200, 204, 210, 216, 225, 231, 240, 244, 250, 259, 264, 270, 279, 287, 302, 307, 437

aidom.init_abstract_domain/2 .. 33, 41, 47, 53, 70, 82, 89, 97, 103, 111, 119, 128, 137, 143, 157, 163, 170, 175, 186, 192, 199, 203, 209, 215, 224, 230, 239, 243, 249, 257, 263, 269, 277, 286, 301, 305, 436

aidom.input_interface/5 .... 35, 43, 49, 55, 73, 84, 91, 100, 106, 114, 121, 131, 139, 146, 159, 165, 172, 177, 188, 195, 201, 205, 211, 217, 226, 232, 241, 245, 251, 260, 265, 271, 280, 288, 303, 308, 438

aidom.input_user_interface/6 .. 35, 43, 50, 55, 73, 85, 92, 100, 106, 114, 121, 131, 140, 146, 160, 166, 172, 178, 189, 195, 201, 206, 212, 217, 226, 232, 241, 246, 252, 260, 266, 271, 280, 288, 303, 308, 438

aidom.less_or_equal/3 ... 34, 42, 48, 54, 72, 83, 90, 99, 105, 113, 120, 130, 138, 145, 158, 164, 171, 176, 187, 194, 200, 204, 210, 216, 225, 231, 240, 244, 250, 259, 264, 270, 279, 287, 302, 307, 437

aidom.multi_part_conc/4 .... 36, 44, 50, 56, 73, 85, 92, 100, 106, 115, 122, 131, 140, 146, 160, 166, 173, 178, 189, 195, 202, 206, 212, 218, 227, 233, 242, 246, 252, 260, 266, 272, 281, 289, 304, 309, 439

aidom.needs/2 .... 34, 41, 48, 54, 71, 83, 90, 98, 104, 112, 119, 129, 138, 144, 158, 164, 170, 176, 187, 193, 199, 204, 210, 216, 224, 230, 239, 244, 250, 258, 264, 270, 278, 286, 301, 306, 436

aidom.obtain_info/5 ..... 35, 43, 49, 55, 73, 84, 91, 100, 106, 114, 121, 131, 139, 146, 159, 165, 172, 177, 188, 195, 201, 205, 211, 217, 226, 232, 241, 245, 251, 260, 265, 271, 280, 288, 303, 308, 438

aidom.part_conc/5 ... 36, 44, 50, 56, 73, 85, 92, 100, 106, 115, 122, 131, 140, 146, 160, 166, 173, 178, 189, 195, 202, 206, 212, 218, 227, 233, 242, 246, 252, 260, 266, 272, 281, 289, 304, 308, 439

aidom.project/6 . . 33, 41, 47, 53, 71, 82, 89, 98, 104, 112, 119, 129, 137, 144, 157, 163, 170, 175, 186, 193, 199, 203, 209, 215, 224, 230, 239, 243, 249, 258, 263, 269, 278, 286, 301, 306, 436
aidom.rename_auxinfo_asub/4 . . . 36, 44, 50, 56, 74, 85, 92, 100, 106, 115, 122, 131, 140, 146, 160, 166, 173, 178, 189, 196, 202, 206, 212, 218, 227, 233, 242, 246, 252, 261, 266, 272, 281, 289, 304, 309, 439
aidom.special_builtin/6 . . . . 35, 43, 49, 55, 72, 84, 91, 99, 105, 113, 121, 130, 139, 145, 159, 165, 172, 177, 188, 194, 201, 205, 211, 217, 226, 232, 241, 245, 251, 259, 265, 271, 279, 288, 303, 307, 438
aidom.split_combined_domain/4 . . . . 35, 43, 49, 55, 72, 84, 91, 99, 105, 114, 121, 130, 139, 145, 159, 165, 172, 177, 188, 194, 201, 205, 211, 217, 226, 232, 241, 245, 251, 259, 265, 271, 280, 288, 303, 308, 438
aidom.success_builtin/7 . . . . 35, 43, 49, 55, 73, 84, 91, 99, 105, 114, 121, 130, 139, 145, 159, 165, 172, 177, 188, 195, 201, 205, 211, 217, 226, 232, 241, 245, 251, 260, 265, 271, 280, 288, 303, 308, 438
aidom.unknown_call/5 . . . . 36, 44, 50, 56, 73, 85, 92, 100, 106, 114, 122, 131, 140, 146, 160, 166, 173, 178, 189, 195, 202, 206, 212, 218, 227, 233, 242, 246, 252, 260, 266, 272, 280, 289, 304, 308, 439
aidom.unknown_entry/4 . . . 36, 44, 50, 56, 73, 85, 92, 100, 106, 114, 122, 131, 140, 146, 160, 166, 173, 178, 189, 195, 202, 206, 212, 218, 227, 233, 242, 246, 252, 260, 266, 272, 280, 289, 304, 308, 439
aidom.widen/4 . . . . 34, 42, 48, 54, 71, 83, 90, 98, 104, 112, 120, 129, 138, 144, 158, 164, 170, 176, 187, 193, 199, 204, 210, 216, 224, 230, 239, 244, 250, 258, 264, 270, 278, 287, 301, 306, 436
aidom.widencall/4 . . . . 33, 41, 48, 53, 71, 82, 89, 98, 104, 112, 119, 129, 137, 144, 157, 164, 170, 176, 186, 193, 199, 203, 209, 215, 224, 230, 239, 243, 249, 258, 263, 269, 278, 286, 301, 306, 436
aidomain/1 . . . 15, 33, 41, 47, 53, 70, 82, 89, 97, 103, 111, 119, 128, 137, 143, 157, 163, 170, 175, 186, 192, 199, 203, 209, 215, 224, 230, 239, 243, 249, 257, 263, 269, 277, 286, 301, 305, 436, 456, 463
all_assertions_pred/4 494
all_different_mods/0 503
all_terms_identical/2 184
amgu/4 . . . . . 191, 229, 235
amgu/5 422
analysis/4 456
analysis_module/2 456
analysis_start/2 584
analysis_task/4 597
analyze/1 . . . . . 24, 453
analyze/2 454
analyze/7 560
analyze1/2 454
analyzed_mods/1 504
apply_assrt_call_to_success/8 412
apply_assrt_exit/7 413
apply_assrt_no_source/6 413
apply_success_policy/9 481
approx/6 562
assert_domain/1 453
assertion_set_calls/3 534
assertion_set_comp/3 534
assertion_set_head/3 533
assertion_set_status/3 533
assertion_set_success/3 534
assrt_used_as_entry/2 444
asub/4 . . . . . 128, 137
asub_gt/2 236
asub_to_info/5 432
asub_to_native/5 . . . . . 40, 183, 223, 237, 276
asub_to_native/6 432
augment_asub/3 . . . . . 191, 229, 236
augment_asub/4 423
augment_asub0/3 192
augment_two_asub/3 229
augment_two_asub/4 423
auto_analyze/1 12
auto_analyze/2 12
auto_check_assert/1 12
auto_check_assert/2 12
auto_optimize/1 12
auto_optimize/2 12

B

body/1 547
body_builtin/9 435
body_succ_builtin/9 431
bottom_up_delete_complete/5 500
bottom_up_delete_completes_preds/4 499
bu_delete_clauses/2 496
builtin/2 537

C

call_asr/5 412
call_to_entry/10 423

call_to_entry/9 ... 39, 182, 191, 197, 221, 229, 235, 275
call_to_prime_fact/6 ..... 182, 192, 222, 237, 276
call_to_success_builtin/6 ..... 183, 192, 223, 238, 277
call_to_success_builtin/7 439
call_to_success_fact/10 430
call_to_success_fact/9 .... 40, 182, 192, 198, 222, 237, 276
caller_module/2 466
change_id_clause/2 501
change_open_mode/2 476
change_values/4 185
change_values_if_f/4 185
change_values_if_not_g/4 185
check/1 ..... 343, 375
check_curr_entry_id/1 479
clause_key/2 541
clause_number/2 542
clausebody/1 545
clauses_keys/2 541
clean_analysis_info/0 455
clean_analysis_info0/0 455
clean_db/0 ..... 594, 597
clean_fixpoint_graph/0 581
clean_incanal_mod_data/0 503
clean_incremental_db/0 501
clean_persistent_analysis/0 506
clean_program_structure/0 466
clean_rev_idx/1 571
clean_tmp_db/0 594
cleanup_applied_assertions/1 412
cleanup_comment_db/0 532
cleanup_commented_assrt/0 532
cleanup_fixpoint/1 ..... 514, 561
cleanup_for_codegen/0 455
cleanup_history/0 444
cleanup_intermod/0 461
cleanup_intermod_scheduling/0 470
cleanup_libcache/0 534
cleanup_plai/1 559
cleanup_plai_db/1 566
cleanup_program_keys/0 541
cleanup_punit/0 533
cleanup_registry/1 467
cleanup_tr_syntax/0 549
clid_of_atomid/2 544
clique_make_decomposition/5 238
clique_part_less_or_equal/2 237
collect_types_in_abs/4 434
complete/7 565
complete_id_key/3 571
complete_key_from_id/3 570
complete_parent/2 566
compute/9 516
compute_glb/3 427
compute_imported_modules/0 477
compute_lub/2 ..... 39, 182, 222, 237, 276
compute_lub/3 427
compute_lub_el/3 ..... 40, 182, 198
compute_lub_sh/3 182
compute_punit_modules/3 473
compute_type/3 295
compute_upper_amgu/2 238
concrete/4 432
config_incremental_load/1 494
contains_parameters/2 435
counter/3 546
covering/3 184
curr_entry_id/1 479
current_pp_flag/2 ..... 17, 483
current_task_proc/2 594
customize/0 12
customize/1 12
customize_and_preprocess/0 13
customize_and_preprocess/1 13
customize_but_dont_save/1 13

D

db_data_dir/1 595
decode_clkey/4 543
decode_entrykey/4 543
decode_litkey/5 543
decode_predkey/3 543
define_flag/3 535
del_assertion_source_db/1 503
del_parent/4 569
del_parent_complete/6 568
delete_complete/3 569
delete_plai_db_one_clause/4 569
det_abs_sort/2 126
det_asub_to_native/5 127
det_call_to_entry/9 125
det_call_to_success_fact/9 126
det_collect_auxinfo_asub/3 128
det_combined_special_builtin0/2 127
det_compute_clauses_lub/3 126
det_compute_lub/2 126
det_dom_statistics/1 127

det_eliminate_equivalent/2 126
det_empty_entry/3 127
det_exit_to_prime/7 125
det_extend/5 126
det_glb/3 126
det_identical_abstract/2 126
det_init_abstract_domain/1 125
det_input_interface/4 127
det_input_user_interface/5 127
det_less_or_equal/2 126
det_obtain_info/4 127
det_project/5 126
det_rename_auxinfo_asub/3 128
det_special_builtin/5 127
det_split_combined_domain/3 127
det_success_builtin/6 127
det_unknown_call/4 127
det_unknown_entry/3 127
det_widen/3 126
det_widencall/3 126
determinate_sel/3 70
diff/4 510
difflsign_abs_sort/2 118
difflsign_asub_to_native/5 118
difflsign_call_to_entry/9 117
difflsign_call_to_success_fact/9 117
difflsign_compute_lub/2 117
difflsign_empty_entry/3 119
difflsign_exit_to_prime/7 118
difflsign_extend/5 118
difflsign_glb/3 118
difflsign_input_interface/4 118
difflsign_input_user_interface/5 118
difflsign_less_or_equal/2 118
difflsign_project/5 118
difflsign_special_builtin/5 118
difflsign_success_builtin/6 118
difflsign_unknown_call/4 118
difflsign_unknown_entry/3 119
dom_statistics/2 435
dual_widen/4 426
dual_widencall/4 426
dump_file/4 591
dump_flags/1 486
dump_flags_list/2 ..... 463, 488
dynamic_or_unknown_predicate/1 529

E

eliminate_couples_clique/4 238
eliminate_equivalent/2 236
eliminate_equivalent/3 430
eliminate_non_element/4 184
empty_entry/3 ..... 41, 183, 198, 223, 238, 276
empty_entry/4 433
end_view/0 581
ensure_libcache_loaded/0 446
ensure_registry_file/3 475
entry_assertion/3 444
entry_point/5 560
entry_to_exit/7 514
entry_to_exit/9 562
enum_mod_typedb/1 468
erase_directive/1 529
erase_last_memo_table/3 570
erase_previous_memo_lubs/2 570
erase_previous_memo_tables_and_parents/4 .. 570
erase_previous_parents_info/5 570
eterms_abs_sort/2 63
eterms_arg_call_to_success/9 67
eterms_asub_to_native/5 68
eterms_call_to_entry/9 61
eterms_call_to_success_builtin/6 67
eterms_call_to_success_fact/9 66
eterms_collect_auxinfo_asub/3 69
eterms_compute_lub/2 60
eterms_compute_lub_el/3 60
eterms_concrete/3 64
eterms_empty_entry/3 65
eterms_exit_to_prime/7 62
eterms_extend/5 63
eterms_glb/3 64
eterms_glbnames/3 64
eterms_identical_abstract/2 69
eterms_init_abstract_domain/1 60
eterms_input_interface/4 68
eterms_input_user_interface/5 68
eterms_less_or_equal/2 64
eterms_multi_part_conc/3 70
eterms_needs/1 60
eterms_obtain_info/4 68
eterms_output_interface/2 68
eterms_part_conc/4 70
eterms_project/5 63
eterms_rename_auxinfo_asub/3 69
eterms_special_builtin/5 66
eterms_success_builtin/6 67
eterms_unknown_call/4 65

eterms_unknown_entry/3 64
eterms_widen/3 60
eterms_widencall/3 60
etermsvar_abs_sort/2 77
etermsvar_arg_call_to_success/9 80
etermsvar_asub_to_native/5 81
etermsvar_call_to_entry/9 76
etermsvar_call_to_success_builtin/6 81
etermsvar_call_to_success_fact/9 79
etermsvar_collect_auxinfo_asub/3 81
etermsvar_compute_lub/2 76
etermsvar_compute_lub_el/3 76
etermsvar_concrete/3 78
etermsvar_empty_entry/3 79
etermsvar_exit_to_prime/7 77
etermsvar_extend/5 78
etermsvar_glb/3 78
etermsvar_identical_abstract/2 82
etermsvar_init_abstract_domain/1 75
etermsvar_input_interface/4 81
etermsvar_input_user_interface/5 81
etermsvar_less_or_equal/2 78
etermsvar_multi_part_conc/3 82
etermsvar_needs/1 76
etermsvar_obtain_info/4 81
etermsvar_output_interface/2 81
etermsvar_part_conc/4 82
etermsvar_project/5 77
etermsvar_rename_auxinfo_asub/3 81
etermsvar_special_builtin/5 80
etermsvar_success_builtin/6 80
etermsvar_unknown_call/4 79
etermsvar_unknown_entry/3 79
etermsvar_widen/3 76
etermsvar_widencall/3 76
exit_to_prime/7 .... 39, 182, 191, 197, 222, 235, 275
exit_to_prime/8 424
extend/5 ..... 40, 182, 197, 222, 236, 276
extend/6 428
external_calls/4 500

F

false/1 ..... 343, 375
file_search_path/2 ..... 448, 463
filtered_program_clauses/3 528
find_list_entry/3 295
first_key/2 542
fixpoint/6 562
fixpoint_compute_change/9 518
fixpoint_id_/2 504
fixpoint_trace/7 577
force_analysis/1 470
fr_abs_sort/2 96
fr_asub_to_native/5 97
fr_call_to_entry/9 95
fr_call_to_success_fact/9 95
fr_compute_lub/2 95
fr_empty_entry/3 97
fr_exit_to_prime/7 95
fr_extend/5 96
fr_glb/3 96
fr_identical_abstract/2 96
fr_input_interface/4 96
fr_input_user_interface/5 96
fr_less_or_equal/2 96
fr_output_interface/3 96
fr_project/5 96
fr_special_builtin/5 96
fr_success_builtin/6 96
fr_unknown_call/4 97
fr_unknown_entry/3 97
frdef_abs_sort/2 88
frdef_asub_to_native/5 88
frdef_call_to_entry/9 87
frdef_call_to_success_fact/9 87
frdef_compute_lub/2 87
frdef_empty_entry/3 89
frdef_exit_to_prime/7 87
frdef_extend/5 88
frdef_glb/3 88
frdef_identical_abstract/2 88
frdef_input_interface/4 88
frdef_input_user_interface/5 88
frdef_less_or_equal/2 88
frdef_project/5 88
frdef_special_builtin/5 88
frdef_success_builtin/6 88
frdef_unknown_call/4 89
frdef_unknown_entry/3 89
full_info_to_asub/5 432

G

gen_and_load_libcache/0 446
gen_libcache/1 534
generate_a_type_assignment/3 295
generate_subs/3 63
generate_subs_exit/4 62
generate_trans_clauses/4 560

generateSucc0_cond/5 69
get_absint/4 553
get_all_module_cycles/2 474
get_applicable_status/3 415
get_assert_count/1 455
get_assertion/2 529
get_call_assertions_asub/5 414
get_call_from_call_assrt/7 533
get_changed_registry/4 503
get_clkey/4 546
get_comment/1 532
get_commented_assertion/2 532
get_complete/8 567
get_completes/4 554
get_completes_lub/6 554
get_current_assertions/1 502
get_current_clauses/1 502
get_entry_info/3 479
get_free_vars/3 97
get_imported_module_base/2 477
get_info/5 553
get_list_names_is/2 70
get_litkey/5 547
get_memo_lub/5 553
get_memo_table/7 567
get_menu_configs/1 13
get_mod_name_from_file/2 591
get_modules_analyzed/1 477
get_output_operator/3 532
get_output_package/1 531
get_output_path/2 445
get_parent_key/4 567
get_pred_mod_defined/2 533
get_predkey/3 546
get_predkeys/2 546
get_punit_included_files/1 474
get_punit_modules/1 474
get_raw_success/6 571
get_raw_success/7 567
get_registry/4 467
get_succ_assertion_asubs/7 414
get_success_info/7 481
get_type/3 60
get_var_types_by_unification/3 295
getargtypes/6 69
getfunctors/2 69
getvalue/2 69
getvalues_comp_cond/3 70
glb/3 ..... 40, 182, 198, 222, 237, 276
glb/4 429

H

has_dump/2 505
hook_cleanup_lib_regtypes/0 ..... 448, 535, 538
hook_compact_calls_prop/2 ..... 447, 535, 538
hook_compact_global_prop/2 ..... 447, 535, 538
hook_insert_regtype/2 ..... 448, 535, 538
hook_legal_regtype/1 ..... 447, 535, 538
hook_menu_check_flag_value/3 15
hook_menu_default_option/3 15
hook_menu_flag_help/3 15
hook_menu_flag_values/3 15
hook_native_prop/2 ..... 447, 535, 538
hook_post_init_regtypes/0 ..... 448, 535, 538
hook_pp_info_clause/3 ..... 447, 535, 538
hook_pp_info_lit/4 ..... 447, 535, 538
hook_restore_lib_regtypes/1 ..... 448, 535, 538
hook_save_lib_regtypes/1 ..... 448, 536, 538

I

identical_abstract/2 ..... 198, 236
identical_abstract/3 428
identical_proj/5 427
identical_proj_1/7 428
imported_module/2 466
inc_add_source_clauses/3 507
incremental_analyze/1 493
incremental_analyze/2 493
incremental_module/1 493
incremental_module/2 493
incrementally_update_analysis/2 497
inductive_ctcheck/2 462
inductive_ctcheck/4 462
inductive_ctcheck_summary/3 463
info_to_asub/7 432
init_abstract_domain/2 422
init_analysis_db/0 594
init_clkeys/0 501
init_empty_inc_analysis/0 495
init_file_inc_analysis/3 495
init_fixpoint/0 ..... 514, 561
init_fixpoint/1 560
init_rev_idx/1 571
init_tasks_db/0 598
init_tmp_db/1 594
inject_output_package/1 531
input_interface/4 ..... 40, 183, 198, 223, 237, 277
input_interface/5 440
input_user_interface/5 ..... 40, 169, 183, 198, 223, 237, 276

input_user_interface/6 440
insert_after_clkey/2 501
insert_each/3 185
intermod_analyze/2 461
intermod_analyze/3 462
intermod_ctcheck/2 462
intermod_ctcheck_opt/2 463
intermod_ctcheck_opt/3 463
intermod_entry_point/7 479
intermod_simp_libs/2 462
intermod_simp_libs/3 462
intermod_transform/3 462
invalid_call/6 566
inverse_rewrite_source_body/2 542
inverse_rewrite_source_program_cl/2 542
is_checker/1 559
is_clause/4 544
is_clkey/1 544
is_directive/3 544
is_entrykey/1 544
is_library/1 444
is_litkey/1 544
is_naive_scheduling/1 471
iterations/1 470

K

keys_same_value/3 67
kind_of_info/7 554

L

language_extension/2 443
language_output_extension/2 443
last_clause/1 542
last_domain_used/1 453
last_file_log/2 594
lazy_analysis/1 456
less_or_equal/2 .... 41, 169, 183, 198, 223, 236, 277
less_or_equal/3 429
less_or_equal_proj/5 429
library_directory/1 ..... 448, 463
lit_ppkey/3 544
load_libcache/1 534
load_persistent_if_needed/2 505
loaded_analysis/1 456
loaded_libcache/0 534
loaded_mods/1 503
local_ana_module/2 465
logged_once_port_reify/4 589
lsign_abs_sort/2 111
lsign_abs_subset/2 110
lsign_asub_to_native/5 110
lsign_call_to_entry/9 109
lsign_call_to_success_fact/9 109
lsign_compute_lub/2 110
lsign_eliminate_equivalent/2 110
lsign_empty_entry/3 111
lsign_exit_to_prime/7 110
lsign_extend/5 110
lsign_glb/3 110
lsign_global_info/5 110
lsign_init_abstract_domain/1 109
lsign_input_interface/4 110
lsign_input_user_interface/5 110
lsign_less_or_equal/2 110
lsign_output_interface/2 111
lsign_project/5 110
lsign_propagate_fixpoint/8 111
lsign_special_builtin/5 111
lsign_success_builtin/6 111
lsign_sum/3 111
lsign_unknown_call/4 111
lsign_unknown_entry/3 111
lub/3 ..... 222, 276
lub_complete/6 565

M

main_module/2 465
make_atom/2 542
make_dependence/5 185
make_dir_nofail/1 592
mark_parents_change_list_scc/3 517
may_be_var/2 237
member_value_freeness_differ/3 185
memo_call/5 566
memo_lub/5 566
memo_table/6 566
memo_table_id_key/3 571
memotable_trace/3 578
merge_parents/3 569
mod_plai/5 559
mod_topdown_analysis/3 560
mod_typedb/2 468
module/1 ..... 22, 443
module/2 444
module_depth/2 466
module_has_entries/1 497
module_is_processable/1 475

module_processed/2 470
modules_analyzed/1 469
multi_part_conc/4 434
multifile_predicate_names/1 531
myappend/3 237

N

naive_module_order/1 470
naive_pending_modules/1 470
native_prop_map/3 537
native_to_prop/2 528
native_to_props_visible/2 529
needs/1 181
needs/2 425
new_predicate/3 531
newer/2 591
nf_abs_sort/2 135
nf_asub_to_native/5 135
nf_call_to_entry/9 133
nf_call_to_success_fact/9 135
nf_collect_auxinfo_asub/3 137
nf_combined_special_builtin0/2 135
nf_compute_clauses_lub/3 134
nf_compute_lub/2 134
nf_dom_statistics/1 136
nf_eliminate_equivalent/2 134
nf_empty_entry/3 136
nf_exit_to_prime/7 133
nf_extend/5 134
nf_glb/3 134
nf_identical_abstract/2 135
nf_init_abstract_domain/1 133
nf_input_interface/4 135
nf_input_user_interface/5 135
nf_less_or_equal/2 135
nf_obtain_info/4 136
nf_project/5 134
nf_rename_auxinfo_asub/3 137
nf_special_builtin/5 135
nf_split_combined_domain/3 135
nf_success_builtin/6 135
nf_unknown_call/4 135
nf_unknown_entry/3 136
nf_widen/3 134
nf_widencall/3 134
nonrel_abs_sort/2 149
nonrel_amgu/5 148
nonrel_asub_to_native/6 154
nonrel_bot/2 147
nonrel_call_to_entry/10 149
nonrel_call_to_success_builtin/7 153
nonrel_call_to_success_fact/10 151
nonrel_compute_glb_elem/4 147
nonrel_compute_lub/3 151
nonrel_compute_lub_elem/4 148
nonrel_exit_to_prime/8 150
nonrel_extend/6 151
nonrel_glb/4 155
nonrel_identical_abstract/2 155
nonrel_input_interface/5 153
nonrel_input_user_interface/6 153
nonrel_less_or_equal/3 154
nonrel_less_or_equal_elem/3 147
nonrel_project/5 149
nonrel_special_builtin/6 152
nonrel_success_builtin/7 152
nonrel_top/2 147
nonrel_unknown_call/5 154
nonrel_unknown_entry/4 149
nonrel_var_elem/2 147
nonrel_widen/4 155
nonrel_widen_elem/4 148
nonrel_widencall/4 155
normal_asub/2 62
normalize_asub/3 427

O

obtain_freeness/2 185
obtain_info/3 183
obtain_info/4 183
obtain_info/5 431
obtain_prime_var_var/3 185
obtains_names/4 70
open_mode/3 476
orig_clause_id/2 544
output/0 ..... 22, 445
output/1 ..... 22, 445
output/2 445
output_by_ext/2 446
output_ext/1 446

P

part_conc/5 434
partition_sf/4 184
patch/3 510
patch_parents/6 568
path_to_shfr/3 305

persistent_dir/2 ..... 487, 595, 598
persistent_dir/4 ..... 487, 595, 598
plai/5 559
polyhedra_finalize/0 169
polyhedra_initialize/0 169
pop/2 470
pop_history/1 445
pop_pp_flag/1 ..... 18, 483
pop_task/4 597
pos/4 222
postcondition_builtin/4 300
powerset_with_empty_set/2 236
pp_flag/1 18
pp_flag/2 484
pr_key_add/1 530
pr_key_clean/0 530
pr_key_get/1 530
pragma/5 566
precondition_builtin/2 300
predicate_names/1 531
predicates/1 507
predkey_from_sg/2 546
preprocessing_unit/3 527
process_external_complete_change/6 497
product/8 184
program/2 528
proj_to_prime/9 515
proj_to_prime_nr/9 514
proj_to_prime_r/8 515
project/5 ..... 39, 181, 197, 221, 236, 275, 424
project/6 425
project_freeness/3 182
project_freeness_n/3 186
project_share/3 221
projected_gvars_clique/3 238
prop_to_native/2 529
propagate_non_freeness/5 186
propagate_to_sh/4 277
propagate_to_son/4 277
prune/4 184
prune/5 184
prune_success/5 236
punit_module/2 465
push/2 469
push_history/1 445
push_pp_flag/2 ..... 18, 483

Q

query/8 ..... 513, 561

R

raw_output/1 451
raw_success/6 567
read_registry_file/3 475
rearrange_tarjan_after_deletion/1 507
rec/1 508
rec_preds/1 508
reg_version/1 467
registry/3 466
registry_header/2 466
registry_header_format/2 468
remove_clauses_and_related_info_collect_
preds/4 499
remove_clauses_pred/2 502
remove_config/1 486
remove_extra_info_complete/3 569
remove_menu_config/1 13
remove_useless_completes/1 497
rename_types_in_abs/4 434
replace_names/3 62
replace_program/2 528
replaceintype/5 70
replacetype/4 69
report_mod_info/3 595
reset_incremental_analysis_info/0 494
reset_persistent_db/0 505
reset_queue/0 469
restore_clause_db/0 502
restore_config/1 486
restore_fixpoint_id/1 504
restore_menu_config/1 14
rewrite_source_all_clauses/2 542
rewrite_source_clause/3 542
run_inc_fixpoint/1 497

S

save_clause_db/0 501
save_config/1 486
save_menu_config/1 13
save_persistent_analysis/0 506
save_registry_info/2 477
save_registry_info/3 476
script_p/3 222
script_p_star/3 222
set_analyzed_mods/1 504
set_current_task/2 594
set_inc_persistent/1 505
set_last_error/3 595
set_loaded_mods/1 503

set_loaded_module/1 505
set_local_ana_modules/1 467
set_main_module/1 467
set_modules_analyzed/1 477
set_pp_flag/2 ..... 18, 484
set_punit_modules/1 467
setup_scheduling/4 470
sh_free_vars_compatible/2 185
share_clique_lub_cl/3 237
share_make_reduction/5 238
share_to_son/3 277
sharefree_delete_variables/3 192
sharing_part_less_or_equal/3 237
sharing_possible/4 236
shfret_abs_sort/2 256
shfret_asub_to_native/5 257
shfret_call_to_entry/9 255
shfret_call_to_success_fact/9 256
shfret_combined_special_builtin0/2 256
shfret_compute_lub/2 256
shfret_eliminate_equivalent/2 256
shfret_empty_entry/3 257
shfret_exit_to_prime/7 255
shfret_extend/5 256
shfret_glb/3 256
shfret_identical_abstract/2 256
shfret_init_abstract_domain/1 255
shfret_input_interface/4 257
shfret_input_user_interface/5 257
shfret_less_or_equal/2 256
shfret_project/5 256
shfret_split_combined_domain/3 257
shfret_unknown_call/4 257
shfret_unknown_entry/3 257
shfret_widen/3 256
shfret_widencall/3 256
show_analysis/0 452
show_change_list/0 452
show_config/1 487
show_configs/0 487
show_global_answer_table/1 452
show_menu_config/1 14
show_menu_configs/0 14
show_registry_info/0 452
show_spypoint_op_count/0 578
show_trans_clauses/0 452
show_updated_memotable/3 578
son_to_share/4 277
special_builtin/5 .. 40, 183, 192, 198, 223, 238, 277
special_builtin/6 430
split_coupled/4 184
split_f/4 69
src_changed/1 466
start_view/0 581
start_worker/1 589
store_current_fixpoint_id/1 504
store_raw_success/6 571
string_contained/2 591
sublist2/2 487
substitution/3 298
success_asr/6 412
success_builtin/6 ..... 40, 183, 192, 223, 238, 277
success_builtin/7 431
supported_language/1 443
svterms_abs_sort/2 284
svterms_asub_to_native/5 285
svterms_call_to_entry/9 284
svterms_call_to_success_builtin/6 285
svterms_call_to_success_fact/9 285
svterms_collect_auxinfo_asub/3 285
svterms_compute_lub/2 283
svterms_compute_lub_el/3 283
svterms_concrete/3 283
svterms_empty_entry/3 285
svterms_exit_to_prime/7 284
svterms_extend/5 284
svterms_glb/3 284
svterms_identical_abstract/2 286
svterms_init_abstract_domain/1 284
svterms_input_interface/4 285
svterms_input_user_interface/5 285
svterms_less_or_equal/2 284
svterms_needs/1 284
svterms_output_interface/2 285
svterms_project/5 284
svterms_rename_auxinfo_asub/3 286
svterms_special_builtin/5 285
svterms_success_builtin/6 285
svterms_unknown_call/4 285
svterms_unknown_entry/3 285
svterms_widen/3 284
svterms_widencall/3 284

T

take_coupled/3 184
tarjan_data/1 507
task_status/5 593
td_add_clauses/2 495
td_delete_clauses/2 496

td_mark_parents_change_list/2 516
td_rec_delete_complete/3 496
terms_abs_sort/2 296
terms_asub_to_native/5 300
terms_call_to_entry/9 293
terms_call_to_success_builtin/6 299
terms_call_to_success_fact/9 298
terms_collect_auxinfo_asub/3 300
terms_compute_lub/2 292
terms_compute_lub_el/3 292
terms_concrete/3 292
terms_empty_entry/3 297
terms_exit_to_prime/7 294
terms_extend/5 296
terms_glb/3 297
terms_identical_abstract/2 300
terms_init_abstract_domain/1 292
terms_input_interface/4 291
terms_input_user_interface/5 300
terms_internal_to_native/3 300
terms_less_or_equal/2 296
terms_needs/1 292
terms_output_interface/2 300
terms_project/5 295
terms_rename_auxinfo_asub/3 300
terms_special_builtin/5 299
terms_success_builtin/6 299
terms_unknown_call/4 298
terms_unknown_entry/3 297
terms_widen/3 292
terms_widencall/3 292
top_level_of_files/2 505
topdown_analysis/3 560
trace_end/0 578
trace_fixp/1 ..... 455, 577
trace_init/0 578
trace_reset/0 578
transform/1 ..... 23, 459
transform/2 459
transform_clauses_/5 560
transformation/4 460
traverse_clauses/4 549
true/1 ..... 343, 375
trust/1 ..... 343, 375
type_fails/3 553
type_holds/3 553
type_of_directive/2 530
type2measure/3 553
typeanalysis/1 487
typeslib_flag/1 25
typeslib_interesting_type/2 25
typeslib_is_user_type/1 25
typeslib_is_visible/2 25

U

undef_call_to_success_builtin/2 435
unify_term_and_type_term/5 294
unifytoterm/1 69
unknown_call/4 ..... 40, 185, 198, 223, 238, 276
unknown_call/5 433
unknown_entry/3 ..... 40, 182, 222, 238, 276
unknown_entry/4 433
unset_src_changed/1 466
update_complete_id/4 569
update_inc_clkey/1 503
update_lambda_non_free/5 184
update_lambda_sf/5 184
update_names/2 62
update_task_status/0 593
update_tasks_analysis_status/0 595

V

valid_flag_values/2 486
values_differ/3 185
values_equal/3 185
variables_are_top_type/2 ..... 65, 298
variables_are_variable_type/2 294
vertexes/1 508
view_fixpoint/7 581

W

wam_builtin/2 537
widen/4 ..... 238, 426
widen/5 238
widencall/4 426
write_one_type/2 446
write_registry_file/3 475

Property Index

A

analysis/1 ..... 26, 456
analysis_opt/1 584
asub/1 107
asub_elem/1 107

B

bind_ins/1 374
binding/1 107
binds/1 107

C

callable/1 363
cardinality/3 389
clique/1 380
clique_1/1 381
compat/2 369
constraint/1 397
cost/4 405
costb/4 405
covered/1 385
covered/2 380

D

deprecated/1 370
det/1 383
docstring/1 350

E

equiv/2 374
error_free/1 374
eval/1 374
example/1 371
exception/1 391
exception/2 391
extrainfo/1 107

F

fails/1 383
filter/2 374
finite_solutions/1 390

H

head_pattern/1 346

I

indep/1 380
indep/2 379
inst/2 370
is_det/1 386
iso/1 370
ivar/1 380

L

leaves_choicepoints/1 386
linear/1 380

M

member/2 366
memo/1 374
mshare/1 379
mshare/2 379
multi/1 384
mut_exclusive/1 384

N

nabody/1 348
native/1 372
native/2 372
no_choicepoints/1 386
no_exception/1 391
no_exception/2 392
no_rtcheck/1 373
no_signal/1 392
no_signal/2 392
non_det/1 386
nondet/1 384
nonground/1 380
not_covered/1 385
not_fails/1 387
not_further_inst/2 371
not_mut_exclusive/1 384
num_solutions/2 389

P

pe_type/1 375
possible_exceptions/2 391
possible_signals/2 392
possibly_fails/1 387
possibly_nondet/1 386
possibly_not_covered/1 386

possibly_not_mut_exclusive/1 385

R

regtype/1 372
relations/2 389
resource_id/1 399
rsize/2 405
rtcheck/1 373
rtcheck/2 373

S

semidet/1 383
sideff/2 372
sideff_hard/1 395
sideff_pure/1 395
sideff_soft/1 395
signal/1 392
signal/2 392
size/2 401
size/3 401
size/4 401
size_lb/2 402
size_metric/3 403
size_metric/4 403
size_o/2 402
size_ub/2 402
solutions/2 390
srcloc/4 371
steps/2 404
steps_lb/2 404
steps_o/2 405
steps_ub/2 404

T

terminates/1 406
transformation/1 ..... 26, 460, 463

V

valid_flag_value/2 ..... 20, 485
valid_mod_analysis/1 461

Regular Type Index

A

agg_expression/1 400
approx/1 399
assrt_body/1 345
assrt_status/1 349
assrt_type/1 350
atm/1 360
atm_or_atm_list/1 369

B

bytelist/1 368

C

c_assrt_body/1 348
cgoal/1 362
character_code/1 367
clause/1 545
clkey/1 546
complex_arg_property/1 346
complex_goal_property/1 347
constant/1 362
cost_expression/1 399
ctcheck_sum/1 454

D

det_asub/1 128
dictionary/1 348
diff_item/1 511
drid/1 547

F

flag_value/1 ..... 20, 485
flag_values/1 375
flt/1 359

G

g_assrt_body/1 349
gnd/1 361
gndstr/1 362
gr_mode/1 107

H

head/1 547

I

inc_persistent_status/1 506
indexvar/1 401
int/1 358
internal_module_id/1 363

L

list/1 364
list/2 365
literal_ppkey/1 545
litkey/1 545

M

measure_t/1 403

N

native/1 539
native_prop_term/1 537
nf_asub/1 136
nf_par_asub/2 136
nf_pred_asub/1 136
nf_pred_asub_sl/1 136
nlist/2 365
nnegint/1 358
num/1 359
number_lattice/1 401
numeric_constant/1 400

O

operator_specifier/1 363

P

plai_db_id/1 572
pp_flag/1 484
predfunctor/1 350
predkey/1 546
predname/1 368
property_conjunction/1 347
property_starterm/1 347
propfunctor/1 350

S

s_assrt_body/1 348
sequence/2 366
sequence_or_list/2 367
size_term/1 401
string/1 368
struct/1 361

T

task_status/1 590
term/1 357
trace_option/1 578

V

vlist/1 540

Declaration Index

C

calls/1 337
calls/2 337
comment/2 342
comp/1 338
comp/2 338

D

decl/1 342
decl/2 342
doc/2 342

E

entry/1 340
exit/1 340
exit/2 341

M

modedef/1 341

P

pred/1 336
pred/2 337
prop/1 339
prop/2 339

R

regtype/1 354
regtype/2 355

S

success/1 338
success/2 338

T

test/1 339
test/2 339
texec/1 340
texec/2 340

Concept Index

A

assertion body syntax 345, 348, 349

B

builtin predicate 524

C

calls assertion 337
check assertion 343
comment assertion 342
comments, machine readable 335
comp assertion 338
compatibility properties 351
current module 441

D

data declaration 331
decl assertion 342
dynamic declaration 331

E

entry assertion 340
entry declaration 331
exit assertion 341

F

false assertion 344
formatting commands 335

H

hard side-effects 395

I

instantiation properties 351
ISO-Prolog 325

M

module declaration 332

N

native properties 524

P

parametric type functor 354
pred assertion 336, 337
preprocessing unit 523
prop assertion 339
properties of computations 351
properties of execution states 351
properties, basic 357
properties, native 377

R

regtype assertion 354, 355
regular type expression 355

S

sharing sets 379
soft side-effects 395
success assertion 338

T

test assertion 339
texec assertion 340
true assertion 343
trust assertion 343
trust assertions 330

U

useful modes 346

Author Index

A

Alejandro Serrano 75
Amadeo Casas 377

C

Ciao Development Team 47, 59, 75, 175, 291
CiaoPP development team 11
Claudio Vaucheret 59, 75, 103, 175, 291

D

Daniel Cabeza 357

E

Edison Mera 377, 407

F

Francisco Bueno 59, 75, 175, 181, 221, 291, 325, 335, 351, 377, 421, 561

G

German Puebla 335

I

Isabel Garcia-Contreras 143, 317, 319, 321, 411, 451, 461, 489, 491, 495, 499, 507, 509, 583, 589, 593

J

Jorge Navas . . . 191, 197, 203, 229, 235, 243, 249, 263
Jose F. Morales 143, 377, 421, 509

K

Kalyan Muthukumar 221, 561

M

Manuel Hermenegildo 335, 345, 351, 357, 377
Maria Garcia de la Banda 181, 209, 221, 421, 561

N

Nataliia Stulova 407

P

Pawel Pietrzak 47
Pedro Lopez 351, 377

T

The Ciao Development Team 9, 17, 27, 323, 417, 419, 461, 527

Global Index

This is a global index containing pointers to places where concepts, predicates, modes, properties, types, applications, authors, etc., are referred to in the text of the document.

$

`$change_list/3` 513, 514
`$CIAOROOT/core/lib/rtchecks/rtchecks_rt_propimpl.pl` 408
`$depend_list/3` 561, 562
`$is_persistent/2` 483, 487, 593, 595, 597, 598

,

`','/2` 366

(

`(Sg,Proj,Prime)` 565

*

`* /2` 400
`** /2` 400
`*/2` 347

-

`- /1` 400
`- /2` 400
`-- /1` 400

.

`.(notrace)` 415, 519, 562

/

`/ /2` 400

:

`:- include` 474
`::/2` 336

=

`=/2` 153
`==/2` 153
`=>/2` 336

+

`+ /1` 400
`+ /2` 400
`+/1` 346
`+/2` 346
`++ /1` 400

A

`abs-int-naclp89` 379
`abs_eval_arith/3` 59, 69
`abs_eval_arithcomp/4` 59, 69
`abs_exec` 15
`abs_normalize/8` 412, 415
`abs_sort/2` 39, 40, 181, 182, 198, 221, 222, 235, 236, 275
`abs_sort/3` 422, 428
`abs_subset/3` 422, 430
`abstract_instance/5` 422, 435
`absu/1` 76, 77, 78, 79, 80, 183, 223
`absub_eliminate_equivalent/3` 422, 435
`absub_fixpoint_covered/3` 422, 435
`acc_ops` 15
`acheck/0` 23, 453, 455
`acheck/1` 453, 455
`acheck/2` 23, 453, 455
`acheck_summary/1` 24, 453, 454
`acheck_summary/2` 24, 453, 454
`add_all_clauses/1` 501, 502
`add_assertion/1` 527, 529
`add_assertion_source_db/1` 501, 502
`add_assertions/1` 527, 529
`add_change/5` 513, 517
`add_change_scc/6` 513, 518
`add_changed_registry/4` 501, 503
`add_comment/1` 527, 532
`add_commented_assertion/1` 527, 533
`add_commented_assertions/1` 527, 533
`add_defined_pred/2` 527, 530
`add_directive/1` 527, 529, 530
`add_entries_to_registry/1` 479, 480
`add_environment_vars/3` 181, 186
`add_invalid_call/6` 565, 571
`add_main_module/1` 465
`add_mod_typedb/2` 465, 468
`add_naive_pending_modules/1` 469, 471
`add_new_preds/1` 501, 502

add_output_operator/3 ..... 527, 532
add_output_package/1 ..... 527, 531
add_parent_complete/5 ..... 565, 568
add_registry/2 ..... 465, 467
add_src_changed/1 ..... 465, 466
add_success_asr/6 ..... 412, 414
add_task/1 597
add_task/3 597
add_task_status/5 593
add_tasks/1 597
add_to_db/1 ..... 21, 447
adding_new_domain 419
aeq 33, 440
again/0 ..... 11, 13
agg_expression/1 ..... 399, 400
aggregates .. 15, 74, 86, 242, 290, 415, 448, 452, 457, 464, 478, 482, 488, 494, 498, 500, 504, 508, 519, 536, 554, 560, 562, 579
ai-jlp 32
ai-spec-defs-tr 32
aidom.abs_sort/3 .. 34, 39, 42, 48, 54, 59, 72, 75, 83, 87, 90, 95, 98, 104, 109, 113, 117, 120, 125, 129, 133, 138, 144, 158, 164, 169, 171, 176, 181, 187, 191, 194, 197, 200, 204, 210, 216, 221, 225, 229, 231, 235, 240, 244, 250, 255, 259, 264, 270, 275, 279, 283, 287, 291, 302, 305, 307, 422, 437
aidom.abs_subset/3 ... 35, 39, 43, 49, 55, 59, 72, 75, 84, 87, 91, 95, 99, 105, 109, 113, 117, 121, 125, 130, 133, 139, 145, 159, 165, 169, 171, 177, 181, 188, 191, 194, 197, 200, 205, 211, 217, 221, 225, 229, 231, 235, 240, 245, 251, 255, 259, 265, 271, 275, 279, 283, 288, 291, 302, 305, 307, 422, 437
aidom.amgu/5 .. 33, 39, 41, 47, 53, 59, 70, 75, 82, 87, 89, 95, 97, 103, 109, 111, 117, 119, 125, 128, 133, 137, 143, 157, 163, 169, 170, 175, 181, 186, 191, 192, 197, 199, 203, 209, 215, 221, 224, 229, 230, 235, 239, 243, 249, 255, 257, 263, 269, 275, 277, 283, 286, 291, 301, 305, 422, 436
aidom.asub_to_native/6 .. 36, 39, 44, 50, 56, 59, 73, 75, 85, 87, 92, 95, 100, 106, 109, 114, 117, 122, 125, 131, 133, 140, 146, 160, 166, 169, 172, 178, 181, 189, 191, 195, 197, 201, 206, 212, 218, 221, 226, 229, 232, 235, 241, 246, 252, 255, 260, 266, 272, 275, 280, 283, 289, 291, 303, 305, 308, 422, 438
aidom.augment_asub/4 .... 33, 39, 41, 47, 53, 59, 70, 75, 82, 87, 89, 95, 97, 103, 109, 112, 117, 119, 125, 128, 133, 137, 143, 157, 163, 169, 170, 175, 181, 186, 191, 192, 197, 199, 203, 209, 215, 221, 224, 229, 230, 235, 239, 243, 249, 255, 257, 263, 269, 275, 278, 283, 286, 291, 301, 305, 306, 422, 436
aidom.augment_two_asub/4 ... 33, 39, 41, 47, 53, 59, 70, 75, 82, 87, 89, 95, 97, 103, 109, 112, 117, 119, 125, 128, 133, 137, 143, 157, 163, 169, 170, 175, 181, 186, 191, 192, 197, 199, 203, 209, 215, 221, 224, 229, 230, 235, 239, 243, 249, 255, 257, 263, 269, 275, 278, 283, 286, 291, 301, 305, 306, 422, 436
aidom.body_succ_builtin/9 .. 35, 39, 43, 49, 55, 59, 72, 75, 84, 87, 91, 95, 99, 105, 109, 114, 117, 121, 125, 130, 133, 139, 145, 159, 165, 169, 172, 177, 181, 188, 191, 194, 197, 201, 205, 211, 217, 221, 226, 229, 232, 235, 241, 245, 251, 255, 259, 265, 271, 275, 280, 283, 288, 291, 303, 305, 307, 422, 438
aidom.call_to_entry/10 .. 33, 39, 41, 47, 53, 59, 71, 75, 82, 87, 89, 95, 97, 103, 109, 112, 117, 119, 125, 128, 133, 137, 143, 157, 163, 169, 170, 175, 181, 186, 191, 193, 197, 199, 203, 209, 215, 221, 224, 229, 230, 235, 239, 243, 249, 255, 258, 263, 269, 275, 278, 283, 286, 291, 301, 305, 306, 422, 436
aidom.call_to_success_builtin/7 .. 35, 39, 43, 49, 55, 59, 73, 75, 84, 87, 91, 95, 99, 105, 109, 114, 117, 121, 125, 130, 133, 139, 145, 159, 165, 169, 172, 177, 181, 188, 191, 195, 197, 201, 205, 211, 217, 221, 226, 229, 232, 235, 241, 245, 251, 255, 260, 265, 271, 275, 280, 283, 288, 291, 303, 305, 308, 422, 438
aidom.call_to_success_fact/10 .... 35, 39, 43, 49, 55, 59, 72, 75, 84, 87, 91, 95, 99, 105, 109, 113, 117, 121, 125, 130, 133, 139, 145, 159, 165, 169, 172, 177, 181, 188, 191, 194, 197, 201, 205, 211, 217, 221, 226, 229, 232, 235, 241, 245, 251, 255, 259, 265, 271, 275, 279, 283, 288, 291, 303, 305, 307, 422, 438
aidom.collect_auxinfo_asub/4 .. 36, 39, 44, 50, 56, 59, 74, 75, 85, 87, 92, 95, 100, 106, 109, 115, 117, 122, 125, 131, 133, 140, 146, 160, 166, 169, 173, 178, 181, 189, 191, 196, 197, 202, 206, 212, 218, 221, 227, 229, 233, 235, 242, 246, 252, 255, 261, 266, 272, 275, 281, 283, 289, 291, 304, 305, 309, 422, 439
aidom.combined_special_builtin0/3.... 35, 39, 43, 49, 55, 59, 72, 75, 84, 87, 91, 95, 99, 105, 109,

113, 117, 121, 125, 130, 133, 139, 145, 159, 165, 169, 172, 177, 181, 188, 191, 194, 197, 201, 205, 211, 217, 221, 226, 229, 232, 235, 241, 245, 251, 255, 259, 265, 271, 275, 279, 283, 288, 291, 303, 305, 307, 422, 438

aidom.compute_clauses_glb/4 . . . 34, 39, 42, 48, 54, 59, 71, 75, 83, 87, 90, 95, 98, 104, 109, 112, 117, 120, 125, 129, 133, 138, 144, 158, 164, 169, 171, 176, 181, 187, 191, 193, 197, 200, 204, 210, 216, 221, 225, 229, 231, 235, 240, 244, 250, 255, 258, 264, 270, 275, 278, 283, 287, 291, 302, 305, 306, 422, 437

aidom.compute_clauses_lub/4 . . . 34, 39, 42, 48, 54, 59, 71, 75, 83, 87, 90, 95, 98, 104, 109, 112, 117, 120, 125, 129, 133, 138, 144, 158, 164, 169, 171, 176, 181, 187, 191, 193, 197, 200, 204, 210, 216, 221, 225, 229, 231, 235, 240, 244, 250, 255, 258, 264, 270, 275, 278, 283, 287, 291, 302, 305, 306, 422, 437

aidom.compute_lub/3 . . 34, 39, 42, 48, 54, 59, 71, 75, 83, 87, 90, 95, 98, 104, 109, 112, 117, 120, 125, 129, 133, 138, 144, 158, 164, 169, 170, 176, 181, 187, 191, 193, 197, 199, 204, 210, 216, 221, 224, 229, 230, 235, 239, 244, 250, 255, 258, 264, 270, 275, 278, 283, 287, 291, 301, 305, 306, 422, 437

aidom.concrete/4 . . 36, 39, 44, 50, 56, 59, 73, 75, 85, 87, 92, 95, 100, 106, 109, 114, 117, 122, 125, 131, 133, 140, 146, 160, 166, 169, 172, 178, 181, 189, 191, 195, 197, 201, 206, 212, 218, 221, 226, 229, 232, 235, 241, 246, 252, 255, 260, 266, 272, 275, 280, 283, 289, 291, 303, 305, 308, 422, 438

aidom.contains_parameters/2 . . . 36, 39, 44, 50, 56, 59, 74, 75, 85, 87, 92, 95, 101, 107, 109, 115, 117, 122, 125, 132, 133, 140, 147, 160, 166, 169, 173, 178, 181, 189, 191, 196, 197, 202, 206, 212, 218, 221, 227, 229, 233, 235, 242, 246, 252, 255, 261, 266, 272, 275, 281, 283, 289, 291, 304, 305, 309, 422, 439

aidom.dom_statistics/2 . . 36, 39, 44, 50, 56, 59, 74, 75, 85, 87, 92, 95, 101, 107, 109, 115, 117, 122, 125, 132, 133, 140, 147, 160, 166, 169, 173, 178, 181, 189, 191, 196, 197, 202, 206, 212, 218, 221, 227, 229, 233, 235, 242, 246, 252, 255, 261, 266, 272, 275, 281, 283, 289, 291, 304, 305, 309, 422, 439

aidom.eliminate_equivalent/3 . . 35, 39, 43, 49, 55, 59, 72, 75, 84, 87, 91, 95, 99, 105, 109, 113, 117, 121, 125, 130, 133, 139, 145, 159, 165, 169, 171, 177, 181, 188, 191, 194, 197, 200, 205, 211, 217, 221, 225, 229, 231, 235, 240, 245, 251, 255, 259, 265, 271, 275, 279, 283, 288, 291, 302, 305, 307, 422, 437

aidom.empty_entry/4 . . 36, 39, 44, 50, 56, 59, 73, 75, 85, 87, 92, 95, 100, 106, 109, 114, 117, 122, 125, 131, 133, 140, 146, 160, 166, 169, 173, 178, 181, 189, 191, 195, 197, 202, 206, 212, 218, 221, 227, 229, 233, 235, 242, 246, 252, 255, 260, 266, 272, 275, 280, 283, 289, 291, 304, 305, 308, 422, 439

aidom.exit_to_prime/8 . . . 33, 39, 41, 47, 53, 59, 71, 75, 82, 87, 89, 95, 97, 104, 109, 112, 117, 119, 125, 128, 133, 137, 143, 157, 163, 169, 170, 175, 181, 186, 191, 193, 197, 199, 203, 209, 215, 221, 224, 229, 230, 235, 239, 243, 249, 255, 258, 263, 269, 275, 278, 283, 286, 291, 301, 305, 306, 422, 436

aidom.extend/6 . . . . 34, 39, 42, 48, 54, 59, 72, 75, 83, 87, 90, 95, 99, 105, 109, 113, 117, 120, 125, 130, 133, 138, 145, 158, 164, 169, 171, 176, 181, 187, 191, 194, 197, 200, 204, 210, 216, 221, 225, 229, 231, 235, 240, 244, 250, 255, 259, 264, 270, 275, 279, 283, 287, 291, 302, 305, 307, 422, 437

aidom.fixpoint_covered/3 . . . 34, 39, 42, 48, 54, 59, 71, 75, 83, 87, 90, 95, 98, 104, 109, 113, 117, 120, 125, 129, 133, 138, 144, 158, 164, 169, 171, 176, 181, 187, 191, 193, 197, 200, 204, 210, 216, 221, 225, 229, 231, 235, 240, 244, 250, 255, 258, 264, 270, 275, 279, 283, 287, 291, 302, 305, 306, 422, 437

aidom.fixpoint_covered_gfp/3 . . 34, 39, 42, 48, 54, 59, 71, 75, 83, 87, 90, 95, 98, 104, 109, 113, 117, 120, 125, 129, 133, 138, 144, 158, 164, 169, 171, 176, 181, 187, 191, 193, 197, 200, 204, 210, 216, 221, 225, 229, 231, 235, 240, 244, 250, 255, 258, 264, 270, 275, 279, 283, 287, 291, 302, 305, 307, 422, 437

aidom.glb/4 . . . 34, 39, 42, 49, 54, 59, 72, 75, 84, 87, 91, 95, 99, 105, 109, 113, 117, 120, 125, 130, 133, 139, 145, 159, 165, 169, 171, 177, 181, 188, 191, 194, 197, 200, 205, 211, 216, 221, 225, 229, 231, 235, 240, 245, 251, 255, 259, 265, 270, 275, 279, 283, 287, 291, 302, 305, 307, 422, 437

aidom.identical_abstract/3 . . . . 34, 39, 42, 48, 54, 59, 72, 75, 83, 87, 90, 95, 98, 104, 109, 113, 117, 120, 125, 129, 133, 138, 144, 158, 164, 169, 171, 176, 181, 187, 191, 194, 197, 200, 204, 210, 216, 221, 225, 229, 231, 235, 240, 244, 250, 255, 259,

264, 270, 275, 279, 283, 287, 291, 302, 305, 307, 422, 437

aidom.init_abstract_domain/2 .. 33, 39, 41, 47, 53, 59, 70, 75, 82, 87, 89, 95, 97, 103, 109, 111, 117, 119, 125, 128, 133, 137, 143, 157, 163, 169, 170, 175, 181, 186, 191, 192, 197, 199, 203, 209, 215, 221, 224, 229, 230, 235, 239, 243, 249, 255, 257, 263, 269, 275, 277, 283, 286, 291, 301, 305, 422, 436

aidom.input_interface/5 .... 35, 39, 43, 49, 55, 59, 73, 75, 84, 87, 91, 95, 100, 106, 109, 114, 117, 121, 125, 131, 133, 139, 146, 159, 165, 169, 172, 177, 181, 188, 191, 195, 197, 201, 205, 211, 217, 221, 226, 229, 232, 235, 241, 245, 251, 255, 260, 265, 271, 275, 280, 283, 288, 291, 303, 305, 308, 422, 438

aidom.input_user_interface/6 .. 35, 39, 43, 50, 55, 59, 73, 75, 85, 87, 92, 95, 100, 106, 109, 114, 117, 121, 125, 131, 133, 140, 146, 160, 166, 169, 172, 178, 181, 189, 191, 195, 197, 201, 206, 212, 217, 221, 226, 229, 232, 235, 241, 246, 252, 255, 260, 266, 271, 275, 280, 283, 288, 291, 303, 305, 308, 422, 438

aidom.less_or_equal/3 ... 34, 39, 42, 48, 54, 59, 72, 75, 83, 87, 90, 95, 99, 105, 109, 113, 117, 120, 125, 130, 133, 138, 145, 158, 164, 169, 171, 176, 181, 187, 191, 194, 197, 200, 204, 210, 216, 221, 225, 229, 231, 235, 240, 244, 250, 255, 259, 264, 270, 275, 279, 283, 287, 291, 302, 305, 307, 422, 437

aidom.multi_part_conc/4 .... 36, 39, 44, 50, 56, 59, 73, 75, 85, 87, 92, 95, 100, 106, 109, 115, 117, 122, 125, 131, 133, 140, 146, 160, 166, 169, 173, 178, 181, 189, 191, 195, 197, 202, 206, 212, 218, 221, 227, 229, 233, 235, 242, 246, 252, 255, 260, 266, 272, 275, 281, 283, 289, 291, 304, 305, 309, 422, 439

aidom.needs/2 ..... 34, 39, 41, 48, 54, 59, 71, 75, 83, 87, 90, 95, 98, 104, 109, 112, 117, 119, 125, 129, 133, 138, 144, 158, 164, 169, 170, 176, 181, 187, 191, 193, 197, 199, 204, 210, 216, 221, 224, 229, 230, 235, 239, 244, 250, 255, 258, 264, 270, 275, 278, 283, 286, 291, 301, 305, 306, 422, 436

aidom.obtain_info/5 .. 35, 39, 43, 49, 55, 59, 73, 75, 84, 87, 91, 95, 100, 106, 109, 114, 117, 121, 125, 131, 133, 139, 146, 159, 165, 169, 172, 177, 181, 188, 191, 195, 197, 201, 205, 211, 217, 221, 226, 229, 232, 235, 241, 245, 251, 255, 260, 265, 271, 275, 280, 283, 288, 291, 303, 305, 308, 422, 438

aidom.part_conc/5 .... 36, 39, 44, 50, 56, 59, 73, 75, 85, 87, 92, 95, 100, 106, 109, 115, 117, 122, 125, 131, 133, 140, 146, 160, 166, 169, 173, 178, 181, 189, 191, 195, 197, 202, 206, 212, 218, 221, 227, 229, 233, 235, 242, 246, 252, 255, 260, 266, 272, 275, 281, 283, 289, 291, 304, 305, 308, 422, 439

aidom.project/6 ... 33, 39, 41, 47, 53, 59, 71, 75, 82, 87, 89, 95, 98, 104, 109, 112, 117, 119, 125, 129, 133, 137, 144, 157, 163, 169, 170, 175, 181, 186, 191, 193, 197, 199, 203, 209, 215, 221, 224, 229, 230, 235, 239, 243, 249, 255, 258, 263, 269, 275, 278, 283, 286, 291, 301, 305, 306, 422, 436

aidom.rename_auxinfo_asub/4 ... 36, 39, 44, 50, 56, 59, 74, 75, 85, 87, 92, 95, 100, 106, 109, 115, 117, 122, 125, 131, 133, 140, 146, 160, 166, 169, 173, 178, 181, 189, 191, 196, 197, 202, 206, 212, 218, 221, 227, 229, 233, 235, 242, 246, 252, 255, 261, 266, 272, 275, 281, 283, 289, 291, 304, 305, 309, 422, 439

aidom.special_builtin/6 .... 35, 39, 43, 49, 55, 59, 72, 75, 84, 87, 91, 95, 99, 105, 109, 113, 117, 121, 125, 130, 133, 139, 145, 159, 165, 169, 172, 177, 181, 188, 191, 194, 197, 201, 205, 211, 217, 221, 226, 229, 232, 235, 241, 245, 251, 255, 259, 265, 271, 275, 279, 283, 288, 291, 303, 305, 307, 422, 438

aidom.split_combined_domain/4 .... 35, 39, 43, 49, 55, 59, 72, 75, 84, 87, 91, 95, 99, 105, 109, 114, 117, 121, 125, 130, 133, 139, 145, 159, 165, 169, 172, 177, 181, 188, 191, 194, 197, 201, 205, 211, 217, 221, 226, 229, 232, 235, 241, 245, 251, 255, 259, 265, 271, 275, 280, 283, 288, 291, 303, 305, 308, 422, 438

aidom.success_builtin/7 .... 35, 39, 43, 49, 55, 59, 73, 75, 84, 87, 91, 95, 99, 105, 109, 114, 117, 121, 125, 130, 133, 139, 145, 159, 165, 169, 172, 177, 181, 188, 191, 195, 197, 201, 205, 211, 217, 221, 226, 229, 232, 235, 241, 245, 251, 255, 260, 265, 271, 275, 280, 283, 288, 291, 303, 305, 308, 422, 438

aidom.unknown_call/5 .... 36, 39, 44, 50, 56, 59, 73, 75, 85, 87, 92, 95, 100, 106, 109, 114, 117, 122, 125, 131, 133, 140, 146, 160, 166, 169, 173, 178, 181, 189, 191, 195, 197, 202, 206, 212, 218, 221, 227, 229, 233, 235, 242, 246, 252, 255, 260, 266,

272, 275, 280, 283, 289, 291, 304, 305, 308, 422, 439
aidom.unknown_entry/4 ... 36, 39, 44, 50, 56, 59, 73, 75, 85, 87, 92, 95, 100, 106, 109, 114, 117, 122, 125, 131, 133, 140, 146, 160, 166, 169, 173, 178, 181, 189, 191, 195, 197, 202, 206, 212, 218, 221, 227, 229, 233, 235, 242, 246, 252, 255, 260, 266, 272, 275, 280, 283, 289, 291, 304, 305, 308, 422, 439
aidom.widen/4 ..... 34, 39, 42, 48, 54, 59, 71, 75, 83, 87, 90, 95, 98, 104, 109, 112, 117, 120, 125, 129, 133, 138, 144, 158, 164, 169, 170, 176, 181, 187, 191, 193, 197, 199, 204, 210, 216, 221, 224, 229, 230, 235, 239, 244, 250, 255, 258, 264, 270, 275, 278, 283, 287, 291, 301, 305, 306, 422, 436
aidom.widencall/4 .... 33, 39, 41, 48, 53, 59, 71, 75, 82, 87, 89, 95, 98, 104, 109, 112, 117, 119, 125, 129, 133, 137, 144, 157, 164, 169, 170, 176, 181, 186, 191, 193, 197, 199, 203, 209, 215, 221, 224, 229, 230, 235, 239, 243, 249, 255, 258, 263, 269, 275, 278, 283, 286, 291, 301, 305, 306, 422, 436
aidomain ... 37, 45, 51, 57, 74, 86, 93, 101, 108, 115, 123, 132, 141, 156, 161, 167, 173, 179, 190, 196, 202, 207, 213, 219, 227, 233, 242, 247, 253, 261, 267, 273, 281, 290, 304, 309, 440
aidomain/1 ..... 11, 15, 33, 39, 41, 47, 53, 59, 70, 75, 82, 87, 89, 95, 97, 103, 109, 111, 117, 119, 125, 128, 133, 137, 143, 157, 163, 169, 170, 175, 181, 186, 191, 192, 197, 199, 203, 209, 215, 221, 224, 229, 230, 235, 239, 243, 249, 255, 257, 263, 269, 275, 277, 283, 286, 291, 301, 305, 422, 436, 453, 456, 461, 463
Alejandro Serrano 75
all_assertions_pred/4 ..... 493, 494
all_different_mods/0 ..... 501, 503
all_terms_identical/2 ..... 181, 184
Amadeo Casas 377
amgu/4 ..... 191, 229, 235
amgu/5 422
analysis/1 ..... 24, 26, 453, 454, 456
analysis/4 ..... 453, 456
analysis_module/2 ..... 453, 456
analysis_opt/1 584
analysis_start/2 584
analysis_stats 15, 448, 457, 464, 478, 494, 498, 506, 508, 560, 579
analysis_task/4 597
analyze/1 ..... 24, 453
analyze/2 ..... 453, 454
analyze/7 ..... 559, 560
analyze_driver ... 15, 23, 24, 26, 448, 453, 460, 464, 494, 498, 590
analyze1/2 ..... 24, 453, 454
analyzed_mods/1 ..... 501, 504
analyzer output 343, 344
annotators-jlp 312
apply_assertions 411, 480, 519
apply_assertions_inc 494
apply_assertions_old 74, 86, 415, 519, 562
apply_assrt_call_to_success/8 412
apply_assrt_exit/7 ..... 412, 413
apply_assrt_no_source/6 ..... 412, 413
apply_success_policy/9 481
approx/1 ..... 399, 401, 402, 403, 405, 406
approx/6 ..... 561, 562
arg_filtering 460
argnames 15, 449, 536
arithmetic ... 15, 26, 37, 45, 51, 57, 74, 86, 93, 101, 108, 115, 123, 132, 141, 156, 161, 167, 173, 179, 190, 196, 202, 207, 213, 219, 227, 233, 242, 247, 253, 261, 267, 273, 281, 290, 304, 309, 336, 337, 350, 354, 375, 381, 387, 390, 393, 396, 397, 406, 408, 415, 440, 449, 452, 457, 460, 464, 468, 471, 478, 480, 482, 488, 494, 498, 500, 504, 506, 508, 511, 519, 536, 540, 548, 549, 554, 560, 562, 572, 579, 581, 585, 590, 592, 596, 598
arrays 37
assert-lang-disciplbook 325, 335
assert_domain/1 ..... 24, 453
assertion body syntax 345, 348, 349
assertion language 1, 3
assertion status 339, 340, 341
assertion_set_calls/3 ..... 527, 534
assertion_set_comp/3 ..... 527, 534
assertion_set_head/3 ..... 527, 533
assertion_set_status/3 ..... 527, 533
assertion_set_success/3 ..... 527, 534
assertions .. 15, 26, 45, 51, 57, 74, 86, 108, 115, 123, 132, 141, 156, 161, 167, 179, 190, 196, 202, 207, 213, 227, 233, 242, 247, 253, 261, 267, 281, 290, 304, 309, 335, 345, 350, 354, 357, 375, 381, 387, 390, 393, 396, 397, 406, 408, 415, 440, 449, 452, 457, 460, 464, 468, 471, 478, 480, 482, 488, 494, 498, 500, 504, 506, 508, 511, 519, 536, 540, 548, 549, 554, 560, 562, 572, 579, 581, 585, 590, 592, 596, 598

assertions/assertions_basic ... 15, 26, 45, 51, 57, 74, 86, 108, 115, 123, 132, 141, 156, 161, 167, 179, 190, 196, 202, 207, 213, 227, 233, 242, 247, 253, 261, 267, 281, 290, 304, 309, 336, 350, 354, 375, 381, 387, 390, 393, 396, 397, 406, 408, 415, 440, 449, 452, 457, 460, 464, 468, 471, 478, 480, 482, 488, 494, 498, 500, 504, 506, 508, 511, 519, 536, 540, 548, 549, 554, 560, 562, 572, 579, 581, 585, 590, 592, 596, 598
assertions/native_props ... 408
assertions_basic ... 336
assertions_props ... 336, 345, 354
assoc ... 74, 290, 304
assrt_body/1 ... 336, 337, 339, 341, 342, 345, 355
assrt_db ... 525
assrt_lib ... 15, 415, 448, 452, 480, 536
assrt_norm ... 525
assrt_status/1 ... 337, 338, 339, 340, 341, 342, 345, 349, 355
assrt_type/1 ... 345, 350
assrt_used_as_entry/2 ... 22, 443, 444
assrt_write ... 452
asub/1 ... 107
asub/4 ... 125, 128, 133, 137
asub_elem/1 ... 107
asub_gt/2 ... 235, 236
asub_to_info/5 ... 422, 432, 489
asub_to_native/5 ... 39, 40, 181, 183, 221, 223, 235, 237, 275, 276
asub_to_native/6 ... 422, 432, 489
atm/1 ... 13, 14, 67, 149, 150, 151, 152, 153, 154, 155, 357, 360, 412, 413, 414, 415, 423, 424, 425, 426, 427, 428, 429, 430, 431, 432, 433, 434, 444, 445, 446, 455, 468, 469, 470, 475, 476, 477, 480, 486, 487, 493, 494, 496, 498, 501, 503, 505, 507, 513, 514, 515, 516, 517, 518, 519, 530, 531, 532, 535, 543, 544, 545, 546, 547, 553, 565, 566, 567, 568, 569, 591, 592, 593, 594
atm_or_atm_list/1 ... 357, 369, 532
atom/1 ... 445, 591
atomic_basic .. 15, 26, 37, 45, 51, 57, 74, 86, 93, 101, 108, 115, 123, 132, 141, 156, 161, 167, 173, 179, 190, 196, 202, 207, 213, 219, 227, 233, 242, 247, 253, 261, 267, 273, 281, 290, 304, 309, 336, 350, 354, 375, 381, 387, 390, 393, 396, 397, 406, 408, 415, 440, 449, 452, 457, 460, 464, 468, 471, 478, 480, 482, 488, 494, 498, 500, 504, 506, 508, 511, 519, 536, 540, 548, 549, 554, 560, 562, 572, 579, 581, 585, 590, 592, 596, 598
augment_asub/3 ... 191, 229, 235, 236
augment_asub/4 ... 422, 423
augment_asub0/3 ... 191, 192
augment_two_asub/3 ... 229
augment_two_asub/4 ... 422, 423
auto_analyze/1 ... 11, 12, 13
auto_analyze/2 ... 11, 12
auto_check_assert/1 ... 11, 12, 13
auto_check_assert/2 ... 11, 12
auto_check_assrt/1 ... 12
auto_interface ... 11, 24, 25, 26
auto_optimize/1 ... 11, 12, 13
auto_optimize/2 ... 11, 12
aux_filenames ... 464, 468, 478

B

basic_props ... 15, 26, 45, 51, 57, 74, 86, 108, 115, 123, 132, 141, 156, 161, 167, 173, 179, 190, 196, 202, 207, 213, 227, 233, 242, 247, 253, 261, 267, 281, 290, 304, 309, 336, 350, 354, 357, 381, 387, 390, 393, 396, 397, 406, 408, 415, 440, 449, 452, 457, 460, 464, 468, 471, 478, 480, 482, 488, 494, 498, 500, 504, 506, 508, 511, 519, 536, 540, 548, 549, 554, 560, 562, 572, 579, 581, 585, 590, 592, 596, 598
basic_props:regtype/1 ... 351
basiccontrol .. 15, 26, 37, 45, 51, 57, 74, 86, 93, 101, 108, 115, 123, 132, 141, 156, 161, 167, 173, 179, 190, 196, 202, 207, 213, 219, 227, 233, 242, 247, 253, 261, 267, 273, 281, 290, 304, 309, 336, 350, 354, 375, 381, 387, 390, 393, 396, 397, 406, 408, 415, 440, 449, 452, 457, 460, 464, 468, 471, 478, 480, 482, 488, 494, 498, 500, 504, 506, 508, 511, 519, 536, 540, 548, 549, 554, 560, 562, 572, 579, 581, 585, 590, 592, 596, 598
basicmodes .. 51, 74, 86, 108, 132, 141, 156, 161, 167, 179, 261, 290, 304, 346, 449, 457, 460, 464, 536, 548, 549, 562
batch_analyze ... 594
bind_ins/1 ... 357, 360, 366, 374
binding/1 ... 107
binds/1 ... 107
bitcodesets ... 37
body/1 ... 547
body_builtin/9 ... 422, 435

body_succ_builtin/9 ..... 422, 431
bottom_up_delete_complete/5 ..... 499, 500
bottom_up_delete_completes_preds/4 499
bu_delete_clauses/2 ..... 495, 496
builtin predicate 524
builtin/2 537
bundle_paths 478, 536, 596, 598
bytelist/1 ..... 357, 368

C

c_assrt_body/1 ..... 337, 340, 345, 348
c_itf 464, 478, 536
c_itf_props 478, 536
call/1 348
call_asr/5 412
call_to_entry 421
call_to_entry/10 ..... 422, 423
call_to_entry/9 ... 39, 151, 181, 182, 191, 197, 221, 229, 235, 275
call_to_prime_fact/6 ..... 181, 182, 191, 192, 221, 222, 235, 237, 275, 276
call_to_success_builtin/6 ..... 181, 183, 192, 221, 223, 235, 238, 275, 277
call_to_success_builtin/7 439
call_to_success_fact/10 ..... 422, 430
call_to_success_fact/9 ..... 39, 40, 181, 182, 191, 192, 197, 198, 221, 222, 235, 237, 275, 276
callable/1 ..... 357, 363
caller_module/2 ..... 465, 466
calls assertion 337
calls/1 ..... 19, 336, 337, 340, 485
calls/2 ..... 19, 336, 337, 485
cardinality/3 389
caslog 32, 402, 404
cgoal/1 ..... 61, 62, 65, 66, 67, 77, 79, 80, 149, 150, 152, 153, 154, 183, 223, 293, 294, 295, 297, 298, 299, 357, 362, 372, 373, 374, 389, 390, 403, 404, 405, 406, 433, 434, 444, 486, 530, 542, 544
change_id_clause/2 501
change_open_mode/2 ..... 473, 476
change_values/4 ..... 181, 185
change_values_if_f/4 ..... 181, 185
change_values_if_not_g/4 ..... 181, 185
character string 335
character_code/1 ..... 357, 367, 368
check assertion 343
Check(X) 389
check/1 ..... 336, 343, 344, 357, 375
check_curr_entry_id/1 479
check_stop_one_module/1 473
checking the assertions 1, 3
chip-manual 325
Ciao Development Team 47, 59, 75, 175, 291
ciao-manual-1.10 325
ciaopp 17, 27, 335, 377, 442, 443, 453, 459
ciaopp(analysis_register) 457
ciaopp(ciaopp_options) 15, 26, 440, 449, 457, 460, 488, 519, 554, 562, 581
ciaopp(plai/notrace) 494, 498, 500
ciaopp-batch 589
ciaopp-sas03-journal-scp 335
ciaopp_batch 583
ciaopp_batch(ciaopp_batch) 319
ciaopp_batch(db_analysis) 589
ciaopp_batch_aux 590, 591, 596
ciaopp_log 15, 448, 457, 460, 464, 478, 494, 498, 506, 560
ciaopp_worker 589
CiaoPP development team 11
Claudio Vaucheret 59, 75, 103, 175, 291
clause(Clause) 543
clause(Clause0) 543
clause/1 ..... 541, 543, 545
clause_db 525
clause_key/2 541
clause_number/2 ..... 541, 542
clausebody/1 ..... 541, 545
clauses_keys/2 541
clean_all_ciaopp_db/0 ..... 20, 446
clean_analysis_info/0 ..... 453, 455
clean_analysis_info0/0 ..... 23, 453, 455
clean_ciaopp_db/1 ..... 20, 446
clean_db/0 ..... 593, 594, 597
clean_fixpoint_graph/0 581
clean_incanal_mod_data/0 ..... 501, 503
clean_incremental_db/0 501
clean_persistent_analysis/0 ..... 505, 506
clean_program_structure/0 ..... 465, 466
clean_rev_idx/1 ..... 565, 571
clean_tmp_db/0 ..... 593, 594
cleanup_applied_assertions/1 412
cleanup_comment_db/0 ..... 527, 532
cleanup_commented_assrt/0 ..... 527, 532
cleanup_fixpoint/1 ..... 513, 514, 561
cleanup_for_codegen/0 ..... 23, 453, 455

cleanup_history/0 ..... 22, 443, 444
cleanup_intermod/0 461
cleanup_intermod_scheduling/0 ..... 469, 470
cleanup_libcache/0 ..... 527, 534
cleanup_plai/1 559
cleanup_plai_db/1 ..... 565, 566
cleanup_program_keys/0 541
cleanup_punit/0 ..... 527, 533
cleanup_registry/1 ..... 465, 467
cleanup_tr_syntax/0 549
clid_of_atomid/2 ..... 541, 544
clique/1 ..... 379, 380
clique_1/1 ..... 379, 381
clique_make_decomposition/5 ..... 235, 238
clique_part_less_or_equal/2 ..... 235, 237
clkey/1 ..... 541, 542, 543, 546, 547
codegen 460, 464
collect_types_in_abs/4 ..... 422, 434
comdom 32
comment assertion 342
comment string 346, 348, 349
comment/2 ..... 336, 342
comments, machine readable 335
comp assertion 338
comp/1 ..... 19, 336, 338, 349, 485
comp/2 ..... 19, 336, 338, 485
compat/2 ..... 357, 369
compatibility properties 351
compatible 345
compiler 457
compiler/p_unit/p_unit_argnames 449, 536
complete/7 565
complete_id_key/3 ..... 565, 571
complete_key_from_id/3 ..... 565, 570
complete_parent/2 ..... 565, 566
complex argument property 345, 346, 348, 349
complex goal property 345, 347, 349
complex_arg_property/1 ..... 345, 346, 348, 349
complex_goal_property/1 ..... 345, 347, 349
computational cost 1, 3
compute/9 ..... 513, 516
compute_change 518
compute_glb/3 ..... 422, 427
compute_imported_modules/0 ..... 473, 477
compute_intermodule_graph/1 473
compute_lub/2 ..... 39, 181, 182, 221, 222, 235, 237, 275, 276
compute_lub/3 ..... 422, 427
compute_lub_el/3 ..... 39, 40, 181, 182, 197, 198
compute_lub_sh/3 ..... 181, 182
compute_punit_modules/2 474
compute_punit_modules/3 473
compute_type/3 ..... 291, 295
compute_upper_amgu/2 ..... 235, 238
concrete/4 ..... 422, 432
condcomp 15, 26, 37, 45, 51, 57, 74, 86, 93, 101, 108, 115, 123, 132, 141, 156, 161, 167, 173, 179, 190, 196, 202, 207, 213, 219, 227, 233, 242, 247, 253, 261, 267, 273, 281, 290, 304, 309, 336, 350, 354, 375, 381, 387, 390, 393, 396, 397, 406, 408, 415, 440, 449, 452, 457, 460, 464, 468, 471, 478, 480, 482, 488, 494, 498, 500, 504, 506, 508, 511, 519, 536, 540, 548, 549, 554, 560, 562, 572, 579, 581, 585, 590, 592, 596, 598
config_common 585
config_incremental_load/1 ..... 493, 494
consind-toplas 312
constant/1 ..... 357, 362
constraint/1 397
contains_parameters/2 ..... 422, 435
cost/4 ..... 399, 405
cost_expression/1 ..... 399, 400, 401, 402, 403, 404, 405, 406
costb/4 ..... 399, 405
counter/3 ..... 541, 546
counters 457, 464, 480, 560
covered/1 ..... 383, 385
covered/2 ..... 379, 380
covering/3 ..... 181, 184
ctcheck_sum(S) 454
ctcheck_sum/1 ..... 24, 453, 454
ctchecks_common 457
ctchecks_pp 457
ctchecks_pred 457, 464
ctrlcclean 478
curr_entry_id/1 479
current module 441
current_pp_flag/2 ..... 17, 483
current_task_proc/2 ..... 593, 594
customize/0 ..... 11, 12, 25
customize/1 ..... 11, 12
customize_and_preprocess/0 ..... 11, 13, 25
customize_and_preprocess/1 ..... 11, 13
customize_but_dont_save/1 ..... 11, 13

D

Daniel Cabeza 357
Dart-Zobel 47, 59, 291
data declaration 331
datadir 536, 596
datafacts 15, 37, 45, 86, 101, 108, 173, 190, 415, 449, 452, 457, 460, 464, 468, 471, 478, 480, 482, 488, 494, 498, 500, 504, 506, 508, 519, 536, 548, 549, 554, 562, 572, 579, 581, 585, 590, 596, 598
datafacts_rt 15, 37, 45, 86, 101, 108, 173, 190, 415, 448, 452, 457, 460, 464, 468, 471, 478, 480, 482, 488, 494, 498, 500, 504, 506, 508, 519, 536, 548, 549, 554, 562, 572, 579, 581, 585, 590, 596, 598
db_analysis 584, 585, 590, 593, 598
db_data_dir/1 ..... 593, 595
dcg 15
Debug_plai 489
debugger_support .. 15, 26, 37, 45, 51, 57, 74, 86, 93, 101, 108, 115, 123, 132, 141, 156, 161, 167, 173, 179, 190, 196, 202, 207, 213, 219, 227, 233, 242, 247, 253, 261, 267, 273, 281, 290, 304, 309, 336, 350, 354, 375, 381, 387, 390, 393, 396, 397, 406, 408, 415, 440, 449, 452, 457, 460, 464, 468, 471, 478, 480, 482, 488, 494, 498, 500, 504, 506, 508, 511, 519, 536, 540, 548, 549, 554, 560, 562, 572, 579, 581, 585, 590, 592, 596, 598
debugging_in_ciaopp 325
decl assertion 342
decl/1 ..... 336, 342, 345
decl/2 ..... 336, 342
decode_clkey/4 ..... 541, 543
decode_entrykey/4 ..... 541, 543
decode_litkey/5 ..... 541, 543
decode_predkey/3 ..... 541, 543
def 39, 93, 207, 253, 440
define_flag 536
define_flag/3 ..... 527, 535
deftools 45, 115
deftypes 47, 440
del(Pos, Elem) 511
del_assertion_source_db/1 ..... 501, 503
del_parent/4 ..... 565, 569
del_parent_complete/6 ..... 565, 568
del_strategy 491
delete_complete/3 ..... 565, 569
delete_plai_db_one_clause/4 ..... 565, 569
deprecated/1 ..... 342, 357, 370
depthk 53, 440
det/1 ..... 383, 530, 531
det_abs_sort/2 126
det_asub/1 ..... 125, 128
det_asub_to_native/5 ..... 125, 127
det_call_to_entry/9 125
det_call_to_success_fact/9 126
det_collect_auxinfo_asub/3 ..... 125, 128
det_combined_special_builtin0/2 ..... 125, 127
det_compute_clauses_lub/3 ..... 125, 126
det_compute_lub/2 126
det_dom_statistics/1 ..... 125, 127
det_eliminate_equivalent/2 ..... 125, 126
det_empty_entry/3 127
det_exit_to_prime/7 125
det_extend/5 126
det_glb/3 126
det_identical_abstract/2 126
det_init_abstract_domain/1 125
det_input_interface/4 127
det_input_user_interface/5 127
det_less_or_equal/2 126
det_obtain_info/4 ..... 125, 127
det_project/5 126
det_rename_auxinfo_asub/3 ..... 125, 128
det_special_builtin/5 ..... 125, 127
det_split_combined_domain/3 ..... 125, 127
det_success_builtin/6 127
det_unknown_call/4 127
det_unknown_entry/3 127
det_widen/3 ..... 125, 126
det_widencall/3 ..... 125, 126
detabs 132
determ-lopstr04 ..... 383, 384, 386
determinacy 1, 3
determinacy-ngc09 ..... 383, 384, 386
determinate_sel/3 ..... 59, 70
detplai 125, 440
dictionary/1 ..... 345, 348
diff 494, 509
diff/4 510
diff_item/1 ..... 510, 511
difflsign_abs_sort/2 ..... 117, 118
difflsign_asub_to_native/5 ..... 117, 118
difflsign_call_to_entry/9 117
difflsign_call_to_success_fact/9 117
difflsign_compute_lub/2 117

difflsign_empty_entry/3 ..... 117, 119
difflsign_exit_to_prime/7 ..... 117, 118
difflsign_extend/5 ..... 117, 118
difflsign_glb/3 ..... 117, 118
difflsign_input_interface/4 ..... 117, 118
difflsign_input_user_interface/5 ..... 117, 118
difflsign_less_or_equal/2 ..... 117, 118
difflsign_project/5 ..... 117, 118
difflsign_special_builtin/5 ..... 117, 118
difflsign_success_builtin/6 ..... 117, 118
difflsign_unknown_call/4 ..... 117, 118
difflsign_unknown_entry/3 ..... 117, 119
doc/2 ..... 336, 342
docstring/1 ..... 335, 342, 345, 346, 348, 349, 350
dom_statistics/2 ..... 422, 435
domain/1 ..... 23, 455
domains 37, 45, 51, 57, 74, 86, 93, 101, 108, 115, 123, 132, 141, 156, 161, 167, 173, 179, 190, 196, 202, 207, 213, 219, 227, 233, 242, 247, 253, 261, 267, 273, 281, 290, 304, 309, 415, 421, 441, 480, 482, 498, 500, 504, 519, 524, 554, 557, 560, 562
drid/1 547
driver 441
dual_widen/4 ..... 422, 426
dual_widencall/4 ..... 422, 426
dump/1 ..... 21, 447
dump/2 ..... 20, 446
dump_dir/1 ..... 20, 446
dump_file/4 591
dump_flags/1 ..... 483, 486
dump_flags_list 486
dump_flags_list/2 ..... 461, 463, 483, 488
dynamic 464
dynamic declaration 331
dynamic_or_unknown_predicate/1 ..... 527, 529
dynamic_rt 464

E

Edison Mera 377, 407
eliminate_couples_clique/4 ..... 235, 238
eliminate_equivalent/2 ..... 235, 236
eliminate_equivalent/3 ..... 422, 430
eliminate_non_element/4 ..... 181, 184
emacs 9, 11
empty_entry/3 .. 39, 41, 181, 183, 197, 198, 221, 223, 238, 275, 276
empty_entry/4 ..... 422, 433
end_view/0 581
engine(basic_props) 524
ensure_libcache_loaded/0 ..... 21, 443, 446
ensure_registry_file/3 ..... 473, 475
entry assertion 340
entry declaration 331
entry/1 ..... 19, 336, 340, 348, 485
entry_assertion/3 ..... 22, 443, 444
entry_point/5 ..... 559, 560
entry_policy 479
entry_to_exit/7 ..... 513, 514
entry_to_exit/9 ..... 561, 562
enum_mod_typedb/1 ..... 465, 468
equiv/2 ..... 357, 358, 374
erase_directive/1 ..... 527, 529
erase_last_memo_table/3 ..... 565, 570
erase_previous_memo_lubs/2 ..... 565, 570
erase_previous_memo_tables_and_parents/4 .. 565, 570
erase_previous_parents_info/5 ..... 565, 570
errhandle 478
error_free/1 ..... 357, 374
eterms 59, 75, 86, 132, 141, 227, 261, 290, 440
eterms-sas02 ..... 32, 563
eterms_abs_sort/2 ..... 59, 63
eterms_arg_call_to_success/9 ..... 59, 67
eterms_asub/1 ..... 60, 61, 62, 63, 64, 65, 66, 68
eterms_asub_to_native/5 ..... 59, 68
eterms_call_to_entry/9 ..... 59, 61
eterms_call_to_success_builtin/6 ..... 59, 67
eterms_call_to_success_fact/9 ..... 59, 66
eterms_collect_auxinfo_asub/3 ..... 59, 69
eterms_compute_lub/2 ..... 59, 60
eterms_compute_lub_el/3 ..... 59, 60
eterms_concrete/3 ..... 59, 64
eterms_empty_entry/3 ..... 59, 65
eterms_exit_to_prime/7 ..... 59, 62
eterms_extend/5 ..... 59, 63
eterms_extrainfo(ExtraInfo) 61, 62
eterms_extrainfo/1 ..... 61, 62
eterms_glb/3 ..... 59, 64
eterms_glbnames/3 ..... 59, 64
eterms_identical_abstract/2 ..... 59, 69
eterms_init_abstract_domain/1 ..... 59, 60
eterms_input_interface/4 ..... 59, 68
eterms_input_user_interface/5 ..... 59, 68
eterms_less_or_equal/2 ..... 59, 64
eterms_multi_part_conc/3 ..... 59, 70

eterms_needs/1 ..... 59, 60
eterms_obtain_info/4 ..... 59, 68
eterms_output_interface/2 ..... 59, 68
eterms_part_conc/4 ..... 59, 70
eterms_project/5 ..... 59, 63
eterms_rename_auxinfo_asub/3 ..... 59, 69
eterms_special_builtin/5 ..... 59, 66
eterms_success_builtin/6 ..... 59, 67
eterms_unknown_call/4 ..... 59, 65
eterms_unknown_entry/3 ..... 59, 64
eterms_widen/3 ..... 59, 60
eterms_widencall/3 ..... 59, 60
etermsvar 75, 440
etermsvar_abs_sort/2 ..... 75, 77
etermsvar_arg_call_to_success/9 ..... 75, 80
etermsvar_asub_to_native/5 ..... 75, 81
etermsvar_call_to_entry/9 ..... 75, 76
etermsvar_call_to_success_builtin/6 ..... 75, 81
etermsvar_call_to_success_fact/9 ..... 75, 79
etermsvar_collect_auxinfo_asub/3 ..... 75, 81
etermsvar_compute_lub/2 ..... 75, 76
etermsvar_compute_lub_el/3 ..... 75, 76
etermsvar_concrete/3 ..... 75, 78
etermsvar_empty_entry/3 ..... 75, 79
etermsvar_exit_to_prime/7 ..... 75, 77
etermsvar_extend/5 ..... 75, 78
etermsvar_glb/3 ..... 75, 78
etermsvar_identical_abstract/2 ..... 75, 82
etermsvar_init_abstract_domain/1 75
etermsvar_input_interface/4 ..... 75, 81
etermsvar_input_user_interface/5 ..... 75, 81
etermsvar_less_or_equal/2 ..... 75, 78
etermsvar_multi_part_conc/3 ..... 75, 82
etermsvar_needs/1 ..... 75, 76
etermsvar_obtain_info/4 ..... 75, 81
etermsvar_output_interface/2 ..... 75, 81
etermsvar_part_conc/4 ..... 75, 82
etermsvar_project/5 ..... 75, 77
etermsvar_rename_auxinfo_asub/3 ..... 75, 81
etermsvar_special_builtin/5 ..... 75, 80
etermsvar_success_builtin/6 ..... 75, 80
etermsvar_unknown_call/4 ..... 75, 79
etermsvar_unknown_entry/3 ..... 75, 79
etermsvar_widen/3 ..... 75, 76
etermsvar_widencall/3 ..... 75, 76
eval/1 ... 357, 358, 359, 360, 361, 362, 363, 364, 365, 366, 367, 368, 369, 370, 374
example 371
example/1 ..... 357, 371
exception/1 391
exception/2 391
exceptions ... 15, 26, 37, 45, 51, 57, 74, 86, 93, 101, 108, 115, 123, 132, 141, 156, 161, 167, 173, 179, 190, 196, 202, 207, 213, 219, 227, 233, 242, 247, 253, 261, 267, 273, 281, 290, 304, 309, 336, 350, 354, 375, 381, 387, 390, 393, 396, 397, 406, 408, 415, 440, 449, 452, 457, 460, 464, 468, 471, 478, 480, 482, 488, 494, 498, 500, 504, 506, 508, 511, 519, 536, 540, 548, 549, 554, 560, 562, 572, 579, 581, 585, 590, 592, 596, 598
exit assertion 341
exit/1 ..... 336, 340, 341
exit/2 ..... 336, 341
exit_to_prime 421
exit_to_prime/7 ... 39, 151, 181, 182, 191, 197, 221, 222, 235, 275
exit_to_prime/8 ..... 422, 424
exp/1 400
exp/2 400
exports 407
extend/4 151
extend/5 ... 39, 40, 181, 182, 197, 221, 222, 235, 236, 275, 276
extend/6 ..... 422, 428
external_calls/4 ..... 499, 500
extrainfo(ExtraInfo) 77
extrainfo/1 ..... 77, 107

F

fact/1 400
fails/1 383
false assertion 344
false/1 ..... 336, 343, 357, 375
fastrw 478
file_search_path/2 ..... 443, 448, 461, 463
filename/1 527
filter/2 ..... 357, 374
filtered_program_clauses/3 ..... 527, 528
find_list_entry/3 ..... 291, 295
finite_solutions/1 ..... 389, 390
first_key/2 ..... 541, 542
fixp_stick_to_calls 411
fixp_stick_to_success 411
fixpo_bu 560
fixpo_check_di 560

fixpo_check_di2 560
fixpo_check_di3 560
fixpo_check_di4 560
fixpo_check_di5 560
fixpo_check_reduced_di 560
fixpo_dd 452, 494, 498, 513, 557, 560
fixpo_del 557
fixpo_di 557, 560
fixpo_ops 15, 415, 440, 464, 482, 498, 504, 519, 560, 562
fixpo_ops:inexistent/1 514
fixpo_plai 557, 560, 561, 579
fixpo_plai_gfp 560
fixpoint/6 ..... 561, 562
fixpoint_compute_change/9 ..... 513, 518
fixpoint_id_/2 ..... 501, 504
fixpoint_trace/7 577
flag_value/1 ..... 20, 483, 485, 486
flag_values/1 ..... 357, 375, 535
flt/1 ..... 357, 359
foo.pl 408
foo_rtc.pl 408
force_analysis/1 ..... 469, 470
format 448, 452, 579, 596, 598
formatting commands 335
formulae 448
fr_abs_sort/2 ..... 95, 96
fr_asub_to_native/5 ..... 95, 97
fr_call_to_entry/9 95
fr_call_to_success_fact/9 95
fr_compute_lub/2 95
fr_empty_entry/3 ..... 95, 97
fr_exit_to_prime/7 95
fr_extend/5 ..... 95, 96
fr_glb/3 ..... 95, 96
fr_identical_abstract/2 ..... 95, 96
fr_input_interface/4 ..... 95, 96
fr_input_user_interface/5 ..... 95, 96
fr_less_or_equal/2 ..... 95, 96
fr_output_interface/3 ..... 95, 96
fr_project/5 ..... 95, 96
fr_sets 93, 101
fr_shared 93, 101
fr_special_builtin/5 ..... 95, 96
fr_success_builtin/6 ..... 95, 96
fr_top 93, 95, 440
fr_unknown_call/4 ..... 95, 97
fr_unknown_entry/3 ..... 95, 97
Francisco Bueno 59, 75, 175, 181, 221, 291, 325, 335, 351, 377, 421, 561
frdef 87, 440
frdef_abs_sort/2 ..... 87, 88
frdef_asub_to_native/5 ..... 87, 88
frdef_call_to_entry/9 87
frdef_call_to_success_fact/9 87
frdef_compute_lub/2 87
frdef_empty_entry/3 ..... 87, 89
frdef_exit_to_prime/7 87
frdef_extend/5 ..... 87, 88
frdef_glb/3 ..... 87, 88
frdef_identical_abstract/2 ..... 87, 88
frdef_input_interface/4 ..... 87, 88
frdef_input_user_interface/5 ..... 87, 88
frdef_less_or_equal/2 ..... 87, 88
frdef_project/5 ..... 87, 88
frdef_special_builtin/5 ..... 87, 88
frdef_success_builtin/6 ..... 87, 88
frdef_unknown_call/4 ..... 87, 89
frdef_unknown_entry/3 ..... 87, 89
freeness-iclp91 32
frontend_driver 15, 20, 21, 22, 23, 26, 415, 443, 453, 457, 459, 460, 464, 478, 488, 494, 498, 560, 590
fsyntax 15, 464
full-prolog-esop96 ..... 329, 335
full_info_to_asub/5 ..... 422, 432
func/1 348
functor1/2 ..... 15, 25

G

g_assrt_body/1 ..... 338, 345, 349
gallagher-types-iclp94 ..... 32, 292
gen_and_load_libcache/0 ..... 21, 443, 446
gen_libcache/1 ..... 527, 534
gen_registry_info/3 ..... 476, 477
generate_a_type_assignment/3 ..... 291, 295
generate_subs/3 ..... 59, 63
generate_subs_exit/4 ..... 59, 62
generate_trans_clauses/4 ..... 559, 560
generateSucc0_cond/5 ..... 59, 69
German Puebla 335
get_absint/4 553
get_all_module_cycles/2 ..... 473, 474
get_applicable_status/3 ..... 412, 415
get_assert_count/1 ..... 23, 453, 455

get_assertion/2 ..... 527, 529
get_call_assertions_asub/5 ..... 412, 414
get_call_from_call_assrt/7 ..... 527, 533
get_changed_registry/4 ..... 501, 503
get_clkey/4 ..... 541, 546
get_comment/1 ..... 527, 532
get_commented_assertion/2 ..... 527, 532
get_complete/8 ..... 565, 567
get_completes/4 ..... 553, 554
get_completes_lub/6 ..... 553, 554
get_current_assertions/1 ..... 501, 502
get_current_clauses/1 ..... 501, 502
get_data/2 ..... 20, 446
get_entry_info/3 479
get_free_vars/3 ..... 95, 97
get_imported_module_base/2 ..... 473, 477
get_info/5 553
get_list_names_is/2 ..... 59, 70
get_litkey/5 ..... 541, 547
get_memo_lub/5 553
get_memo_table/7 ..... 565, 567
get_menu_configs/1 13
get_menu_flag/3 14
get_mod_name_from_file/2 591
get_modules_analyzed/1 ..... 473, 477
get_output_operator/3 ..... 527, 532
get_output_package/1 ..... 527, 531
get_output_path/2 ..... 22, 443, 445
get_parent_key/4 ..... 565, 567
get_pred_mod_defined/2 ..... 527, 533
get_predkey/3 ..... 541, 546
get_predkeys/2 ..... 541, 546
get_punit_included_files/1 ..... 473, 474
get_punit_modules/1 ..... 473, 474
get_raw_success/6 ..... 565, 571
get_raw_success/7 ..... 565, 567
get_registry/4 ..... 465, 467
get_succ_assertion_asubs/7 ..... 412, 414
get_success_info/7 481
get_type/3 ..... 59, 60
get_var_types_by_unification/3 ..... 291, 295
getargtypes/6 ..... 59, 69
getfunctors/2 ..... 59, 69
getvalue/2 ..... 59, 69
getvalues_comp_cond/3 ..... 59, 70
glb/3 .. 39, 40, 182, 198, 221, 222, 235, 237, 275, 276
glb/4 ..... 422, 429
global_control 519
gnd/1 ..... 357, 361, 553, 554
gndstr/1 ..... 357, 362
GNU general public license 1, 3
gr 103, 440
gr_mode/1 107
granularity control 1, 3
granularity-jsc 312, 402, 404
ground/1 ..... 361, 362, 365, 366, 367, 368, 369, 370, 379, 381

H

hard side-effects 395
has_dump/2 505
head pattern 345, 346, 349
head/1 ..... 541, 547
head_pattern/1 ..... 342, 345, 346, 349
hentenwid/3 175
hermenegildo11:ciao-design-tplp 335
hiord 37, 74, 141, 449, 511, 536, 540
hiord_rt .. 15, 37, 51, 74, 86, 108, 132, 141, 156, 161, 167, 179, 190, 196, 202, 207, 213, 227, 233, 242, 247, 253, 261, 267, 290, 304, 375, 415, 440, 449, 452, 457, 460, 464, 468, 471, 478, 480, 482, 488, 494, 498, 500, 504, 508, 511, 519, 536, 540, 548, 549, 562, 572, 585, 590, 596
hiordlib 74, 464, 478, 504, 536
hook_cleanup_lib_regtypes/0 .. 443, 448, 527, 535, 537, 538
hook_compact_calls_prop/2 ..... 443, 447, 527, 535, 537, 538
hook_compact_global_prop/2 ... 443, 447, 527, 535, 537, 538
hook_insert_regtype/2 .... 443, 448, 527, 535, 537, 538
hook_legal_regtype/1 .. 443, 447, 527, 535, 537, 538
hook_menu_check_flag_value/3 ..... 11, 15
hook_menu_default_option/3 ..... 11, 15
hook_menu_flag_help/3 ..... 11, 15
hook_menu_flag_values/3 ..... 11, 15
hook_native_prop/2 .... 443, 447, 527, 535, 537, 538
hook_post_init_regtypes/0 ..... 443, 448, 527, 535, 537, 538
hook_pp_info_clause/3 .... 443, 447, 527, 535, 537, 538
hook_pp_info_lit/4 .... 443, 447, 527, 535, 537, 538
hook_restore_lib_regtypes/1 .. 443, 448, 527, 535, 537, 538

hook_save_lib_regtypes/1 ..... 443, 448, 527, 536, 537, 538

I

identical_abstract/2 ..... 197, 198, 235, 236
identical_abstract/3 ..... 422, 428
identical_proj/5 ..... 422, 427
identical_proj_1/7 ..... 422, 428
idlists 37, 132, 141, 309, 508
imported_module/2 ..... 465, 466
inc-fixp-sas 314
inc_add_source_clauses/3 507
inc_persistent_status/1 ..... 505, 506
incanal 448, 457, 491
incanal-toplas 314
incanal_db 494, 498, 501
incanal_deletion 498, 499
incanal_driver 491, 494, 495
incanal_persistent_db 494, 505
incremental_analyze/1 ..... 491, 493, 494
incremental_analyze/2 ..... 491, 493
incremental_module/1 ..... 491, 493
incremental_module/2 ..... 491, 493, 503
incrementally_update_analysis/2 ..... 495, 497
indep/1 ..... 379, 380, 381
indep/2 ..... 379, 381
indexvar/1 ..... 399, 400, 401
inductive_ctcheck/2 ..... 461, 462
inductive_ctcheck/4 ..... 461, 462
inductive_ctcheck_summary/3 ..... 461, 463
infer 441, 442, 551, 553
infer_db 15, 448, 457, 551, 554
infer_dom 15, 132, 141, 448, 457, 554
infercost 442
Inference of properties 1, 3
infernf 442
inferseff 457, 554
info_to_asub/7 ..... 422, 432
init_abstract_domain/2 422
init_analysis_db/0 ..... 593, 594
init_clkeys/0 501
init_empty_inc_analysis 495
init_empty_inc_analysis/0 495
init_file_inc_analysis/3 495
init_fixpoint/0 ..... 513, 514, 561
init_fixpoint/1 ..... 559, 560
init_rev_idx/1 ..... 565, 571
init_tasks_db/0 ..... 597, 598
init_tmp_db/1 ..... 593, 594
initial .. 15, 26, 37, 45, 51, 57, 74, 86, 93, 101, 108, 115, 123, 132, 141, 156, 161, 167, 173, 179, 190, 196, 202, 207, 213, 219, 227, 233, 242, 247, 253, 261, 267, 273, 281, 290, 304, 309, 336, 350, 354, 375, 381, 387, 390, 393, 396, 397, 406, 408, 415, 440, 449, 452, 457, 460, 464, 468, 471, 478, 480, 482, 488, 494, 498, 500, 504, 506, 508, 511, 519, 536, 540, 548, 549, 554, 560, 562, 572, 579, 581, 585, 590, 592, 596, 598
inject_output_package/1 ..... 527, 531
inner 407
input_interface/4 .. 39, 40, 183, 198, 221, 223, 237, 277
input_interface/5 440
input_user_interface/5 ..... 39, 40, 169, 183, 198, 221, 223, 237, 276
input_user_interface/6 440
ins(Pos, Elem) 511
insert_after_clkey/2 501
insert_each/3 ..... 181, 185
inst/2 ..... 357, 370
instantiation properties 351
int/1 .... 357, 358, 389, 390, 469, 470, 518, 532, 565, 566, 567
integer/1 ..... 347, 470
inter-modular analysis 314
intermod 15, 457, 461
intermod_analyze/2 461
intermod_analyze/3 ..... 461, 462
intermod_ctcheck/2 ..... 461, 462
intermod_ctcheck_opt/2 ..... 461, 463
intermod_ctcheck_opt/3 ..... 461, 463
intermod_db 452, 464, 465, 471, 478, 480, 482
intermod_entry 464, 479, 498, 560
intermod_entry_point/7 479
intermod_ops 448, 457, 464, 478, 480, 482, 498
intermod_punit 464, 471, 473, 482
intermod_schedule 464, 469
intermod_simp_libs/2 ..... 461, 462
intermod_simp_libs/3 ..... 461, 462
intermod_success 481
intermod_transform/3 ..... 461, 462
internal_module_id/1 ..... 357, 363
internals 449, 464, 536
invalid_call/6 ..... 565, 566
inverse_rewrite_source_body/2 ..... 541, 542

inverse_rewrite_source_program_cl/2 ... 541, 542
io_alias_redirection ... 590
io_basic 15, 37, 57, 108, 115, 190, 309, 449, 452, 478, 488, 579, 585, 590
is_checker/1 ... 559
is_clause/4 ... 541, 544
is_clkey/1 ... 541, 544
is_det/1 ..... 358, 359, 360, 361, 362, 363, 364, 365, 383, 386, 413, 424, 425, 426, 427, 428, 429, 430, 434, 435, 467, 474, 475, 476, 477, 496, 497, 499, 515, 516, 517, 518, 519, 567
is_directive/3 ... 541, 544
is_entrykey/1 ... 541, 544
is_library/1 ... 20, 22, 443, 444
is_litkey/1 ... 541, 544
is_naive_scheduling/1 ... 469, 471
Isabel Garcia-Contreras ... 143, 317, 319, 321, 411, 451, 461, 489, 491, 495, 499, 507, 509, 583, 589, 593
iso-prolog ... 325
iso/1 ... 357, 370
ISO-Prolog ... 325
isomodes .. 15, 190, 196, 202, 207, 213, 227, 233, 242, 247, 253, 267, 346, 415, 440, 452, 468, 471, 480, 482, 488, 498, 500, 504, 508, 519, 572, 585, 596
iterations/1 ... 469, 470
itf_db ... 525
ivar/1 ... 379, 380

J

jacobs88 ... 379
janss92 ... 32
Jorge Navas ... 191, 197, 203, 229, 235, 243, 249, 263
Jose F. Morales ... 143, 377, 421, 509

K

Kalyan Muthukumar ... 221, 561
keys ... 37, 309
keys_same_value/3 ... 59, 67
kind_of_info/7 ... 553, 554
knuth-lit ... 335

L

language_extension/2 ... 443
language_output_extension/2 ... 23, 443
last_clause/1 ... 541, 542
last_domain_used/1 ... 24, 453
last_file_log/2 ... 593, 594
lazy_analysis/1 ... 453, 456
leaves_choicepoints/1 ... 383, 386
less_or_equal/2 .... 39, 41, 169, 183, 198, 221, 223, 235, 236, 275, 277
less_or_equal/3 ... 422, 429
less_or_equal_proj/5 ... 422, 429
Leuschel:SAS98 ... 312
library ... 476
library(assertions/native_props) ... 524
library(isomodes) ... 346
library_directory/1 ... 443, 448, 461, 463
linear/1 ... 379, 380
list/1 .. 61, 62, 63, 64, 65, 66, 67, 68, 77, 78, 79, 80, 149, 150, 151, 152, 153, 154, 155, 183, 223, 293, 294, 295, 296, 297, 298, 299, 357, 364, 365, 366, 370, 390, 391, 412, 413, 414, 415, 424, 425, 427, 433, 434, 467, 468, 471, 474, 475, 477, 493, 494, 495, 496, 498, 502, 503, 504, 505, 507, 508, 510, 511, 513, 514, 515, 517, 518, 528, 529, 531, 533, 546, 568, 571, 584, 597
list/2 .. 13, 23, 60, 76, 292, 347, 357, 365, 424, 444, 455, 456, 462, 470, 474, 510, 515, 516, 519, 527, 528, 529, 542, 546, 554, 565, 566, 578
lists 15, 37, 57, 74, 86, 93, 115, 132, 141, 173, 190, 196, 202, 213, 227, 233, 242, 247, 261, 267, 281, 290, 304, 309, 336, 338, 415, 440, 448, 452, 464, 471, 480, 482, 488, 494, 498, 500, 504, 508, 511, 519, 536, 540, 548, 549, 554, 560, 562, 585, 590, 592
lit_ppkey/3 ... 541, 544
literal ... 408
literal_ppkey(Arg1) ... 544
literal_ppkey/1 ... 541, 544, 545
litkey/1 ..... 541, 543, 544, 545, 547, 566, 567, 568
llists ... 15, 37, 219, 273, 281, 464
lnewiden_el/4 ... 59
load_config(X) ... 494
load_config/1 ... 494
load_libcache/1 ... 527, 534
load_persistent_if_needed/2 ... 505
loaded_analysis/1 ... 453, 456
loaded_libcache/0 ... 527, 534
loaded_mods/1 ... 501, 503
local_ana_module/2 ... 465
log/1 ... 400

log/2 ... 400
log10/1 ... 400
log2/1 ... 400
logged_once_port_reify/4 ... 589
long ... 408
low-bounds-ilps97 ... 32, 404
low_level_props ... 440
lpdoc ... 1, 3, 335, 342, 346, 350
lpdoc-tr ... 335
lsets ... 115, 190, 196, 202, 213, 219, 227, 233, 242, 247, 281, 309
Lsign ... 32
lsign ... 109, 123, 440
lsign_abs_sort/2 ... 109, 111
lsign_abs_subset/2 ... 109, 110
lsign_asub_to_native/5 ... 109, 110
lsign_call_to_entry/9 ... 109
lsign_call_to_success_fact/9 ... 109
lsign_compute_lub/2 ... 109, 110
lsign_eliminate_equivalent/2 ... 109, 110
lsign_empty_entry/3 ... 109, 111
lsign_exit_to_prime/7 ... 109, 110
lsign_extend/5 ... 109, 110
lsign_glb/3 ... 109, 110
lsign_global_info/5 ... 109, 110
lsign_init_abstract_domain/1 ... 109
lsign_input_interface/4 ... 109, 110
lsign_input_user_interface/5 ... 109, 110
lsign_less_or_equal/2 ... 109, 110
lsign_output_interface/2 ... 109, 111
lsign_project/5 ... 109, 110
lsign_propagate_fixpoint/8 ... 109, 111
lsign_special_builtin/5 ... 109, 111
lsign_success_builtin/6 ... 109, 111
lsign_sum/3 ... 109, 111
lsign_unknown_call/4 ... 109, 111
lsign_unknown_entry/3 ... 109, 111
lsigndiff ... 117, 440
lub/3 ... 221, 222, 275, 276
lub_complete/6 ... 565

M

main_module/2 ... 465
make_atom/2 ... 541, 542
make_dependence/5 ... 181, 185
make_dir_nofail/1 ... 591, 592
Manuel Hermenegildo ... 335, 345, 351, 357, 377
Maria Garcia de la Banda ... 181, 209, 221, 421, 561
mark_parents_change_list_scc/3 ... 513, 517
max/2 ... 400
may_be_var/2 ... 235, 237
mcctr-ai ... 314
measure_t/1 ... 399, 401, 402, 403
mem_usage ... 464, 560
member/2 ... 357, 366, 372
member_value_freeness_differ/3 ... 181, 185
memo/1 ... 357, 374
memo_call/5 ... 565, 566
memo_lub/5 ... 565, 566
memo_table/6 ... 565, 566
memo_table_id_key/3 ... 565, 571
memotable_trace/3 ... 577, 578
menu ... 15
menu_branch/3 ... 14, 24
menu_branch/4 ... 14, 24
menu_generator ... 14, 15, 488
menu_rt ... 14, 15
merge_parents/3 ... 565, 569
messages ... 15, 26, 37, 74, 86, 108, 115, 207, 242, 253, 304, 440, 448, 519, 536, 560, 562
messages_basic ... 457, 460, 464, 488, 498, 519, 548, 579
min/2 ... 400
minimal_functors ... 563
minimal_lists ... 563
mod-an-spec_tr_2003 ... 466
mod_plai/5 ... 559
mod_topdown_analysis/3 ... 559, 560
mod_typedb/2 ... 465, 468
moddesc/1 ... 528
mode ... 336, 346
modedef/1 ... 336, 341, 346
modes ... 1, 3, 478, 494, 551, 590
module declaration ... 332
module/1 ... 22, 24, 443, 444, 453
module/2 ... 443, 444
module_depth/2 ... 465, 466
module_has_entries/1 ... 495, 497
module_is_processable/1 ... 473, 475
module_processed/2 ... 469, 470
modules_analyzed/1 ... 469
mshare/1 ... 379
mshare/2 ... 379
multi/1 ... 383, 384, 530
multi_part_conc/4 ... 422, 434

multifile_predicate_names/1 ..... 527, 531
mut_exclusive/1 ..... 383, 384
myappend/3 ..... 235, 237
myers1986 509

N

n_assrt_body/5 ..... 348, 349
nabody/1 ..... 345, 348
naive_module_order/1 ..... 469, 470
naive_pending_modules/1 ..... 469, 470
Nataliia Stulova 407
native 448, 536, 537, 549
native properties 524
native/1 ..... 357, 358, 359, 360, 361, 362, 372, 380, 383, 387, 397, 539
native/2 ..... 357, 372, 379, 380, 381
native_prop_map/3 537
native_prop_term/1 537
native_props 108, 375, 379, 383, 389, 391, 395, 397, 399, 415, 440, 448, 457, 460, 464, 468, 471, 478, 480, 494, 498, 500, 519, 536, 540, 562, 572
native_props_cardinality 389
native_props_cost 399
native_props_exceptions 391
native_props_nfdet 383
native_props_polyhedral 397
native_props_rtc 377, 440
native_props_shfrg 379
native_props_sideff 395
native_to_prop/2 ..... 527, 528
native_to_props_visible/2 ..... 527, 529
nativeprops .. 108, 375, 415, 440, 449, 457, 460, 464, 468, 471, 478, 480, 494, 498, 500, 519, 536, 540, 562, 572
needs/1 181
needs/2 ..... 422, 425
new_predicate/3 ..... 527, 531
newer/2 591
nf_abs_sort/2 135
nf_asub/1 ..... 133, 134, 136
nf_asub_to_native/5 ..... 133, 135
nf_call_to_entry/9 133
nf_call_to_success_fact/9 135
nf_collect_auxinfo_asub/3 ..... 133, 137
nf_combined_special_builtin0/2 ..... 133, 135
nf_compute_clauses_lub/3 ..... 133, 134
nf_compute_lub/2 134
nf_dom_statistics/1 ..... 133, 136
nf_eliminate_equivalent/2 ..... 133, 134
nf_empty_entry/3 136
nf_exit_to_prime/7 133
nf_extend/5 134
nf_glb/3 134
nf_identical_abstract/2 135
nf_init_abstract_domain/1 133
nf_input_interface/4 135
nf_input_user_interface/5 135
nf_less_or_equal/2 135
nf_obtain_info/4 ..... 133, 136
nf_par_asub/2 ..... 133, 136
nf_pred_asub/1 ..... 133, 136
nf_pred_asub_sl(ASubL) 134
nf_pred_asub_sl(LubL) 134
nf_pred_asub_sl/1 ..... 133, 134, 136
nf_project/5 134
nf_rename_auxinfo_asub/3 ..... 133, 137
nf_special_builtin/5 ..... 133, 135
nf_split_combined_domain/3 ..... 133, 135
nf_success_builtin/6 135
nf_unknown_call/4 135
nf_unknown_entry/3 136
nf_widen/3 134
nf_widencall/3 ..... 133, 134
nfabs 141
nfdet 440
nfdet_common 554
nfplai 133, 440
nfplai-flops04 ..... 32, 383, 384, 385, 387
nlist/1 365
nlist/2 ..... 357, 365
nnegint/1 ..... 357, 358, 359
no 407, 408
no_choicepoints/1 ..... 24, 383, 386, 454
no_exception/1 391
no_exception/2 ..... 391, 392
no_rtcheck/1 ..... 357, 371, 372, 373, 379, 381, 384, 385, 386, 387, 389, 390, 395, 401, 402, 403, 404, 405, 406
no_signal/1 ..... 391, 392
no_signal/2 ..... 391, 392
non-failure 1, 3
non-failure-iclp97 ..... 32, 383, 384, 385, 387, 390
non_det/1 ..... 383, 386
nondet/1 ..... 383, 384, 533
nonground/1 ..... 379, 380

nonleftmost-lopstr05 312
nonrel_abs_sort/2 149
nonrel_amgu/5 148
nonrel_asub_to_native/6 154
nonrel_base.pl 143
nonrel_bot/2 147
nonrel_call_to_entry/10 149
nonrel_call_to_success_builtin/7 153
nonrel_call_to_success_fact/10 151
nonrel_compute_glb_elem/4 147
nonrel_compute_lub/3 151
nonrel_compute_lub_elem/4 148
nonrel_exit_to_prime/8 150
nonrel_extend/6 151
nonrel_glb/4 155
nonrel_identical_abstract/2 155
nonrel_input_interface/5 153
nonrel_input_user_interface/6 153
nonrel_intervals 143, 440
nonrel_less_or_equal/3 154
nonrel_less_or_equal_elem/3 147
nonrel_project/5 149
nonrel_special_builtin/6 152
nonrel_success_builtin/7 152
nonrel_top/2 147
nonrel_unknown_call/5 154
nonrel_unknown_entry/4 149
nonrel_var_elem/2 147
nonrel_widen/4 155
nonrel_widen_elem/4 148
nonrel_widencall/4 155
nonvar/1 ... 22, 23, 24, 60, 61, 62, 63, 64, 65, 66, 67, 68, 76, 77, 78, 79, 80, 81, 147, 148, 149, 150, 151, 152, 153, 154, 155, 156, 183, 223, 292, 293, 294, 295, 296, 297, 298, 299, 300, 358, 359, 360, 361, 362, 363, 364, 367, 412, 413, 414, 415, 423, 424, 425, 426, 427, 428, 429, 430, 431, 432, 433, 434, 444, 445, 454, 455, 459, 460, 462, 463, 467, 469, 470, 473, 474, 475, 476, 477, 479, 480, 481, 482, 496, 497, 498, 499, 500, 502, 507, 513, 514, 515, 516, 517, 518, 519, 528, 529, 531, 533, 545, 549, 554, 561, 567, 568, 569, 570, 571
normal_asub/2 ..... 59, 62
normalize 557
normalize_args 460, 560
normalize_asub/3 ..... 422, 427
nortchecks 375, 488, 540
not_covered/1 ..... 383, 385
not_fails/1 ... 24, 383, 387, 413, 415, 423, 424, 425, 426, 427, 428, 429, 430, 431, 433, 434, 435, 439, 454, 462, 467, 471, 474, 475, 476, 477, 480, 493, 494, 496, 497, 498, 499, 500, 513, 514, 515, 516, 517, 518, 519, 569, 570
not_further_inst/1 348
not_further_inst/2 ..... 357, 371, 456, 577, 578
not_mut_exclusive/1 ..... 383, 384
nsicond-sas94 312
num/1 ..... 357, 359, 360, 543
num_solutions/2 389
number_lattice 400
number_lattice/1 ..... 399, 401
numeric_constant/1 ..... 399, 400

O

obtain_freeness/2 ..... 181, 185
obtain_info/3 ..... 181, 183
obtain_info/4 ..... 181, 183
obtain_info/5 ..... 422, 431
obtain_prime_var_var/3 ..... 181, 185
obtains_names/4 ..... 59, 70
op/3 532
open_mode/3 ..... 473, 476
operator_specifier/1 ..... 357, 363, 364
orig_clause_id/2 ..... 541, 544
output/0 ..... 17, 22, 443, 445
output/1 ..... 22, 443, 445
output/2 ..... 21, 443, 445
output_by_ext/2 ..... 21, 443, 446
output_ext/1 ..... 21, 443, 446
output_option/1 445

P

p_abs 523, 525
p_asr 478, 523, 525, 536
p_dump 15, 446, 447, 448, 464, 498, 506, 590
p_printer 448
p_unit 15, 45, 101, 304, 415, 440, 441, 442, 448, 452, 457, 460, 464, 480, 498, 525, 527, 549, 554, 560
p_unit:gen_libcache/1 446
p_unit:load_libcache/1 446
p_unit_basic 534, 536, 548
p_unit_db .. 15, 26, 415, 448, 452, 457, 460, 464, 478, 480, 482, 494, 498, 504, 508, 536, 549, 560, 579

parametric type functor 354
parents_complete(Parents) 565
parents_complete/1 565
part_conc/5 ..... 422, 434
Partial deduction 312
partial evaluation 1, 3, 312
partition_sf/4 ..... 181, 184
patch/3 510
patch_parents/6 ..... 565, 568
path_to_shfr/3 305
pathnames 15, 448, 464, 478, 488, 494, 504, 506, 536, 579, 592, 596
paths.pl 442
Pawel Pietrzak 47
pd 157, 440
pdb 163, 440
pe_type/1 ..... 357, 375
Pedro Lopez 351, 377
persdb 488, 596, 598
persdb/persdb_decl 488, 596, 598
persdb_rt 488, 596, 598
persistent_dir/2 ..... 483, 487, 593, 595, 597, 598
persistent_dir/4 ..... 483, 487, 593, 595, 597, 598
plai 441, 442, 452, 457, 464, 498, 508, 557, 559
plai-tr 314
plai/5 559
plai_db .. 452, 464, 498, 500, 508, 519, 554, 557, 559, 562, 565, 579
plai_db_comparator 498, 500, 519
plai_db_id(Id) ... 496, 498, 515, 516, 517, 519, 567, 568, 569
plai_db_id/1 ..... 496, 498, 515, 516, 517, 519, 565, 567, 568, 569, 572
plai_errors 37, 93, 101, 115, 123, 213, 219, 273, 309, 415, 560
Plai0 557
polyhedra 169
polyhedra_finalize/0 169
polyhedra_initialize/0 169
pool 37, 554
pop/2 ..... 469, 470
pop_history/1 ..... 22, 443, 445
pop_pp_flag/1 ..... 18, 483
pop_task/4 597
port_reify 15, 560, 590
pos/4 ..... 221, 222
possible_exceptions/2 391
possible_signals/2 ..... 391, 392
possibly_fails/1 ..... 383, 387
possibly_nondet/1 ..... 383, 386
possibly_not_covered/1 ..... 383, 386
possibly_not_mut_exclusive/1 ..... 383, 385
postcondition_builtin/4 ..... 291, 300
powerset_with_empty_set/2 ..... 235, 236
pp_flag/1 ..... 17, 18, 20, 483, 484, 486
pp_flag/2 ..... 483, 484
ppl_interface 173
pr_key/1 530
pr_key_add/1 ..... 527, 530
pr_key_clean/0 ..... 527, 530
pr_key_get/1 ..... 527, 530
pragma/5 ..... 565, 566
precondition_builtin/2 ..... 291, 300
pred assertion 336, 337
pred/1 ..... 336, 337, 342, 345, 348
pred/2 ..... 336, 337
predfunctor/1 ..... 345, 350
predicate 408
predicate_names/1 ..... 527, 531
predicates/1 507
predkey/1 ..... 541, 543, 546, 565, 567
predkey_from_sg/2 ..... 541, 546
predname/1 ..... 152, 153, 346, 357, 368, 369
prednames 548
prelude .. 15, 26, 37, 45, 51, 57, 74, 86, 93, 101, 108, 115, 123, 132, 141, 156, 161, 167, 173, 179, 190, 196, 202, 207, 213, 219, 227, 233, 242, 247, 253, 261, 267, 273, 281, 290, 304, 309, 336, 350, 354, 375, 381, 387, 390, 393, 396, 397, 406, 408, 415, 440, 449, 452, 457, 460, 464, 468, 471, 478, 480, 482, 488, 494, 498, 500, 504, 506, 508, 511, 519, 536, 540, 548, 549, 554, 560, 562, 572, 579, 581, 585, 590, 592, 596, 598
prepare_ai_output 448
preproc_errors 457
preprocess_flags .. 15, 26, 37, 45, 51, 57, 74, 86, 93, 101, 108, 115, 123, 132, 141, 156, 161, 167, 173, 179, 190, 196, 202, 207, 213, 219, 227, 233, 242, 247, 253, 261, 267, 273, 281, 290, 304, 309, 415, 440, 448, 452, 457, 460, 464, 478, 480, 482, 483, 494, 498, 504, 506, 519, 554, 560, 562, 579, 590
preprocessing unit 523
preprocessing_unit/3 527
pretty_print 448
process 464, 585
process_changed_module/1 473

process_external_complete_change/6 .... 495, 497
prod(Index,LowerBound,UpperBound,Exp) 400
prod/4 400
product/8 ..... 181, 184
prog-glob-an 335
program assertions 335
program parallelization 1, 3
program specialization 1, 3
program transformations 1, 3
program/2 ..... 527, 528
program_keys 415, 441, 452, 468, 480, 482, 494, 498, 500, 504, 508, 519, 536, 541, 549, 554, 560, 572
proj_to_prime/9 ..... 513, 515
proj_to_prime_nr/9 ..... 513, 514
proj_to_prime_r/8 ..... 513, 515
project/5 ..... 39, 181, 197, 221, 236, 275, 422, 424
project/6 ..... 422, 425
project_freeness/3 ..... 181, 182
project_freeness_n/3 ..... 181, 186
project_share/3 221
projected_gvars_clique/3 ..... 235, 238
prologiv-manual 325
prompt 15
prop assertion 339
prop/1 ..... 336, 339
prop/2 ..... 336, 339
prop_to_native/2 ..... 527, 529
propagate_non_freeness/5 ..... 181, 186
propagate_to_sh/4 ..... 275, 277
propagate_to_son/4 ..... 275, 277
properties of computations 351
properties of execution states 351
properties, basic 357
properties, native 377
property 339
property compatibility 369
property_conjunction/1 .... 343, 344, 345, 346, 347
property_starterm/1 ..... 345, 346, 347
propfunctor/1 ..... 345, 350
providing information to the compiler ... 340, 343
prune/4 ..... 181, 184
prune/5 ..... 181, 184
prune_success/5 ..... 235, 236
psets 562
ptypes 175, 440
punit_module/2 465
Punit0 523
push/2 469
push_history/1 ..... 22, 443, 445
push_pp_flag/2 ..... 18, 483

Q

query/8 ..... 513, 561

R

raw_output/1 451
raw_printer 448, 451, 464, 498
raw_success/6 ..... 565, 567
re_analysis 460, 464, 557
read 478, 590, 596
read_only 476
read_registry_file/3 ..... 473, 475
read_write 476
rearrange_tarjan_after_deletion/1 507
rec/1 ..... 507, 508
rec_preds/1 ..... 507, 508
redo_unchanged_module/1 473
reg_version/1 ..... 465, 467
registry/3 ..... 465, 466
registry_header/2 ..... 465, 466
registry_header_format/2 ..... 465, 468
regtype assertion 354, 355
regtype/1 ..... 354, 355, 357, 372
regtype/2 ..... 354, 355
regtypes 51, 74, 86, 108, 132, 141, 156, 161, 167, 179, 190, 227, 261, 290, 304, 350, 351, 381, 387, 390, 393, 396, 397, 406, 440, 449, 457, 460, 468, 488, 494, 506, 511, 519, 536, 540, 548, 572, 579, 585, 590
regular type 354
regular type definitions 351
regular type expression 355
regular types 351
relations/2 ..... 364, 389
remove_clauses_and_related_info_collect_preds/4 499
remove_clauses_pred/2 ..... 501, 502
remove_config/1 ..... 483, 486
remove_extra_info_complete/3 ..... 565, 569
remove_menu_config/1 13
remove_useless_completes/1 ..... 495, 497
rename_types_in_abs/4 ..... 422, 434
replace_names/3 ..... 59, 62

replace_program/2 ..... 527, 528
replaceintype/5 ..... 59, 70
replacetype/4 ..... 59, 69
report_mod_info/3 ..... 593, 595
reset_incremental_analysis_info/0 ..... 493, 494
reset_persistent_db/0 505
reset_queue/0 469
resource_id/1 ..... 399, 405, 406
resources_basic.pl 399, 403
resources_decl 399
restore/1 ..... 21, 447
restore/2 ..... 21, 447
restore_clause_db/0 ..... 501, 502
restore_config/1 ..... 483, 486
restore_fixpoint_id/1 ..... 501, 504
restore_menu_config/1 14
rewrite_source_all_clauses/2 ..... 541, 542
rewrite_source_clause/3 ..... 541, 542
rsize/2 ..... 399, 405
rtc_status/1 373
rtcheck/1 ..... 357, 373
rtcheck/2 ..... 357, 373, 384, 385, 390, 391, 392
rtchecks 407, 408
rtchecks_asrloc 407
rtchecks_callloc 407
rtchecks_entry 407
rtchecks_exit 407
rtchecks_level 407
rtchecks_namefmt 408
rtchecks_predloc 407
rtchecks_test 407
rtchecks_trust 407
run-time checks 339
run-time tests 1, 3
run_inc_fixpoint/1 ..... 495, 497
runtime_control 26, 173, 449, 464, 498, 536, 540

S

s_assrt_body/1 ..... 338, 339, 340, 341, 345, 348
s_eqs 37, 57, 190, 213, 309
s_grshfr 115, 123, 190, 196, 202, 207, 213, 219, 227, 233, 242, 247, 253, 267, 273, 281
Saglam-Gallagher-94 ..... 32, 292
save_clause_db/0 501
save_config/1 ..... 483, 486
save_menu_config/1 ..... 13, 14
save_persistent_analysis/0 ..... 505, 506
save_registry_info/2 ..... 473, 476, 477
save_registry_info/3 ..... 473, 476, 477
script_p/3 ..... 221, 222
script_p_star/3 ..... 221, 222
semidet/1 383
sequence/2 ..... 357, 366
sequence_or_list/2 ..... 357, 367
set_analyzed_mods/1 ..... 501, 504
set_current_task/2 ..... 593, 594
set_inc_persistent/1 505
set_last_error/3 ..... 593, 595
set_loaded_mods/1 ..... 501, 503
set_loaded_module/1 505
set_local_ana_modules/1 ..... 465, 467
set_main_module/1 ..... 465, 467
set_menu_flag/3 ..... 11, 14
set_modules_analyzed/1 ..... 473, 477
set_pp_flag/2 ..... 18, 483, 484
set_punit_modules/1 ..... 465, 467
sets ... 37, 45, 51, 57, 74, 86, 93, 101, 108, 115, 123, 132, 141, 156, 161, 167, 173, 179, 190, 196, 202, 207, 213, 219, 227, 233, 242, 247, 253, 261, 267, 273, 281, 290, 304, 309, 440, 471, 508, 519, 549, 562
setup_scheduling/4 ..... 469, 470
sh_free_vars_compatible/2 ..... 181, 185
share_amgu_aux 233, 242, 247
share_amgu_sets 196, 202, 233, 242, 247
share_aux .. 37, 93, 101, 115, 190, 196, 202, 207, 213, 219, 227, 242, 247, 253, 267, 273, 281, 309
share_clique_1_aux 242, 247
share_clique_aux 202, 207, 242, 247, 253
share_clique_lub_cl/3 ..... 235, 237
share_make_reduction/5 ..... 235, 238
share_to_son/3 ..... 275, 277
sharefree 132, 141, 161, 167, 181, 196, 202, 213, 261, 267, 273, 440
sharefree_amgu 190, 191, 202, 267, 440
sharefree_amgu_aux 196, 202, 267
sharefree_clique 197, 207, 440
sharefree_clique_aux 202
sharefree_clique_def 203, 440
sharefree_delete_variables/3 ..... 191, 192
sharefree_non_var 209, 440
shareson 215, 440
sharing ... 37, 190, 196, 213, 219, 221, 233, 242, 247, 281, 440
sharing sets 379

sharing_amgu 196, 227, 229, 440
sharing_clique 202, 235, 247, 253, 440
sharing_clique_1 ..... 243, 440
sharing_clique_def 249, 440
sharing_part_less_or_equal/3 ..... 235, 237
sharing_possible/4 ..... 235, 236
shfret 255, 440
shfret_abs_sort/2 ..... 255, 256
shfret_asub_to_native/5 ..... 255, 257
shfret_call_to_entry/9 255
shfret_call_to_success_fact/9 ..... 255, 256
shfret_combined_special_builtin0/2 .... 255, 256
shfret_compute_lub/2 ..... 255, 256
shfret_eliminate_equivalent/2 ..... 255, 256
shfret_empty_entry/3 ..... 255, 257
shfret_exit_to_prime/7 255
shfret_extend/5 ..... 255, 256
shfret_glb/3 ..... 255, 256
shfret_identical_abstract/2 ..... 255, 256
shfret_init_abstract_domain/1 255
shfret_input_interface/4 ..... 255, 257
shfret_input_user_interface/5 ..... 255, 257
shfret_less_or_equal/2 ..... 255, 256
shfret_project/5 ..... 255, 256
shfret_split_combined_domain/3 ..... 255, 257
shfret_unknown_call/4 ..... 255, 257
shfret_unknown_entry/3 ..... 255, 257
shfret_widen/3 ..... 255, 256
shfret_widencall/3 ..... 255, 256
shfrlin_amgu 263, 440
shfrlin_amgu_aux 267
shfrson 269, 440
short 408
shortening_el/3 291
show_analysis/0 ..... 451, 452
show_change_list/0 ..... 451, 452
show_config/1 ..... 483, 487
show_configs/0 ..... 483, 487
show_dump/1 ..... 21, 447
show_global_answer_table/1 ..... 451, 452
show_menu_config/1 14
show_menu_configs/0 14
show_registry_info/0 ..... 451, 452
show_spypoint_op_count/0 ..... 577, 578
show_trans_clauses/0 ..... 451, 452
show_updated_memotable/3 ..... 577, 578
sideff/2 ..... 357, 358, 359, 360, 361, 362, 363, 364, 365, 366, 367, 368, 369, 370, 371, 372, 373, 374
sideff_hard/1 395
sideff_pure/1 395
sideff_soft/1 395
signal/1 ..... 391, 392
signal/2 ..... 391, 392
sinsi-jlp 312
size of terms 3
size/2 ..... 399, 401
size/3 ..... 399, 401
size/4 ..... 399, 401
size_lb/2 ..... 399, 402
size_metric 400
size_metric/3 ..... 399, 403
size_metric/4 ..... 399, 403
size_o/2 ..... 399, 402
size_term/1 ..... 399, 401
size_ub/2 ..... 399, 402
sizes of terms 1
slicing 460
soft side-effects 395
solutions/2 ..... 389, 390
son_to_share/4 ..... 275, 277
sonder86 32
sondergaard 219, 273, 275, 440
sort 15, 37, 45, 51, 57, 74, 86, 93, 101, 108, 115, 123, 132, 141, 156, 161, 167, 173, 179, 190, 196, 202, 207, 213, 219, 227, 233, 242, 247, 253, 261, 267, 273, 281, 290, 304, 309, 440, 448, 498, 500, 508, 519, 554, 562
sourcename/1 ..... 22, 444, 446
sp_clauses 560
spec 460, 464
spec(no_debug) 519, 562
spec(nomem_usage) 464
spec_multiple 460
special_builtin/5 .. 39, 40, 181, 183, 192, 198, 221, 223, 238, 275, 277
special_builtin/6 ..... 422, 430
specifications 1, 3, 335
split_coupled/4 ..... 181, 184
split_f/4 ..... 59, 69
sqrt/1 400
src_changed/1 ..... 465, 466
srcloc/4 ..... 357, 371
start_view/0 581
start_worker/1 589
static debugging 1, 3
static_abs_exec_table 15

steps/2 ..... 399, 404
steps_lb/2 ..... 399, 404
steps_o/2 ..... 399, 405
steps_ub/2 ..... 399, 404
store_current_fixpoint_id/1 ..... 501, 504
store_raw_success/6 ..... 565, 571
stream/1 452
stream_basic 449, 452, 464, 478, 536, 579, 585, 590, 596
stream_utils 590
streams 37, 173, 468, 478, 536
string/1 ..... 357, 368, 532, 589, 591
string_contained/2 591
stringcommand/1 ..... 342, 346, 348, 349, 350
struct/1 ..... 357, 361
sublist2/2 ..... 483, 487
substitution/3 ..... 291, 298
success assertion 338
success/1 ..... 19, 336, 338, 341, 485
success/2 ..... 19, 336, 338, 485
success_asr/6 412
success_builtin/6 .. 39, 40, 181, 183, 192, 221, 223, 235, 238, 275, 277
success_builtin/7 ..... 422, 431
sum(Index,LowerBound,UpperBound,Exp) 400
sum/4 400
supported_language/1 443
svterms 283, 440
svterms_abs_sort/2 ..... 283, 284
svterms_asub_to_native/5 ..... 283, 285
svterms_call_to_entry/9 ..... 283, 284
svterms_call_to_success_builtin/6 ..... 283, 285
svterms_call_to_success_fact/9 ..... 283, 285
svterms_collect_auxinfo_asub/3 ..... 283, 285
svterms_compute_lub/2 283
svterms_compute_lub_el/3 283
svterms_concrete/3 283
svterms_empty_entry/3 ..... 283, 285
svterms_exit_to_prime/7 ..... 283, 284
svterms_extend/5 ..... 283, 284
svterms_glb/3 ..... 283, 284
svterms_identical_abstract/2 ..... 283, 286
svterms_init_abstract_domain/1 ..... 283, 284
svterms_input_interface/4 ..... 283, 285
svterms_input_user_interface/5 ..... 283, 285
svterms_less_or_equal/2 ..... 283, 284
svterms_needs/1 ..... 283, 284
svterms_output_interface/2 ..... 283, 285
svterms_project/5 ..... 283, 284
svterms_rename_auxinfo_asub/3 ..... 283, 286
svterms_special_builtin/5 ..... 283, 285
svterms_success_builtin/6 ..... 283, 285
svterms_unknown_call/4 ..... 283, 285
svterms_unknown_entry/3 ..... 283, 285
svterms_widen/3 ..... 283, 284
svterms_widencall/3 ..... 283, 284
switch/1 ..... 527, 528
system 15, 26, 448, 464, 478, 488, 506, 585, 590, 592, 596
system_extra 464, 506, 590, 596

T

take_coupled/3 ..... 181, 184
tarjan 478, 498, 500, 508, 519, 557, 560
tarjan_data/1 507
tarjan_inc 494, 498, 507
task_status/1 590
task_status/5 593
tasks_db 590, 597
td_add_clauses/2 495
td_delete_clauses/2 ..... 495, 496
td_mark_parents_change_list/2 ..... 513, 516
td_rec_delete_complete/3 ..... 495, 496
term/1 .. 60, 61, 62, 63, 64, 65, 66, 68, 76, 77, 78, 80, 149, 150, 151, 152, 153, 154, 155, 292, 293, 294, 295, 296, 297, 298, 299, 357, 366, 401, 402, 403, 425, 427, 434, 468, 476, 477, 503, 513, 518, 529, 530, 533, 546, 553, 565, 566, 593
term_basic ... 15, 26, 37, 45, 51, 57, 74, 86, 93, 101, 108, 115, 123, 132, 141, 156, 161, 167, 173, 179, 190, 196, 202, 207, 213, 219, 227, 233, 242, 247, 253, 261, 267, 273, 281, 290, 304, 309, 336, 350, 354, 375, 381, 387, 390, 393, 396, 397, 406, 408, 415, 440, 449, 452, 457, 460, 464, 468, 471, 478, 480, 482, 488, 494, 498, 500, 504, 506, 508, 511, 519, 536, 540, 548, 549, 554, 560, 562, 572, 579, 581, 585, 590, 592, 596, 598
term_compare .. 15, 26, 37, 45, 51, 57, 74, 86, 93, 101, 108, 115, 123, 132, 141, 156, 161, 167, 173, 179, 190, 196, 202, 207, 213, 219, 227, 233, 242, 247, 253, 261, 267, 273, 281, 290, 304, 309, 336, 350, 354, 375, 381, 387, 390, 393, 396, 397, 406, 408, 415, 440, 449, 452, 457, 460, 464, 468, 471, 478, 480, 482, 488, 494, 498, 500, 504, 506, 508, 511,

519, 536, 540, 548, 549, 554, 560, 562, 572, 579, 581, 585, 590, 592, 596, 598
term_typing .. 15, 26, 37, 45, 51, 57, 74, 86, 93, 101, 108, 115, 123, 132, 141, 156, 161, 167, 173, 179, 190, 196, 202, 207, 213, 219, 227, 233, 242, 247, 253, 261, 267, 273, 281, 290, 304, 309, 336, 350, 354, 357, 375, 381, 387, 390, 393, 396, 397, 406, 408, 415, 440, 449, 452, 457, 460, 464, 468, 471, 478, 480, 482, 488, 494, 498, 500, 504, 506, 508, 511, 519, 536, 540, 548, 549, 554, 560, 562, 572, 579, 581, 585, 590, 592, 596, 598
terminates/1 ..... 399, 406
terms 448, 464, 579
terms_abs_sort/2 ..... 291, 296
terms_asub_to_native/5 ..... 291, 300
terms_call_to_entry/9 ..... 291, 293
terms_call_to_success_builtin/6 ..... 291, 299
terms_call_to_success_fact/9 ..... 291, 298
terms_check 37, 45, 51, 57, 74, 86, 108, 115, 156, 190, 196, 202, 213, 227, 233, 242, 247, 267, 281, 290, 304, 309, 375, 440, 482, 536, 554
terms_collect_auxinfo_asub/3 ..... 291, 300
terms_compute_lub/2 ..... 291, 292
terms_compute_lub_el/3 ..... 291, 292
terms_concrete/3 ..... 291, 292
terms_empty_entry/3 ..... 291, 297
terms_exit_to_prime/7 ..... 291, 294
terms_extend/5 ..... 291, 296
terms_glb/3 ..... 291, 297
terms_identical_abstract/2 ..... 291, 300
terms_init_abstract_domain/1 ..... 291, 292
terms_input_interface/4 291
terms_input_user_interface/5 ..... 291, 300
terms_internal_to_native/3 ..... 291, 300
terms_io 596
terms_less_or_equal/2 ..... 291, 296
terms_needs/1 ..... 291, 292
terms_output_interface/2 ..... 291, 300
terms_project/5 ..... 291, 295
terms_rename_auxinfo_asub/3 ..... 291, 300
terms_special_builtin/5 ..... 291, 299
terms_success_builtin/6 ..... 291, 299
terms_unknown_call/4 ..... 291, 298
terms_unknown_entry/3 ..... 291, 297
terms_vars 37, 45, 57, 74, 86, 93, 108, 115, 156, 173, 190, 196, 202, 213, 219, 227, 233, 242, 247, 267, 273, 281, 290, 304, 309, 415, 440, 448, 480, 482, 498, 519, 549, 554, 560, 562, 579
terms_widen/3 ..... 291, 292
terms_widencall/3 ..... 291, 292
termsd 47, 51, 74, 86, 179, 291, 440
termsd_asub/1 .... 292, 293, 294, 295, 296, 297, 298, 299
termsd_extrainfo(ExtraInfo) 293, 294
termsd_extrainfo/1 ..... 293, 294
test assertion 339
test/1 ..... 336, 339
test/2 ..... 336, 339
test_type/2 ..... 358, 359, 360, 361
texec assertion 340
texec/1 ..... 336, 340
texec/2 ..... 336, 340
The Ciao Development Team 9, 17, 27, 323, 417, 419, 461, 527
top_level_of_files/2 505
top_path_sharing 305, 440
topdown_analysis/3 ..... 559, 560
tr_syntax 441, 442, 536, 549
trace_end/0 ..... 577, 578
trace_fixp 457, 557, 560, 577
trace_fixp/1 ..... 455, 575, 577
trace_init/0 ..... 577, 578
trace_option(X) 456, 577
trace_option/1 ..... 456, 577, 578
trace_reset/0 ..... 577, 578
trans_clause/3 452
transform 452, 480, 498, 500, 508, 519, 557, 560, 562, 572
transform/1 ..... 23, 459
transform/2 459
transform_clauses_/5 ..... 559, 560
transform_driver 15, 26, 448, 459
transformation/1 ..... 23, 26, 459, 460, 461, 463
transformation/4 ..... 459, 460
traverse_clauses/4 549
true assertion 343
true/1 ..... 336, 343, 357, 375
true/2 ..... 14, 24
true1/1 ..... 15, 25
trust 557
Trust 573
trust assertion 343
trust assertions 330
trust/1 ..... 336, 343, 357, 375
type_fails/3 553
type_holds/3 553

type_of_directive/2 ..... 527, 530
type_of_goal/2 534
type2measure/3 553
typeanalysis/1 ..... 483, 487
types 1, 3
typeslib 26, 51, 74, 86, 179, 227, 290, 304, 448, 452, 457, 551, 554
typeslib_flag/1 25
typeslib_interesting_type/2 25
typeslib_is_user_type/1 25
typeslib_is_visible/2 25

U

undef_call_to_success_builtin/2 ..... 422, 435
unexpand 448, 536
unfold_builtins 74
unfold_non_rec 460
unfold_times 464, 560
unify_term_and_type_term/5 ..... 291, 294
unifytoterm/1 ..... 59, 69
unknown_call/4 ..... 39, 40, 181, 185, 197, 198, 221, 223, 235, 238, 275, 276
unknown_call/5 ..... 422, 433
unknown_entry/3 ..... 39, 40, 181, 182, 221, 222, 235, 238, 275, 276
unknown_entry/4 ..... 422, 433
unset_src_changed/1 ..... 465, 466
update_complete_id/4 ..... 565, 569
update_inc_clkey/1 ..... 501, 503
update_lambda_non_free/5 ..... 181, 184
update_lambda_sf/5 ..... 181, 184
update_names/2 ..... 59, 62
update_task_status/0 593
update_tasks_analysis_status/0 ..... 584, 593, 595
usage 336
use_check_as_trust 411
useful modes 346
user 476

V

v.phd 32
valid_flag_value/2 ..... 17, 18, 20, 483, 484, 485
valid_flag_values/2 ..... 483, 486
valid_mod_analysis/1 461
values_differ/3 ..... 181, 185
values_equal/3 ..... 181, 185
VanHentenryckCortesiLeCharlier95 32
var/1 ..... 13, 23, 60, 61, 62, 63, 64, 65, 66, 67, 68, 76, 77, 78, 79, 80, 81, 134, 148, 149, 150, 151, 152, 153, 154, 155, 156, 183, 223, 292, 293, 294, 295, 296, 297, 298, 299, 300, 347, 412, 413, 414, 415, 423, 424, 425, 426, 427, 429, 430, 431, 432, 433, 444, 454, 459, 460, 470, 479, 481, 482, 487, 499, 500, 502, 513, 514, 515, 516, 518, 528, 529, 531, 533, 541, 542, 543, 545, 546, 547, 549, 553, 561, 568, 591, 594
variable instantiation 1, 3
variable names 335
variables_are_top_type/2 ..... 59, 65, 291, 298
variables_are_variable_type/2 ..... 291, 294
varnamedict/1 528
vartypes 457, 551, 554
vertexes/1 ..... 507, 508
view_fixp 557, 579, 581
view_fixpoint/7 581
vlist/1 540
vndict 480, 536, 549, 560

W

wam_builtin/2 537
widen/4 ..... 235, 238, 422, 426
widen/5 ..... 235, 238
widencall/4 ..... 422, 426
write 37, 57, 173, 452, 478, 488, 519, 579, 596
write_one_type/2 ..... 21, 443, 446
write_registry_file/3 ..... 473, 475

Y

yes 407